MN3207

1024-STAGE LOW VOLTAGE OPERATION LOW NOISE BBD

■ General description

The MN3207 is a 1024-stage long delay low noise BBD that provides a signal delay of up to 51.2ms and is particularly suitable as a device for generation of reverberation effect in audio equipment such as low voltage operation portable stereo and radio cassette recorders.



8-Lead Dual-In-Line Plastic Package

■ Features

- Variable delay of audio signals: 2.56ms ~ 51.2ms.
- Wide supply votage: 4 ~ 10V.
- No insertion loss: L_i = 0dB typ.
- Wide dynamic range: S/N = 73dB typ.
- Low distortion: THD = 0.4% typ. (V_i = 0.25Vrms).
- Clock frequency range: 10KHz ~ 200KHz.
- N-channel silicon gate process.
- 8-lead dual-in-line plastic package.

■ Applications

- Reverberation and echo effects of audio equipment such as radio cassette recorder, car radio, portable radio, portable stereo, echo microphone and pre-taped musical accompaniment (Karaoke), etc.
- Sound effect in electronic musical instruments.
- Variable or fixed delay of analog signals.

■ Block Diagram



■ Quick Reference Data

Item	Symbol	Value	Unit
Supply Voltage	V_{DD}, V_{GG}	+ 5 , $\frac{14}{15}V_{DD}$	V
Signal Delay Time	t_D	2.56~51.2	ms
Total Harmonic Distortion	THD	0.4	%
Signal to Noise Ratio	S/N	73	dB

■ Absolute Maximum Ratings (Ta = 25°C)

Item	Symbol	Rating	Unit
Terminal Voltage	V_{DD}, V_{GG}, V_{CP}, V_I	−0.3~+11	V
Output Voltage	V_O	−0.3~+11	V
Operating Temprature	Topr	−20~+60	℃
Storage Temperature	Tstg	−55~+125	℃

■ Operating Condition (Ta = 25°C)

Item	Symbol	Condition	Min.	Typ.	Max.	Unit
Drain Supply Voltage	V_{DD}		+4	+5	+10	V
Gate Supply Voltage	V_{GG}			$\frac{14}{15}V_{DD}$		V
Clock Voltage "H" Level	V_{CPH}			V_{DD}		V
Clock Voltage "L" Level	V_{CPL}		0		+1	V
Clock frequency	f_{CP}		10		200	kHz
Clock Pulse Width *1	t_{CPW}				0.5T *2	
Clock Rise Time *1	t_{CPr}				500	ns
Clock Fall Time *1	t_{CPf}				500	ns
Clock Input Capacitance	C_{CP}				700	pF
Clock Cross Point *1	V_X		0		$0.3V_{CPH}$	V

■ Electrical Characteristics (Ta = 25°C, V_{DD} = V_{CPH} = 5V, V_{CPL} = 0V, V_{GG} = 4.67V, R_L = 100kΩ)

Item	Symbol	Condition	Min.	Typ.	Max.	Unit
Signal Delay Time	t_D		2.56		51.2	ms
Input Signal Frequency	f_i	f_{cp} = 40kHz, V_i = 0.35Vrms 3dB down (0dB at f_i = 1kHz) = 1kHz)	10			kHz
Input Signal Swing	V_i	f_{CP}=40kHz, f_i=1kHz, THD=2.5%	0.36			Vrms
Insertion Loss	L_i	f_{CP}=40kHz, f_i=1kHz, V_i=0.36Vrms	−4	0	4	dB
Total Harmonic Distortion	THD	f_{CP}=40kHz, f_i=1kHz, V_i=0.25Vrms		0.4	2.5	%
Noise Voltage	V_{no}	f_{cp} = 100kHz, Weighted by "A" curve			0.25	mVrms
Signal to Noise Ratio	S/N			73		dB

*1 Clock Pulse Waveforms



*2 T = $1/f_{CP}$ (Clock Period)

■ Terminal Assignments



(Top View)

■ Circuit Diagram



■ Typical Electrical Characteristic Curves

$V_O - V_I$



$V_O - V_i$



THD − V_i



$V_{no} - f_{CP}$



$G_i - f_i$



$G_i - V_i$



$G_i - f_{CP}$



THD − V_{Bias}



$G_i - Ta$



$V_{i(max.)}$ — Ta



f_i — Ta



THD — Ta



■ Supply Voltage Characteristics

V_{Bias} — V_{DD}



THD — V_{DD}



f_i — V_{DD}



$V_{i(max.)}$ — V_{DD}



G_i — V_{DD}



S/N — V_{DD}



■ Application Circuit



Echo Effect Generation Circuit