Bipolar Transistors






Description:


NPN Silicon Planar Epitaxial Transistors.

TO-92 Plastic Package




Dimensions	Minimum	Maximum		
А	4.32	5.33		
В	4.45	5.20		
С	3.18	4.19		
D	0.41	0.55		
Е	0.35	0.50		
F	5°			
G	1.14	1.40		
Н	1.14	1.53		
K	12.70	-		
L	1.982	2.082		

Dimensions : Millimetres



Pin Configuration:

- 1. Emitter
- 2. Collector
- 3. Base





Bipolar Transistors



Absolute Maximum Ratings

Rating	Symbol	Value	Unit		
Collector Emitter Voltage	V _{CEO}	30			
Collector Base Voltage	V _{CBO}	50	V		
Emitter Base Voltage	V _{EBO}	5			
Collector Current Continuous	I _C	600	mA		
Power Dissipation at T _a = 25°C Derate above 25°C	P _D	625 5	W mW/°C		
Operating and Storage Junction Temperature Range	T _j , T _{stg}	-55 to +150	°C		
Thermal Resistance					
Junction to Ambient	R _{th (j-a)}	200	°C/W		

Electrical Characteristics ($T_a = 25$ °C unless otherwise specified)

Characteristic	Symbol	Test Condition	Minimum	Maximum	Unit	
Collector Emitter Voltage	BV _{CEO} *	$I_{C} = 10 \text{mA}, I_{B} = 0$	30	-		
Collector Base Voltage	BV _{CBO}	$I_C = 100 \mu A, I_E = 0$	50	-	V	
Emitter to Base Voltage	V _{EBO}	$I_E = 100 \mu A, I_C = 0$	5	-		
DC Current Gain 2N3704	h _{FE} *	$I_C = 50$ mA, $V_{CE} = 2V$	100	300	-	
Collector Leakage Current	I _{CBO}	$V_{CB} = 20V, I_{E} = 0$	-	0.1	μА	
Emitter Leakage Current	I _{EBO}	$V_{EB} = 3V, I_{C} = 0$	-	0.1		
Collector Emitter Saturation Voltage 2N3704	V _{CE (sat)} *	$I_{C} = 100 \text{mA}, I_{B} = 5 \text{mA}$	-	0.6	V	
Base Emitter On Voltage	V _{BE (on)} *	$I_{C} = 100 \text{mA}, V_{CE} = 2 \text{V}$	0.5	1.0		

^{*}Pulse Test : Pulse Width = \leq 300 μ s, Duty Cycle = \leq 2.0%.



Bipolar Transistors



Electrical Characteristics ($T_a = 25$ °C unless otherwise specified)

Characteristic	Symbol	Test Condition	Minimum	Maximum	Unit	
Small Signal Characteristics						
Output Capacitance	C _{ob}	I _E = 0, V _{CB} = 10V, f = 1MHz	-	12	pF	
Transition Frequency	f _T	$I_C = 50$ mA, $V_{CE} = 2$ V, $f = 20$ MHz	100	-	MHz	

Specifications

V _{CEO} (V)	V _{CBO} Maximum (V)	I _C (mA)	h _{FE} Minimum at I _C = 50mA	f _T Minimum (MHz)	P _{tot} (mW)	Package	Part Number
30	50	0.8	100	100	360	TO-92	2N3704



Bipolar Transistors



Notes:

International Sales Offices:



AUSTRALIA - Farnell

Tel No: ++61 1300 361 005 Fax No: ++61 1300 361 225



FINLAND - Farnell

Tel No: ++ 358 9 560 7780 Fax No: ++ 358 9 345 5411



Tel No: ++ 39 02 93 995 200 Fax No: ++ 39 02 93 995 300



SPAIN - Farnell

Tel No: 901 20 20 80 Fax No: 901 20 20 90



AUSTRIA - Farnell

Tel No: ++ 43 662 2180 680 Fax No: ++ 43 662 2180 670



FRANCE - Farnell

Tel No: ++ 33 474 68 99 99 Fax No: ++ 33 474 68 99 90



MALAYSIA -

Tel No: ++ 60 3 7873 8000 Fax No: ++ 60 3 7873 7000



SWEDEN - Farnell Tel No: ++ 46 8 730 50 00

Fax No: ++ 46 8 83 52 62



BELGIUM - Farnell

Tel No: ++ 32 3 475 2810 Fax No: ++ 32 3 227 3648



GERMANY - Farnell

Tel No: ++ 49 89 61 39 39 39 Fax No: ++ 49 89 613 59 01



NETHERLANDS - Farnell

Tel No: ++ 31 30 241 7373 Fax No: ++ 31 30 241 7333



SWITZERLAND - Farnell

Tel No: ++ 44 204 64 64 Fax No: ++ 44 204 64 54



BRAZIL - Farnell-Newark

Tel No: ++ 55 11 4066 9400 Fax No: ++ 55 11 4066 9410



Tel No: ++ 852 2268 9888 Fax No: ++ 852 2268 9899



NEW ZEALAND - Farnell

Tel No: 0800 90 80 80 Fax No: 0800 90 80 81



UK - Farnell

Tel No: ++ 44 8701 200 200 Fax No: ++ 44 8701 200 201



CHINA - Farnell-Newark

Tel No: ++86 10 6238 5152 Fax No: ++86 10 6238 5022



HUNGARY - Farnell

Tel No: ++ 44 870 1200 208 Fax No: ++ 44 870 1200 209



NORWAY - Farnell

Tel No: 800 146 70 Fax No: 800 146 76



UK - CPC

++ 44 8701 202 530 ++ 44 8701 202 531



CZECH REPUBLIC - Farnell

Tel No: ++ 44 870 1200 208 Fax No: ++ 44 870 1200 209



INDIA - Farnell

Tel No: ++ 44 870 1200 208 Fax No: ++ 44 870 1200 209



PORTUGAL - Farnell

Tel No: ++ 34 93 475 8804 Fax No: ++ 34 93 474 5288



Tel No: 800 463 9275



Tel No: ++ 45 44 53 66 44 Fax No: ++ 45 44 53 66 06



Tel No: ++ 353 1 830 9277 Fax No: ++ 353 1 830 9016



RUSSIA - Farnell

Tel No: ++ 44 870 1200 208 Fax No: ++ 44 870 1200 209



Tel No: ++ 44 8701 200 208



ESTONIA - Farnell

Tel No: ++ 358 9 560 7780 Fax No: ++ 358 9 345 5411



ISRAEL - Farnell

Tel No: ++ 180 937 0015 Fax No: ++ 180 937 0014



SINGAPORE -

Tel No: ++ 65 6788 0200 Fax No: ++ 65 6788 0300 http://www.farnell.com http://www.newark.com

http://www.cpc.co.uk

Disclaimer This data sheet and its contents (the "Information") belong to the Premier Farnell Group (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The information is subject to change without notice and replaces all data sheets previously supplied. The information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. SPC Multicomp is the registered trademark of the Group. © Premier Farnell plc 2008.

