

MMB ASYNCHRONOUS MOTORS CATALOGUE





Operating Conditions

Ambient temperature: $-15^{\circ}\text{C} \leq 0 \leq 40^{\circ}\text{C}$

Altitude: not exceeding 1000m

Rated voltage: 380V or any voltage between 220–760V

Rated frequency: 50Hz、60Hz

Protection class: IP55

Insulation class: F、H

Cooling method: ICO141

Duty: S1(continuous)

Connection: Star-connection for up to 3kw,
delta-connection for 4kw and above.

Adopting the national uniform design, MT series high efficiency three-phase asynchronous motor, are conformity with ICE34- 1 and JB/T8680-1998 standards, also up to the international advanced level 90's as substitute of MT series induction motors, It possesses sophisticated features such as new structure, good appearance, slight vibration, low noise etc

Type	Output		Full Load				Ist/TN	Tst/TN	Tmax/TN
	KW	HP	r/min	IN(A)	η (%)	(cos ^φ)			Tmax/TN
Synchronous Speed 3000									
MT-63M1-2	0.18	0.25	2720	0.53	65	0.80	5.5	2.2	2.2
MT-63M2-2	0.25	0.34	2720	0.69	68	0.81	5.5	2.2	2.2
MT-71M1-2	0.37	0.5	2740	0.99	70	0.81	6.1	2.2	2.2
MT-71M2-2	0.55	0.75	2740	1.4	73	0.82	6.1	2.2	2.3
MT-80M1-2	0.75	1	2835	1.83	77.4	0.83	6.1	2.2	2.3
MT-80M2-2	1.1	1.5	2835	2.58	79.6	0.84	7	2.2	2.3
MT-90S-2	1.5	2	2845	3.43	81.3	0.84	7	2.2	2.3
MT-90L-2	2.2	3	2845	4.85	83.2	0.85	7	2.2	2.3
MT-100L-2	3	4	2875	6.31	84.6	0.87	7.5	2.2	2.3
MT-112M-2	4	5.5	2895	8.1	85.8	0.88	7.5	2.2	2.3
MT-132S1-2	5.5	7.5	2905	11	87	0.88	7.5	2.2	2.3
MT-132S2-2	7.5	10	2905	14.9	88.1	0.88	7.5	2.2	2.3
MT-160M1-2	11	15	2935	21.3	89.4	0.89	7.5	2.2	2.3
MT-160M2-2	15	20	2935	28.8	90.3	0.89	7.5	2.2	2.3
MT-160L-2	18.5	25	2935	34.7	90.9	0.90	7.5	2.2	2.3
MT-180M-2	22	30	2945	41	91.3	0.90	7.5	2	2.3
MT-200L1-2	30	40	2955	55.5	92	0.90	7.5	2	2.3
MT-200L2-2	37	50	2955	67.9	92.5	0.90	7.5	2	2.3
MT-225M-2	45	60	2975	82.3	92.9	0.90	7.5	2	2.3
MT-250M-2	55	75	2975	101	93.2	0.90	7.5	2	2.3
MT-280S-2	75	100	2975	134	93.8	0.90	7.5	2	2.3
MT-280M-2	90	125	2975	160	94.1	0.91	7.5	2	2.3
MT-315S-2	110	150	2980	195	94.3	0.91	7.1	1.8	2.2
MT-315M-2	132	180	2980	233	94.6	0.91	7.1	1.8	2.2
MT-315L1-2	160	200	2980	279	94.8	0.92	7.1	1.8	2.2
MT-315L2-2	200	270	2980	348	95	0.92	7.1	1.8	2.2
MT-355M-2	250	340	2980	433	95	0.92	7.1	1.6	2.2
MT-355L-2	315	430	2980	544	95	0.92	7.1	1.6	2.2
MT-400M1-2	355	475	2975	618	95.9	0.91	5.8	1.23	2.53
MT-400M2-2	400	535	2982	689	96	0.92	5.74	1.31	2.43
MT-400M3-2	450	600	2982	775	96.1	0.92	7.27	1.83	2.98
MT-400L1-2	500	670	2982	853	96.3	0.92	6.14	1.2	2.9
MT-400L2-2	560	750	2982	952	96.3	0.92	5.46	0.98	2.57
Synchronous Speed 1500									
MT-63M1-4	0.12	0.17	1310	0.44	57	0.72	4.4	2.1	2.2
MT-63M2-4	0.18	0.25	1310	0.62	60	0.73	4.4	2.1	2.2
MT-71M1-4	0.25	0.34	1330	0.79	65	0.75	5.2	2.1	2.2
MT-71M2-4	0.37	0.5	1330	1.12	67	0.74	5.2	2.1	2.2
MT-80M1-4	0.55	0.75	1395	1.57	71	0.75	5.2	2.4	2.3
MT-80M2-4	0.75	1	1395	2.03	79.6	0.76	6	2.3	2.3
MT-90S-4	1.1	1.5	1405	2.89	81.4	0.77	6	2.3	2.3
MT-90L-4	1.5	2	1405	3.7	82.8	0.79	6	2.3	2.3
MT-100L1-4	2.2	3	1435	5.16	84.3	0.81	7	2.3	2.3
MT-100L2-4	3	4	1435	6.78	85.5	0.82	7	2.3	2.3
MT-112M-4	4	5.5	1445	8.8	86.6	0.82	7	2.3	2.3
MT-132S-4	5.5	7.5	1445	11.7	87.7	0.83	7	2.3	2.3
MT-132M-4	7.5	10	1445	15.6	88.7	0.84	7	2.3	2.3
MT-160M-4	11	15	1460	22.3	89.8	0.84	7	2.2	2.3
MT-160L-4	15	20	1460	30.1	90.6	0.85	7.5	2.2	2.3
MT-180M-4	18.5	25	1470	36.5	91.2	0.86	7.5	2.2	2.3
MT-180L-4	22	30	1470	43.2	91.6	0.86	7.5	2.2	2.3
MT-200L1-4	30	40	1470	57.6	92.3	0.86	7.2	2.2	2.3
MT-225S-4	37	50	1485	69.9	92.7	0.87	7.2	2.2	2.3
MT-225M-4	45	60	1485	84.4	93.1	0.87	7.2	2.2	2.3
MT-250M-4	55	75	1485	103	93.5	0.87	7.2	2.2	2.3
MT-280S-4	75	100	1485	140	94	0.87	7.2	2.2	2.3
MT-280M-4	90	125	1490	167	94.2	0.87	7.2	2.2	2.3
MT-315S-4	110	150	1490	201	94.5	0.88	6.9	2.1	2.2
MT-315M-4	132	180	1490	240	94.7	0.88	6.9	2.1	2.2
MT-315L1-4	160	200	1490	287	94.9	0.89	6.9	2.1	2.2
MT-315L2-4	200	270	1490	359	95.1	0.89	6.9	2.1	2.2
MT-355M-4	250	340	1485	443	95.1	0.90	6.9	2.1	2.2
MT-355L-4	315	430	1485	556	95.1	0.90	6.9	2.1	2.2
MT-400M1-4	355	475	1490	641	95.5	0.88	6.5	2.6	1.93
MT-400M2-4	400	535	1490	723	95.5	0.88	6.5	2.75	1.8
MT-400M3-4	450	600	1490	804	95.5	0.89	6.5	2.81	2.03
MT-400L1-4	500	670	1490	893	95.6	0.89	6.61	2.52	1.83
MT-400L2-4	560	750	1490	971	96.0	0.89	6.6	2.67	2.02