

# DS-2CD3132-I(3MP)


## IR Fixed Dome Network Camera



### Key features

- 3MP high resolution
- HD real-time video
- 3D DNR & DWDR & BLC
- IR LEDs: up to 30m
- IP66
- IK08
- PoE

### Dimensions



### Accessories



DS-1272ZJ-110  
Wall mounting



DS-1259ZJ  
Inclined ceiling mount

DS-2CD3132-I	
Camera	
Image sensor	1/3" progressive scan CMOS
Min. illumination	0.07 lux @F1.2, AGC ON, 0 lux with IR
Shutter time	1/25s ~ 1/100,000s
Lens	4mm@ F2.0 (2.8mm, 6mm, 12mm optional) 2048 × 1536: Angle of view: 86°(2.8mm), 70°(4mm), 43.3°(6mm), 20.6°(12mm) 1920 × 1080: Angle of view: 98.5°(2.8mm), 79°(4mm), 49°(6mm), 23.2°(12mm)
Lens mount	M12
Angle adjustment	Pan: 0° ~ 355°, tilt: 0° ~ 65°
Digital noise reduction	3D DNR
Wide dynamic range	Digital WDR
Day & night	IR cut filter with auto switch
Compression Standard	
Video compression	H.264 / MJPEG
H.264 codec profile	Main profile
Bit rate	32 Kbps ~ 12 Mbps
Dual stream	Yes
Image	
Max. Image Resolution	2048 × 1536
Frame rate	50Hz: 20fps (2048 × 1536), 25fps (1920 × 1080), 25fps (1280 × 720) 60Hz: 20fps (2048 × 1536), 30fps (1920 × 1080), 30fps (1280 × 720)
Image settings	Rotate mode, Saturation, brightness, contrast, sharpness adjustable through client software or web browser
BLC	Yes, zone configurable
ROI	Support
Network	
Network storage	NAS (support NFS, SMB/CIFS)
Alarm trigger	Line Crossing, Intrusion Detection, Motion detection, Tampering alarm, Storage exception
Protocols	TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, PPPoE, NTP, UPnP, SMTP, SNMP, IGMP, 802.1X, QoS, IPv6, Bonjour
System compatibility	OINVIF(PROFILE S, PROFILE G), PSIA, CGI, ISAPI
General functionalities	User authentication, watermark
Interface	
Communication interface	1 RJ45 10 M / 100 M Ethernet interface
General	
Operating conditions	-30 °C ~ 60 °C (-22°F ~ 140 °F) humidity 95% or less (non-condensing)
Power supply	12 VDC ± 10%, PoE (802.3af)
Power consumption	Max. 5W (max. 7W with ICR on)
Impact protection	IK08
Ingress protection	IP66
IR range	Approx. 10 to 30 meters
Dimensions	Φ111 × 82 (4.4" × 3.2")
Weight	500g (1.1 lb)