

Exercise 2 Linux

Linux New Commands:

sudo useradd -m -d /home/username username: adds a new user to the system and sets the directory to home

sudo groupadd groupname: adds a new group to the system

sudo usermod -aG groupname username: adds a username to a group name

sudo userdel username: to delete a user from the system

sudo groupdel groupname: to delete a group from the system

passwd: creates a new (changes) password for the current logged in user

su: allows you to switch user, when you write su only it makes you switch to the root user, but if you write su and a specific user name it gives you the ability to switch to this user.

who: which user are we logged in as right now

whoami: which user am I right now

groups: which groups does the current user belong to right now

Questions & Answers:

Q: Which command can you use to display the users currently logged in on the Linux/Unix system?

A: who

Q: which configuration files list the authorized users and groups on the system! And how the files are structured.

A: /etc/passwd: Contains information about all user accounts on the system. Every line represents one user. First it would be the username then the password which is usually X then the userID then the groupID then the name of the user, the current directory and the shell directory

/etc/shadow: Stores the passwords for the users, it has first the username then the password, last_change, Days since Jan 1, 1970 password was last changed. Min, Minimum days before password change allowed. Max, Maximum days password is valid.

Warn, Days before expiration to warn user. Inactive, Days after expiration before account disabled. Expire, Absolute expiration date (days since Jan 1, 1970).

/etc/group: Contains all groups on the system, including primary and supplementary groups. Group name, password, group id, users list.

/etc/gshadow: contains all the passwords for the corresponding groups.
group_name:password:group_admins:group_members