

BINF 5007

# Lecture 11: BioPython



- Biopython is a package of freely available Python tools for (mostly) genomic data.
- Motivation: dealing with sequences as text requires a lot of explicit manipulation and coding, and much of that code could be reused in other biomolecular computations.
- Well documented:  
[biopython.org](http://biopython.org)  
[Biopython Tutorial and Cookbook](#)
- Latest release is Biopython 1.85 (Jan 15, 2025)  
Requires Python version 3.6 or higher.

## Learning Objects

1. Understand Sequence Manipulations in Biopython:
  - Perform translation and transcription of nucleotide sequences.
  - Work with sequence annotations, locations, and features.
2. Work with `SeqRecord` Objects:
  - Create and manage `SeqRecord` objects, including adding metadata and annotations.
3. Handle Multiple Sequences Using `Bio.SeqIO`:
  - Read and parse multiple sequences from biological data files using `Bio.SeqIO`.
  - Write sequences back into standard formats such as FASTA.
4. Parse and Filter Biological Data:
  - Parse and filter sequences from a FASTA file while excluding invalid or empty entries.
  - Monitor and optimize memory usage during file parsing and sequence processing.
5. Read and Write Biological Data Files:
  - Understand the process of reading and writing various biological data formats efficiently.

# Sequences in BioPython

## Working with Sequences

Biopython has Seq objects, whose definition are in the submodule Bio.Seq.

They are essentially strings with some extra methods.

```
>>> from Bio.Seq import Seq
>>> seq = Seq('AGTACACTGTAG')
>>> type(seq) Bio.Seq.Seq
>>> seq
Seq('AGTACACTGTAG')
>>> print(seq)
AGTACACTGTAG

>>> seq.complement()
TCATGTGACATC

>>> seq.reverse_complement()
CTACAGTGTACT
```

*Note: earlier versions of Biopython (<=1.77) used the concept of an Alphabet object that was always associated with any sequence. Newer version do not; in those cases where it matters, functions will have additional arguments to indicate whether it is a “DNA”, “RNA” or “protein” sequence.*

## Sequences are like strings

Almost all string manipulations are possible with Seq.

For example:

```
>>> seq = Seq('AGTACACTGTAG')
>>> seq[0:4]
Seq('AGTA')

>>> seq*2
Seq('AGTACACTGTAGAGTACACTGTAG')

>>> seq.find("ACA")
3

>>> seq.split("ACA")
[Seq('AGT'), Seq('CTGTAG')]
```

For any string manipulation that might not work for Seq, you can always convert the Seq to a string:

```
>>> seq = Seq('AGTACAcTGGTAG')
>>> seq.isupper()
AttributeError - Traceback (most recent call last)
...
AttributeError: 1Seq1 object has no attribute 1isupper1
>>> str(seq).isupper()
False
```

## Transcription and Translation

Biopython knows how to transcribe DNA to RNA and translate it to protein sequences.

```
>>> seq = Seq('AGTACACTGTAG')
>>> rna = seq.transcribe()    # assumes sequence is coding dna
>>> rna
Seq('AGUACACUGUAG')
```

```
>>> prot = seq.translate()    # assumes sequence is coding dna or rna
>>> prot
Seq('STL*')
```

This uses a one-letter alphabet for the protein sequence. If you want the 3-letter abbreviation, you can use:

```
>>> from Bio.SeqUtils import seq3
>>> seq3(prot)
SerThrLeuTer
```

The Seq object does not distinguish the kind sequence, so sometimes we need to be specific, e.g.

```
>>> from Bio.SeqUtils import molecular_weight
>>> molecular_weight(seq)
3749.40220000000004
>>> molecular_weight(prot[:-1])
ValueError: 1S1 is not a valid unambiguous letter for DNA
>>> molecular_weight(prot[:-1], "protein")
9.3541
```



**SeqRecord**

## Annotation, locations, features

The SeqRecord provides a standard way to add information to a sequence. It contains:

- `.seq`

The sequence itself, typically a Seq object.

- `.id`

The primary ID (a string) to identify the sequence. In most cases something like an accession number.

- `.name`

A “common” name/id for the sequence.

- `.description`

A human readable description or expressive name for the sequence.

- `.letter_annotations`

A dict of information about the letters in the sequence. Keys are the name of the information, and the information is as a Python sequence with the same length as the sequence. Used for quality scores, secondary structure, . . .

- `.annotations`

A dict additional information about the sequence.

- `.features`

A list of SeqFeature objects with more structured information about the features on a sequence. o

- `.dbxrefs`

A list of database cross-references as strings.

## Creating SeqRecords

You can create [SeqRecords](#) yourself, e.g.

```
>>> from Bio.Seq import Seq
>>> from Bio.SeqRecord import SeqRecord
>>> seq = Seq('AGTACACTGTAG')
>>> seqrec = SeqRecord(seq)
```

You do not need to provide all the data at creation time, you can fill those in later:

```
>>> seqrec.id = 'ABCDEFGF'
>>> seqrec.description = ' Nonsensical sequence'
>>> seqrec
SeqRecord(seq=Seq('AGTACACTGTAG'), id='ABCDEFGF', name='<unknown name>', description='Nonsensical sequence', dbxrefs=[])
>>> print(seqrec)
ID: ABCDEFG
Name: <unknown name>
Description: Nonsensical sequence
Number of features: 0
Seq('AGTACACTGTAG')
```

More commonly, you'll get the SeqRecord information from a data file that Biopython can read in for you, filling in the information into SeqRecords using [Bio.SeqIO](#) .

# Bio.SeqIO

- **Bio.SeqIO** aims to provide a simple uniform interface to input and output of **sequence file formats**.
- It always returns SeqRecord's.
- Can deal with files containing multiple sequences.
- Many file formats are supported:  
abi ace clustal fasta fastq genbank ...
- <https://biopython.org/wiki/SeqIO>

## Example: Reading a FASTA file into a SeqRecord

```
>>> from Bio import SeqIO
>>> record = SeqIO.read("chromosome1.fa", "fasta")
>>> type(record)
<class 'Bio.SeqRecord.SeqRecord'>
>>> print(record)
ID: 1
Name: 1
Description: 1 dna:chromosome chromosome:Galgal4:1:1:195276750:1 REF
Number of features: 0
Seq('CCGACCAGTTGTA ACTCAAAAACCAAAGAAACGCAGGACAGGCCA
GCGGGGCT...GGA')
```

```
>>> # Do something with the sequence:
>>> record.seq.count("ACT")
331810
```

## Reading multiple sequences with Bio.SeqIO

If a file contains multiple sequences, you can read them one by one using the `Bio.SeqIO.parse` function. This function returns a `SeqRecord iterator`, which allows you to go over the list of sequences in the file.

### *Example*

```
>>> from Bio import SeqIO
>>> parser = SeqIO.parse("egg1.mfa", "fasta")
>>> for seqrec in parser:
...     print(seqrec.description, len(seqrec.seq))
...
sample 1 fragment 0 232
sample 1 fragment 1 235
sample 1 fragment 2 123
...
sample 1 fragment 46 168
>>>
```

## Writing Sequences with Bio.SeqIO

You can write one or a list of sequences to a file as well.

For instance, suppose we wanted a file with only long reads:

```
>>> from Bio import SeqIO
>>> parser = SeqIO.parse("egg1.mfa", "fasta")
>>> longseqrecs = []
>>> for seqrec in parser:
...     if len(seqrec.seq) > 200:
...         longseqrecs.append(seqrec)
```

We can write this to a new file using SeqIO.write:

```
>>> SeqIO.write(longseqrecs, "longegg1.mfa", "fasta")
```

You can of course also write just one sequence, e.g.

```
>>> SeqIO.write(SeqRecord(Seq("ATCGTACC")), "example.fa", "fasta")
```

Instead of filenames, you can also use Python file handles.

## Your Turn

```
from Bio import SeqIO
from memory_profiler import memory_usage
# pip3 install memory_profiler

def retseq(seqfh):
    """ Parse a fasta file and store non empty records
        into the fullseqs list.
    """

    # Empty list to store good sequences
    fullseqs = []
    for record in SeqIO.parse(seqfh, 'fasta'):
        if len(record.seq) != 0:
            fullseqs.append(record)

    seqfh.close()
    return fullseqs

print(f'Memory usage to start: {memory_usage()}MB')
# Name of the input file
fh = open('../assignment3/influenza.fasta')
# Name of the output file
newfh = open('test.fasta', 'w')
seqs = retseq(fh)
SeqIO.write(seqs, newfh, 'fasta')
newfh.close()
print(f'Memory usage after: {memory_usage()}MB')
```

Although this program does its job, it is not an example of efficient use of computer resources

The list `fullseqs` ends up with the information on every non-empty sequence in the file

For short sequence files this is not noticeable. In a realistic scenario, an input file of 100 Gigabytes can be very problematic!