Typical Athletic Field System Specifications

PES Field Systems delivers internationally patented, self-contained athletic field solutions engineered for safety, durability, and superior play. Designed to reduce long-term maintenance and replacement costs, these systems support traditional and non-traditional athletes alike.

Underdrain Layer

• Series of parallel shallow trenches excavated within the entire proposed turfed area(s).

• Non-woven fabric placed within underdrain trenches.

• 4-inch diameter perforated PVC SDR35 pipe.

• Washed limestone or equivalent used to backfill around perforated pipe.

Trunk Line

• 6-inch diameter solid PVC SDR35 pipe connected to each 4-inch underdrain pipe.

• Washed limestone or equivalent to backfill around PVC solid pipe.

• Alignment per Owner-approved discharge location.

• No. 8 stone or equivalent used to backfill around solid PVC pipe.

Drainage Stone Base

• Washed limestone installed across the entire proposed turfed area(s).

• System engineered to achieve proper finished playing surface elevation and grade.

Head Impact Coefficient (HIC) Layer

• 1.0" to 2.0" HIC layer composed of SBR granular rubber and EPDM.

• Polyurethane base binder enhances shock absorption and player safety.

Nylon Field Turf System

- Owner-selected turf color options available.
- ¼" layer of patented sand mixture used for turf infill to enhance performance and longevity.

All PES Field Systems are designed and installed with a commitment to safety, environmental responsibility, and professional execution. Specifications may be customized to meet project-specific requirements.