ПРОТОКОЛ ЗА КОМУНИКАЦИЯ МЕЖДУ PAYMENT BRIDGE И ПЕРСОНАЛЕН КОМПЮТЪР

V1.2026	ПРОТОКОЛ ЗА КОМУНИКАЦИЯ МЕЖДУ PAYMENT BRIDGE И ПЕРСОНАЛЕН КОМПЮТЪР

Версии

Версия	***Дата***	***Описание***
v.1.2026	01.03.2026	Начална версия

1. Въведение

Payment bridge изпълнява командите, изпращани от PC и връща съобщение, зависещо от изпълнението на командата. До PC се изпращат само съобщения, които са резултат от получените команди. Всички данни се предават към ФУ и се получават в отговор съгласно протокола формат json.

2. Формат на съобщенията

Всички съобщения се изпращат във формат json и ФУ отговаря в същия формат.

3. Списък с основни команди към payment bridge

Име	**Информация**
payment_request	**Request за иницииране на плащане (dsk, viva)**
check_status	**Request за взимане на статус (dsk, viva)**

4. payment_request

Request params

Param	*Description*	*Type*	*Required*
operation	**operatiorLogin - string**	**String**	**YES**
bank	**Bank key name (“dsk” или “viva”)**	**String**	**YES**
payload	**Масив от данни за транзакцията**	**Array**	**YES**

Request params for payload

Param	*Description*	*Type*	*Required*
reference_id	**Референтен номер от софтуера**	**String**	**YES**
currency	**Валута 3 буквен стандарт EUR**	**String**	**YES**
amount	**Сума**	**float**	**YES**
tip	**Бакшиш само за VIVA или 0.00**	**float**	**YES**
description	**Описание на транзакцията**	**string**	**YES**

Example:

```
{
  "operation": "payment_request", // required
  "bank": "dsk", // required
  "payload": {
    "reference_id": "INV123456", // required
    "currency": "BGN", // required
    "amount": 42.50, // required
    "tip": 2.50,
    "description": "Плащане на фактура 123456"
  }
}
```

JSON Response on success

Response	*Description*	*Type*	*Required*
status		**Array**	**YES**

5. check_status

Request params

Param	*Description*	*Type*	*Required*
operation	check_status	**String**	**YES**
bank	**Bank key name (“dsk” или “viva”)**	**String**	**YES**
payload	**Масив от данни за транзакцията**	**Array**	**YES**

Request params for payload

Param	*Description*	*Type*	*Required*
reference_id	**Референтен номер от софтуера**	**String**	**YES**

Example:

```
{
  "operation": "check_status", // required
  "bank": "dsk", // required
  "payload": {
    "reference_id": "INV123456", // required
  }
```

```
}
```

JSON Response on success

Response	*Description*	*Type*	*Required*
status	SUCCESS REJECTED NOT_FOUND FAILED	**text**	**YES**
reference_id	**Подадения reference**		
transaction_details	**Данни за транзакцията**		
receipt	**Данни за печат на бележка от транзакция**		
error_code	required if transaction was not attempted/approved		**YES**
message	Transaction was approved, // required		**YES**
timestamp	"2025-05-07T13:45:00Z", // required		**YES**

Structure transaction_details

Param	*Description*	*Type*	*Required*
amount	**Сума**	**float**	**YES**

rrn	“REF123456”, // required if available in the transaction response		**NO**
currency			**YES**
card_type	”VISA”, // required if available in the transaction response		**NO**
masked_pan	“**** **** **** 1234”, // required if available in the transaction response		**NO**
stan	“STAN123456”, // required if available in the transaction response		**NO**
verification_method	CONTACTLESS”, // required if available in the transaction response		**NO**
authorisation_code	“AUTH123456”		**NO**
aid	AID123456”, // required if available in the transaction response		**NO**
order_code	“OC123456”, // required if available in the transaction response		**NO**

Structure receipt one element of array

Param	***Description***	***Type***	***Required***
text1	**Текст от ляво**	**String**	**YES**
align	Left_right, left,right	**String**	**YES**
text2	**Текст от дясно**	**String**	**NO**

Example:

```
{
  "status": "success",
  "reference_id": "INV123456", // required if transaction was attempted successfully
  "transaction_details": { // required if transaction was attempted successfully
    “amount”: 45.00, // required if transaction was attempted successfully
    “rrn”: “REF123456”, // required if available in the transaction response
    “currency”: ”BGN”, // required if available in the transaction response
    “card_type”: ”VISA”, // required if available in the transaction response
    “masked_pan”: “**** **** **** 1234”, // required if available in the transaction response
    “stan”: “STAN123456”, // required if available in the transaction response
```

```
    “verification_method”: “CONTACTLESS”, // required if available in the transaction response
    “authorisation_code”: “AUTH123456”, // required if available in the transaction response
    “aid”: “AID123456”, // required if available in the transaction response
    “order_code”: “OC123456”, // required if available in the transaction response
  },
  “receipt”: [  {
      "text1": "+359123456789",
      "align": "left"
    },
    {
      "text1": "TERMINAL_ID:",
      "align": "left_right",
      "text2": "12345678"
    },
  ]
  "error_code": 10, // required if transaction was not attempted/approved
  "message": "Transaction was approved", // required
  "timestamp": "2025-05-07T13:45:00Z", // required
}
```

6. Заключителни бележки

Сървера Payment Bridge трябва да бъде предварително инсталиран и конфигуриран на съответния порт.