BEU CONNECT

Bihar Engineering University, Patna

B.Tech 6th Semester Exam., 2026

Code: 105601		***Time: 03 Hours***
Semester: VI	***Subject: Compiler Design***	***Full Marks: 70***

Instructions:-

(i) The marks are indicated in the right-hand margin.
(ii) There are NINE questions in this paper.
(iii) Attempt FIVE questions in all.
(iv) Question No. 1 is compulsory.

Q.1 Choose the correct option / answer the following (Any seven question only): **[2 x 7 = 14]**

(a) Consider the statement: int total = 25; Which of the following represents a lexeme?
(i) int
(ii) 25
(iii) total
(iv) All of the Above

(b) The regular expression (a|b)* represents:
(i) Strings containing only a
(ii) Strings containing only b
(iii) All strings over {a,b}, including ε
(iv) Strings beginning with ab

(c) Which of the following is a problem for a top-down parser?
(i) Left recursion
(ii) Right recursion
(iii) Ambiguity only
(iv) Bottom-up derivation

(d) In bottom-up parsing, the parser constructs:
(i) Leftmost derivation
(ii) Rightmost derivation
(iii) Reverse of a rightmost derivation
(iv) Leftmost derivation in reverse

(e) Consider a symbol table implemented using hashing with table size 10. For key 27, using h(k) = k mod 10, the initial position is:
(i) 5
(ii) 7
(iii) 6
(iv) 8

(f) Under static scoping, the meaning of a variable reference is determined primarily by:
(i) Runtime call sequence
(ii) CPU register contents
(iii) Heap location
(iv) Lexical program structure

(g) Which optimization eliminates repeated computation of the same expression?
(i) Loop interchange
(ii) Dead-code elimination only
(iii) Common subexpression elimination
(iv) Register allocation

(h) Which pipeline hazard occurs when an instruction depends on the result of a previous instruction?
(i) Structural hazard
(ii) Data hazard
(iii) Syntax hazard
(iv) Memory hazard

(i) Dynamic method dispatch is primarily used to implement:
(i) Lexical analysis
(ii) Constant folding
(iii) Runtime polymorphism
(iv) Register allocation

(j) Which statement is true regarding DFA and NFA?
(i) NFA is strictly more powerful than DFA
(ii) DFA and NFA recognize the same class of languages
(iii) DFA is strictly more powerful than NFA
(iv) Every NFA requires more states than every equivalent DFA

BEU CONNECT
LEARN • GROW • SUCCEED
Your Engineering Journey, Simplified
PYQs • SYLLABUS • RESULTS
AI DOUBT SOLVER • ATTENDANCE • GATE MOCK TESTS
Free • Fast • Made by students
GET IT ON Google Play
Scan QR to download
Search BEU Connect on Play Store

BEU CONNECT

Q.2 Solve both questions : **[7 x 2 = 14]**

(a) Explain the different phases of compilation with a suitable example. Show the input and output produced at each phase.

(b) Construct a DFA over {0,1} that accepts all strings containing an even number of 0s and an odd number of 1s. Verify the constructed DFA using suitable accepted and rejected input strings.

Q.3 Solve both questions : **[7 x 2 = 14]**

(a) For a lexical analyzer, design regular expressions to recognize the following token classes:
(i) Identifiers beginning with a letter and containing letters and digits thereafter.
(ii) Unsigned integer constants.
(iii) Relational operators <, <=, >, >=, ==, and !=.

(b) Consider the grammar:
$S \rightarrow ABC$
$A \rightarrow aA \mid \varepsilon$
$B \rightarrow bB \mid \varepsilon$
$C \rightarrow cC \mid d$
Compute the FIRST and FOLLOW sets for all non-terminals. Using these, construct the LL(1) parsing table. Use the parsing table to show the parsing steps for the input string “aabd”.

Q.4 Solve both questions : **[7 x 2 = 14]**

(a) Explain ambiguity in context-free grammars. Illustrate how ambiguity can lead to shift-reduce or reduce-reduce conflicts during LR parsing.

(b) Construct a transition diagram for the Pushdown Automaton for the language:
$L = \{wcw^R \mid w \in \{a,b\}^*\}$

Q.5 Solve both questions : **[7 x 2 = 14]**

(a) Explain the structure of an activation record and its role during procedure execution.

(b) Discuss the structure of a symbol table and the information stored for each identifier.

Q.6 Solve both questions : **[7 x 2 = 14]**

(a) Generate the three-address code for the following expression. Then represent the generated code using quadruple, triple, and indirect-triple representations.
x=a*(b+c)−d/e

(b) Explain the construction of basic blocks and control-flow graphs (CFGs) in compiler design using a suitable three-address code example.

Q.7 Solve both questions : **[7 x 2 = 14]**

(a) Explain cache locality and its importance in loop optimization.

(b) Explain the major stages involved in target code generation in a compiler. Discuss instruction selection, register allocation, and instruction scheduling, and explain how each stage contributes to generating efficient target machine code.

Q.8 Solve both questions : **[7 x 2 = 14]**

(a) Discuss the major challenges involved in compiling object-oriented features such as classes, inheritance, and polymorphism.

BEU CONNECT
LEARN • GROW • SUCCEED
Your Engineering Journey, Simplified
PYQs • SYLLABUS • RESULTS
AI DOUBT SOLVER • ATTENDANCE • GATE MOCK TESTS
Free • Fast • Made by students
GET IT ON Google Play
Scan QR to download
Search BEU Connect on Play Store

BEU CONNECT

(b) Consider the following grammar:

E → E + T | T

T → T * F | F

F → digit

Define suitable synthesized attributes to evaluate an arithmetic expression. Construct the annotated syntax tree and evaluate the following expression:

3 + 5 * 2

Q.9 Write a short note on any two of the following: **[7 x 2 = 14]**

(a) SLR(1) parser

(b) Syntax Directed Definition

(c) peep-hole optimization

(d) Attribute grammar

BEU CONNECT

BEU CONNECT
LEARN • GROW • SUCCEED
Your Engineering Journey, Simplified
PYQs • SYLLABUS • RESULTS
AI DOUBT SOLVER • ATTENDANCE • GATE MOCK TESTS
Free • Fast • Made by students
GET IT ON Google Play
Scan QR to download
Search BEU Connect on Play Store