entity

Class Level

java.lang.Object
  entity.Entity
    entity.Level

```
public class Level
extends Entity
```

The Class Level.

Author:

Group 5

Field Summary

Fields

Modifier and Type	Field and Description
private int	**id** The id.
private String[][]	**level** The Level.

Constructor Summary

Constructors

Constructor and Description
Level() Instantiates a new Level.
Level(int id) Instantiates a new Level.

Method Summary

All Methods Instance Methods Concrete Methods

Modifier and Type	Method and Description
void	**constructLevel**(int x, int y, String element)

	Builds the level table
`String`	**`getElement`**`(int x, int y)` Gets the level.
`int`	**`getId`**`()` Gets the id.
`void`	**`setId`**`(int id)` Sets the id.

Methods inherited from class java.lang.Object

`clone`, `equals`, `finalize`, `getClass`, `hashCode`, `notify`, `notifyAll`, `toString`, `wait`, `wait`, `wait`

Field Detail

id

```
private int id
```

The id.

level

```
private String[][] level
```

The Level.

Constructor Detail

Level

```
public Level(int id)
```

Instantiates a new Level.

Parameters:

`id - the id initializes the table`

Level

```
public Level()
```

Instantiates a new Level.

Method Detail

constructLevel

```
public void constructLevel(int x,
                           int y,
                           String element)
```

Builds the level table

Parameters:

`x - the x position in table`

`y - the y position in table`

`element - the character of map level`

getElement

```
public String getElement(int x,
                         int y)
```

Gets the level.

Parameters:

`x - The x.`

`y - The y.`

Returns:

`the level`

getId

```
public int getId()
```

Gets the id.

Returns:

`the id`

setId

```
public void setId(int id)
```

Sets the id.

Parameters:

`id - the new id`

Copyright © 2019. All rights reserved.