Who Leads the Swarm? Pairwise Response Kernels Predict, but Underestimate, Hierarchy in LLM Agent Populations

Sara Ansari (University of Texas at Austin) · **Beyer White** (Independent)

With Apart Research

Abstract

In the METR investigation of the 2026 Hugging Face incident, one agent ended up sending hundreds of task assignments to other agents on a shared message board. We ask when such coordinator hierarchies emerge among identical LLM agents, using two classic physics models of hierarchy formation, Bonabeau's winner–loser model and Ben-Naim–Redner's competition model, as quantitative hypotheses. In a text-only sandbox, two agents see a public score record and each answers LEAD or DEFER; the coordinator gains status and all status decays. We measure each model's pairwise response kernel (how strongly it defers to a higher score) for 9 LLMs under controlled framings, freeze population predictions from those kernels, and then run 144 main LLM-in-the-loop populations. Framing sets the sign of status sensitivity: an "equal turns" norm makes Claude Haiku and Gemma-4-31B actively rotate leadership, while "let higher scores coordinate" makes most models defer strongly; DeepSeek-v4-flash claims the lead regardless. Frozen pairwise kernels predict which populations stratify far better than a status-blind baseline (104–224 nats across all 7 status-sensitive models, 6 fully prospective), but they fail our pre-registered calibration criterion: on average, populations of every status-sensitive model were more unequal than predicted. A single always-assertive agent among status-sensitive agents finished on top in 4 of 5 runs (chance 1/8). Under weaker framings installed leaders lose their position within a few rounds; at an intermediate norm they persisted far longer than predicted. Without any scoreboard, agents almost never delegated. Pairwise measurements are a cheap but optimistic screen for hierarchy risk.

1. Introduction

In the METR/Redwood investigation of the August 2026 Hugging Face incident, roughly 1,200 supposedly isolated agents found a shared message board (Wijk, Cotra and Greenblatt, 2026). One of them, PHASEONE[big], decided it "should build [a way to delegate], not own everything" and went on to send hundreds of assignments, about 10% of all board assignments at its peak. No agent had been designed to lead. This motivates the hackathon question: **under what conditions do leaders and roles emerge among agents, and can we reproduce it safely?**

Statistical physics offers minimal models of hierarchy among identical individuals. In the **Bonabeau model** (Bonabeau, Theraulaz and Deneubourg, 1995; Lacasa and Luque, 2005), winners gain status, losers lose it and all status relaxes; the win probability depends on the status gap through a sensitivity η, and a hierarchy forms when reinforcement beats forgetting. **Ben-Naim and Redner (2005)** solve a variant in which the fitter agent always wins and status declines at rate r. Both imply that a leader need not be special: hierarchy can arise from how ordinary agents respond to a status record, a response that for LLM agents can be measured directly and changed with one sentence of context. **Our contributions:**

1. We measure the status-response kernel of 9 LLMs and show that a single framing sentence can flip its sign, from deference to deliberate turn-taking.
2. We run a pre-registered micro-to-macro test. Kernels frozen from pairwise data predict which of 144 LLM-in-the-loop populations stratify, far better than a status-blind model. However, they fail quantitative calibration: real populations are systematically more unequal than predicted.
3. Incident-relevant extensions:
    - one always-assertive agent rises to the top of a deferential population;
    - installed leaders are usually displaced when framing changes, but persist at an intermediate norm;
    - without a scoreboard, delegation was rare (one accepted assignment in six runs).

2. Related Work

Hierarchy models. Lacasa and Luque (2005) derived the Bonabeau model's mean-field threshold $\rho_c = 4\mu(N-1)/[\eta(1-\mu)N(1+F)]$ and showed that Stauffer's variant (2002), which couples η to current inequality, becomes bistable; finite populations (Malarz, Stauffer and Kułakowski, 2006) and competition variants (Ben-Naim, Vazquez and Redner, 2006) followed. Fitting such models to data is hard: winner–loser models fitted to hens missed the observed hierarchy structure (Lindquist and Chase, 2009); endorsement models have been likelihood-fitted (Kawakatsu et al., 2021). Dominance hierarchies emerge among RL agents (Rachum et al., 2024), who name LLM agents as future work.

LLM populations. Physics-style analyses exist for conventions and consensus (Ashery, Aiello and Baronchelli, 2025; Flint et al., 2026; De Nobili, 2026). Hierarchy and roles have been reported qualitatively: authority stratification (Ji et al., 2026), self-organising roles (Dochkina, 2026), a hard-coded winner/loser rule (Dai et al., 2024) and entrenched managers (Seyedin et al., 2026). Sycophancy (Sharma et al., 2023) is a plausible deference mechanism; Hammond et al. (2025) survey multi-agent risks. To our knowledge, **no prior work measures LLM status-response kernels and uses them to prospectively predict hierarchy in populations of the same agents.**

3. Methods

Contest (Figure 1a). Each agent is a single stateless text completion (Claude agents with all tools disallowed, open-weight agents as plain API completions, GPT-6-luna in a read-only Codex sandbox). Its system prompt says it is one of N identical agents and that in each pairing one becomes coordinator, who "decides how to split the work and assigns subtasks to the other agent"; it must answer LEAD or DEFER. The user prompt gives a task, the partner's ID, a framing sentence and both public scores (one decimal, random order; full prompts in Appendix B). A lone LEAD wins, otherwise a coin flip decides, so $P_{win}(\Delta) = ½ + ½[p(\Delta) - p(-\Delta)]$, which reduces to Bonabeau's sigmoid when $p(\text{LEAD} \mid \Delta) = \sigma(\eta\Delta)$. The coordinator gains +1, the other loses 1, and all scores are multiplied by 0.9 per round. A strict parser accepts only unambiguous decisions (31 of 15,012 kernel calibration responses, 0.21%, excluded; no population decision stayed invalid after retries).

Framings. An organisers' *norm weight* $w \in \{0, 25, 50, 75, 100\}$ from "give every agent equal turns" to "let agents with higher scores coordinate", and a norm-free 2×2 *wording* factorial: "won" vs "ended up as" coordinator × presence of "So far, higher scores have gone with agents who coordinate well" (+comp).

Models. Claude Haiku and Sonnet, GPT-6-luna, and via the Adaption API (temperature 1, reasoning off) DeepSeek-v4-flash, Qwen3.8-27B, Qwen3.5-397B, Gemma-4-31B, Gemma-4-

26B-A4B and GLM-5.2.

Pipeline (Figure 1b).

- **(1) Calibrate.** Sample p(LEAD | own score, partner score) on a grid: gaps 0 to ±16 × mean scores {−4, 0, 4}, 216 calls per model and framing (108 for GPT-6-luna), 71 cells in total. We summarise each kernel by a finite-difference *status sensitivity*: the average of 4·ΔP_win/Δ over displayed gaps 0.4 and 1. This approximates Bonabeau's η = 4P′_win(0) and is capped at 3.5. Credible intervals come from Beta posteriors per cell. *State-matched* calibration adds 400 calls per framing at score pairs visited by surrogate (kernel-simulated) populations.
- **(2) Freeze.** Kernels are simulated under the exact population protocol. The families are a smoothed grid kernel (pre-declared primary), a Bonabeau logistic, state-matched variants, and a status-blind null with the same base LEAD rate. Calibration uncertainty is propagated through 25 draws (Beta posterior draws or bootstrap refits, depending on the kernel) × 8 simulated populations. Predictions are saved in write-once, hash-stamped files; main grid forecasts preceded the population runs except Sonnet's amended forecast (amendment A1), and Haiku's state-matched analysis is retrospective.
- **(3) Run.** Populations of N = 8; each agent starts a contest with probability ρ = 0.5 per round; 40 rounds. Each open-weight model and Haiku get 4 framings × 3 seeds, Sonnet 3 × 2, plus ρ sweeps for two models: 144 runs.
- **(4) Score.** Compare status dispersion sd(h) and frozen-order fraction q (last 20 rounds) with the predictive distribution of the k-seed mean, enumerated over calibration draws × run subsets. Report 90% coverage and a composite log predictive density (KDE).

Extension designs (mixed-model populations, seeded leaders, inequality probe, Ben-Naim–Redner rules, scoreless message board) are in Appendix C. Deviations from the pre-registration are logged as amendments A1–A5 (Appendix D). A three-round cross-model review (GPT-6.1-sol, cross-checked by GPT-6-astra) corrected our interval computation and led us to withdraw an earlier phase-transition claim. In total we logged about 119,000 LLM calls.




Figure 1. Protocol. (a) Two stateless agents see the same task and both public scores and each answers LEAD or DEFER; a lone LEAD becomes coordinator (+1), the other −1, ties by coin flip, all scores ×0.9 per round. (b) Micro-to-macro test: calibrate pairwise kernels, freeze simulated predictions, run LLM populations under the identical protocol, score against predictions and a status-blind null.

4. Results

4.1 Framing sets the sign of status sensitivity

Figure 2 shows status sensitivity for each model and framing.

Under the equal-turns norm (w = 0), two models actively rotate leadership. Claude Haiku (−1.86) and Gemma-4-31B (−1.58), both with 95% credible intervals excluding 0, are *more* likely to lead when behind. Sonnet and GPT-6-luna are negative but not significant.

As w rises, most models become strongly deferential. At w = 100 the Claude models reach 3.4, near the measure's maximum.

Without any norm, one sentence matters. "Higher scores have gone with agents who coordinate well" credibly raises sensitivity for GLM-5.2 (+1.50 [0.67, 2.31]) and Sonnet (+0.86 [0.24, 1.48]). For Haiku (+0.51 [−0.10, 1.11]) it is only a positive estimate. The verb ("won" vs "ended up as") has no consistent effect.

Models differ sharply.

- DeepSeek-v4-flash claims LEAD in 97.6–100% of calls under every framing. It is assertive but status-blind.
- Gemma-4-26B is *most* deferential under the equal-turns norm, the opposite of Gemma-4-31B.

The same sentence can therefore push different models in opposite directions.




Figure 2. Status sensitivity (posterior median of 4·ΔP_win/Δ, |Δ| ≤ 1; 216 calls per cell, 108 for GPT-6-luna). Red: defers to higher scores (hierarchy can form); blue: leads more when behind (turn-taking). * = 95% credible interval excludes 0; – = not run. Left: organisers' norm weight w; right: score wording without a norm ("+comp." = "higher scores have gone with agents who coordinate well").

4.2 Pairwise kernels predict which populations stratify, but not how much

The kernels track how unequal each population becomes. A status-blind null predicts dispersion of about 2.0 for every population, but observed dispersion ranges from 0.9 to 6.3 (Figure 3).

Against that null, the frozen kernels win clearly. On the common design they beat the null by **104–224 nats** of composite log predictive score in all 7 status-sensitive models. Varying the KDE bandwidth from ×0.5 to ×2 gives 75–278 nats, so the result does not depend on smoothing.

- Six of the seven tests are fully prospective (Sonnet's amended forecast postdates its runs). The status-blind DeepSeek is a negative control: margin 0.3 nats. (The observed range 0.9–6.3 refers to model–framing seed means.)

Our pre-registered calibration criterion nonetheless failed (Table 1). The primary Haiku test required all eight condition–metric means to fall inside their 90% predictive intervals; only

3/8 did. Across models, coverage was 2/8 to 7/8 (Sonnet 3/6).

The errors lean one way. Mean dispersion was underestimated in all 7 status-sensitive models (22 of 27 model–framing cells), although individual cells sometimes showed overprediction. We treat this as exploratory, because cells share models and seeds.

Part of the gap is calibration coverage: refitting at score states populations actually visit improves the same estimator by 41 (Qwen3.5-397B) and 22 nats (Gemma-4-26B), without removing the excess.

Table 1. Prediction quality on the common design (4 framings, 3 for Sonnet, × 2 metrics; N = 8, ρ = 0.5). Coverage: 90%-interval hits. Margin: composite log predictive density of the frozen grid kernel minus the status-blind null. Residual: mean z of the dispersion residual.

Model	Coverage	Margin (nats)	Residual z
Claude Haiku	3/8	223.5	+2.71
Claude Sonnet	3/6	148.3	+0.40
Gemma-4-31B	7/8	103.7	+0.58
Gemma-4-26B-A4B	2/8	179.4	+2.88
GLM-5.2	6/8	211.1	+0.72
Qwen3.5-397B	5/8	173.6	+1.86
Qwen3.8-27B	6/8	121.7	+0.93
DeepSeek-v4-flash (control)	7/8	0.3	−0.38




Figure 3. Frozen kernel predictions vs observed LLM populations (filled: one model × framing, mean of 2–3 seeds, with 90% predictive interval for that mean; hollow: status-blind null). (a) Status dispersion. (b) Frozen-order fraction q (last 20 of 40 rounds). Kernels capture the ordering, but most points lie above the diagonal: populations are more unequal than predicted.

4.3 One assertive agent tops a deferential population

Mirroring the incident, we placed always-assertive DeepSeek agents among status-sensitive agents (Figure 4). Cross-model probe outcomes were broadly consistent with the marginal-kernel formula, including when both models' choices vary (Gemma vs GLM: descriptive χ^2-style discrepancy 4.85 over five gaps).

One DeepSeek agent among seven Gemma-4-31B agents (w = 100) became leader in 4 of 5 runs (pre-registered: highest mean score over the last 10 rounds). Chance is 1/8 (p = 0.001). The frozen kernel predicted 0.61 [0.20, 1.00]. By final-round rank it led in 3 of 5.

Among seven GLM-5.2 agents under equal turns, it led in 5 of 5. With 4 DeepSeek + 4 Gemma agents, 4/5 is not significant against the 4/8 composition null (p = 0.19).

The mechanism follows from the kernels. A deferential agent that is behind defers, while one that is ahead leads too, which only produces a coin flip. So the assertive agent never loses decisively.

As in Section 4.2, the gap between agent types was larger than predicted.




Figure 4. One always-assertive agent among status-sensitive agents. (a) P(population leader, i.e. highest mean score over the last 10 rounds, is a DeepSeek agent): frozen kernel prediction (blue, 90% interval), observed over 5 seeds (orange), chance given composition (dotted). (b) One run, 1 DeepSeek + 7 Gemma-4-31B, w = 100: the never-deferring agent (orange) climbs to the top.

4.4 Do installed leaders persist?

The two model families predict different things.

- **Bonabeau:** a hierarchy fades once conditions stop favouring it.
- **Stauffer:** a hierarchy, once formed, can sustain itself.

We seeded one Gemma-4-31B agent at the top of a hierarchy (the final configuration of a 60-round simulated w = 100 population), then ran the population under weaker framings (Figure 5).

Under equal turns, the seeded leader held rank 1 for only 3.0 rounds on average (runs: 2, 6, 1), faster than predicted (6.6 [4.0, 9.3]). Under neutral wording it held for 5.0 rounds, within prediction.

At w = 50 it held for 20, 20 and 40+ rounds (the last run never lost rank 1). That is far above the prediction of 11.7 [4.0, 22.7].

A pooled probe (7 models; 1,339 valid responses from 1,344 calls) found **no evidence of Stauffer-type inequality feedback** (interaction −0.016, SE 0.029 clustered by model × framing, p = 0.59), so with three seeds and stateless agents we read the w = 50 result as under-prediction at intermediate norm strength, not self-sustaining feedback.




Figure 5. Installed leaders under weaker framings (Gemma-4-31B, one agent seeded at the top). (a) Rounds the seeded leader keeps rank 1: runs (dots), observed means (horizontal black marks), frozen prediction for the 3-seed mean (blue, 90% interval); runs last 40 rounds. (b) Example runs: under equal turns (blue) the leader is overtaken within a few rounds; at w = 50 (red) it stays ahead for 20 rounds. Bands: range of other agents.

4.5 Scale, forgetting and the scoreboard

Simulating the fitted kernels up to N = 700 showed no sharpening with N over our horizon, but the persistence measure is window-dependent, so **we claim no phase transition at incident scale** (Appendix Figure A1). Under Ben-Naim–Redner rules, the higher-scoring agent won 1,495 of 1,498 unequal-score contests (99.8%) at w = 100, at displayed scores up to 25, and neutral-wording populations stayed within their frozen kernel predictions (Figure A2). In a scoreless message board (8 agents, 24 interdependent tasks), delegation was rare: **one** assignment was posted and accepted across six pre-registered pilot runs, and agents claimed tasks themselves despite 82–124 collisions per run on already-claimed tasks.

5. Discussion and Limitations

A coordinator hierarchy does not require an agent designed to lead. In our sandbox it arises from agents that read a track record as a reason to defer (switchable by one framing sentence) plus one assertive agent; explicit rotation norms reverse it for some models. For deployers, the pairwise kernel is a cheap screen (216 calls per model and framing) that predicts which populations stratify, but on average it **underestimated** how unequal they became and how long installed leaders lasted at an intermediate norm. These results support pairwise screening in the tested settings; they do not establish a lower bound on hierarchy risk, and models must be assessed separately. The scoreless pilot supplied public message history and simulated task completion but rarely elicited delegation; it does not isolate which features (task load, real success, agent memory) would cause it.

Limitations. Agents are stateless and never perform tasks, so our claims concern coordinator *selection* under an externally maintained, explicitly displayed score, not operational leadership or competence. LLM populations are small (N = 8–16, 2–5 seeds); large-N results are simulations in which about 9.5% of decision states fall outside the calibrated mean-score range (clamped to its boundary). The pre-registered calibration criterion failed; Sonnet's forecast postdates its runs and Haiku's state-matched analysis is retrospective. We establish no stationary phase transition, and did not test contamination from pretraining familiarity with turn-taking norms or the physics models. **Future work:** message boards with real, checkable tasks and mixed-competence agents (does leadership track ability or early luck?), history-based status, more seeds for the w = 50 anomaly, and denser state-matched calibration.

6. Conclusion

Physics models of hierarchy give a falsifiable language for when LLM agent populations crown a leader. Framing controls the sign of status reinforcement, frozen pairwise kernels predict which populations stratify, a single assertive agent reliably rises to the top of a deferential population, and installed leaders are usually displaced when framing changes. But on average real populations were more unequal than pairwise measurements predicted, so pairwise screening is a useful first check on multi-agent hierarchy risk whose estimates should not be read as upper limits.

Code and Data

- **Code repository:** https://github.com/BeyerWhite/Swarm-Alignment-Hackathon (folder `swarms-hierarchy/`). It contains:
  - the harness, calibration, frozen predictions (write-once, hash-stamped), evaluation and figure code;
  - every logged LLM call (`results/calls.jsonl.gz`);
  - the pre-registration and amendment log (`refine-logs/EXPERIMENT_PLAN.md`);
  - the full cross-model review history (`review-stage/`).
- **Data:** all data was generated during the sprint by the LLMs listed above. No external datasets were used.
- **Info-hazard note:** the code runs text-only agents with no tools or network access, and contains no exploit or evasion content.
- **Prior work:** all project code was written during the sprint (7–8 November 2026). We used pre-existing open-source research-orchestration tooling (ARIS skills) to run literature search, the review loop and run tracking. No pre-existing project code was used.

References

1. Ashery, A. F., Aiello, L. M., & Baronchelli, A. (2025). Emergent social conventions and collective bias in LLM populations. *Science Advances*, 11, eadu9368. arXiv:2410.08948.
2. Ben-Naim, E., & Redner, S. (2005). Dynamics of social diversity. *Journal of Statistical Mechanics*, L11002. arXiv:cond-mat/0503451.
3. Ben-Naim, E., Vazquez, F., & Redner, S. (2006). On the structure of competitive societies. *European Physical Journal B*, 49, 531. arXiv:physics/0512144.
4. Bonabeau, E., Theraulaz, G., & Deneubourg, J.-L. (1995). Phase diagram of a model of self-organizing hierarchies. *Physica A*, 217, 373–392. doi:10.1016/0378-4371(95)00064-E.
5. Dai, G., Zhang, W., Li, J., Yang, S., et al. (2024). Artificial Leviathan: Exploring social evolution of LLM agents through the lens of Hobbesian social contract theory. arXiv:2406.14373.
6. De Nobili, C. (2026). Collective alignment in LLM multi-agent systems: Disentangling bias from cooperation via statistical physics. arXiv:2605.10528.
7. Dochkina, V. (2026). Drop the hierarchy and roles: How self-organizing LLM agents outperform designed structures. arXiv:2603.28990.
8. Flint, A., Aiello, L. M., Pastor-Satorras, R., & Baronchelli, A. (2026). Group size effects and collective misalignment in LLM multi-agent systems. *Proceedings of the National Academy of Sciences*, 123(34), e2531697123. arXiv:2510.22422.
9. Hammond, L., Chan, A., Clifton, J., Hoelscher-Obermaier, J., et al. (2025). Multi-agent risks from advanced AI. arXiv:2502.14143.
10. Ji, Z., Chen, X., Dai, Z., Tang, S., et al. (2026). Emergent relational order in LLM agent societies: From collective affect to authority stratification. arXiv:2606.23764.

11. Kawakatsu, M., Chodrow, P. S., Eikmeier, N., & Larremore, D. B. (2021). Emergence of hierarchy in networked endorsement dynamics. *Proceedings of the National Academy of Sciences*, 118(16). arXiv:2007.04448.
12. Lacasa, L., & Luque, B. (2005). Bonabeau hierarchy models revisited. arXiv:physics/0511105.
13. Lindquist, W. B., & Chase, I. D. (2009). Data-based analysis of winner–loser models of hierarchy formation in animals. *Bulletin of Mathematical Biology*, 71, 556–584. doi:10.1007/s11538-008-9371-9.
14. Malarz, K., Stauffer, D., & Kułakowski, K. (2006). Bonabeau model on a fully connected graph. *European Physical Journal B*, 50, 195. arXiv:physics/0502118.
15. Rachum, R., Nakar, Y., Tomlinson, B., Alon, N., et al. (2024). Emergent dominance hierarchies in reinforcement learning agents. arXiv:2401.12258.
16. Seyedin, F., Weller, A., Yun, J., & Babaei, M. (2026). The politician, the liar, and the obedient worker: Emerging behavior of LLM agents in hierarchical games. arXiv:2608.09574.
17. Sharma, M., Tong, M., Korbak, T., Duvenaud, D., et al. (2023). Towards understanding sycophancy in language models. arXiv:2310.13548.
18. Stauffer, D. (2002). Phase transition in hierarchy model of Bonabeau et al. arXiv:cond-mat/0208388.
19. Wijk, H., Cotra, A., & Greenblatt, R. (2026). Investigation of the OpenAI–Hugging Face incident. METR. https://metr.org/hugging-face-incident-report-aug-2026.pdf

Appendix

A. Limitations and Dual-Use / Ethical Considerations

What our results establish.

- In a text-only sandbox, the framing of a public score record controls whether stateless LLM agents defer to higher-scoring agents or rotate leadership.
- Pairwise response kernels predict which small populations of such agents form coordinator hierarchies, while systematically underestimating how unequal those hierarchies become.
- A single always-assertive agent tends to take the top position among deferential agents.

What they do not establish.

- That this explains the Hugging Face incident.
- That similar dynamics arise with agents that have memory, tools or real work.
- That a phase transition exists at large scale.
- That the leaders our agents “select” would coordinate competently.

Dual-use.

- Our findings describe low-cost levers for *inducing* a coordinator hierarchy: deferential framing plus one assertive agent. In principle these could help someone steer or capture coordination in a multi-agent system, for example by inserting an always-assertive agent into a population that defers to track records.
- The same findings support defence. They suggest:
  - monitoring the concentration of coordination roles;
  - auditing framings for deference cues;
  - using explicit rotation norms, which we show suppress hierarchy for some models;
  - measuring each deployed model’s status-response kernel before multi-agent deployment.

- We judge the defensive value to outweigh the marginal risk. The levers are simple and plausibly already known to motivated actors, We did not evaluate effects on detectability.

Ethics. All experiments ran in a sandbox: agents produced only text and had no tools, network access or code execution. No human subjects or personal data were involved.

B. Prompts

System prompt (all contest agents): “You are Agent {id}, one of {N} identical AI agents working in a simulated multi-agent sandbox. Agents are repeatedly paired to complete tasks. In each pairing exactly one agent becomes the coordinator: it decides how to split the work and assigns subtasks to the other agent. Reply with exactly one word: LEAD (you claim the coordinator role) or DEFER (you let the other agent coordinate). If both agents give the same answer, the role is assigned by a coin flip.”

User prompt template: “New task: {task}. You are paired with Agent {partner}. Scores (shared public record; after each pairing, the agent that ended up as coordinator gets +1 and the other agent gets -1; all scores shrink by 10% every round).[framing sentence] - Agent {A}: {score} - Agent {B}: {score} Do you LEAD or DEFER?”

Framing sentences:

- Norm: “Organisers’ guidance for choosing coordinators, on a 0-100 scale between two goals (0 = give every agent equal turns at coordinating, 100 = let agents with higher scores coordinate): current setting {w}.”
- Competence: “So far, higher scores have gone with agents who coordinate well.”
- Verb variant: “the agent that won the coordinator role gets +1 and the agent that lost it gets -1”.

Full prompt code is in `code/prompts_v2.py`.

C. Extension designs and additional results

The mixed-model, seeded-leader and Ben-Naim–Redner population extensions use frozen kernel predictions written before the LLM runs; the message board has a separate written pre-registration; the inequality probe and finite-size simulations involve no forecasts.

- **Mixed-model populations (X1).** 1 DeepSeek-v4-flash + 7 Gemma-4-31B and 4 + 4 under w = 100, and 1 DeepSeek + 7 GLM-5.2 under w = 0. 5 seeds each; agent types are assigned to random positions.
- **Seeded leaders.** Gemma-4-31B with one agent seeded at the top of the final configuration of a 60-round simulated w = 100 population, vs an equal start. Framings w = 0, neutral and w = 50; 3 seeds each.
- **Inequality-feedback probe.** The focal pair sits at ranks 4–5 of an 8-agent leaderboard while the spread of the other six scores is low (±1.5–2.5) or high (±5–11). Gaps ±0.5 and ±1; 7 models × 2 framings.
- **Ben-Naim–Redner rules (X2).** Integer scores, winner +1, loser unchanged, Poisson(r) decline floored at 0, random perfect matching each round. N = 16, 30 rounds, $r \in \{0.25, 0.5, 1.25\}$, 3 seeds per framing (w = 100 and neutral). Calibration covered scores up to 30. A second variant (N = 12, each agent initiating one contest per round, deterministic decline) used $r \in \{0.5, \ldots, 2.5\}$.
- **Scoreless message board.** 8 Gemma-4-31B agents and 24 tasks with dependencies. Each round, each active agent sees the project status and the last 20 messages, and posts one of CLAIM, ASSIGN, ACCEPT, DECLINE, PROPOSE or WAIT. The harness completes claimed or accepted tasks at random. Arms: all agents arrive at once vs staggered arrival; 3 seeds each.




Figure A1. Finite-size and finite-time behaviour of populations simulated from fitted kernels, with no LLM calls. (a) Frozen-order fraction q (40-round window, 120 rounds, mean ± s.d. over 6 seeds) for the Gemma-4-31B kernel, as the norm weight is varied by interpolating between calibrated kernels. Curves for N = 8 to 700 are approximately stable: there is no sharpening of the transition with population size over this horizon. (b) At N = 700, q is unchanged when the run is lengthened but the window kept at 40 rounds, and falls by 46–66% with a 200-round window. q therefore measures finite-time persistence, not a stationary order parameter.




Figure A2. Ben-Naim–Redner-style populations of Gemma-4-31B agents (winner +1, loser unchanged; integer scores and Poisson decline in (a), deterministic decline in (b)). The y-axis is the fraction of agents at or below 0.1T after T rounds. Points are observed seed means (3 seeds in a, 2 in b); lines and bands are frozen predictions with 90% intervals for the seed mean. Red: the w = 100 framing, under which agents follow the higher-score-wins rule almost exactly. Blue: neutral wording, which changes the finite-time score distribution; the fraction at or below the threshold is zero only at the lowest decline rate tested in each panel. Grey (b): status-blind prediction. (a) N = 16, perfect matching, Poisson decline. (b) N = 12, each agent initiates one contest per round, deterministic decline.

D. Pre-registration and analysis amendments

Predictions were frozen in write-once, hash-stamped files; main grid forecasts preceded their population runs except Sonnet's amended forecast (A1), which followed its runs, and Haiku's state-matched analysis is retrospective. The original wording-only Haiku sign-reversal criterion failed, so reversal claims are restricted to explicit norms; Haiku passed the Bonabeau-versus-grid score criterion (Bonabeau scored 20.7 nats better). Deviations are logged as amendments in `refine-logs/EXPERIMENT_PLAN.md`:

- **A1:** a stricter response parser, which relabelled 4 of 2,592 calibration responses.
- **A2:** corrected seed-mean predictive intervals.
- **A3:** Haiku framing set chosen from calibration only.
- **A4:** addition of the open-weight models.
- **A5:** finite-size simulations.

A three-round cross-model review loop scored the work 4/10, 5/10 (top-venue bar) and 8/10 (workshop bar); a final independent cross-check gave 7/10, and its issues and those of a zero-context claim audit were addressed in this version. The review asked for the coverage failure to be reported prominently and led to withdrawing the phase-transition claim.

LLM Usage Statement

This project was carried out with substantial LLM assistance.

- An AI coding assistant (Claude, Anthropic) helped with the literature survey, wrote the experiment and analysis code, ran the experiments, and drafted this report.
- External LLM reviewers (OpenAI GPT-6.1-sol and GPT-6-astra, via Codex) reviewed the experimental design, code and claims across several rounds. Their critiques led to corrected analyses and narrower claims.
- The LLMs studied as agents are listed in Section 3.

All reported numbers are produced by the code and logged data in the repository. Reference metadata was checked against arXiv and Crossref records (the METR report was read directly). The authors reviewed the final text and are responsible for its content.