

Title

Zitong Zhang
May 28, 2020

Networks

- Pictures of social networks
- Pictures of neural networks
- Pictures of static and dynamic networks

Dynamic networks

Pictures of:

- Networks with slowly-changing communities & connecting probabilities
 - Include related literatures
- Growing networks in nervous system
 - However, not many literatures

Growing networks

- Picture of real growing neural network (Cell paper)
- Pictures of their results
 - Prior expectation: roles of nodes
- Weakness of their method

Outline


- Model growing networks via stochastic block model
- Inference procedure
- Simulation and application to real data

Modeling the growing networks

Introduce terms and notations through pictures:

- Observed neural activity: $N_{\{i,j\}}$
- Roles of nodes: z_i
- “Bridge” between multiple networks and common cell types — —
connecting pattern: $\lambda_{\{q,l\}}$



Graphical representation of the model




The conditional density of $N_{i,j}(\cdot)$ given $z_i = q$ and $z_j = l$ is $\lambda_{q,l}(\cdot)$

(Matias et al, 2018)


There is at most one event in each point process



There is at most one event in each point process




There is at most one event in each point process



Inference

Approximate k-means method


Re-center based on current clustering



Kernel density estimation

$$\hat{f}_h(x) = \frac{1}{nh} \sum_{i=1}^n K\left(\frac{x - x_i}{h}\right)$$

Re-cluster based on estimated connecting patterns and current clustering




$$\sum_q w_{1,q} = 1$$

Inference

Approximate k-means method


Re-center based on current clustering



Kernel density estimation

$$\hat{f}_h(x) = \frac{1}{nh} \sum_{i=1}^n K\left(\frac{x - x_i}{h}\right)$$

Re-cluster based on estimated connecting patterns and current clustering




$$\text{dist}(i, \Gamma_q) = \sum_l w_{i,l} \cdot d(N_{i,\Gamma_l}, \lambda_{q,l}) = \sum_l w_{i,l} \cdot \|f_{N_{i,\Gamma_l}} - \lambda_{q,l}\|_2$$

Inference

Approximate k-means method


Re-center based on current clustering



Kernel density estimation

$$\hat{f}_h(x) = \frac{1}{nh} \sum_{i=1}^n K\left(\frac{x - x_i}{h}\right)$$


Re-cluster based on estimated connecting patterns and current clustering



$$\text{dist}(i, \Gamma_q) = \sum_l w_{i,l} \cdot d(N_{i,\Gamma_l}, \lambda_{q,l}) = \sum_l w_{i,l} \cdot \|f_{N_{i,\Gamma_l}} - \lambda_{q,l}\|_2$$


Time shifts associated with each edge

- Pictures from real data showing the existence of time shifts




$$N_{i,j}(\cdot - \tau_{i,j}), i, j \in [n]$$

Problem



Incorporating time shifts


Given aligned point processes:



$$d(f, g) = \inf_{\tau} \|f(\cdot - \tau) - g(\cdot)\|_2$$


Incorporating time shifts

Given aligned point processes:




$$d(f, g) = \inf_{\tau} \|f(\cdot - \tau) - g(\cdot)\|_2$$

Re-align point processes
based on current clustering




Incorporating time shifts

Given aligned point processes:




$$d(f, g) = \inf_{\tau} \|f(\cdot - \tau) - g(\cdot)\|_2$$

Re-align point processes
based on current clustering




Assumption on time shifts

Align columns




Align rows




Assumption on time shifts

Align columns



















$$\tau_{i,\cdot} - \tau_{j,\cdot} = 0$$

Align rows




$$\tau_{i,\cdot} - \tau_{j,\cdot} = \nu_i - \nu_j$$

Assumption on time shifts


	ν_{Γ_1}	ν_{Γ_2}	...	ν_{Γ_k}
ν_{Γ_1}				
ν_{Γ_2}				
\vdots				
ν_{Γ_k}				

Matrix of time shifts


Estimate time shifts




Estimate time shifts






Re-align point processes



Estimate time shifts



Aligning curves and evaluating their distance




Curves	Fourier coefficients
	θ_j $j = -\frac{N-1}{2}, \dots, \frac{N-1}{2}$
	$\theta'_j = \theta_j e^{i2\pi j(n_0/N)}$ $n_0 = \frac{\tau}{T}N$
	γ_j $j = -\frac{N-1}{2}, \dots, \frac{N-1}{2}$

$$d(f, g) = \min_{\tau} \|f - g\|_2$$

$$= \min_{n_0} \left[\frac{T}{N^2} \sum_j |\theta'_j - \gamma_j|^2 \right]^{1/2}$$

Apply gradient descent algorithm

Aligning curves and evaluating their distance

Curves	Fourier coefficients
	θ_j $j = -\frac{N-1}{2}, \dots, \frac{N-1}{2}$
	$\theta'_j = \theta_j e^{i2\pi j(n_0/N)}$ $n_0 = \frac{\tau}{T}N$
	γ_j $j = -\frac{N-1}{2}, \dots, \frac{N-1}{2}$

$$d(f, g) = \min_{\tau} \|f - g\|_2$$



$$= \min_{n_0} \left[\frac{T}{N^2} \sum_j |\theta'_j - \gamma_j|^2 \right]^{1/2}$$

Apply gradient descent algorithm



Good initialization?

Initializing gradient descent by aligning c.d.f.

Curves




Loss function




Algorithm

Given aligned point processes:




$$d(f, g) = \inf_{\tau} \|f(\cdot - \tau) - g(\cdot)\|_2$$


Re-align point processes
based on current clustering




Initialization of clustering and time shifts




Initialization of clustering and time shifts



Initialization of clustering and time shifts



Initialization of clustering and time shifts



Simulation

Over-clustering can help to find the correct cluster numbers

Real data

Future work

Thank you

Appendix

- Derivation of aligning pdf and cdf
- Details about simulation set up, tuning parameters in algorithm
- Details about dealing with negative event time