




# Text Retrieval and Search Engines

Probabilistic Retrieval Model: Smoothing Methods

ChengXiang “Cheng” Zhai  
Department of Computer Science  
University of Illinois at Urbana-Champaign

# Probabilistic Retrieval Model: Smoothing Methods



## Ranking Function for JM Smoothing

$$f(q, d) = \sum_{\substack{w_i \in d \\ w_i \in q}} c(w, q) \left[ \log \frac{p_{\text{Seen}}(w_i | d)}{\alpha_d p(w_i | C)} \right] + n \log \alpha_d$$

$$p(w | d) = (1 - \lambda) \frac{c(w, d)}{|d|} + \lambda p(w | C) \quad \lambda \in [0, 1]$$

$$\frac{p_{\text{seen}}(w | d)}{\alpha_d p(w | C)} = \frac{(1 - \lambda) p_{\text{ML}}(w | d) + \lambda p(w | C)}{\lambda p(w | C)} = 1 + \frac{1 - \lambda}{\lambda} \frac{c(w, d)}{|d| p(w | C)}$$

$$f_{\text{JM}}(q, d) = \sum_{\substack{w \in d \\ w \in q}} c(w, q) \log \left[ 1 + \frac{1 - \lambda}{\lambda} \frac{c(w, d)}{|d| p(w | C)} \right]$$

# Ranking Function for Dirichlet Prior Smoothing

$$f(q, d) = \sum_{\substack{w_i \in d \\ w_i \in q}} c(w, q) \left[ \log \frac{p_{\text{Seen}}(w_i | d)}{\alpha_d p(w_i | C)} \right] + n \log \alpha_d$$

$$p(w | d) = \frac{c(w; d) + \mu p(w | C)}{|d| + \mu} = \frac{|d|}{|d| + \mu} \frac{c(w, d)}{|d|} + \frac{\mu}{|d| + \mu} p(w | C) \quad \mu \in [0, +\infty)$$

$$\frac{p_{\text{seen}}(w | d)}{\alpha_d p(w | C)} = \frac{\frac{c(w, d) + \mu p(w | C)}{|d| + \mu}}{\frac{\mu p(w | C)}{|d| + \mu}} = 1 + \frac{c(w, d)}{\mu p(w | C)} \quad \alpha_d = \frac{\mu}{|d| + \mu}$$

$$f_{\text{DIR}}(q, d) = \left[ \sum_{\substack{w \in d \\ w \in q}} c(w, q) \log \left[ 1 + \frac{c(w, d)}{\mu p(w | C)} \right] \right] + n \log \frac{\mu}{\mu + |d|}$$

# Summary

- Two smoothing methods
  - Jelinek-Mercer: Fixed coefficient linear interpolation
  - Dirichlet Prior: Adding pseudo counts; adaptive interpolation
- Both lead to state of the art retrieval functions with assumptions clearly articulated (less heuristic)
  - Also implementing TF-IDF weighting and doc length normalization
  - Has precisely one (smoothing) parameter

# Summary of Query Likelihood Probabilistic Model

- Effective ranking functions obtained using pure probabilistic modeling
  - Assumption 1:  $\text{Relevance}(q,d) = p(R=1 | q,d) \approx p(q | d, R=1) \approx \mathbf{p(q | d)}$
  - Assumption 2: Query words are generated independently
  - Assumption 3: Smoothing with  $p(w | C)$
  - Assumption 4: JM **or** Dirichlet prior smoothing
- Less heuristic compared with VSM
- Many extensions have been made [Zhai 08]

## Additional Readings

- ChengXiang Zhai, *Statistical Language Models for Information Retrieval* (Synthesis Lectures Series on Human Language Technologies), Morgan & Claypool Publishers, 2008.

<http://www.morganclaypool.com/doi/abs/10.2200/S00158ED1V01Y200811HLT001>