

```

DELL@DDU-Student MINGW64 /e/Desktop/SEM 7/SEM 7/ddu
$ git config --global user.name "DDU Student"

DELL@DDU-Student MINGW64 /e/Desktop/SEM 7/SEM 7/ddu
$ git config --global user.email "DDU@Student"

DELL@DDU-Student MINGW64 /e/Desktop/SEM 7/SEM 7/ddu
$ git config --global user.email
DDU@Student

```

git config --global user.name "ert" sets your Git username globally. This name appears in every commit you make. It's used to identify you in all your Git projects.

```

DELL@DDU-Student MINGW64 /e/Desktop/SEM 7/SEM 7/ddu
$ pwd
/e/Desktop/SEM 7/SEM 7/ddu

DELL@DDU-Student MINGW64 /e/Desktop/SEM 7/SEM 7/ddu
/.git/

DELL@DDU-Student MINGW64 /e/Desktop/SEM 7/SEM 7/ddu (main)
$ git status
On branch main

No commits yet

nothing to commit (create/copy files and use "git add" to track)

```

❏ pwd (Print Working Directory):

Displays the full path of the current directory you're in. Useful to know your location in the filesystem.

❏ git init:

Creates a new .git folder, making the current directory a Git repository so you can start tracking changes.

```

DELL@DDU-Student MINGW64 /e/Desktop/SEM 7/SEM 7/ddu (main)
$ git status
On branch main

No commits yet

Untracked files:
  (use "git add <file>..." to include in what will be committed)
    ddu.txt

nothing added to commit but untracked files present (use "git add" to track)

```

📖 **git status:**

Shows which files are staged, unstaged, or untracked — helping you understand what will go into your next commit.

```
DELL@DDU-Student MINGW64 /e/Desktop/SEM 7/SEM 7/ddu (main)
$ git add .

DELL@DDU-Student MINGW64 /e/Desktop/SEM 7/SEM 7/ddu (main)
$ git status
On branch main

No commits yet

Changes to be committed:
  (use "git rm --cached <file>..." to unstage)
    new file:   ddu.txt
```

The command `git add .` stages **all changes** (new, modified, deleted files) in the current directory and its subdirectories.

It prepares these changes to be included in the next commit.

The `.` means "everything in the current folder."

```
DELL@DDU-Student MINGW64 /e/Desktop/SEM 7/SEM 7/ddu (main)
$ git commit -m "first commit"
[main (root-commit) 33a68ce] first commit
 1 file changed, 1 insertion(+)
 create mode 100644 ddu.txt

DELL@DDU-Student MINGW64 /e/Desktop/SEM 7/SEM 7/ddu (main)
$ git log
commit 33a68ce10f47d66db805de674c6824559b011c13 (HEAD -> main)
Author: DDU Student <DDU@Student>
Date:   Tue Aug 12 16:06:29 2025 +0530

    first commit
```

📖 **git commit:**

Records the staged changes to the repository history.

You usually add a message with `-m "Your message"` to describe the changes.

📖 **git log:**

Shows a list of all past commits in reverse chronological order.

It includes commit IDs, author info, dates, and commit messages.

```
DELL@DDU-Student MINGW64 /e/Desktop/SEM 7/SEM 7/ddu (main)
$ git checkout -b DDU
Switched to a new branch 'DDU'

DELL@DDU-Student MINGW64 /e/Desktop/SEM 7/SEM 7/ddu (DDU)
```

git checkout -b name creates a **new branch** called name and **switches** to it in one step. This is useful when starting a new feature or making changes without affecting the main branch.

```
DELL@DDU-Student MINGW64 /e/Desktop/SEM 7/SEM 7/ddu (DDU)
$ git branch dduitsem7
```

git branch dduitsem7 creates a **new branch** named dduitsem7. It does **not switch** to the new branch — it just creates it. You can switch to it later using **git checkout dduitsem7**.

```
DELL@DDU-Student MINGW64 /e/Desktop/SEM 7/SEM 7/ddu (DDU)
$ git branch
* DDU
  dduitsem7
  main
```

git branch lists all the branches in your Git repository. It also highlights the current branch you're on with an asterisk (*). You can use it to **create**, **delete**, or **view** branches.

```
DELL@DDU-Student MINGW64 /e/Desktop/SEM 7/SEM 7/ddu (DDU)
$ git checkout dduitsem7
Switched to branch 'dduitsem7'

DELL@DDU-Student MINGW64 /e/Desktop/SEM 7/SEM 7/ddu (dduitsem7)
$
```

git checkout main switches your working directory to the **main** branch. It updates your files to match the latest commit on main, allowing you to work on that branch. Use it when you want to stop working on another branch and return to main.