```python
from pyspark.sql import SparkSession

spark = SparkSession.builder.appName("practice").getOrCreate()

customers_data = [
    (1, "Ravi", "Hyderabad", 25),
    (2, "Sita", "Chennai", 32),
    (3, "Arun", "Hyderabad", 28),
    (4, "Meena", "Bengaluru", 35),
    (5, "Kiran", "Chennai", 22)
]
customers = spark.createDataFrame(customers_data, ["customer_id","customer_n
customers.show()
```

Run Code

Follow for Spark tips & updates

TABLE | STDOUT | STDERR

```
+-----------+-------------+---------+---+
|customer_id|customer_name|     city|age|
+-----------+-------------+---------+---+
|          1|         Ravi|Hyderabad| 25|
|          2|         Sita|  Chennai| 32|
|          3|         Arun|Hyderabad| 28|
|          4|        Meena|Bengaluru| 35|
|          5|        Kiran|  Chennai| 22|
+-----------+-------------+---------+---+
```

Help Us Improv

```python
from pyspark.sql import SparkSession

spark = SparkSession.builder.appName("practice").getOrCreate()

customers_data = [
    (1, "Ravi", "Hyderabad", 25),
    (2, "Sita", "Chennai", 32),
    (3, "Arun", "Hyderabad", 28),
    (4, "Meena", "Bengaluru", 35),
    (5, "Kiran", "Chennai", 22)
]
customers = spark.createDataFrame(customers_data, ["customer_id","customer_name
customers.filter(customers.city == "Chennai").show()
```

Run Code

Follow for Spark tips & updates

TABLE | STDOUT | STDERR

```
+-----------+-------------+-------+---+
|customer_id|customer_name|   city|age|
+-----------+-------------+-------+---+
|          2|         Sita|Chennai| 32|
|          5|        Kiran|Chennai| 22|
+-----------+-------------+-------+---+
```

```python
from pyspark.sql import SparkSession

spark = SparkSession.builder.appName("practice").getOrCreate()

customers_data = [
    (1, "Ravi", "Hyderabad", 25),
    (2, "Sita", "Chennai", 32),
    (3, "Arun", "Hyderabad", 28),
    (4, "Meena", "Bengaluru", 35),
    (5, "Kiran", "Chennai", 22)
]
customers = spark.createDataFrame(customers_data, ["customer_id","customer_n
customers.filter(customers.age > 25).show()
```

Run Code

Follow for Spark tips & updates

TABLE | STDOUT | STDERR

```
+-----------+-------------+---------+---+
|customer_id|customer_name|     city|age|
+-----------+-------------+---------+---+
|          2|         Sita|  Chennai| 32|
|          3|         Arun|Hyderabad| 28|
|          4|        Meena|Bengaluru| 35|
```

```python
from pyspark.sql import SparkSession

spark = SparkSession.builder.appName("practice").getOrCreate()

customers_data = [
    (1, "Ravi", "Hyderabad", 25),
    (2, "Sita", "Chennai", 32),
    (3, "Arun", "Hyderabad", 28),
    (4, "Meena", "Bengaluru", 35),
    (5, "Kiran", "Chennai", 22)
]
customers = spark.createDataFrame(customers_data, ["customer_id","customer_name
customers.select("customer_name", "city").show()
```

Run Code

Follow for Spark tips & updates

TABLE | STDOUT | STDERR

```
+-------------+---------+
|customer_name|     city|
+-------------+---------+
|         Ravi|Hyderabad|
|         Sita|  Chennai|
|         Arun|Hyderabad|
|        Meena|Bengaluru|
|        Kiran|  Chennai|
```

Help Us Improve

```python
spark = SparkSession.builder.appName("practice").getOrCreate()

customers_data = [
    (1, "Ravi", "Hyderabad", 25),
    (2, "Sita", "Chennai", 32),
    (3, "Arun", "Hyderabad", 28),
    (4, "Meena", "Bengaluru", 35),
    (5, "Kiran", "Chennai", 22)
]
customers = spark.createDataFrame(customers_data, ["customer_id","customer_n
from pyspark.sql.functions import count

customers.groupBy("city").agg(count("*").alias("total_customers")).show()
```

Run Code

Follow for Spark tips & updates

TABLE | STDOUT | STDERR

```
+---------+---------------+
|     city|total_customers|
+---------+---------------+
|  Chennai|              2|
|Hyderabad|              2|
|Bengaluru|              1|
```