



# HTML Form Elements

[< Previous](#)[Next >](#)

This chapter describes all the different HTML form elements.

## The <input> Element

One of the most used form element is the `<input>` element.

The `<input>` element can be displayed in several ways, depending on the `type` attribute.

### Example

```
<input type="text" id="firstname" name="firstname">
```

[Try it Yourself »](#)

If the `type` attribute is omitted, the input field gets the default type: "text".

All the different input types are covered in the next chapter: [HTML Input Types](#).

## The <select> Element

The `<select>` element defines a **drop-down list**:



HTML

CSS

MORE ▼



```
<select id="cars" name="cars">
  <option value="volvo">Volvo</option>
  <option value="saab">Saab</option>
  <option value="fiat">Fiat</option>
  <option value="audi">Audi</option>
</select>
```

[Try it Yourself »](#)

The `<option>` element defines an option that can be selected.

By default, the first item in the drop-down list is selected.

To define a pre-selected option, add the `selected` attribute to the option:

## Example

```
<option value="fiat" selected>Fiat</option>
```

[Try it Yourself »](#)

## Visible Values:

Use the `size` attribute to specify the number of visible values:

## Example

```
<select name="cars" size="3">
  <option value="volvo">Volvo</option>
  <option value="saab">Saab</option>
  <option value="fiat">Fiat</option>
  <option value="audi">Audi</option>
</select>
```



## Allow Multiple Selections:

Use the `multiple` attribute to allow the user to select more than one value:

### Example

```
<select name="cars" size="4" multiple>
  <option value="volvo">Volvo</option>
  <option value="saab">Saab</option>
  <option value="fiat">Fiat</option>
  <option value="audi">Audi</option>
</select>
```

Try it Yourself »

## The <textarea> Element

The `<textarea>` element defines a multi-line input field (**a text area**):

### Example

```
<textarea name="message" rows="10" cols="30">
The cat was playing in the garden.
</textarea>
```

Try it Yourself »

The `rows` attribute specifies the visible number of lines in a text area.

The `cols` attribute specifies the visible width of a text area.

This is how the HTML code above will be displayed in a browser:



HTML

CSS

MORE ▼



You can also define the size of the text area by using CSS:

## Example

```
<textarea name="message" style="width:200px; height:600px;">
The cat was playing in the garden.
</textarea>
```

Try it Yourself »

## The <button> Element

The `<button>` element defines a clickable **button**:

## Example

```
<button type="button" onclick="alert('Hello World!')">Click Me!</button>
```

Try it Yourself »

This is how the HTML code above will be displayed in a browser:

Click Me!



# The <fieldset> and <legend> Elements

The `<fieldset>` element is used to group related data in a form.

The `<legend>` element defines a caption for the `<fieldset>` element.

## Example

```
<form action="/action_page.php">
  <fieldset>
    <legend>Personalia:</legend>
    <label for="fname">First name:</label><br>
    <input type="text" id="fname" name="fname" value="John"><br>
    <label for="lname">Last name:</label><br>
    <input type="text" id="lname" name="lname" value="Doe"><br><br>
    <input type="submit" value="Submit">
  </fieldset>
</form>
```

Try it Yourself »

This is how the HTML code above will be displayed in a browser:

Personalia:

First name:

Last name:

## The <datalist> Element



Users will see a drop-down list of the pre-defined options as they input data.

The `list` attribute of the `<input>` element, must refer to the `id` attribute of the `<datalist>` element.

## Example

```
<form action="/action_page.php">
  <input list="browsers">
  <datalist id="browsers">
    <option value="Internet Explorer">
    <option value="Firefox">
    <option value="Chrome">
    <option value="Opera">
    <option value="Safari">
  </datalist>
</form>
```

Try it Yourself »

## The <output> Element

The `<output>` element represents the result of a calculation (like one performed by a script).

## Example

Perform a calculation and show the result in an `<output>` element:

```
<form action="/action_page.php"
oninput="x.value=parseInt(a.value)+parseInt(b.value)">
  0
  <input type="range" id="a" name="a" value="50">
  100 +
  <input type="number" id="b" name="b" value="50">
  =
  <output name="x" for="a b"></output>
```



HTML

CSS

MORE ▼



&lt;/form&gt;

[Try it Yourself »](#)

## HTML Exercises

### Test Yourself With Exercises

#### Exercise:

In the form below, add an empty drop down list with the name "cars".

```
<form action="/action_page.php">  
<          >  
</      >  
</form>
```

[Submit Answer »](#)[Start the Exercise](#)

## HTML Form Elements

Tag	Description
<u>&lt;form&gt;</u>	Defines an HTML form for user input
<u>&lt;input&gt;</u>	Defines an input control



HTML

CSS

MORE ▼




<u>&lt;label&gt;</u>	Defines a label for an <input> element
<u>&lt;fieldset&gt;</u>	Groups related elements in a form
<u>&lt;legend&gt;</u>	Defines a caption for a <fieldset> element
<u>&lt;select&gt;</u>	Defines a drop-down list
<u>&lt;optgroup&gt;</u>	Defines a group of related options in a drop-down list
<u>&lt;option&gt;</u>	Defines an option in a drop-down list
<u>&lt;button&gt;</u>	Defines a clickable button
<u>&lt;datalist&gt;</u>	Specifies a list of pre-defined options for input controls
<u>&lt;output&gt;</u>	Defines the result of a calculation

For a complete list of all available HTML tags, visit our [HTML Tag Reference](#).

[◀ Previous](#)[Next ▶](#)

## COLOR PICKER



## HOW TO

[Tabs](#)[Dropdowns](#)[Accordions](#)[Side Navigation](#)[Top Navigation](#)



[HTML](#)[CSS](#)[MORE ▼](#)

---

[Parallax](#)  
[Login Form](#)  
[HTML Includes](#)  
[Google Maps](#)  
[Range Sliders](#)  
[Tooltips](#)  
[Slideshow](#)  
[Filter List](#)  
[Sort List](#)

## SHARE



## CERTIFICATES

[HTML](#)  
[CSS](#)  
[JavaScript](#)  
[SQL](#)  
[Python](#)  
[PHP](#)  
[jQuery](#)  
[Bootstrap](#)  
[XML](#)

[Read More »](#)

---

[REPORT ERROR](#)

[PRINT PAGE](#)

[FORUM](#)

[ABOUT](#)

---

[HTML](#)[CSS](#)[MORE ▼](#)[HTML Tutorial](#)[CSS Tutorial](#)[JavaScript Tutorial](#)[How To Tutorial](#)[SQL Tutorial](#)[Python Tutorial](#)[W3.CSS Tutorial](#)[Bootstrap Tutorial](#)[PHP Tutorial](#)[jQuery Tutorial](#)[Java Tutorial](#)[C++ Tutorial](#)

## Top References

[HTML Reference](#)[CSS Reference](#)[JavaScript Reference](#)[SQL Reference](#)[Python Reference](#)[W3.CSS Reference](#)[Bootstrap Reference](#)[PHP Reference](#)[HTML Colors](#)[jQuery Reference](#)[Java Reference](#)[Angular Reference](#)

## Top Examples

[HTML Examples](#)[CSS Examples](#)[JavaScript Examples](#)[How To Examples](#)[SQL Examples](#)[Python Examples](#)[W3.CSS Examples](#)[Bootstrap Examples](#)[PHP Examples](#)[jQuery Examples](#)[Java Examples](#)[XML Examples](#)

## Web Certificates

[HTML Certificate](#)[CSS Certificate](#)[JavaScript Certificate](#)[SQL Certificate](#)[Python Certificate](#)[jQuery Certificate](#)[PHP Certificate](#)[Bootstrap Certificate](#)

[HTML](#)[CSS](#)[MORE ▼](#)[Get Certified »](#)

W3Schools is optimized for learning, testing, and training. Examples might be simplified to improve reading and basic understanding. Tutorials, references, and examples are constantly reviewed to avoid errors, but we cannot warrant full correctness of all content. While using this site, you agree to have read and accepted our terms of use, cookie and privacy policy. Copyright 1999-2020 by Refsnes Data. All Rights Reserved.

Powered by W3.CSS.

