Quiz- CS 303 - 18/11/21 (Thrusday) - 8.40 AM to 8.50 AM-Btech(Regular)

u19cs012@coed.svnit.ac.in Switch account



Draft saved

Your email will be recorded when you submit this form

* Required

CS303 - Quiz

Total Questions - 10

Time of the Exam: 8.40 am to 8.50 am

Instructions:

- 1. Attempt all questions.
- 2. You need to compulsory submit the test/exam before the due/end time. Your response will not be recorded, If you don't submit the test.
- 3. There is no negative marking

VLAN can group stations based on *

- **Broadcasting Address**
- Logical Address
- Port Number
- **Physical Address**

Which of the statements are true *		
No ICMP error messages are generated for the datagrams with mulicast address		
✓ ARP request is broadcast and ARP reply is unicast		
ARP requests can cross network boundaries		
BOOTP requests can cross network boundaries		
Which of the statements are true in regard to network layer *		
Communication at the network layer is connectionless		
Dual Stack enables a system to communicate via IPv4 and IPv6		
Maximum length of data which can be encapsulated in the ethernet is 1540 bytes.		
Header Length filed in IPv6 to tell the length of the header in the frame		
Which of the statements are true *		
Three layer switch can work on physical, data link and network layer		
A bridge does not change the physical (MAC) addresses in a frame.		
Switch can have many ports and can hold frames for processing		
Repeater can act as a active Hub, but a active Hub cannot act as a Repeater		

Which of the statements are true *			
In stop and wait only one specific frame will need ACK, irrespective of several copies of the same frame			
Stop and Wait ARQ is a special case of Go-Back-N ARQ where size of sender window is 1			
Go-Back-N ARQ is inefficient for noisy links			
All three protocols (Stop and Wait, Go-Back-N and Selective Repeat) can implement "Piggybacking"			
Which of the statements are true *			
A piconet can have up to eight stations, one of which should be a primary station			
The CTS frame in CSMA/CA handshake can prevent collision from a hidden station			
A BSS (Basic Service Set) without and AP (Access Point) is called an Infrastructure network			
Communication between two secondary devices in Bluetooth is always via primary station			
Which of the statements are true in regard to routing *			
Two node instability can be avoided by split horizon and poison reverse			
In Distance Vector routing, each node sends periodic information packets only to its neighbors.			
In Link state routing, each node sends periodic information packets only to its neighbors.			
Effect of Three node instability can be reduced with help of defining infinity to a smaller number.			

	Store and forward technique is used in which of the following switching technique/(s)? *			
O	Message Switching			
0	Both of the above			
0	None of the above			
0	Packet Switching			
		_		
Whi	ch of the statements are true in regard to UDP and TCP *			
	Value of the sequence number define the first byte contained in that segment			
~	UDP and TCP maintain a buffer both at receiver and sender end.			
	UDP and TCP assign sequence nembers to the segments.			
~	ACK segnments do not consume sequence numbers			
		_		
Whi	ch of the statements are true in regard of congestion control *			
	If time-out occurs, value of the threshold will be set to zero			
	If 3 ACKs are received, value of the threshold will be set to half of the current window size			
~	Congestion avoidance is achived with additive increase technique			
Sender's window size is decided based on avaliable buffer space in receiver and size of congestion window				
	Page 2 of 2			
Back	Submit Clear form	n		

Never submit passwords through Google Forms.

This form was created inside of Sardar Vallabhbhai National Institute of Technology, Surat. Report Abuse

Google Forms