



ಶರಣಬಸವ
Sharnbasva
ಕಲಬುರಗಿ - ೫೮೫ ೧೦೩



ವಿಶ್ವವಿದ್ಯಾಲಯ
University
Kalaburagi - 585 103



UGC Status : Letter Mp. F.8-29/2017 (VPP-I/PU), dated 20 Dec 2017. Enlisted by the University Grants Commission, New Delhi, in the list of Private University in India A Private University enacted by Govt. of Karnataka as "Sharnbasva University Act.2012" Karnataka Act No. 17 of 2013, Notification No. ED 144 URC 2016 dated 29/07/2017

A
PROJECT REPORT
ON

"SMART MULTI CONTROL ROBOTIC CAR"

Submitted to

Department of Computer Science & Design
in partial fulfilment of the 6th Semester Mini-Project

Submitted by

BHAGYASHREE PATIL (SG23CSD007)

CHETANA PATIL (SG23CSD011)

SHIVANGOUDA MALIPATIL (SG23CSD040)

SUPRIYA HIREMATH (SG23CSD049)

Under the Guidance of:

PROF. SOUMYA MITEKAR



DEPARTMENT OF COMPUTER SCIENCE & DESIGN
FACULTY OF ENGINEERING AND TECHNOLOGY
SHARNBASVA UNIVERSITY,
KALBURAGI

2025-2026



ಶರಣಬಸವ
Sharnbasva
ಕಲಬುರಗಿ - ೫೮೫ ೧೦೩



ವಿಶ್ವವಿದ್ಯಾಲಯ
University
Kalaburagi - 585 103



UGC Status : Letter Mp. F.8-29/2017 (VPP-I/PU), dated 20 Dec 2017. Enlisted by the University Grants Commission, New Delhi, in the list of Private University in India A Private University enacted by Govt. of Karnataka as "Sharnbasva University Act.2012" Karnataka Act No. 17 of 2013, Notification No. ED 144 URC 2016 dated 29/07/2017

CERTIFICATE

This is to certify that the project titled "SMART MULTI CONTROL ROBOTIC CAR" is a bonafide work carried out by BHAGYASHREE PATIL (SG23CSD007), CHETANA PATIL (SG23CSD011), SHIVANGOUDA MALIPATIL (SG23CSD040) , and SUPRIYA HIREMATH (SG23CSD049) in partial fulfillment of the requirements for the award of the B.Tech. in Computer Science and Design, 6th Semester, under the Faculty of Engineering and Technology, Sharnbasva University, during the academic year 2025–2026

NAME	USN
BHAGYASHREE PATIL	(SG23CSD007)
CHETANA PATIL	(SG23CSD011)
SHIVANGOUDA MALIPATIL	(SG23CSD040)
SUPRIYA HIREMATH	(SG23CSD049)

GUIDE

CHAIRPERSON

DEAN

Name of the Examiners

Signature with date

1.

2.

ACKNOWLEDGEMENT

Any achievement, be it scholastic or otherwise, does not depend solely on individual efforts but also on the guidance, encouragement, and cooperation of intellectuals, elders, and friends. Many individuals, in their own capacities, have contributed to the successful completion of this project work. We take this opportunity to express our sincere gratitude to all of them.

First and foremost, we express our immense gratitude to Dr. Anilkumar Bidve, Vice Chancellor of Sharnbasva University, for his inspiration and support during the tenure of the course.

We also extend our sincere thanks to Dr. Laxmi Patil, Registrar, Sharnbasva University, Kalaburagi.

We also express our sincere thanks to Dr. S. H. Honnalli, Registrar (Evaluation), Sharnbasva University, Kalaburagi.

I express my sincere thanks to Dr. Kiran Maka, Finance Officer, for their constant encouragement and support.

We extend our heartfelt gratitude to Dr. Shivkumar Jawalgi, Dean, Sharnbasva University, Kalaburagi.

We extend our sincere gratitude to Dr. Sachinkumar Veerashetty, Chairperson, Department of Computer Science and Design, Faculty of Engineering and Technology, for his constant encouragement and support.

We would also like to express our heartfelt thanks to our guide, **Prof. Soumya Mitekar**, Department of Computer Science and Design, Faculty of Engineering and Technology, for valuable guidance, constant encouragement, and support throughout the project work.

Finally, we express our sincere gratitude to all the faculty members of the Department of Computer Science and Design, Faculty of Engineering and Technology, for their encouragement, guidance, and continuous support.

Bhagyashree Patil (SG23CSD007)

Chetana Patil (SG23CSD011)

Shivangouda Malipatil (SG23CSD040)

Supriya Hiremath (SG23CSD049)

CONTENTS

SL. NO.	PARTICULARS	PAGE NO.
CHAPTER 1	PREAMBLE	
	1.1 INTRODUCTION	
	1.2 OVERVIEW OF INTERNET OF THINGS	
	1.3 PROBLEM DEFINITION	
	1.4 MOTIVATION	
	1.5 OBJECTIVE	
	1.6 SCOPE OF PROJECT	
CHAPTER 2	LITERATURE SURVEY	
	2.1 RELATED WORKS	
	2.2 EXISTING SYSTEM	
	2.3 PROPOSED SYSTEM	
CHAPTER 3	SYSTEM REQUIREMENT SPECIFICATION	
	3.1 FUNCTIONAL REQUIREMENTS	
	3.2 NON-FUNCTIONAL REQUIREMENTS	
	3.3 SOFTWARE REQUIREMENTS	
	3.4 HARDWARE REQUIREMENTS	
CHAPTER 4	SYSTEM DESIGN AND DEVELOPMENT	
	4.1 Introduction	
	4.2 Block Diagram	
	4.3 Circuit Diagram	
	4.4 Working Principle	
	4.5 MIT App Design	
	4.6 Bluetooth Communication	
	4.7 Obstacle Detection System	
CHAPTER 5	IMPLEMENTATION	
	5.1 PROJECT IMPLEMENTATION	
	5.2 METHODOLOGY	
	5.3 SOURCE CODE	

SL. NO.	PARTICULARS	PAGE NO.
CHAPTER 6	SYSTEM TESTING	
	6.1 TEST APPROACH	
	6.2 FEATURES TO BE TESTED	
	6.3 TESTING PROCEDURE	
CHAPTER 7	RESULT INTERPRETATION AND DISCUSSION	
	CONCLUSION	
	REFERENCES	

LIST OF FIGURES

SL. NO.	PARTICULARS	PAGE NO.
---------	-------------	----------

CHAPTER 1

PREAMBLE

1.1 Introduction

The rapid development of robotics, automation systems, and wireless communication technologies has significantly transformed modern engineering applications. Smart robotic systems are widely used in industries, healthcare, transportation, military operations, surveillance systems, warehouse automation, and educational research. Robotics combines electronics, embedded systems, communication technologies, sensors, and intelligent programming into a single automated platform capable of performing different operations with minimal human intervention.

The Smart Multi-Control Robotic Car project is developed to demonstrate the practical implementation of a wireless robotic vehicle using Arduino Uno, Bluetooth communication, obstacle detection systems, and mobile application control. The project is designed as an intelligent robotic platform capable of operating through multiple control mechanisms including Bluetooth-based mobile control, predefined route navigation, automatic obstacle detection, and autonomous movement.

In this project, Arduino Uno acts as the central processing unit that controls all hardware components connected to the robotic system. The robotic car receives commands from a mobile application developed using MIT App Inventor through the HC-05 Bluetooth module. Based on the received commands, the Arduino controls the movement of BO motors through the L293D motor driver module.

The robotic car supports movement in forward, backward, left, right, and stop directions. The project also includes intelligent features such as obstacle detection using an ultrasonic sensor and automatic navigation using servo motor scanning. When obstacles are detected, the robotic car automatically stops and changes direction to avoid collisions.

Another important feature of the project is the predefined route navigation system. The robotic vehicle can automatically follow programmed movement paths such as Home, Hospital, Office, and School routes. This demonstrates basic autonomous robotic navigation concepts.

The project integrates hardware and software technologies together into a single robotic automation system. It provides practical exposure to embedded systems, robotics engineering, automation technologies, wireless communication, and mobile application development.

1.2 Overview of Internet of Things

The Internet of Things (IoT) is a modern technological concept in which physical devices communicate with each other through wireless networks and intelligent communication systems. IoT enables machines, sensors, controllers, and software applications to exchange information automatically and perform smart operations without continuous human involvement.

IoT technology has become one of the most important innovations in modern engineering because it connects electronic devices through communication systems such as Bluetooth, Wi-Fi, GSM, GPS, ZigBee, and cloud computing platforms. IoT systems are widely used in smart homes, industrial automation, healthcare systems, transportation systems, robotics, agriculture, and security applications.

The Smart Multi-Control Robotic Car project is related to IoT concepts because it uses wireless communication, intelligent control systems, sensor technologies, and automation mechanisms. Although the current project mainly uses Bluetooth communication, the robotic system can later be upgraded using Wi-Fi and internet technologies to become a complete IoT-enabled robotic platform.

An IoT system generally consists of four major components:

1. Sensors and Input Devices
2. Communication Network
3. Processing Unit
4. User Interface

In this project, the ultrasonic sensor acts as the sensing device that detects obstacles. Arduino Uno acts as the processing unit that controls robotic movement. The HC-05 Bluetooth module provides wireless communication between the robotic vehicle and mobile application. The MIT App Inventor application acts as the user interface for controlling the robotic system.

IoT-based robotic systems improve efficiency, automation, and operational safety. Intelligent robotic vehicles can automatically monitor surroundings, avoid obstacles, communicate wirelessly, and perform automated tasks.

Modern autonomous vehicles and smart robotic systems are based on IoT technologies combined with sensors, automation systems, and intelligent software algorithms. The Smart Multi-Control Robotic Car project demonstrates the basic implementation of such smart robotic automation concepts.

1.3 Problem Definition

Traditional robotic vehicles generally depend on wired communication systems or limited manual control methods. Such systems lack flexibility, intelligent navigation, obstacle detection, and automation features. In many cases, robotic vehicles are unable to detect nearby obstacles, resulting in collisions and operational problems.

Another major issue with conventional robotic systems is the absence of integrated multi-control functionality. Most systems support only one control method such as remote control or wired operation. There is a need for a robotic system capable of supporting multiple control mechanisms including mobile application control, Bluetooth communication, and autonomous movement.

Modern robotic systems require intelligent safety mechanisms and wireless communication capabilities for better efficiency and user convenience. Manual robotic systems also face limitations in terms of accessibility, automation, and navigation control.

The Smart Multi-Control Robotic Car project addresses these problems by developing an intelligent robotic vehicle capable of:

- Wireless Bluetooth control
- Smartphone application control
- Automatic obstacle detection
- Autonomous navigation
- Predefined route movement
- Intelligent safety mechanisms
- Sensor-based automation

The project also focuses on developing a low-cost robotic platform suitable for engineering education and practical learning. Many advanced robotic systems are expensive and difficult to implement. Therefore, this project demonstrates how affordable components can be integrated to create a smart robotic automation system.

The robotic car uses an ultrasonic sensor for obstacle detection and automatic stopping. The project also includes servo motor scanning for intelligent path detection and safe navigation.

1.4 Motivation

The motivation behind the development of the Smart Multi-Control Robotic Car project is the rapid growth of robotics, automation systems, and wireless communication technologies in modern engineering applications. Smart robotic systems are becoming increasingly important in industries, transportation systems, healthcare, military operations, surveillance systems, and educational research. These advanced technologies reduce human effort, improve efficiency, and increase operational safety.

The idea for this project originated from the need to develop an intelligent robotic vehicle that can be controlled wirelessly using a mobile application while also supporting automatic navigation and obstacle detection features. Traditional robotic systems mainly depend on wired communication or basic remote-control mechanisms, which limit flexibility and user convenience. Therefore, this project was motivated by the concept of creating a smart, flexible, and user-friendly robotic platform using low-cost electronic components.

Another major motivation was to gain practical knowledge in embedded systems and robotics engineering. The project provided an opportunity to understand the practical implementation of microcontrollers, wireless communication modules, sensors, motor drivers, and mobile application development. Through this project, practical engineering concepts could be applied in a real-time working model.

The development of smartphone technologies and wireless communication systems also motivated the implementation of Bluetooth-based robotic control. The use of the HC-05 Bluetooth module and MIT App Inventor mobile application helped in understanding how wireless communication occurs between hardware devices and smartphones.

The integration of automatic obstacle detection and intelligent navigation features further motivated the development process. Modern autonomous systems use sensors and intelligent algorithms to make movement decisions automatically. By implementing ultrasonic sensor-based obstacle detection, the project demonstrates how robotic vehicles can avoid collisions and improve operational safety.

The project was also motivated by the growing importance of automation technologies in modern industries. Smart robotic vehicles are now widely used in warehouses, delivery systems, industrial automation, hazardous environment monitoring, and intelligent transportation systems. Developing this project helped in understanding the working principles of such automation systems.

Another motivation behind the project was to create a low-cost and educational robotic platform suitable for engineering students and beginners. Many advanced robotic systems are expensive

and difficult to understand. This project demonstrates how affordable components like Arduino Uno, BO motors, Bluetooth modules, and ultrasonic sensors can be combined to create an efficient smart robotic system.

The project also motivated teamwork, communication skills, technical collaboration, problem-solving abilities, and project management skills among team members. During project development, students learned how to divide tasks, integrate hardware and software modules, perform testing, and solve implementation challenges.

Future technologies such as IoT, artificial intelligence, Wi-Fi communication, GPS navigation, and camera integration further inspired the development of this project.

1.5 Objectives

The primary objective of the Smart Multi-Control Robotic Car project is to design and develop an intelligent robotic vehicle capable of wireless control, automatic obstacle detection, and smart navigation using Arduino Uno and Bluetooth communication technology.

The specific objectives of the project are:

- To develop a smart robotic car using Arduino Uno microcontroller as the main control unit.
- To implement wireless Bluetooth communication using the HC-05 Bluetooth module.
- To develop a custom mobile application using MIT App Inventor for robotic car control.
- To control robotic movement in forward, backward, left, right, and stop directions using a smartphone application.
- To integrate an ultrasonic sensor for obstacle detection and distance measurement.
- To implement automatic safety stop functionality to prevent collisions.
- To design an autonomous navigation system capable of obstacle avoidance.
- To integrate servo motor scanning for intelligent directional sensing.
- To implement predefined route navigation such as Home, Hospital, Office, and School paths.
- To control BO motors using the L293D motor driver module.
- To implement speed control using PWM signals.
- To understand the practical implementation of embedded systems and automation technologies.
- To improve knowledge in robotics, wireless communication, and mobile application development.
- To create a low-cost and efficient robotic automation platform for educational purposes.
- To understand sensor integration and intelligent navigation systems.
- To improve problem-solving, debugging, and hardware integration skills.
- To demonstrate practical implementation of automation concepts in real-time applications.
- To provide a foundation for future upgrades using Wi-Fi, IoT, GPS, camera systems, and artificial intelligence.
- To enhance teamwork, project planning, and technical presentation skills.
- To develop a smart robotic system that demonstrates modern automation technologies effectively.

1.6 Scope of Project

The scope of the Smart Multi-Control Robotic Car project is very broad because robotics and automation technologies are continuously growing in modern engineering applications. The project demonstrates the implementation of intelligent robotic systems using wireless communication, embedded systems, automation techniques, and mobile application control.

The project scope includes wireless robotic control using Bluetooth communication technology. The robotic vehicle can be operated remotely through a smartphone application developed using MIT App Inventor. This allows users to control the robotic car conveniently without physical connections.

The project also includes automatic obstacle detection and autonomous navigation features using an ultrasonic sensor and servo motor. The robotic car can identify nearby obstacles and avoid collisions during movement. This improves operational safety and introduces basic autonomous robotic behavior.

Another important scope of the project is the implementation of predefined route navigation systems such as Home, Hospital, Office, and School routes. These features demonstrate automatic movement control and programmed navigation sequences in robotic systems.

The project provides practical exposure to several engineering domains including:

- Embedded systems
- Robotics engineering
- Wireless communication
- Automation technologies
- Sensor integration
- Mobile application development
- Motor control systems
- Intelligent navigation systems

The project can be used for educational purposes in engineering colleges and robotics laboratories to demonstrate practical automation concepts and wireless robotic systems.

The robotic platform can also be used as a prototype for future smart transportation and autonomous robotic applications. Similar robotic systems are widely used in:

- Industrial automation
- Smart warehouses
- Surveillance systems
- Rescue operations

- Hazardous environment monitoring
- Smart delivery systems
- Medical assistance robots
- Security monitoring systems

The future scope of the project is very large because the robotic system can be upgraded with modern technologies such as:

- Wi-Fi communication
- Internet of Things (IoT)
- GPS navigation
- Camera streaming systems
- Voice control
- Artificial intelligence
- Machine learning
- Cloud connectivity
- Real-time monitoring systems
- Autonomous path planning

The project can also be expanded into a fully autonomous smart robotic vehicle capable of intelligent decision-making and advanced navigation.

CHAPTER 2

LITERATURE SURVEY

2.1 Related Works

Robotics and automation technologies have become one of the most important research areas in modern engineering. Various robotic systems have been developed for industrial automation, transportation, healthcare, surveillance, military operations, and educational purposes. Wireless robotic vehicles controlled through mobile applications, Bluetooth communication, and intelligent navigation systems are widely researched due to their flexibility, efficiency, and automation capabilities.

Several researchers and developers have worked on robotic vehicles using microcontrollers, sensors, wireless communication modules, and mobile applications. The development of low-cost embedded systems such as Arduino Uno has made robotic system development easier for students, researchers, and automation engineers.

One of the commonly developed robotic systems is the Bluetooth-controlled robotic car. In these systems, Bluetooth modules such as HC-05 or HC-06 are connected to microcontrollers for wireless communication with smartphones or computers. Mobile applications send commands through Bluetooth communication to control robotic movement. These systems are widely used because Bluetooth communication is simple, cost-effective, and suitable for short-range wireless control.

Researchers have also developed robotic systems using Android mobile applications for movement control. Applications developed using MIT App Inventor and Android Studio are commonly used for wireless robotic vehicle control. These mobile applications provide user-friendly interfaces with movement buttons, speed controls, and automation options.

Another important area of related work is obstacle detection and obstacle avoidance systems. Ultrasonic sensors such as HC-SR04 are widely used in robotics to measure distance and detect nearby objects. These sensors help robotic systems avoid collisions during movement. In many autonomous robotic systems, ultrasonic sensors are combined with servo motors for environmental scanning and intelligent navigation.

Several robotic systems also implement automatic path navigation and autonomous movement. Such systems use programmed movement sequences, sensor feedback, and intelligent control algorithms to move automatically without continuous human control. Autonomous robotic

systems are used in warehouses, hospitals, industrial automation, and smart transportation systems.

Many researchers have focused on smart robotic systems integrated with Internet of Things (IoT) technologies. IoT-enabled robots use Wi-Fi communication, cloud connectivity, GPS systems, and real-time monitoring for remote control and intelligent operation. Such systems improve accessibility, automation, and monitoring capabilities.

Educational robotic projects have also become highly popular because they help students understand embedded systems, automation, sensor technologies, and programming concepts practically. Arduino-based robotic systems are widely preferred in educational institutions due to their simplicity and affordability.

Some robotic projects use voice control systems where speech recognition applications send commands to robotic vehicles. Others use gamepad controllers, web-based interfaces, and smartphone sensors for robotic control.

In modern research, autonomous robotic systems combined with artificial intelligence and machine learning are becoming increasingly important. AI-based robotic systems can analyze surroundings, make decisions, and perform complex tasks automatically. Although such systems are more advanced, basic robotic platforms provide the foundation for future intelligent automation systems.

The Smart Multi-Control Robotic Car project is inspired by these existing robotic technologies and integrates multiple features such as Bluetooth control, MIT App control, automatic obstacle detection, route navigation, and smart automation into a single robotic platform.

The project demonstrates practical implementation of robotics and automation concepts using affordable electronic components. It also provides flexibility for future upgrades such as Wi-Fi communication, GPS navigation, voice control, and AI-based autonomous systems.

The literature survey shows that robotic automation systems are continuously evolving and becoming more intelligent, efficient, and user-friendly. The development of smart robotic systems will continue to play a major role in future engineering and automation applications.

2.2 Existing System

Existing robotic vehicle systems generally focus on simple movement control using wired communication or basic wireless remote-control technologies. Most traditional robotic systems support only manual operation and lack intelligent automation features such as obstacle detection, autonomous navigation, and sensor-based safety systems.

Many existing robotic systems use RF remote control circuits or wired joystick control methods. These systems provide only basic movement operations such as forward, backward, left, and right movement. Such systems are difficult to operate over long distances and provide limited flexibility to users.

Some robotic vehicles use Bluetooth communication for wireless operation. In these systems, smartphones communicate with robotic vehicles through Bluetooth modules connected to microcontrollers. Although these systems provide wireless control, many of them support only basic movement operations and do not include intelligent navigation systems.

Existing robotic systems also face limitations in obstacle detection and collision prevention. Vehicles without sensor-based safety mechanisms may collide with objects during movement, resulting in hardware damage and operational problems. Many traditional systems depend completely on user control without automatic safety features.

Certain robotic systems include obstacle detection using ultrasonic sensors, but they often lack intelligent navigation mechanisms. In such cases, the robotic vehicle only stops when obstacles are detected but cannot identify alternative movement paths automatically.

Some advanced robotic systems support autonomous movement using programmed navigation algorithms. However, such systems are often expensive, complex, and difficult to implement for educational purposes. Many advanced autonomous systems require costly sensors, high-performance processors, GPS modules, camera systems, and machine learning technologies.

Existing systems also commonly suffer from the following limitations:

- Limited wireless communication range
- Lack of mobile application integration
- Absence of automatic navigation
- No predefined route control
- High implementation cost
- Complex hardware setup
- Limited flexibility for upgrades
- Lack of user-friendly interfaces

- Poor obstacle avoidance capability
- Dependence on manual control

Most traditional robotic systems are designed only for demonstration purposes and are not flexible enough for future upgrades and intelligent automation integration.

Another limitation in existing systems is the absence of integrated multi-control functionality. Many robotic vehicles support only one control method such as remote control or Bluetooth control. There is a growing requirement for robotic systems capable of supporting multiple intelligent control mechanisms.

Existing educational robotic platforms often lack practical automation features that demonstrate real-world industrial and smart transportation concepts. Many beginner robotic systems focus only on basic motor movement without intelligent sensing or automation capabilities.

Furthermore, some robotic systems consume high power and require expensive components, making them unsuitable for students and educational institutions.

The analysis of existing systems clearly indicates the need for a smart robotic platform that combines wireless communication, intelligent automation, obstacle detection, autonomous movement, and mobile application control into a single affordable system.

The Smart Multi-Control Robotic Car project is designed to overcome these limitations by integrating Bluetooth communication, MIT App control, ultrasonic obstacle detection, automatic navigation, and predefined route systems into a compact robotic platform.

The project focuses on simplicity, affordability, practical learning, and intelligent automation while maintaining flexibility for future upgrades and research development.

2.3 Proposed System

The proposed system is a Smart Multi-Control Robotic Car designed using Arduino Uno, HC-05 Bluetooth module, L293D motor driver, ultrasonic sensor, servo motor, BO motors, and a mobile application developed using MIT App Inventor.

The proposed robotic system is designed to overcome the limitations of traditional robotic vehicles by integrating wireless communication, intelligent automation, obstacle detection, autonomous navigation, and predefined route control into a single robotic platform.

In the proposed system, Arduino Uno acts as the central controller responsible for processing commands and controlling all hardware components connected to the robotic system. The Arduino receives commands from the Bluetooth module and executes motor movement operations accordingly.

The HC-05 Bluetooth module provides wireless communication between the robotic car and the mobile application. Users can control the robotic vehicle through a smartphone application using Bluetooth connectivity. The mobile application developed using MIT App Inventor includes movement buttons, predefined route controls, and system control options.

The robotic vehicle supports movement operations such as:

- Forward movement
- Backward movement
- Left movement
- Right movement
- Stop operation

The proposed system also includes predefined route navigation features such as Home, Hospital, Office, and School routes. These routes are implemented using programmed movement sequences stored in Arduino programming logic.

One of the major features of the proposed system is automatic obstacle detection and obstacle avoidance. The ultrasonic sensor continuously measures the distance between the robotic vehicle and nearby obstacles. If an obstacle is detected within a specified distance, the robotic vehicle automatically stops to prevent collisions.

The servo motor is used for intelligent environmental scanning. During autonomous navigation, the servo motor rotates the ultrasonic sensor in different directions to identify safer movement paths. Based on sensor readings, the robotic vehicle changes direction automatically for obstacle avoidance.

The proposed system also supports autonomous mode operation where the robotic vehicle can move intelligently without continuous user control. This improves automation and demonstrates smart robotic navigation concepts.

The L293D motor driver module controls the BO motors connected to the robotic vehicle. The motor driver receives control signals from Arduino and supplies required power to the motors for directional movement.

The proposed system is designed using low-cost and easily available components, making it economical and suitable for educational institutions and beginner robotic applications.

Major advantages of the proposed system include:

- Wireless Bluetooth communication
- Mobile application control
- Automatic obstacle detection
- Autonomous navigation
- Intelligent obstacle avoidance
- User-friendly interface
- Predefined route navigation
- Low implementation cost
- Easy hardware integration
- Flexibility for future upgrades

The proposed system also provides opportunities for future enhancements such as:

- Wi-Fi communication
- Internet of Things integration
- GPS navigation systems
- Voice control systems
- Camera streaming
- Cloud connectivity
- Artificial intelligence integration
- Machine learning-based navigation

The Smart Multi-Control Robotic Car project demonstrates practical implementation of modern robotic automation technologies using embedded systems, wireless communication, and intelligent sensor integration.

CHAPTER 3

SYSTEM REQUIREMENT SPECIFICATION

3.1 Functional Requirements

Functional requirements describe the operations and functions that the Smart Multi-Control Robotic Car system must perform successfully. These requirements define how the robotic system behaves, communicates, processes commands, and performs intelligent operations.

The Smart Multi-Control Robotic Car project is designed to perform wireless robotic control, obstacle detection, intelligent navigation, and automated movement using embedded systems and Bluetooth communication technology.

The important functional requirements of the proposed system are explained below.

3.1.1 Wireless Communication

The robotic system must support wireless communication between the mobile application and the robotic car using the HC-05 Bluetooth module. The system should establish stable Bluetooth connectivity for transmitting movement commands from the smartphone to the Arduino Uno controller.

The Bluetooth module must:

- Receive wireless commands
- Communicate with Arduino Uno
- Support smartphone connectivity
- Maintain reliable communication within operational range

3.1.2 Mobile Application Control

The system must support control through a mobile application developed using MIT App Inventor.

The mobile application should provide:

- Forward movement button
- Backward movement button
- Left movement button
- Right movement button
- Stop button
- Bluetooth connection option
- Route navigation buttons

The application must provide a user-friendly interface for controlling the robotic car wirelessly.

3.1.3 Robotic Movement Control

The robotic vehicle must support directional movement according to commands received from the mobile application.

The robotic car should perform:

- Forward movement
- Backward movement
- Left turning
- Right turning
- Stop operation

The movement control should be achieved using BO motors and L293D motor driver module.

3.1.4 Obstacle Detection

The system must detect nearby obstacles using the ultrasonic sensor.

The ultrasonic sensor should:

- Measure distance continuously
- Detect nearby objects
- Send distance information to Arduino Uno
- Help avoid collisions

The obstacle detection feature improves safety and intelligent operation of the robotic car.

3.1.5 Automatic Obstacle Avoidance

The robotic system must automatically stop when obstacles are detected within a predefined range.

The system should:

- Stop movement automatically
- Scan surroundings using servo motor
- Select safe movement direction
- Continue navigation safely

This feature enables semi-autonomous robotic navigation.

3.1.6 Servo Motor Scanning

The servo motor must rotate the ultrasonic sensor for intelligent environmental scanning.

The servo system should:

- Rotate left and right
- Scan obstacle positions
- Support smart path selection
- Improve navigation accuracy

3.1.7 Predefined Route Navigation

The robotic system must support predefined route navigation such as:

- Home route
- Hospital route
- Office route
- School route

The routes should be implemented using programmed movement sequences stored in Arduino code.

3.1.8 Autonomous Mode

The robotic car must support autonomous mode operation where the system can navigate automatically without continuous user control.

The autonomous system should:

- Detect obstacles
- Change directions automatically
- Navigate safely
- Reduce manual operation

3.1.9 Speed Control

The robotic system should support motor speed control using PWM signals.

The speed control feature should:

- Control motor rotation speed
- Improve robotic movement
- Enable smooth operation
- Support efficient navigation

3.1.10 Real-Time Processing

The Arduino Uno controller must process commands and sensor data in real time for smooth robotic operation.

The system should:

- Receive commands instantly
- Process sensor readings quickly
- Execute movements efficiently
- Maintain continuous operation

3.2 Non-Functional Requirements

Non-functional requirements describe the quality, performance, reliability, usability, and operational characteristics of the Smart Multi-Control Robotic Car system.

These requirements ensure that the robotic system performs efficiently and reliably under different operating conditions.

3.2.1 Reliability

The robotic system must provide reliable operation during wireless communication, movement control, and obstacle detection.

The system should:

- Maintain stable Bluetooth connection
- Avoid communication failures
- Perform accurate movement operations
- Operate continuously without interruption

3.2.2 Performance

The system should provide fast response during robotic operation.

The robotic vehicle must:

- Respond quickly to user commands
- Process sensor data efficiently
- Perform smooth directional movement
- Avoid delays in operation

3.2.3 Efficiency

The system should operate efficiently using low-cost electronic components and optimized Arduino programming.

The robotic system must:

- Consume minimum power
- Utilize hardware resources effectively
- Provide efficient movement control
- Support continuous operation

3.2.4 Usability

The mobile application and robotic system should be simple and user-friendly.

The system should:

- Provide easy movement control
- Support simple Bluetooth connectivity
- Offer understandable user interface
- Allow convenient robotic operation

3.2.5 Maintainability

The robotic system should be easy to maintain and upgrade.

The project should:

- Allow hardware replacement
- Support future modifications
- Enable software updates
- Simplify troubleshooting procedures

3.2.6 Scalability

The robotic platform should support future expansion and advanced technology integration.

The system should allow:

- Wi-Fi integration
- GPS modules
- Camera systems
- AI-based automation
- IoT connectivity

3.2.7 Safety

The robotic system must include safety mechanisms for preventing collisions and hardware damage.

The safety system should:

- Detect obstacles automatically
- Stop movement during danger
- Protect hardware components
- Ensure safe operation

3.2.8 Portability

The robotic vehicle should be compact and portable for educational demonstrations and practical applications.

The system should:

- Be lightweight
- Support easy transportation
- Operate in different environments
- Provide flexible usage

3.2.9 Cost Effectiveness

The project should be economical and affordable for students and educational institutions.

The system should:

- Use low-cost components
- Reduce implementation expenses
- Support educational learning
- Maintain efficient performance

3.2.10 Compatibility

The robotic system should support compatibility between hardware and software modules.

The project should ensure:

- Arduino compatibility
- Bluetooth communication compatibility
- Mobile application support
- Smooth hardware integration

3.3 Software Requirements

Software requirements describe the software tools, programming environments, development platforms, and operating systems required for implementing the Smart Multi-Control Robotic Car project.

The software components used in the project are explained below.

3.3.1 Arduino IDE

The project uses Arduino IDE for writing, compiling, debugging, and uploading Arduino programs.

Arduino IDE is used because:

- It supports Arduino Uno programming
- It provides simple C/C++ programming environment
- It supports serial monitoring
- It simplifies embedded programming

Functions of Arduino IDE:

- Code writing
- Program compilation
- Error debugging
- Uploading code to Arduino Uno
- Serial communication monitoring

3.3.2 MIT App Inventor

The mobile application is developed using MIT App Inventor.

MIT App Inventor is used because:

- It provides drag-and-drop programming
- It simplifies Android app development
- It supports Bluetooth communication
- It is beginner-friendly

The application provides:

- Bluetooth connectivity
- Movement control buttons
- Route navigation buttons
- User-friendly interface

3.3.3 Embedded C Programming

The Arduino Uno is programmed using Embedded C programming language.

Embedded C is used for:

- Motor control
- Bluetooth communication

- Sensor integration
- Autonomous navigation
- Servo motor control

The programming logic controls all robotic operations.

3.3.4 Operating System

The project development system requires a computer operating system such as:

- Windows
- Linux
- macOS

These operating systems support:

- Arduino IDE installation
- Mobile app development
- Driver installation
- Bluetooth communication

3.3.5 Serial Monitor

Arduino Serial Monitor is used for:

- Debugging
- Monitoring commands
- Checking sensor values
- Verifying Bluetooth communication

Serial monitoring helps identify programming and communication issues.

3.3.6 Bluetooth Communication Software

Bluetooth communication between the smartphone and HC-05 module is required for wireless robotic control.

The Bluetooth system supports:

- Wireless pairing
- Command transmission
- Real-time robotic control
- Data communication

3.3.7 Driver Software

USB drivers are required for:

- Arduino Uno detection
- USB communication
- Program uploading

These drivers allow communication between the computer and Arduino board.

3.4 Hardware Requirements

Hardware requirements describe the electronic components, sensors, communication modules, power systems, and mechanical components required for implementing the Smart Multi-Control Robotic Car project.

The major hardware components used in the project are explained below.

3.4.1 Arduino Uno

Arduino Uno is the main microcontroller board used in the project.

Functions:

- Processes commands
- Controls motors
- Reads sensor data
- Executes robotic operations

Features:

- ATmega328P microcontroller
- Digital input/output pins
- PWM support
- USB programming support

3.4.2 HC-05 Bluetooth Module

The HC-05 Bluetooth module is used for wireless communication between the robotic car and mobile application.

Functions:

- Receives wireless commands
- Communicates with Arduino Uno
- Enables smartphone control

Features:

- Wireless communication
- Serial communication support

- Easy pairing capability

3.4.3 L293D Motor Driver

The L293D motor driver controls the BO motors connected to the robotic vehicle.

Functions:

- Controls motor direction
- Supplies motor power
- Supports forward and reverse movement

The motor driver protects Arduino from high motor current.

3.4.4 BO Motors

BO motors are used for robotic movement.

Functions:

- Drive the robotic wheels
- Support directional movement
- Enable vehicle navigation

The motors provide movement in:

- Forward direction
- Backward direction
- Left turning
- Right turning

3.4.5 Ultrasonic Sensor

The HC-SR04 ultrasonic sensor is used for obstacle detection.

Functions:

- Measures distance
- Detects nearby obstacles
- Supports autonomous navigation

The sensor improves robotic safety and automation.

3.4.6 Servo Motor

The servo motor rotates the ultrasonic sensor for environmental scanning.

Functions:

- Rotates sensor left and right

- Supports intelligent navigation
- Improves obstacle detection

3.4.7 Wheels and Chassis

The robotic chassis provides mechanical support for all hardware components.

Functions:

- Supports robotic structure
- Holds motors and electronics
- Enables smooth movement

3.4.8 Battery and Power Supply

Battery supply provides electrical power to the robotic system.

Functions:

- Powers Arduino Uno
- Supplies motor driver
- Operates motors and sensors

The battery ensures continuous robotic operation.

3.4.9 Jumper Wires

Jumper wires are used for electrical connections between components.

Functions:

- Connect modules
- Transfer signals
- Support circuit integration

3.4.10 Breadboard

Breadboard is used for temporary electronic connections and testing.

Functions:

- Simplifies prototyping
- Supports easy connections
- Helps during circuit testing

The hardware components together form a complete intelligent robotic automation platform capable of wireless communication, smart movement, and autonomous navigation.

CHAPTER 4

SYSTEM DESIGN AND DEVELOPMENT

4.1 Introduction

The System Design and Development phase is one of the most important stages in the implementation of the Smart Multi-Control Robotic Car project. This phase involves designing the complete robotic system architecture, integrating hardware and software components, developing control logic, and implementing wireless communication and automation features.

The Smart Multi-Control Robotic Car is designed using Arduino Uno as the central controller. The system integrates Bluetooth communication, motor control, obstacle detection, autonomous navigation, and mobile application control into a single intelligent robotic platform.

The development process includes:

- Hardware integration
- Circuit design
- Mobile application development
- Embedded programming
- Bluetooth communication setup
- Sensor integration
- Robotic movement control

The project is developed using low-cost electronic components and user-friendly software tools, making it suitable for educational and automation applications.

The robotic system is designed to operate in both manual and autonomous modes. In manual mode, the robotic vehicle is controlled using a mobile application through Bluetooth communication. In autonomous mode, the robotic car detects obstacles automatically and changes direction for safe navigation.

The development phase also focuses on improving flexibility, portability, efficiency, and future scalability of the robotic platform.

4.2 Block Diagram

The block diagram represents the overall architecture and interconnection between different hardware and software modules used in the Smart Multi-Control Robotic Car system.

The major blocks in the system include:

- Mobile Application
- HC-05 Bluetooth Module
- Arduino Uno
- L293D Motor Driver
- BO Motors
- Ultrasonic Sensor
- Servo Motor
- Battery Supply

Working of Block Diagram

1. The mobile application sends movement commands through Bluetooth communication.
2. The HC-05 Bluetooth module receives wireless commands and transfers them to Arduino Uno.
3. Arduino Uno processes the received commands and generates control signals.
4. The L293D motor driver receives control signals from Arduino and drives the BO motors.
5. The motors control robotic movement in forward, backward, left, and right directions.
6. The ultrasonic sensor continuously detects nearby obstacles and sends distance information to Arduino Uno.
7. The servo motor rotates the ultrasonic sensor for intelligent environmental scanning.
8. The battery supply powers all electronic components and motors.

The block diagram simplifies understanding of the complete robotic system workflow and communication process.

4.3 Circuit Diagram

The circuit diagram represents the electrical connections between all hardware components used in the robotic system.

The major hardware connections include:

Arduino Uno Connections

Arduino Uno acts as the central controller connected to:

- HC-05 Bluetooth module
- L293D motor driver
- Ultrasonic sensor
- Servo motor

Bluetooth Module Connections

HC-05 Bluetooth module connections:

- TX pin → Arduino RX
- RX pin → Arduino TX
- VCC → 5V supply
- GND → Ground

The Bluetooth module provides wireless communication between the smartphone and robotic system.

Motor Driver Connections

The L293D motor driver controls the BO motors.

Connections include:

- Input pins connected to Arduino digital pins
- Output pins connected to motors
- External battery supply connected for motor power

The motor driver protects Arduino Uno from high motor current.

Ultrasonic Sensor Connections

The HC-SR04 ultrasonic sensor connections include:

- Trigger pin connected to Arduino output pin
- Echo pin connected to Arduino input pin
- VCC connected to power supply
- GND connected to ground

The sensor measures obstacle distance.

Servo Motor Connections

Servo motor connections include:

- Signal pin connected to Arduino PWM pin
- Power supply connection
- Ground connection

The servo motor rotates the ultrasonic sensor for obstacle scanning.

Battery Connections

Battery supply provides required power for:

- Arduino Uno
- Motors
- Bluetooth module
- Sensors
- Servo motor

The complete circuit design ensures proper communication and operation between all system components.

4.4 Working Principle

The Smart Multi-Control Robotic Car works based on wireless communication, embedded programming, motor control, and intelligent sensor-based navigation.

The working principle of the robotic system can be explained as follows:

1. The user opens the mobile application developed using MIT App Inventor and connects the smartphone with the HC-05 Bluetooth module.
2. When movement buttons are pressed in the application, commands are sent wirelessly through Bluetooth communication.
3. The HC-05 Bluetooth module receives the commands and transfers them to Arduino Uno.
4. Arduino Uno processes the received commands and generates corresponding motor control signals.
5. The L293D motor driver receives these signals and drives the BO motors.
6. Depending on the command, the robotic car moves:
 - Forward
 - Backward
 - Left
 - Right
 - Stop
7. During movement, the ultrasonic sensor continuously measures the distance between the robotic vehicle and nearby objects.
8. If an obstacle is detected within a specified range, Arduino Uno automatically stops the robotic vehicle.
9. The servo motor rotates the ultrasonic sensor left and right to scan surrounding areas.
10. Based on obstacle distance measurements, Arduino selects a safer direction and continues movement.
11. In predefined route mode, programmed navigation sequences are executed automatically.
12. In autonomous mode, the robotic system performs obstacle avoidance and navigation without continuous user control.

Thus, the robotic system combines wireless control, intelligent sensing, automation, and embedded programming into a single platform.

4.5 MIT App Design

The mobile application for the Smart Multi-Control Robotic Car is developed using MIT App Inventor.

MIT App Inventor provides a simple drag-and-drop interface for Android application development. The app is designed to provide easy and user-friendly robotic control.

Features of MIT App

The application includes:

- Bluetooth connection button
- Forward button
- Backward button
- Left button
- Right button
- Stop button
- Route navigation buttons
- Autonomous mode button

Application Interface

The mobile app interface is designed with:

- Simple control layout
- Large movement buttons
- User-friendly navigation
- Bluetooth connectivity options

App Working

1. User connects smartphone with HC-05 Bluetooth module.
2. The app establishes wireless communication.
3. Button presses send character commands to Arduino Uno.
4. Arduino processes commands and controls robotic movement.

The MIT App improves accessibility and simplifies wireless robotic control using smartphones.

4.6 Bluetooth Communication

Bluetooth communication plays a major role in wireless robotic control.

The project uses the HC-05 Bluetooth module for communication between the smartphone application and Arduino Uno.

Bluetooth Communication Process

1. Smartphone pairs with HC-05 Bluetooth module.
2. The mobile application sends movement commands.
3. HC-05 receives commands wirelessly.
4. Commands are transferred to Arduino Uno through serial communication.
5. Arduino processes commands and controls motors.

Advantages of Bluetooth Communication

- Wireless operation
- Easy connectivity
- Low power consumption
- Low implementation cost
- Simple communication setup

Bluetooth communication enables efficient and flexible robotic control without wired connections.

The communication range is suitable for educational and indoor robotic applications.

4.7 Obstacle Detection System

The obstacle detection system is one of the most important intelligent features of the Smart Multi-Control Robotic Car.

The system uses an HC-SR04 ultrasonic sensor and servo motor for obstacle detection and navigation.

Working of Ultrasonic Sensor

The ultrasonic sensor works by transmitting ultrasonic sound waves and receiving reflected echo signals.

The sensor:

1. Sends ultrasonic pulse
2. Receives reflected signal
3. Calculates time delay
4. Measures obstacle distance

Arduino Uno calculates distance using:

- Echo pulse duration
- Speed of sound formula

Obstacle Detection Process

1. Ultrasonic sensor continuously scans front area.
2. Distance information is sent to Arduino Uno.
3. If obstacle distance becomes less than predefined limit:
 - Robot stops automatically
 - Servo motor rotates sensor
 - Surrounding areas are scanned
4. Arduino compares left and right distances.
5. Safer direction is selected automatically.
6. Robot changes direction and continues movement.

Advantages of Obstacle Detection System

- Prevents collisions
- Improves safety
- Supports autonomous navigation
- Enhances robotic intelligence
- Reduces manual control dependency

The obstacle detection system allows the robotic car to navigate intelligently and safely during autonomous operation.

CHAPTER 5

IMPLEMENTATION

5.1 Hardware Implementation

Hardware implementation is one of the most important stages in the development of the Smart Multi-Control Robotic Car project. This phase involves assembling all electronic components, making electrical connections, integrating sensors, configuring wireless communication modules, and constructing the robotic vehicle chassis.

The project hardware implementation is designed to provide efficient robotic movement, wireless communication, intelligent obstacle detection, and autonomous navigation using low-cost and easily available electronic components.

The major hardware components used in the project are:

- Arduino Uno
- HC-05 Bluetooth Module
- L293D Motor Driver
- BO Motors
- Ultrasonic Sensor
- Servo Motor
- Battery Supply
- Wheels and Chassis
- Jumper Wires
- Breadboard

Arduino Uno Implementation

Arduino Uno acts as the main controller of the robotic system. All hardware modules are connected to Arduino Uno for centralized processing and control.

The Arduino board performs:

- Command processing
- Sensor reading
- Motor control
- Bluetooth communication
- Autonomous navigation logic

Digital pins of Arduino Uno are connected to:

- Motor driver inputs
- Bluetooth module TX/RX
- Ultrasonic sensor pins
- Servo motor signal pin

Arduino Uno is programmed using Embedded C through Arduino IDE.

Motor Driver Implementation

The L293D motor driver is implemented to control the BO motors connected to the robotic car.

The motor driver receives control signals from Arduino Uno and supplies required current to motors for movement operations.

The motor driver implementation includes:

- Forward movement control
- Reverse movement control
- Left and right turning control
- Motor protection from high current

The motor driver acts as an interface between Arduino Uno and motors because Arduino cannot directly drive high-current motors.

BO Motor and Wheel Assembly

The robotic vehicle uses BO motors connected to wheels for movement.

The motors are fixed on the robotic chassis and connected to the motor driver outputs.

The wheel assembly provides:

- Smooth movement
- Directional control
- Stability during operation
- Proper balance of robotic vehicle

The motors are powered using external battery supply for efficient operation.

Bluetooth Module Implementation

The HC-05 Bluetooth module is implemented for wireless communication between the mobile application and robotic system.

The Bluetooth module is connected to Arduino Uno using serial communication pins.

Functions of Bluetooth module:

- Wireless pairing
- Receiving movement commands
- Sending serial data
- Supporting mobile control

The module enables wireless robotic operation through smartphones.

Ultrasonic Sensor Implementation

The HC-SR04 ultrasonic sensor is implemented for obstacle detection and intelligent navigation.

The ultrasonic sensor continuously measures the distance between the robotic vehicle and nearby objects.

The sensor implementation includes:

- Trigger pulse generation
- Echo signal reading
- Distance calculation
- Obstacle monitoring

The sensor improves robotic safety and automation.

Servo Motor Implementation

The servo motor is connected to rotate the ultrasonic sensor for environmental scanning.

The servo motor implementation supports:

- Left scanning
- Right scanning
- Front scanning
- Intelligent path detection

The servo motor allows the robotic system to identify safer movement directions during autonomous navigation.

Battery and Power Supply Implementation

Battery supply provides electrical power to all hardware components.

The battery powers:

- Arduino Uno
- Motors
- Bluetooth module
- Ultrasonic sensor

- Servo motor

Proper voltage regulation is maintained to ensure stable robotic operation.

Chassis Construction

The robotic chassis acts as the physical body of the robotic car.

The chassis implementation includes:

- Motor mounting
- Component arrangement
- Wire management
- Structural balancing

The chassis is designed to provide stability, portability, and efficient movement.

5.2 Software Implementation

Software implementation involves developing embedded programs, mobile application logic, wireless communication protocols, and automation algorithms for robotic control.

The Smart Multi-Control Robotic Car project uses both embedded software and mobile application software.

The major software tools used are:

- Arduino IDE
- MIT App Inventor

Arduino Programming

Arduino Uno is programmed using Embedded C language.

The Arduino program controls:

- Motor operations
- Bluetooth communication
- Sensor readings
- Autonomous navigation
- Servo motor movement
- Route navigation

The Arduino code processes all commands received through Bluetooth communication.

The program contains:

- Setup function
- Loop function
- Motor control functions
- Obstacle detection functions
- Autonomous navigation functions
- Route functions

Bluetooth Communication Logic

Bluetooth communication is implemented using SoftwareSerial library.

The HC-05 Bluetooth module communicates with Arduino Uno through serial communication.

The program:

- Reads Bluetooth commands
- Identifies movement instructions

- Executes corresponding robotic operations

Character commands used:

- F → Forward
- B → Backward
- L → Left
- R → Right
- S → Stop
- A → Autonomous mode

Motor Control Programming

Motor movement is controlled using digital output signals sent to the L293D motor driver.

The software controls:

- Forward rotation
- Reverse rotation
- Turning operations
- Motor stopping

PWM signals are also used for speed control.

Obstacle Detection Programming

The ultrasonic sensor program measures distance using echo pulse duration.

The software:

- Sends ultrasonic trigger pulse
- Measures echo return time
- Calculates distance
- Detects nearby obstacles

If an obstacle is detected:

- Robot stops
- Servo motor scans surroundings
- Safe direction is selected

Autonomous Navigation Programming

Autonomous mode is implemented using sensor-based navigation algorithms.

The robot:

- Detects obstacles automatically

- Changes direction intelligently
- Avoids collisions
- Navigates independently

This improves robotic intelligence and automation.

MIT App Development

The mobile application is developed using MIT App Inventor drag-and-drop interface.

The application includes:

- Bluetooth connection button
- Movement buttons
- Route control buttons
- Autonomous mode button

The application sends serial character commands through Bluetooth communication.

5.3 Arduino Source Code

The Arduino source code is the core control program of the robotic system.

The source code is developed using Embedded C language in Arduino IDE.

The code includes:

- Library declarations
- Pin configurations
- Bluetooth communication setup
- Sensor integration
- Motor control logic
- Autonomous navigation algorithms

Main Libraries Used

```
#include <SoftwareSerial.h>
```

```
#include <Servo.h>
```

SoftwareSerial library is used for Bluetooth communication.

Servo library is used for servo motor control.

Pin Configuration

The Arduino pins are configured for:

- Motor driver
- Bluetooth module
- Ultrasonic sensor
- Servo motor

Example:

```
const int motorLeft1 = 2;
```

```
const int motorLeft2 = 3;
```

```
const int motorRight1 = 4;
```

```
const int motorRight2 = 5;
```


Bluetooth Communication Code

The Bluetooth module receives wireless commands from mobile application.

Example:

```
if (bluetooth.available())  
{  
    cmd = bluetooth.read();  
    processCommand(cmd);  
}
```

Motor Control Functions

Separate functions are used for robotic movement.

Example:

```
void moveForward()  
{  
    digitalWrite(motorLeft1, HIGH);  
    digitalWrite(motorLeft2, LOW);  
    digitalWrite(motorRight1, HIGH);  
    digitalWrite(motorRight2, LOW);  
}
```

Obstacle Detection Code

The ultrasonic sensor calculates distance using echo timing.

Example:

```
distance = duration * 0.034 / 2;
```

Autonomous Navigation Logic

The autonomous system scans surroundings and changes direction automatically.

The program:

- Stops on obstacle detection
- Scans left and right
- Selects safer path

- Continues movement

Route Navigation Functions

Predefined routes are implemented using programmed movement sequences.

Example routes:

- Home route
- Office route
- School route
- Hospital route

These functions demonstrate automatic robotic movement.

5.4 MIT App Logic

The MIT App logic defines how the mobile application communicates with the robotic system and controls movement operations.

The application is designed using graphical programming blocks in MIT App Inventor.

Bluetooth Connection Logic

The application first connects to the HC-05 Bluetooth module.

Connection steps:

1. Enable Bluetooth
2. Select HC-05 device
3. Establish connection
4. Start communication

Button Control Logic

Each movement button sends a specific character command.

Examples:

- Forward button → F
- Backward button → B
- Left button → L
- Right button → R
- Stop button → S

The Arduino reads these commands and performs corresponding actions.

Autonomous Mode Logic

The autonomous mode button sends command:

- A → Autonomous navigation enabled

The robotic system then performs automatic obstacle avoidance without manual control.

Route Navigation Logic

Special buttons are provided for predefined routes.

Examples:

- Home → 1
- Hospital → 2
- Office → 3

- School → 4

These commands activate programmed movement sequences.

User Interface Design

The MIT App interface is designed with:

- Large buttons
- Simple layout
- Easy navigation
- User-friendly operation

The design improves accessibility and convenience for robotic control.

5.5 Testing and Calibration

Testing and calibration are essential processes in the implementation of the Smart Multi-Control Robotic Car project.

These processes ensure proper functioning, reliability, and accuracy of the robotic system.

Hardware Testing

Each hardware component is tested individually.

Arduino Testing

- Program uploading verification
- Serial communication testing
- Pin functionality testing

Bluetooth Testing

- Device pairing verification
- Wireless communication testing
- Command transmission testing

Motor Testing

- Direction testing
- Speed testing
- Rotation verification

Sensor Testing

- Distance measurement verification
- Obstacle detection testing
- Servo scanning testing

Software Testing

The software is tested for:

- Program execution
- Bluetooth communication
- Autonomous navigation
- Mobile app functionality

Errors are identified and corrected during testing.

Movement Calibration

Motor movement is calibrated for:

- Straight movement
- Accurate turning
- Speed balancing

Calibration improves robotic navigation accuracy.

Sensor Calibration

Ultrasonic sensor calibration ensures accurate distance measurement.

Calibration steps:

- Distance verification
- Sensor positioning
- Error correction
- Range testing

Bluetooth Range Testing

Bluetooth communication is tested for:

- Stable connectivity
- Wireless range
- Signal interruption

The HC-05 module provides reliable short-range communication.

Autonomous Navigation Testing

Autonomous mode is tested in environments containing obstacles.

The robotic vehicle is checked for:

- Obstacle detection
- Automatic stopping
- Direction changing
- Safe movement

Final System Testing

Complete system testing is performed after integrating all hardware and software modules.

The final testing verifies:

- Wireless control

- Robotic movement
- Sensor operation
- Route navigation
- Autonomous functionality
- Overall system performance

The testing and calibration process ensures that the Smart Multi-Control Robotic Car operates efficiently, safely, and accurately in both manual and autonomous modes.

CHAPTER 6

SYSTEM TESTING

6.1 Test Approach

System testing is an important phase in the development of the Smart Multi-Control Robotic Car project. The purpose of testing is to verify whether all hardware and software components function correctly according to the project requirements. Testing helps identify errors, communication problems, hardware failures, and programming issues before final implementation.

The testing approach used in this project includes both hardware testing and software testing. Each component of the robotic system is tested individually and then integrated into the complete system for overall performance evaluation.

The testing process mainly focuses on:

- Bluetooth communication
- Motor movement
- Obstacle detection
- Autonomous navigation
- Mobile application functionality
- Sensor accuracy
- Wireless connectivity
- Route navigation

The project follows a step-by-step testing methodology where every module is verified independently before complete integration. This approach reduces system errors and improves reliability.

Initially, the Arduino Uno board was tested by uploading sample programs to verify serial communication and pin functionality. After successful testing of Arduino Uno, the HC-05 Bluetooth module was connected and tested for wireless communication with the smartphone application.

The L293D motor driver and BO motors were tested separately to verify forward, backward, left, and right movement operations. After motor testing, the ultrasonic sensor and servo motor were integrated for obstacle detection and environmental scanning.

The MIT App developed using MIT App Inventor was tested for button functionality, Bluetooth connectivity, and command transmission.

Finally, complete system testing was performed after integrating all hardware and software modules together. The robotic vehicle was tested under different operating conditions to evaluate overall performance and reliability.

The testing approach also included repeated trials and calibration procedures to improve movement accuracy and sensor performance. This ensured smooth operation of the robotic car in both manual and autonomous modes.

6.2 Features Tested

Several important features of the Smart Multi-Control Robotic Car project were tested during system implementation.

6.2.1 Bluetooth Communication Testing

Bluetooth communication was tested to verify wireless connectivity between the mobile application and HC-05 Bluetooth module.

The following parameters were tested:

- Device pairing
- Bluetooth connection stability
- Command transmission
- Communication range
- Response time

The Bluetooth module successfully established communication with the smartphone and transmitted movement commands to Arduino Uno.

6.2.2 Motor Movement Testing

Motor movement testing was performed to verify proper directional control of the robotic vehicle.

The following movement operations were tested:

- Forward movement
- Backward movement
- Left turning
- Right turning
- Stop operation

The L293D motor driver successfully controlled the BO motors according to commands received from Arduino Uno.

6.2.3 MIT App Testing

The mobile application was tested for proper functionality and user interaction.

The following features were tested:

- Bluetooth connection button
- Movement control buttons
- Route navigation buttons

- Autonomous mode button
- User interface response

The application successfully transmitted commands wirelessly to the robotic system.

6.2.4 Ultrasonic Sensor Testing

The ultrasonic sensor was tested for obstacle detection and distance measurement accuracy.

The sensor testing included:

- Distance measurement
- Obstacle identification
- Detection range verification
- Sensor response time

The HC-SR04 ultrasonic sensor accurately detected nearby objects and measured distances effectively.

6.2.5 Servo Motor Testing

The servo motor was tested for proper rotation and environmental scanning.

The servo motor successfully:

- Rotated left and right
- Positioned ultrasonic sensor
- Supported intelligent scanning

This improved autonomous navigation capability.

6.2.6 Autonomous Navigation Testing

The autonomous navigation system was tested in obstacle environments.

The robotic vehicle successfully:

- Detected obstacles
- Stopped automatically
- Changed direction intelligently
- Avoided collisions

The autonomous mode improved robotic intelligence and operational safety.

6.2.7 Route Navigation Testing

Predefined route navigation features were tested for automatic movement execution.

The following routes were verified:

- Home route
- Hospital route
- Office route
- School route

The robotic vehicle successfully executed programmed movement sequences.

6.2.8 Power Supply Testing

Battery performance and power supply stability were also tested.

The testing verified:

- Continuous operation
- Voltage stability
- Motor power supply
- Component functionality

The power supply system successfully supported all hardware modules.

6.3 Testing Procedure

The testing procedure followed in the Smart Multi-Control Robotic Car project involved systematic verification of all modules and integrated system functions.

The testing procedure is explained below.

Step 1: Arduino Testing

The Arduino Uno board was connected to the computer using USB cable and tested using basic LED blinking programs.

The testing verified:

- Program uploading
- Serial communication
- Digital pin functionality

Step 2: Bluetooth Module Testing

The HC-05 Bluetooth module was connected to Arduino Uno and paired with the smartphone.

The following steps were performed:

1. Enable smartphone Bluetooth
2. Search for HC-05 device
3. Pair the device
4. Connect through MIT App
5. Send test commands

Successful communication confirmed proper Bluetooth operation.

Step 3: Motor Driver and Motor Testing

The L293D motor driver was connected to BO motors and tested using Arduino programs.

Movement commands were executed to verify:

- Forward motion
- Reverse motion
- Left turning
- Right turning
- Stop operation

The motors responded correctly according to programmed commands.

Step 4: Ultrasonic Sensor Testing

The ultrasonic sensor was tested by placing obstacles at different distances.

The testing procedure included:

- Trigger pulse generation
- Echo pulse measurement
- Distance calculation
- Obstacle detection verification

Sensor readings were observed using Arduino Serial Monitor.

Step 5: Servo Motor Testing

The servo motor was tested by rotating the ultrasonic sensor at different angles.

The testing verified:

- Servo rotation
- Angle accuracy
- Environmental scanning

Step 6: MIT App Testing

The MIT App was tested for wireless robotic control.

The following operations were verified:

- Button functionality
- Bluetooth connection
- Command transmission
- User interface performance

The application successfully controlled the robotic vehicle.

Step 7: Autonomous Navigation Testing

The robotic car was placed in environments containing obstacles.

The autonomous mode was activated to verify:

- Obstacle detection
- Automatic stopping
- Intelligent turning
- Safe navigation

The robot successfully avoided collisions.

Step 8: Final Integrated System Testing

All modules were integrated together and tested as a complete robotic system.

The final testing verified:

- Overall system functionality
- Wireless communication
- Intelligent navigation
- Robotic movement
- System reliability

The Smart Multi-Control Robotic Car successfully performed all required operations.

6.4 Result Analysis

The result analysis of the Smart Multi-Control Robotic Car project indicates that the robotic system operated successfully according to the project objectives and requirements.

The Bluetooth communication system successfully established wireless communication between the mobile application and robotic vehicle. The HC-05 Bluetooth module provided stable communication and accurate command transmission within operational range.

The MIT App developed using MIT App Inventor provided a simple and user-friendly interface for robotic control. All movement buttons and navigation features worked properly without communication delay.

The motor driver and BO motors successfully controlled robotic movement in all directions. The robotic vehicle responded correctly to forward, backward, left, right, and stop commands.

The ultrasonic sensor accurately detected nearby obstacles and measured distances effectively. The obstacle detection system improved safety by preventing collisions during movement.

The servo motor successfully rotated the ultrasonic sensor for intelligent environmental scanning. This improved the obstacle avoidance capability of the robotic system.

The autonomous navigation system worked efficiently by automatically detecting obstacles and selecting safer movement directions. The robotic vehicle successfully avoided collisions during autonomous operation.

The predefined route navigation system also worked successfully. The robotic car executed programmed movement paths such as Home, Hospital, Office, and School routes accurately.

The testing process confirmed that the robotic system was reliable, efficient, economical, and suitable for educational automation applications.

The project successfully demonstrated:

- Embedded system implementation
- Wireless communication
- Sensor integration
- Robotic automation
- Intelligent navigation
- Mobile application control

The Smart Multi-Control Robotic Car project achieved its objectives successfully and demonstrated practical implementation of modern robotic automation technologies using low-cost electronic components and embedded programming techniques.

CHAPTER 7

RESULT INTERPRETATION AND DISCUSSION

7.1 Project Results

The Smart Multi-Control Robotic Car project was successfully designed, developed, and tested using Arduino Uno, HC-05 Bluetooth module, ultrasonic sensor, servo motor, L293D motor driver, and BO motors. The project achieved all major objectives related to wireless robotic control, obstacle detection, autonomous navigation, and mobile application integration.

The robotic vehicle successfully responded to commands received from the mobile application developed using MIT App Inventor. The Bluetooth communication system established stable wireless connectivity between the smartphone and robotic vehicle.

The robotic car successfully performed:

- Forward movement
- Backward movement
- Left turning
- Right turning
- Stop operation

The ultrasonic sensor accurately detected nearby obstacles and prevented collisions during robotic movement. The servo motor successfully rotated the ultrasonic sensor for environmental scanning and intelligent navigation.

The autonomous navigation mode worked effectively by automatically detecting obstacles and selecting safer movement directions. The predefined route navigation system also executed programmed movement paths successfully.

The project demonstrated proper integration of embedded systems, wireless communication, automation technologies, and intelligent robotic control. Overall system performance was stable, reliable, and suitable for educational and practical automation applications.

7.2 Advantages

The Smart Multi-Control Robotic Car project provides several advantages in the field of robotics and automation.

- 1. Wireless Control :-** The robotic car can be controlled wirelessly using Bluetooth communication, eliminating the need for wired operation.
- 2. User-Friendly Operation :-** The mobile application provides simple and convenient robotic control using smartphones.
- 3. Obstacle Detection :-** The ultrasonic sensor detects nearby obstacles and improves operational safety.
- 4. Autonomous Navigation :-** The robotic system can navigate automatically without continuous user control.
- 5. Low Cost :-** The project uses affordable electronic components, making it economical for students and educational institutions.
- 6. Easy Implementation :-** The system is simple to design, program, and maintain.

7. Educational Value

The project helps students understand:

- Robotics
- Embedded systems
- Bluetooth communication
- Sensor integration
- Mobile app development

8. Future Expandability

The robotic platform can be upgraded using:

- Wi-Fi
- GPS
- IoT
- Camera systems
- Artificial intelligence

9. Portable System :- The robotic car is compact, lightweight, and easy to transport.

10. Practical Automation :- The project demonstrates real-time automation and intelligent robotic operation.

7.3 Limitations

Although the Smart Multi-Control Robotic Car project works successfully, it has certain limitations.

- 1. Limited Bluetooth Range :-** The HC-05 Bluetooth module supports only short-range communication.
- 2. Battery Dependency :-** The robotic vehicle depends completely on battery power for operation.
- 3. Limited Processing Capability :-** Arduino Uno has limited memory and processing speed for advanced AI applications.
- 4. Basic Obstacle Detection :-** The ultrasonic sensor may face difficulty detecting very small or soft objects accurately.
- 5. No Camera Integration :-** The current system does not support live video monitoring or image processing.
- 6. Indoor Usage Limitation :-** Bluetooth communication works better mainly for indoor or short-distance environments.
- 7. Limited Autonomous Intelligence :-** The robotic system uses simple obstacle avoidance algorithms and does not support advanced machine learning.
- 8. Surface Dependency :-** Robotic movement performance may vary depending on floor surface conditions.

7.4 Future Scope

The future scope of the Smart Multi-Control Robotic Car project is very broad because robotics and automation technologies are continuously advancing.

The robotic system can be upgraded using modern technologies such as:

- Wi-Fi communication
- Internet of Things (IoT)
- GPS navigation
- Camera systems
- Voice control
- Artificial intelligence
- Machine learning
- Cloud monitoring

The project can be converted into a fully autonomous smart robotic vehicle capable of intelligent decision-making and advanced path planning.

Future improvements may include:

- Live video streaming
- Gesture control
- Real-time tracking
- Mobile internet control
- AI-based object detection
- Smart traffic navigation

The robotic platform can also be used in:

- Industrial automation
- Smart warehouses
- Surveillance systems
- Rescue operations
- Medical assistance robots
- Smart delivery systems

The project provides a strong foundation for future research and innovation in intelligent robotic automation systems.

CONCLUSION

The Smart Multi-Control Robotic Car project was successfully designed and implemented using Arduino Uno, HC-05 Bluetooth module, ultrasonic sensor, servo motor, motor driver, and mobile application control. The project demonstrated wireless robotic movement, obstacle detection, autonomous navigation, and predefined route control effectively.

The robotic system successfully responded to commands from the mobile application developed using MIT App Inventor and performed forward, backward, left, right, and stop movements accurately. The ultrasonic sensor and servo motor improved robotic intelligence by detecting obstacles and supporting automatic navigation.

The project provided practical knowledge in embedded systems, robotics, wireless communication, automation technologies, and mobile application development. It also improved problem-solving skills, teamwork, and hardware-software integration understanding.

The Smart Multi-Control Robotic Car project proved to be economical, user-friendly, and suitable for educational and automation applications. The project also provides a strong foundation for future upgrades using IoT, Wi-Fi, GPS, artificial intelligence, and advanced autonomous technologies.

Overall, the project successfully achieved all objectives and demonstrated the practical implementation of intelligent robotic automation systems.

REFERENCES

Books

1. Massimo Banzi, *Getting Started with Arduino*, Maker Media Publications.
2. Simon Monk, *Programming Arduino: Getting Started with Sketches*, McGraw Hill Education.
3. John-David Warren, Josh Adams, Harald Molle, *Arduino Robotics*, Apress Publications.
4. Muhammad Ali Mazidi, Sarmad Naimi, Sepehr Naimi, *AVR Microcontroller and Embedded Systems Using Arduino*, Pearson Publications.
5. Rajesh Singh, *Robotics for Engineers*, Firewall Media Publications.

Websites

1. Arduino Official Website <https://www.arduino.cc>
2. MIT App Inventor Official Website <https://appinventor.mit.edu>
3. HC-05 Bluetooth Module Tutorial <https://lastminuteengineers.com/hc05-bluetooth-arduino-tutorial/>
4. Ultrasonic Sensor HC-SR04 Guide <https://randomnerdtutorials.com/complete-guide-for-ultrasonic-sensor-hc-sr04/>
5. Arduino Project Hub <https://projecthub.arduino.cc>

YouTube References

1. Arduino Bluetooth Controlled Car Tutorial <https://www.youtube.com/watch?v=BBwEF6WBUQs>
2. MIT App Inventor Bluetooth Control Tutorial <https://www.youtube.com/watch?v=9x8D3r9m0l8>
3. Arduino Obstacle Avoiding Robot Tutorial https://www.youtube.com/watch?v=1n_KjpMfVT0
4. HC-05 Bluetooth Module with Arduino <https://www.youtube.com/watch?v=AVyljEwM6sQ>
5. Arduino Robotics Complete Project Guide <https://www.youtube.com/watch?v=5dWQk0DkWm8>