

Koombiyo Delivery API Documentation

Add New Orders

Add new order to koombiyo delivery system.

PHP

```
<?php

    $ch = curl_init();

    curl_setopt($ch, CURLOPT_URL,"https://application.koombiyodelivery.lk/api/Addorders/users");

curl_setopt($ch, CURLOPT_POST, 1);      curl_setopt($ch, CURLOPT_POSTFIELDS,

        "apikey='Your_Key'&orderWaybillid=12345688&orderNo=123&receiverName=kamal&receiverStreet=no123
bibile&receiverDistrict=1&receiverCity=1&receiverPhone=0729666892&description=test order&spclNote=remark&getCod=1000");
curl_setopt($ch, CURLOPT_HTTPHEADER, array('Content-Type: application/x-www-form-urlencoded'));

// receive server response ...

curl_setopt($ch, CURLOPT_RETURNTRANSFER, true);

$server_output = curl_exec ($ch); curl_close

($ch); echo $server_output;

?>
```

Variables

These are body parameters.

1. apikey='Your API Key'
2. orderWaybillid='Waybill ID' - (Barcode no provided by koombiyo)
3. orderNo='Your reference no for order if else waybill id '
4. receiverName = 'Customer Name'
5. receiverStreet= 'Customer Address'
6. receiverDistrict=1
7. receiverCity=1
8. receiverPhone='Customer Phone No'
9. description='What's Contain in package '
10. spclNote='Remarks'
11. getCod='Amount should collect from customer '

Add Pickup Requests PHP

<?php

```
        //Send Pickup Request      $ch = curl_init();    curl_setopt($ch,
CURLOPT_URL, "https://application.koombiyodelivery.lk/api/Pickups/users");  curl_setopt($ch,
CURLOPT_POST, 1);
curl_setopt($ch, CURLOPT_POSTFIELDS,
        "apikey='Your_Key'&vehicleType=Bike&pickup_remark=test&pickup_address=bibile&latitude
= 6.901608599999999& longitude=80.0087746&phone=0760961206&qty=10");
curl_setopt($ch, CURLOPT_HTTPHEADER, array('Content-Type: application/x-www-form-urlencoded'));
// receive server response ...
curl_setopt($ch, CURLOPT_RETURNTRANSFER, true);
$server_output    =    curl_exec($ch);
curl_close ($ch); echo $server_output;
?>
```

Variables

These are body parameters.

1. Apikey='Your API Key'
2. vehicleType='Bike/Three wheel/Lorry'
3. pickup_remark='Remarks'
4. pickup_address='Pickup location'
5. latitude= 'geo coordinate'
6. longitude='geo coordinate'
7. phone='your phone no'
8. qty='shipped quantity'

Track Orders

PHP

```
<?php

    $ch = curl_init();

    curl_setopt($ch, CURLOPT_URL, "https://application.koombiyodelivery.lk/api/Allorders/users");

curl_setopt($ch, CURLOPT_POST, 1);      curl_setopt($ch, CURLOPT_POSTFIELDS,

                                "apikey='Your_Key'&waybillid=12345688&offset=1&limit=10");

    curl_setopt($ch, CURLOPT_HTTPHEADER, array('Content-Type: application/x-www-form-urlencoded'));

// receive server response ...

curl_setopt($ch, CURLOPT_RETURNTRANSFER, true);

$server_output = curl_exec ($ch); curl_close

($ch); echo $server_output;

?>
```

Variables

These are body parameters.

1. Apikey='Your API KEY'
2. Waybillid='Barcode No'(If empty all orders as result)
3. Offset
4. 4. Limit

Return Receive

Receive return orders

PHP

```
<?php
$ch = curl_init();
curl_setopt($ch,
CURLOPT_URL, "https://application.koombiyodelivery.lk/api/Returnreceive/users");
curl_setopt($ch,
CURLOPT_POST, 1); curl_setopt($ch, CURLOPT_POSTFIELDS, "apikey='Your_Key'&orderWaybillid=12345688");
curl_setopt($ch, CURLOPT_HTTPHEADER, array('Content-Type: application/x-www-form-urlencoded'));
// receive server response ...
curl_setopt($ch, CURLOPT_RETURNTRANSFER, true);
$server_output = curl_exec ($ch);
curl_close ($ch); echo $server_output;
?>
```

Variables

These are body parameters.

1. Apikey='Your API key'
2. orderWaybillid='Barcode No'

Order History

Get order history of single order.

PHP

```
<?php
```

```
$ch = curl_init();      curl_setopt($ch, CURLOPT_URL,"https://application.koombiyodelivery.lk/api/Orderhistory/users");  curl_setopt($ch, CURLOPT_POST, 1);  curl_setopt($ch, CURLOPT_POSTFIELDS,"apikey='Your_Key'&waybillid=12345688");  curl_setopt($ch, CURLOPT_HTTPHEADER, array('Content-Type: application/x-www-form-urlencoded'));
```

```
// receive server response ...
```

```
curl_setopt($ch, CURLOPT_RETURNTRANSFER, true);
```

```
$server_output = curl_exec ($ch);
```

```
curl_close ($ch); echo $server_output;
```

```
?>
```

Variables

These are body parameters.

1. Apikey='Your API key'
2. waybillid='Barcode No'

Return Notes

Get all return note ID(s)

PHP

```
<?php
$ch = curl_init();      curl_setopt($ch, CURLOPT_URL,"https://application.koombiyodelivery.lk/api/
Returnnotes/users");   curl_setopt($ch, CURLOPT_POST, 1);   curl_setopt($ch, CURLOPT_POSTFIELDS,
"apikey=Your_Key"); curl_setopt($ch, CURLOPT_HTTPHEADER, array('Content-Type: application/x-www-form-
urlencoded'));

// receive server response ...

curl_setopt($ch, CURLOPT_RETURNTRANSFER, true);

$server_output  = curl_exec ($ch);

curl_close ($ch); echo $server_output;

?>
```

Variables

These are body parameters.

1. apikey='Your API key'

Return Items

Get return items

PHP

```
<?php
```

```
$ch = curl_init();      curl_setopt($ch, CURLOPT_URL,"https://application.koombiyodelivery.lk/api/Returnitems/users");  curl_setopt($ch, CURLOPT_POST, 1);  curl_setopt($ch, CURLOPT_POSTFIELDS,"apikey='Your_Key'&noteid=1"); curl_setopt($ch, CURLOPT_HTTPHEADER, array('Content-Type: application/x-www-form-urlencoded'));
```

```
// receive server response ...
```

```
curl_setopt($ch, CURLOPT_RETURNTRANSFER, true);
```

```
$server_output = curl_exec ($ch);
```

```
curl_close ($ch); echo $server_output;
```

```
?>
```

Variables

These are body parameters.

1. Apikey='Your API key'
2. noteid ='Return note ID'