



Assertions in C/C++

Assertions are statements used to test assumptions made by programmer. For example, we may use assertion to check if pointer returned by malloc() is NULL or not.

Following is syntax for assertion.

```
void assert( int expression );
```

If expression evaluates to 0 (false), then the expression, sourcecode filename, and line number are sent to the standard error, and then abort() function is called.

For example, consider the following program.

```
#include <stdio.h>
#include <assert.h>

int main()
{
    int x = 7;

    /* Some big code in between and let's say x
       is accidentally changed to 9 */
    x = 9;

    // Programmer assumes x to be 7 in rest of the code
    assert(x==7);
}
```

```
/* Rest of the code */  
  
return 0;  
}
```

Output

Assertion failed: x==7, file test.cpp, line 13
This application has requested the Runtime to terminate it in an unusual way. Please contact the application's support team for more information.

Assertion Vs Normal Error Handling

Assertions are mainly used to check logically impossible situations. For example, they can be used to check the state a code expects before it starts running or state after it finishes running. Unlike normal error handling, assertions are generally disabled at run-time. Therefore, it is not a good idea to write statements in `asser()` that can cause side effects. For example writing something like `assert(x = 5)` is not a good idea as `x` is changed and this change won't happen when assertions are disabled. See [this](#) for more details.

Ignoring Assertions

In C/C++, we can completely remove assertions at compile time using the preprocessor `NDEBUG`.

```
// The below program runs fine because NDEBUG is defined  
# define NDEBUG  
# include <assert.h>  
  
int main()  
{  
    int x = 7;  
    assert (x==5);  
    return 0;  
}
```

The above program compiles and runs fine.

In Java, assertions are not enabled by default and we must pass an option to run-time engine to enable them.

Reference:

http://en.wikipedia.org/wiki/Assertion_%28software_development%29

Please write comments if you find anything incorrect, or you want to share more information about the topic discussed above.

Recommended Posts:

[Implementing upper_bound\(\) and lower_bound\(\) for Ordered Set in C++](#)

[How to flatten a Vector of Vectors or 2D Vector in C++](#)

[<complex.h> header file in C with Examples](#)

[Remove odd frequency characters from the string](#)

[Different ways to use Const with Reference to a Pointer in C++](#)

[std::to_address in C++ with Examples](#)

[Program to create Custom Vector Class in C++](#)

[std::is_trivially_copy_constructible in C/C++](#)

[Difference between Python and C++](#)

[tgamma\(\) method in C/C++ with Examples](#)

[boost::type_traits::is_array Template in C++](#)

[boost is_pointer template in C++](#)

[Modulo Operator \(%\) in C/C++ with Examples](#)

[fpclassify\(\) method in C/C++ with Examples](#)

Improved By : Jaideep Kaiwart

Article Tags : [C](#) [C++](#)

Practice Tags : [C](#) [CPP](#)



8

2

☐ To-do ☐ Done

Based on 11 vote(s)

[Feedback/ Suggest Improvement](#)[Add Notes](#)[Improve Article](#)

Please write to us at contribute@geeksforgeeks.org to report any issue with the above content.

Writing code in comment? Please use ide.geeksforgeeks.org, generate link and share the link here.

[Load Comments](#)

A computer science portal for geeks

5th Floor, A-118,
Sector-136, Noida, Uttar Pradesh - 201305
feedback@geeksforgeeks.org

COMPANY

[About Us](#)
[Careers](#)
[Privacy Policy](#)
[Contact Us](#)

PRACTICE

[Courses](#)
[Company-wise](#)
[Topic-wise](#)
[How to begin?](#)

LEARN

[Algorithms](#)
[Data Structures](#)
[Languages](#)
[CS Subjects](#)
[Video Tutorials](#)

CONTRIBUTE

[Write an Article](#)
[Write Interview Experience](#)
[Internships](#)
[Videos](#)

@geeksforgeeks, Some rights reserved