

thispointer.com

[Python](#)[Pandas](#)[C++11 Tutorials](#)[C++ Tutorials](#)[Courses](#)[STL](#)[Multithreading](#)[Boost Library](#) ▾[GDB](#)[Design Patterns](#)[java](#)[Datastructure](#) ▾[Subscribe](#)[Home](#) » [std::map](#) » [unordered_map](#) » You are reading »

map vs unordered_map | When to choose one over another ?

👤 Varun ⌚ March 26, 2017 📄 std::map, unordered_map 💬 1 Comment

In this article we will compare std::map and std::unordered_map and will also discuss when to choose one over another.

Both std::map & std::unordered_map store elements in key value pair & provide member functions to efficiently insert, search & delete key value pairs.

But they are different in following areas,

- Internal Implementation
- Memory Usage
- Time Complexity
- Using user defined objects as keys

Internal Implementation :

std::map Internally store elements in a balanced BST. Therefore, elements will be stored in sorted order of keys.

std::unordered_map store elements using hash table. Therefore, elements will not be stored in any sorted order. They will be stored in arbitrary order . To know more about

C++11 – Unordered_Map

[Basic Usage Detail and Example](#)[Initializing an unordered_map](#)[Searching in unordered_map](#)[Insert elements in unordered_map](#)[Erasing an element](#)[Erase elements while iterating](#)[std::map vs std::unordered_map](#)[Lambda Functions in Python](#)[Vector](#)[List](#)[Deque](#)[Set](#)[Map](#)[MultiMap](#)[STL Algorithms](#)

hashing check following article, [What is Hashing and Hash Table?](#)

Check following example,

```

2 #include <map>
3 #include <unordered_map>
4 #include <string>
5 #include <iterator>
6 #include <algorithm>
7
8 int main()
9 {
10
11     // Map of string & int i.e. words as key & there
12     // occurrence count as values
13     std::map<std::string, int> wordMap = {
14         { "is", 6 },
15         { "the", 5 },
16         { "hat", 9 },
17         { "at", 6 }
18     };
19
20     std::cout<<"std::map Contents : Elements are in sorted order of Keys"<<std::endl;
21
22     // Print map contents
23     std::for_each(wordMap.begin(), wordMap.end(), [](std::pair<std::string, int> elem) {
24         std::cout<<elem.first<< " :: "<< elem.second<<std::endl;
25     });
26
27
28     // Unordered_map of string & int i.e. words as key & there
29     // occurrence count as values
30     std::unordered_map<std::string, int> wordUOMap = {
31         { "is", 6 },
32         { "the", 5 },
33         { "hat", 9 },
34         { "at", 6 }
35     };
36
37     std::cout<<"std::unordered_map Contents : Elements are in Random order of Key";
38
39     // Print Unordered_map
40     std::for_each(wordUOMap.begin(), wordUOMap.end(), [](std::pair<std::string, int> elem) {
41         std::cout<<elem.first<< " :: "<< elem.second<<std::endl;
42     });
43
44     return 0;
45 }

```

Output:

```

1 std::map Contents : Elements are in sorted order of Keys
2 at :: 6
3 hat :: 9
4 is :: 6
5 the :: 5
6 std::unordered_map Contents : Elements are in Random order of Keys
7 hat :: 9
8 the :: 5
9 at :: 6
10 is :: 6

```

Memory Usage :

Memory usage is more in unordered_map as compared to map because unordered_map need space for storing hash table too.

Time Complexity for Searching element :

Time complexity for searching elements in **std::map** is $O(\log n)$. Even in worst case it will be $O(\log n)$ because elements are stored internally as Balanced Binary Search tree (BST).

- 1.) What's std::vector and why to use it?
- 2.) Different ways to initialize a vector
- 3.) How does std::vector works internally
- 4.) User Defined Objects & std::vector
- 5.) How to use vector efficiently in C++?
- 6.) std::vector and Iterator Invalidation
- 7.) Remove repeated elements from a vector
- 8.) Fill a vector with random numbers
- 9.) Hidden cost of std::vector
- 10.) Adding elements in Vector

Popular Categories

Behavioral Design Patterns (6) Boost Date
Time Library (6) Boost Library (17)
C++ (107) C++ 11 (59)
c++11 Threads (16) C++
Interview Questions (30)
collections (17) Dataframe (10)
Data Science (10) Debugging (6) Debugging
Tutorial (6) Design Patterns (9)
dictionary (17) Directories (13)
FileHandling (27) Functions (10)
gdb (6) gdb commands (6) gdb Tutorial (6)
HashSet (8) **java (29)** linkedlist (5) Linux
(8) Linux System Programming (8) List
(27) Method Overriding (5)
Multithreading (12) Numpy (24)
Pandas (44) Python (182)
Smart Pointers (6) std::list (12)
std::map (16) std::set (10) std::string
(12) std::thread (5) std::vector (18)
STL (56) STL Algorithm (8) STL
Interview Questions (16) strings
(14) Uncategorized (11)
unordered_map (8) unordered_set (6)

Search

Subscribe with us

Subscribe For latest Tutorials

* indicates required

Email Address *

Whereas, in **std::unordered_map** best case time complexity for searching is $O(1)$.

[Subscribe](#)

Where as, if hash code function is not good then, worst case complexity can be $O(n)$ (In case all keys are in same bucket).

Using user define objects as Keys :

For **std::map** to use user defined object as keys, we need to override either $<$ operator or pass external comparator i.e. a functor or function pointer that can be used by map for comparing keys.

Where as, For **std::unordered_map** we need to provide definition of function **std::hash<K>** for our key type K. Also we need to override $==$ operator.

Check following article for detailed explanation :

[Using User defined class objects as keys in std::map](#)

[Unordered container and Custom Hasher](#)

When to choose map instead of unordered_map

When you need Low Memory:

Unordered_map consumes extra memory for internal hashing, so if you are keeping millions and billions of data inside the map and want to consume less memory then choose **std::map** instead of **std::unordered_map**.

When you are interested in Ordering too

As **std::map** internally use balanced BST, so all the elements inside it will be in sorted order based on the key. So, if you want all keys to be ordered then go for **std::map**.

When you need guaranteed Performance

For searching an element, **std::unordered_map** gives the complexity $O(1)$ in best case but $O(n)$ in worst case (if hash implementation is not perfect).

So, if your hash implementation is not good and you have millions and billions of data then go for **std::map** because it will give you guaranteed $O(\log N)$.

When to choose unordered_map instead of map

When you have good hasher and no memory limitation

Unordered_map consumes extra memory for internal hashing. But to due to this searching complexity is $O(1)$, if hasher function is good.

Python Recommendations:

- [5 Free Python Courses in 2020 | Best of the lot](#)

- [Reviews of Best Python Courses in 2020](#)

C++ & C++11 Recommendations:

- [Best C++ Courses for beginners to learn from scratch](#)
- [5 Top Courses to learn C++11 / C++14](#)
- [Best books to learn C++11](#)

If you didn't find what you were looking, then do suggest us in the comments below. We will be more than happy to add that.


[Subscribe with us to join 1500+ Python & C++ developers, to get more Tips & Tutorials like this.](#)

Related Posts:

- [Python : How to Sort a Dictionary by key or Value ?](#)
- [What is a dictionary in python and why do we need it?](#)
- [How to copy all Values from a Map to a Vector in C++](#)
- [Python : Filter a dictionary by conditions on keys or values](#)
- [C++ : How to find duplicates in a vector ?](#)
- [Python : 3 ways to check if there are duplicates in a List](#)
- [C++11 : std::array Tutorial and examples](#)
- [Python : Check if all elements in a List are same or matches a condition](#)
- [Python: Find duplicates in a list with frequency count & index positions](#)
- [Pandas : Check if a value exists in a DataFrame using in & not in operator | .isin\(\)](#)
- [C++ : How to check if a Set contains an element | set::find vs set::count?](#)
- [C++ : How to insert element in vector at specific position | vector::insert\(\) examples](#)
- [C++ : How to find an element in vector and get its index ?](#)
- [C++11 : How to get a Thread ID ?](#)
- [Python : How to Remove Duplicates from a List](#)
- [C++ : How to compare two vectors | std::equal\(\) & Comparators](#)
- [Python : How to convert a list to dictionary ?](#)
- [Python : Count elements in a list that satisfy certain conditions](#)
- [Python : How to Remove multiple keys from Dictionary while Iterating ?](#)
- [Python : How to iterate over the characters in string ?](#)
- [C++ : How to get element by index in vector | at\(\) vs operator \[\]](#)
- [C++ : How to reverse a List or sub-list in place?](#)
- [Java: How to get all keys by a value in HashMap ? | Search by Value in Map](#)
- [Python : Get number of elements in a list, lists of lists or nested list](#)

- [C++ : How to copy / clone a STL List or Sub List](#)

1 Comment Already



Leonard Inkret - August 7th, 2019 at 12:35 pm
Thank you, this article was very useful

Reply

Leave a Reply

Your email address will not be published. Required fields are marked * This site uses

Name *

Email *

Website

Post Comment

Akismet to reduce spam. [Learn how your comment data is processed.](#)

[« C++11 – Variadic Template Function | Tutorial & Examples](#) [Different ways to iterate over a set in C++ »](#)

Python tutorials

- Strings
- Lists
- Tuple
- Dictionary
- Functions
- File Handling
- Lambda Functions

C++ / C++11 Tutorials

- C++ Tutorials
- C++11 Tutorial
- C++ Interview Questions
- Multithreading
- C++17
- STL Tutorials

Data Analysis in Python

- Dataframe in Pandas
- Numpy Arrays

Terms of Use

Terms of use

Terms and Policies

- Disclaimer
- Cookie policy (EU)
- Cookie policy (UK)
- Privacy statement (EU)
- Privacy statement (UK)
- Privacy statement (US)
- Do Not Sell My Personal Information

