

SQL Operators

SQL Arithmetic Operators:

```
mysql> select 30+10;
```

```
+-----+
```

```
| 30+10 |
```

```
+-----+
```

```
| 40 |
```

```
+-----+
```

```
1 row in set (0.00 sec)
```

```
mysql> select 30.56*21.32;
```

```
+-----+
```

```
| 30.56*21.32 |
```

```
+-----+
```

```
| 651.5392 |
```

```
+-----+
```

```
1 row in set (0.00 sec)
```

```
mysql> select 20-56;
```

```
+-----+
```

```
| 20-56 |
```

```
+-----+
```

```
| -36 |
```

```
+-----+
```

```
1 row in set (0.00 sec)
```

```
mysql> select 31/3;
```

```
+-----+
```

```
| 31/3 |
```

```
+-----+
```

```
| 10.3333 |
```

```
+-----+
```

```
1 row in set (0.00 sec)
```

```
mysql> select 10%2;
```

```
+-----+
```

```
| 10%2 |
```

```
+-----+
```

```
| 0 |
```

```
+-----+
```

```
1 row in set (0.00 sec)
```

SQL Comparison Operators:

```
mysql> select * from customers;
```

```
+-----+-----+-----+-----+-----+
```

```
| id | name  | age | address  | salary |
```

```
+-----+-----+-----+-----+-----+
```

```
| 1 | BOB   | 23 | Kyoto    | 23999 |
```

```
| 2 | Maya  | 22 | Akahibara | 28000 |
```

```
| 3 | Stephen | 45 | Okinawa  | 32400 |
```

```
| 4 | Shnsui | 153 | New York | 120000 |
```

```
| 5 | Austin | 39 | Tempe    | 230000 |
```

```
| 6 | Byakuya | 345 | Hyderabad | 79400 |
```

```
| 7 | Hitsugaya | 113 | Wales    | 230000 |
```

```
| 8 | Unihana | 639 | Jacksonville | 730000 |
```

```
+-----+-----+-----+-----+-----+
```

```
8 rows in set (0.00 sec)
```

```
mysql> select * from customers where salary > 60000;
```

```
+-----+-----+-----+-----+-----+
```

```
| id | name  | age | address  | salary |
```

```
+-----+-----+-----+-----+-----+
```

```
| 4 | Shnsui | 153 | New York | 120000 |
```

```
| 5 | Austin | 39 | Tempe    | 230000 |
```

```
| 6 | Byakuya | 345 | Hyderabad | 79400 |
```

```
| 7 | Hitsugaya | 113 | Wales    | 230000 |
```

```
| 8 | Unihana | 639 | Jacksonville | 730000 |
```

```
+-----+-----+-----+-----+-----+
```

```
5 rows in set (0.00 sec)
```

```
mysql> select * from customers where salary=230000;
```

```
+-----+-----+-----+-----+
| id | name   | age | address | salary |
+-----+-----+-----+-----+
|  5 | Austin |  39 | Tempe   | 230000 |
|  7 | Hitsugaya | 113 | Wales   | 230000 |
+-----+-----+-----+-----+
2 rows in set (0.00 sec)
```

```
mysql> select * from customers where salary!=230000;
```

```
+-----+-----+-----+-----+
| id | name   | age | address   | salary |
+-----+-----+-----+-----+
|  1 | BOB    |  23 | Kyoto     | 23999 |
|  2 | Maya   |  22 | Akahibara | 28000 |
|  3 | Stephen | 45 | Okinawa    | 32400 |
|  4 | Shnsui | 153 | New York   | 120000 |
|  6 | Byakuya | 345 | Hyderabad | 79400 |
|  8 | Unihana | 639 | Jacksonville | 730000 |
+-----+-----+-----+-----+
6 rows in set (0.00 sec)
```

```
mysql> select * from customers where salary<>230000;
```

```
+-----+-----+-----+-----+
| id | name   | age | address   | salary |
+-----+-----+-----+-----+
|  1 | BOB    |  23 | Kyoto     | 23999 |
|  2 | Maya   |  22 | Akahibara | 28000 |
|  3 | Stephen | 45 | Okinawa    | 32400 |
|  4 | Shnsui | 153 | New York   | 120000 |
|  6 | Byakuya | 345 | Hyderabad | 79400 |
|  8 | Unihana | 639 | Jacksonville | 730000 |
+-----+-----+-----+-----+
```

6 rows in set (0.00 sec)

```
mysql> select * from customers where salary>=32000;
```

id	name	age	address	salary
3	Stephen	45	Okinawa	32400
4	Shnsui	153	New York	120000
5	Austin	39	Tempe	230000
6	Byakuya	345	Hyderabad	79400
7	Hitsugaya	113	Wales	230000
8	Unihana	639	JacksonVille	730000

6 rows in set (0.00 sec)

SQL Logical Operators:

```
mysql> select * from customers where exists(select age from customers where salary>=120000);
```

id	name	age	address	salary
1	BOB	23	Kyoto	23999
2	Maya	22	Akahibara	28000
3	Stephen	45	Okinawa	32400
4	Shnsui	153	New York	120000
5	Austin	39	Tempe	230000
6	Byakuya	345	Hyderabad	79400
7	Hitsugaya	113	Wales	230000
8	Unihana	639	JacksonVille	730000

8 rows in set (0.00 sec)

```
mysql> select age from customers where salary>=120000;
```

age

| 153 |

| 39 |

| 113 |

| 639 |

+-----+

4 rows in set (0.00 sec)

mysql> select * from customers where age>all(select age from customers where salary>120000);

+-----+-----+-----+-----+-----+

| id | name | age | address | salary |

+-----+-----+-----+-----+-----+

| 1 | BOB | 639 | Kyoto | 23999 |

+-----+-----+-----+-----+-----+

1 row in set (0.00 sec)

mysql> select * from customers where age>any(select age from customers where salary>120000);

+-----+-----+-----+-----+-----+

| id | name | age | address | salary |

+-----+-----+-----+-----+-----+

| 1 | BOB | 639 | Kyoto | 23999 |

| 3 | Stephen | 45 | Okinawa | 32400 |

| 4 | Shnsui | 153 | New York | 120000 |

| 6 | Byakuya | 345 | Hyderabad | 79400 |

| 7 | Hitsugaya | 113 | Wales | 230000 |

| 8 | Unihana | 574 | Jacksonville | 730000 |

+-----+-----+-----+-----+-----+

6 rows in set (0.00 sec)

SQL EXPRESSIONS:

mysql> SELECT * FROM CUSTOMERS WHERE SALARY =120000;

+-----+-----+-----+-----+-----+

| id | name | age | address | salary |

+-----+-----+-----+-----+-----+

| 4 | Shnsui | 153 | New York | 120000 |

+-----+-----+-----+-----+-----+

1 row in set (0.00 sec)

```
mysql> SELECT 8+6 AS ADDITION;
```

```
+-----+
| ADDITION |
+-----+
|      14 |
+-----+
```

1 row in set (0.00 sec)

```
mysql> SELECT COUNT(*) AS 'RECORDS COUNT' FORM CUSTOMERS;
```

ERROR 1064 (42000): You have an error in your SQL syntax; check the manual that corresponds to your MySQL server version for the right syntax to use near 'FORM CUSTOMERS' at line 1

```
mysql> SELECT COUNT(*) AS 'RECORDS COUNT' FROM CUSTOMERS;
```

```
+-----+
| RECORDS COUNT |
+-----+
|           8 |
+-----+
```

1 row in set (0.00 sec)

```
mysql> SELECT CURRENT_TIMESTAMP;
```

```
+-----+
| CURRENT_TIMESTAMP |
+-----+
| 2025-06-24 14:45:34 |
+-----+
```

1 row in set (0.00 sec)

```
mysql> SELECT GETDATE();
```

ERROR 1305 (42000): FUNCTION customers.GETDATE does not exist

```
mysql> SELECT GETDATE();;
```

ERROR 1305 (42000): FUNCTION customers.GETDATE does not exist

ERROR:

No query specified