

Assistant.tsx:-

```
import { createFileRoute } from "@tanstack/react-router";

import { Bot, Send } from "lucide-react";

import { useState } from "react";

import { PageHeader, PhoneFrame, Screen } from "@components/app-shell";
import { Button } from "@components/ui/button";
import { Input } from "@components/ui/input";
import { assistantAnswer, assistantQuickQuestions } from "@lib/medsimplify-data";
import { cn } from "@lib/utils";

interface Msg {
  from: "user" | "ai";
  text: string;
}

export const Route = createFileRoute("/assistant")({
  head: () => ({
    meta: [
      { title: "AI health assistant — MedSimplify" },
      {
        name: "description",
        content: "Ask everyday health questions in plain language and get simple, sourced guidance.",
      },
      { property: "og:title", content: "AI health assistant — MedSimplify" },
      { property: "og:description", content: "Plain-language answers to everyday health questions." },
    ],
  })
})
```

```

    }},
    component: AssistantScreen,
  });

function AssistantScreen() {
  const [messages, setMessages] = useState<Msg[]>([
    { from: "ai", text: "Hello Rajesh 🙌 Ask me anything about your health, reports or medicines." },
  ]);
  const [draft, setDraft] = useState("");
  const [thinking, setThinking] = useState(false);

  const ask = (text: string) => {
    const value = text.trim();
    if (!value || thinking) return;
    setMessages((m) => [...m, { from: "user", text: value }]);
    setDraft("");
    setThinking(true);
    setTimeout(() => {
      setMessages((m) => [...m, { from: "ai", text: assistantAnswer }]);
      setThinking(false);
    }, 1200);
  };

  return (
    <PhoneFrame>
      <PageHeader title="🤖 Health Assistant" subtitle="General information, not a diagnosis"
        back="/home" />
    </PhoneFrame>
  );
}

```

```

<Screen className="flex flex-col gap-3">
  {messages.map((m, i) => (
    <div key={i} className={cn("flex", m.from === "user" ? "justify-end" : "justify-start")}>
      {m.from === "ai" ? (
        <div className="flex max-w-[90%] gap-2">
          <div className="mt-1 flex size-8 shrink-0 items-center justify-center rounded-full
bg-primary/10 text-primary">
            <Bot className="size-4" />
          </div>
          <p className="whitespace-pre-line text-[16px] text-foreground">{m.text}</p>
        </div>
      ) : (
        <p className="max-w-[80%] rounded-xl bg-primary px-3 py-2 text-[16px] text-
primary-foreground">
          {m.text}
        </p>
      )}
    </div>
  ))}
  {thinking ? <p className="text-[14px] text-muted-foreground">Thinking...</p> : null}

  <p className="mt-4 rounded-xl bg-muted px-3 py-2 text-[12px] text-muted-
foreground">
    ⚠ This assistant gives general health information only. Always follow your doctor's
advice.
  </p>
</Screen>

```

```

<div className="sticky bottom-0 border-t border-border bg-card px-4 py-3">
  <div className="mb-2 flex gap-2 overflow-x-auto">
    {assistantQuickQuestions.map((q) => (
      <button
        key={q}
        onClick={() => ask(q)}
        className="tap-target whitespace-nowrap rounded-full border border-border px-3
text-[14px]"
      >
        {q}
      </button>
    ))}
  </div>
  <form
    className="flex items-center gap-2"
    onSubmit={(e) => {
      e.preventDefault();
      ask(draft);
    }}
  >
    <Input
      value={draft}
      onChange={(e) => setDraft(e.target.value)}
      placeholder="Ask a health question"
      aria-label="Ask a health question"
      className="h-12 text-[16px]"
    />
    <Button type="submit" aria-label="Send question" className="size-12 shrink-0 p-0">

```

```

        <Send className="size-5" />

      </Button>

    </form>

  </div>

</PhoneFrame>

);
}

```

chat.tsx:

```

import { createFileRoute } from "@tanstack/react-router";

import { AlertTriangle, Send } from "lucide-react";

import { useState } from "react";

import { PageHeader, PhoneFrame, Screen } from "@components/app-shell";
import { Button } from "@components/ui/button";
import { Input } from "@components/ui/input";
import { chatSuggestions, doctor, doctorChat } from "@lib/medsimplify-data";
import { cn } from "@lib/utils";

export const Route = createFileRoute("/chat")({
  head: () => ({
    meta: [
      { title: "Chat with your doctor — MedSimplify" },
      {
        name: "description",
        content: "Message your doctor about symptoms, medicines and test results between visits.",
      },
      { property: "og:title", content: "Chat with your doctor — MedSimplify" },
    ],
  })
});

```

```

    { property: "og:description", content: "Quick answers from your doctor between visits." },
  ],
}),
component: ChatScreen,
});

```

```

function ChatScreen() {
  const [messages, setMessages] = useState(doctorChat);
  const [draft, setDraft] = useState("");

  const send = (text: string) => {
    const value = text.trim();
    if (!value) return;
    setMessages((m) => [...m, { from: "patient" as const, text: value, time: "Now" }]);
    setDraft("");
    setTimeout(() => {
      setMessages((m) => [
        ...m,
        {
          from: "doctor" as const,
          text: "Thank you, I have noted this. I will reply in detail during clinic hours.",
          time: "Now",
        },
      ]);
    }, 900);
  };

  return (

```

```
<PhoneFrame>
```

```
  <PageHeader title={doctor.name} subtitle={` ${doctor.specialty} · usually replies in 2
hours`} back="/home" />
```

```
  <div className="flex items-start gap-2 bg-destructive/10 px-4 py-2 text-[14px] text-
destructive">
```

```
    <AlertTriangle className="mt-0.5 size-4 shrink-0" />
```

```
    <p>For an emergency, do not wait for a reply — call 108 immediately.</p>
```

```
  </div>
```

```
<Screen className="flex flex-col gap-3">
```

```
  {messages.map((m, i) => (
```

```
    <div key={i} className={cn("flex", m.from === "patient" ? "justify-end" : "justify-
start")}>
```

```
      <div
```

```
        className={cn(
```

```
          "max-w-[80%] rounded-xl px-3 py-2 text-[16px]",
```

```
          m.from === "patient"
```

```
            ? "bg-primary text-primary-foreground"
```

```
            : "border border-border bg-card text-foreground",
```

```
        )}
```

```
      >
```

```
        <p>{m.text}</p>
```

```
      <p
```

```
        className={cn(
```

```
          "mt-1 text-[12px]",
```

```
          m.from === "patient" ? "text-primary-foreground/80" : "text-muted-foreground",
```

```
        )}
```

```
      >
```

```

        {m.time}
      </p>
    </div>
  </div>
)}}
</Screen>

```

```

<div className="sticky bottom-0 border-t border-border bg-card px-4 py-3">
  <div className="mb-2 flex gap-2 overflow-x-auto">
    {chatSuggestions.map((s) => (
      <button
        key={s}
        onClick={() => send(s)}
        className="tap-target whitespace-nowrap rounded-full border border-border px-3
text-[14px] text-foreground"
      >
        {s}
      </button>
    ))}
  </div>
  <form
    className="flex items-center gap-2"
    onSubmit={(e) => {
      e.preventDefault();
      send(draft);
    }}
  >
    <Input

```

```

        value={draft}
        onChange={(e) => setDraft(e.target.value)}
        placeholder="Type your message"
        aria-label="Message"
        className="h-12 text-[16px]"
      />
      <Button type="submit" aria-label="Send message" className="size-12 shrink-0 p-0">
        <Send className="size-5" />
      </Button>
    </form>
  </div>
</PhoneFrame>
);
}
doctor.clinic.tsx:
import { createFileRoute } from "@tanstack/react-router";

import {
  Bar,
  BarChart,
  CartesianGrid,
  Line,
  LineChart,
  ResponsiveContainer,
  Tooltip,
  XAxis,
  YAxis,
} from "recharts";

import { PageHeader, PhoneFrame, Screen, SectionTitle } from "@components/app-shell";

```

```
import { Card, CardContent } from "@components/ui/card";

import { commonDiagnoses, revenueByMonth } from "@lib/medsimplify-data";

export const Route = createFileRoute("/doctor/clinic")({
  head: () => ({
    meta: [
      { title: "Clinic dashboard — MedSimplify" },
      {
        name: "description",
        content: "Clinic revenue trend, patient demographics, common diagnoses, staff and stock at a glance.",
      },
      { property: "og:title", content: "Clinic dashboard — MedSimplify" },
      { property: "og:description", content: "Revenue, diagnoses, staff and inventory for your clinic." },
    ],
  }),
  component: ClinicDashboard,
});

const staff = [
  { name: "Nurse Anita", role: "Nursing", status: "On duty" },
  { name: "Ravi (Front desk)", role: "Reception", status: "On duty" },
  { name: "Dr. Anil Mehta", role: "Visiting physician", status: "Off today" },
];

const stock = [
  { item: "Paracetamol 500mg", left: "420 strips", low: false },
  { item: "ORS sachets", left: "38 packs", low: true },
];
```

```
{ item: "Dengue NS1 kits", left: "12 kits", low: true },  
];
```

```
export default function noop() {}
```

```
function ClinicDashboard() {
```

```
  return (
```

```
    <PhoneFrame>
```

```
      <PageHeader title="Clinic Overview" back="/doctor/dashboard" />
```

```
      <Screen>
```

```
        <div className="grid grid-cols-3 gap-2">
```

```
          <Stat value="₹2.4L" label="This month" />
```

```
          <Stat value="312" label="Patients" />
```

```
          <Stat value="4.8★" label="Rating" />
```

```
        </div>
```

```
      <SectionTitle>Revenue trend</SectionTitle>
```

```
      <Card className="shadow-card">
```

```
        <CardContent className="h-56 py-4">
```

```
          <ResponsiveContainer width="100%" height="100%">
```

```
            <LineChart data={revenueByMonth}>
```

```
              <CartesianGrid strokeDasharray="3 3" stroke="hsl(var(--border))" />
```

```
              <XAxis dataKey="month" tick={{ fontSize: 12 }} />
```

```
              <YAxis tick={{ fontSize: 12 }} width={48} tickFormatter={(v) => `₹${v / 1000}k`} />
```

```
              <Tooltip formatter={(v: number) => `₹${v.toLocaleString("en-IN")}`} />
```

```
              <Line type="monotone" dataKey="revenue" stroke="#2563EB" strokeWidth={2} dot
```

```
/>
```

```
            </LineChart>
```

```
</ResponsiveContainer>
```

```
</CardContent>
```

```
</Card>
```

```
<SectionTitle>Most common diagnoses</SectionTitle>
```

```
<Card className="shadow-card">
```

```
<CardContent className="h-56 py-4">
```

```
<ResponsiveContainer width="100%" height="100%">
```

```
<BarChart data={commonDiagnoses}>
```

```
<CartesianGrid strokeDasharray="3 3" stroke="hsl(var(--border))" />
```

```
<XAxis dataKey="name" tick={{ fontSize: 10 }} interval={0} />
```

```
<YAxis tick={{ fontSize: 12 }} width={30} />
```

```
<Tooltip />
```

```
<Bar dataKey="count" fill="#10B981" radius={[4, 4, 0, 0]} />
```

```
</BarChart>
```

```
</ResponsiveContainer>
```

```
</CardContent>
```

```
</Card>
```

```
<SectionTitle>Staff today</SectionTitle>
```

```
<Card className="shadow-card">
```

```
<CardContent className="divide-y divide-border p-0">
```

```
{staff.map((s) => (
```

```
<div key={s.name} className="flex items-center gap-3 px-4 py-3">
```

```
<div className="min-w-0 flex-1">
```

```
<p className="text-[16px] font-semibold">{s.name}</p>
```

```
<p className="caption-text">{s.role}</p>
```

```
</div>
```

```

        <span className="text-[14px] text-muted-foreground">{s.status}</span>
      </div>
    )}
  </CardContent>
</Card>

<SectionTitle>Stock</SectionTitle>
<Card className="shadow-card">
  <CardContent className="divide-y divide-border p-0">
    {stock.map((s) => (
      <div key={s.item} className="flex items-center gap-3 px-4 py-3">
        <p className="flex-1 text-[16px]">{s.item}</p>
        <span className={s.low ? "text-[14px] font-semibold text-destructive" : "text-[14px]}">
          {s.left}
          {s.low ? " · reorder" : ""}
        </span>
      </div>
    ))}
  </CardContent>
</Card>
</Screen>
</PhoneFrame>
);
}

function Stat({ value, label }: { value: string; label: string }) {
  return (

```

```

<Card className="shadow-card">
  <CardContent className="px-2 py-4 text-center">
    <p className="text-[20px] font-bold text-primary">{value}</p>
    <p className="caption-text">{label}</p>
  </CardContent>
</Card>

);
}
doctor.dashboard.tsx:
import { createFileRoute, Link } from "@tanstack/react-router";
import { BarChart3, FilePlus2, Users } from "lucide-react";

import { PageHeader, PhoneFrame, Screen, SectionTitle } from "@components/app-shell";
import { Card, CardContent } from "@components/ui/card";
import { doctor, doctorSchedule, doctorStats } from "@lib/medsimplify-data";

export const Route = createFileRoute("/doctor/dashboard")({
  head: () => ({
    meta: [
      { title: "Doctor dashboard — MedSimplify" },
      {
        name: "description",
        content: "Today's patients, pending reports, earnings and the day's appointment
schedule.",
      },
      { property: "og:title", content: "Doctor dashboard — MedSimplify" },
      { property: "og:description", content: "Your day at a glance: patients, reports and
schedule." },
    ],
  })
});

```

```

    }},
    component: DoctorDashboard,
  });

function DoctorDashboard() {
  return (
    <PhoneFrame>
      <PageHeader title={doctor.name} subtitle={doctor.specialty} back="/doctor" />
      <Screen>
        <div className="grid grid-cols-3 gap-2">
          {doctorStats.map((s) => (
            <Card key={s.label} className="shadow-card">
              <CardContent className="px-2 py-4 text-center">
                <p className="text-[20px] font-bold text-primary">{s.value}</p>
                <p className="caption-text">{s.label}</p>
              </CardContent>
            </Card>
          ))}
        </div>

        <SectionTitle>Quick actions</SectionTitle>
        <div className="grid grid-cols-3 gap-2">
          <Action to="/doctor/patients" icon={<Users className="size-5" />} label="Patients" />
          <Action to="/doctor/prescription" icon={<FilePlus2 className="size-5" />}
label="Prescribe" />
          <Action to="/doctor/clinic" icon={<BarChart3 className="size-5" />} label="Clinic" />
        </div>

```

```

<SectionTitle>Today's appointments</SectionTitle>

<div className="flex flex-col gap-2">

  {doctorSchedule.map((s) => (

    <Card key={s.time} className="shadow-card">

      <CardContent className="flex items-center gap-3 py-4">

        <p className="w-[86px] shrink-0 text-[14px] font-semibold text-
primary">{s.time}</p>

        <div className="min-w-0 flex-1">

          <p className="text-[16px] font-semibold">{s.patient}</p>

          <p className="caption-text">{s.reason}</p>

        </div>

      </CardContent>

    </Card>

  )})

</div>

</Screen>

</PhoneFrame>

);
}

```

```

function Action({
  to,
  icon,
  label,
}: {
  to: "/doctor/patients" | "/doctor/prescription" | "/doctor/clinic";
  icon: React.ReactNode;
  label: string;

```

```

  }) {
    return (
      <Link
        to={to}
        className="tap-target flex flex-col items-center justify-center gap-1 rounded-xl border
border-border bg-card py-4 text-[14px] font-medium text-foreground"
      >
        <span className="text-primary">{icon}</span>
        {label}
      </Link>
    );
  }

```

doctor.index.tsx:

```
import { createFileRoute, Link, useNavigate } from "@tanstack/react-router";
```

```
import { Stethoscope } from "lucide-react";
```

```
import { useState } from "react";
```

```
import { PhoneFrame, Screen } from "@components/app-shell";
```

```
import { Button } from "@components/ui/button";
```

```
import { Input } from "@components/ui/input";
```

```
import { Label } from "@components/ui/label";
```

```
export const Route = createFileRoute("/doctor/")({
```

```
  head: () => ({
```

```
    meta: [
```

```
      { title: "Doctor login — MedSimplify" },
```

```
      {
```

```
        name: "description",
```

```

        content: "Doctors sign in to see today's appointments, patient records and write prescriptions.",
    },
    { property: "og:title", content: "Doctor login — MedSimplify" },
    { property: "og:description", content: "Sign in to the MedSimplify doctor workspace." },
  ],
}),
component: DoctorLogin,
});

```

```

function DoctorLogin() {
  const navigate = useNavigate();
  const [id, setId] = useState("MCI-882140");
  const [password, setPassword] = useState("");

  return (
    <PhoneFrame>
      <Screen className="flex flex-col justify-center gap-6">
        <div className="text-center">
          <div className="mx-auto flex size-16 items-center justify-center rounded-2xl bg-primary/10 text-primary">
            <Stethoscope className="size-8" />
          </div>
          <h1 className="mt-4 text-[24px] font-bold">MedSimplify for Doctors</h1>
          <p className="text-[14px] text-muted-foreground">Sign in with your medical registration ID</p>
        </div>

        <form

```

```

        className="flex flex-col gap-4"
        onSubmit={(e) => {
            e.preventDefault();
            navigate({ to: "/doctor/dashboard" });
        }}
    >
    <div>
        <Label htmlFor="mci">Registration ID</Label>
        <Input id="mci" value={id} onChange={(e) => setId(e.target.value)} className="h-12
text-[16px]" />
    </div>
    <div>
        <Label htmlFor="dpass">Password</Label>
        <Input
            id="dpass"
            type="password"
            value={password}
            onChange={(e) => setPassword(e.target.value)}
            placeholder="Enter password"
            className="h-12 text-[16px]"
        />
    </div>
    <Button type="submit" className="h-12 text-[16px]">
        Sign in
    </Button>
</form>

    <Link to="/login" className="tap-target text-center text-[14px] text-muted-foreground
underline">

```

```

        I'm a patient
      </Link>
    </Screen>
  </PhoneFrame>
);
}
doctor.patient.tsx:
import { createFileRoute, Link } from "@tanstack/react-router";

import { FilePlus2 } from "lucide-react";

import { useState } from "react";

import { toast } from "sonner";

import { PageHeader, PhoneFrame, Screen } from "@components/app-shell";
import { Badge } from "@components/ui/badge";
import { Button } from "@components/ui/button";
import { Card, CardContent } from "@components/ui/card";
import { Tabs, TabsList, TabsTrigger } from "@components/ui/tabs";
import { Textarea } from "@components/ui/textarea";
import { medicines, patient, reports } from "@lib/medsimplify-data";

export const Route = createFileRoute("/doctor/patient")({
  head: () => ({
    meta: [
      { title: "Patient record — MedSimplify" },
      {
        name: "description",
        content: "Full patient record: lab reports, current prescriptions, visit history and clinical notes.",
      },
    ],
  })
});

```

```

    { property: "og:title", content: "Patient record — MedSimplify" },
    { property: "og:description", content: "Reports, prescriptions, history and notes in one record." },
  ],
}),
component: DoctorPatientProfile,
});

```

```

function DoctorPatientProfile() {
  const [tab, setTab] = useState("reports");
  const [note, setNote] = useState("");

  return (
    <PhoneFrame>
      <PageHeader title={patient.name} subtitle={` ${patient.age} · ${patient.bloodGroup} · Dengue fever`} back="/doctor/patients" />
      <Screen>
        <Tabs value={tab} onValueChange={setTab}>
          <TabsList className="grid w-full grid-cols-4">
            <TabsTrigger value="reports">Reports</TabsTrigger>
            <TabsTrigger value="rx">Rx</TabsTrigger>
            <TabsTrigger value="history">History</TabsTrigger>
            <TabsTrigger value="notes">Notes</TabsTrigger>
          </TabsList>
        </Tabs>

        <div className="mt-4 flex flex-col gap-2">
          {tab === "reports" &&
            reports.map((r) => (

```

```

<Card key={r.id} className="shadow-card">
  <CardContent className="py-4">
    <div className="flex items-center gap-2">
      <p className="flex-1 text-[16px] font-semibold">{r.title}</p>
      <Badge variant="secondary">{r.type}</Badge>
    </div>
    <p className="caption-text">
      {r.date} · {r.keyFinding}
    </p>
    {r.abnormal ? <p className="text-[14px] font-semibold text-destructive">{r.abnormal}</p> : null}
  </CardContent>
</Card>
)}}

```

```

{tab === "rx" &&
  medicines.map((m) => (
    <Card key={m.id} className="shadow-card">
      <CardContent className="py-4">
        <p className="text-[16px] font-semibold">{m.name}</p>
        <p className="caption-text">
          {m.dosage} · {m.timing} · day {m.dayOf} of {m.totalDays}
        </p>
      </CardContent>
    </Card>
  ))}

```

```

{tab === "history" && (

```

```

<Card className="shadow-card">
  <CardContent className="py-4 text-[16px]">
    <ul className="list-disc pl-5">
      <li>13-Sep-2026 — Dengue diagnosed, treatment started</li>
      <li>28-Aug-2026 — Viral fever consultation</li>
      <li>12-Aug-2026 — Discharged after viral fever</li>
      <li>Known allergies: {patient.allergies}</li>
    </ul>
  </CardContent>
</Card>
)}

```

```

{tab === "notes" && (
  <Card className="shadow-card">
    <CardContent className="py-4">
      <Textarea
        value={note}
        onChange={(e) => setNote(e.target.value)}
        placeholder="Clinical notes for this visit..."
        aria-label="Clinical notes"
        className="min-h-32 text-[16px]"
      />
      <Button className="mt-3 h-12 w-full text-[16px]" onClick={() =>
toast.success("Note saved")}>
        Save note
      </Button>
    </CardContent>
  </Card>

```

```
  })  
</div>
```

```
  <Button asChild className="mt-6 h-12 w-full text-[16px]">  
    <Link to="/doctor/prescription">  
      <FilePlus2 className="size-4" /> Create prescription  
    </Link>  
  </Button>  
</Screen>  
</PhoneFrame>
```

```
);
```

```
}
```

doctor.patients.tsx:

```
import { createFileRoute, Link } from "@tanstack/react-router";
```

```
import { ChevronRight, Search } from "lucide-react";
```

```
import { useState } from "react";
```

```
import { EmptyState, PageHeader, PhoneFrame, Screen } from "@/components/app-shell";
```

```
import { Card, CardContent } from "@/components/ui/card";
```

```
import { Input } from "@/components/ui/input";
```

```
import { doctorPatients } from "@/lib/medsimplify-data";
```

```
import { cn } from "@/lib/utils";
```

```
const filters = ["All", "Today", "Follow-up", "Critical"] as const;
```

```
export const Route = createFileRoute("/doctor/patients")({
```

```
  head: () => ({
```

```
    meta: [
```

```
      { title: "My patients — MedSimplify" },
```

```

    { name: "description", content: "Search and filter your patient list and open a full patient
record." },
    { property: "og:title", content: "My patients — MedSimplify" },
    { property: "og:description", content: "Your full patient list with search and filters." },
  ],
}),
component: DoctorPatients,
});

```

```

function DoctorPatients() {
  const [query, setQuery] = useState("");
  const [filter, setFilter] = useState<string>("All");

  const list = doctorPatients.filter(
    (p) =>
      p.name.toLowerCase().includes(query.toLowerCase()) ||
      p.condition.toLowerCase().includes(query.toLowerCase()),
  );

  return (
    <PhoneFrame>
      <PageHeader title="My Patients" back="/doctor/dashboard" />
      <Screen>
        <div className="relative">
          <Search className="absolute left-3 top-1/2 size-4 -translate-y-1/2 text-muted-
foreground" />
          <Input
            value={query}
            onChange={(e) => setQuery(e.target.value)}

```

```
placeholder="Search by name or condition"
aria-label="Search patients"
className="h-12 pl-9 text-[16px]"
/>
</div>
```

```
<div className="mt-3 flex gap-2 overflow-x-auto">
  {filters.map((f) => (
    <button
      key={f}
      onClick={() => setFilter(f)}
      className={cn(
        "tap-target whitespace-nowrap rounded-full border px-3 text-[14px]",
        filter === f ? "border-primary bg-primary text-primary-foreground" : "border-
border",
      )}
    >
      {f}
    </button>
  ))}
</div>
```

```
<div className="mt-4 flex flex-col gap-2">
  {list.length === 0 ? (
    <EmptyState
      icon={<Search className="size-6" />}
      title="No patients found"
      message="Try a different name or condition."
    >
```

```

    />
  ) : (
    list.map((p) => (
      <Card key={p.id} className="shadow-card">
        <CardContent className="p-0">
          <Link to="/doctor/patient" className="tap-target flex items-center gap-3 px-4 py-
3">
            <div className="flex size-10 items-center justify-center rounded-full bg-
primary/10 text-[16px] font-bold text-primary">
              {p.name.charAt(0)}
            </div>
            <div className="min-w-0 flex-1">
              <p className="text-[16px] font-semibold">
                {p.name} <span className="text-[14px] font-normal text-muted-
foreground">{p.age}</span>
              </p>
              <p className="caption-text">
                {p.condition} · last visit {p.lastVisit}
              </p>
            </div>
            <ChevronRight className="size-5 text-muted-foreground" />
          </Link>
        </CardContent>
      </Card>
    ))
  )}
</div>
</Screen>
</PhoneFrame>

```

```

    );
  }
  doctor.prescriptions.tsx:
import { createFileRoute } from "@tanstack/react-router";

import { AlertTriangle, Plus, Trash2 } from "lucide-react";

import { useState } from "react";

import { toast } from "sonner";


import { PageHeader, PhoneFrame, Screen, SectionTitle } from "@components/app-shell";
import { Button } from "@components/ui/button";
import { Card, CardContent } from "@components/ui/card";
import { Input } from "@components/ui/input";
import { Label } from "@components/ui/label";
import { Textarea } from "@components/ui/textarea";
import { patient } from "@lib/medsimplify-data";

const catalogue = [
  { name: "Paracetamol 500mg", dose: "1 tablet every 6 hours, after food" },
  { name: "ORS Sachet", dose: "1 sachet in 1 litre water, sip through the day" },
  { name: "Pantoprazole 40mg", dose: "1 tablet daily, empty stomach" },
  { name: "Ibuprofen 400mg", dose: "1 tablet twice daily, after food" },
  { name: "Azithromycin 500mg", dose: "1 tablet daily for 3 days" },
];

export const Route = createFileRoute("/doctor/prescription")({
  head: () => ({
    meta: [
      { title: "Create prescription — MedSimplify" },
    ]
  })
});

```

```

      name: "description",
      content: "Search medicines, get interaction warnings and send a prescription to the
patient's app.",
    },
    { property: "og:title", content: "Create prescription — MedSimplify" },
    { property: "og:description", content: "Write a prescription with automatic interaction
checks." },
  ],
}),
component: CreatePrescription,
});

```

```

function CreatePrescription() {
  const [query, setQuery] = useState("");
  const [items, setItems] = useState<{ name: string; dose: string }[]>([
    { name: "Paracetamol 500mg", dose: "1 tablet every 6 hours, after food" },
  ]);
  const [followUp, setFollowUp] = useState("After 3 days");
  const [advice, setAdvice] = useState("Complete bed rest, 3-4 litres of fluids daily.");

  const matches = query
    ? catalogue.filter((c) => c.name.toLowerCase().includes(query.toLowerCase()))
    : [];

  const warning = items.some((i) => i.name.startsWith("Ibuprofen"));

  return (
    <PhoneFrame>

```

```
<PageHeader title="New Prescription" subtitle={`For ${patient.name} · ${patient.age}`}
back="/doctor/patient" />
```

```
<Screen>
```

```
<Label htmlFor="med">Search medicine</Label>
```

```
<Input
```

```
  id="med"
```

```
  value={query}
```

```
  onChange={(e) => setQuery(e.target.value)}
```

```
  placeholder="Start typing a medicine name"
```

```
  className="h-12 text-[16px]"
```

```
/>
```

```
{matches.length > 0 ? (
```

```
<Card className="mt-2 shadow-card">
```

```
<CardContent className="divide-y divide-border p-0">
```

```
  {matches.map((m) => (
```

```
    <button
```

```
      key={m.name}
```

```
      className="tap-target flex w-full items-center gap-2 px-4 py-3 text-left text-
[16px]"
```

```
      onClick={() => {
```

```
        setItems((list) => [...list, m]);
```

```
        setQuery("");
```

```
      }}
    >
```

```
    <Plus className="size-4 text-primary" />
```

```
    <span className="flex-1">{m.name}</span>
```

```
  </button>
```

```
  )})
```

```
</CardContent>
```

```
</Card>
```

```
) : null}
```

```
{warning ? (
```

```
  <div className="mt-3 flex items-start gap-2 rounded-xl border border-destructive/40  
bg-destructive/10 px-3 py-2 text-[14px] text-destructive">
```

```
    <AlertTriangle className="mt-0.5 size-4 shrink-0" />
```

```
    <p>
```

```
      <strong>Interaction warning:</strong> Ibuprofen increases bleeding risk in dengue  
with low platelets.
```

```
      Prefer Paracetamol.
```

```
    </p>
```

```
  </div>
```

```
) : null}
```

```
<SectionTitle>Medicines</SectionTitle>
```

```
<div className="flex flex-col gap-2">
```

```
  {items.map((i, idx) => (
```

```
    <Card key={` ${i.name}- ${idx}`} className="shadow-card">
```

```
      <CardContent className="flex items-start gap-3 py-4">
```

```
        <div className="min-w-0 flex-1">
```

```
          <p className="text-[16px] font-semibold">{i.name}</p>
```

```
          <p className="caption-text">{i.dose}</p>
```

```
        </div>
```

```
        <button
```

```
          aria-label={`Remove ${i.name}`}>
```

```
          className="tap-target text-destructive"
```

```
          onClick={() => setItems((list) => list.filter((_, n) => n !== idx))}
```

```
        <Trash2 className="size-4" />

      </button>

    </CardContent>

  </Card>

  )}}

</div>
```

```
<SectionTitle>Advice & follow-up</SectionTitle>
```

```
<Textarea
```

```
  value={advice}
```

```
  onChange={(e) => setAdvice(e.target.value)}
```

```
  aria-label="Advice for the patient"
```

```
  className="min-h-24 text-[16px]"
```

```
<div className="mt-3">
```

```
  <Label htmlFor="fu">Follow-up</Label>
```

```
  <Input
```

```
    id="fu"
```

```
    value={followUp}
```

```
    onChange={(e) => setFollowUp(e.target.value)}
```

```
    className="h-12 text-[16px]"
```

```
  />
```

```
</div>
```

```
<Button
```

```
  className="mt-6 h-12 w-full text-[16px]"
```

```
  onClick={() => toast.success("Prescription sent to patient's app")}
```

```
>
```

```

        Send prescription
      </Button>
    </Screen>
  </PhoneFrame>
);
}
emergency.tsx:
import { createFileRoute } from "@tanstack/react-router";

import { AlertTriangle, MapPin, Phone } from "lucide-react";

import { toast } from "sonner";

import { PageHeader, PhoneFrame, Screen, SectionTitle } from "@components/app-shell";
import { Button } from "@components/ui/button";
import { Card, CardContent } from "@components/ui/card";
import { emergencyConditions, patient } from "@lib/medsimplify-data";

export const Route = createFileRoute("/emergency")({
  head: () => ({
    meta: [
      { title: "Emergency information — MedSimplify" },
      {
        name: "description",
        content: "One-tap emergency numbers, your medical ID card, warning signs and the nearest hospital.",
      },
      { property: "og:title", content: "Emergency information — MedSimplify" },
      { property: "og:description", content: "Emergency numbers, medical ID and warning signs in one place." },
    ],
  })
});

```

```
  }},  
  component: EmergencyScreen,  
});
```

```
function EmergencyScreen() {  
  return (  
    <PhoneFrame>  
      <PageHeader title="🚒 Emergency" back="/home" />  
      <Screen withNav>  
        <div className="grid grid-cols-2 gap-3">  
          <Button  
            className="h-20 bg-destructive text-[18px] font-bold text-destructive-foreground  
            hover:bg-destructive/90"  
            onClick={() => toast("Calling ambulance 108")}  
          >  
            <Phone className="size-5" /> Call 108  
          </Button>  
          <Button  
            variant="outline"  
            className="h-20 border-destructive text-[18px] font-bold text-destructive"  
            onClick={() => toast("Calling emergency 112")}  
          >  
            <Phone className="size-5" /> Call 112  
          </Button>  
        </div>  
  
        <SectionTitle>My medical ID</SectionTitle>  
        <Card className="shadow-card">
```

```

<CardContent className="grid grid-cols-2 gap-3 pt-6 text-[16px]">
  <Info label="Name" value={patient.name} />
  <Info label="Age / Sex" value={patient.age} />
  <Info label="Blood group" value={patient.bloodGroup} />
  <Info label="Allergies" value={patient.allergies} />
  <div className="col-span-2">
    <Info label="Current condition" value="Dengue fever, platelets 80,000" />
  </div>
  <div className="col-span-2">
    <Info label="Emergency contact" value={patient.emergencyContact} />
  </div>
</CardContent>
</Card>

<Button
  variant="outline"
  className="mt-3 h-12 w-full text-[16px]"
  onClick={() => toast("Calling emergency contact")}
>
  <Phone className="size-4" /> Call emergency contact
</Button>

<SectionTitle>Warning signs — go to hospital now</SectionTitle>
<div className="flex flex-col gap-3">
  {emergencyConditions.map((c) => (
    <Card key={c.name} className="border-destructive/30 shadow-card">
      <CardContent className="pt-6">
        <p className="flex items-center gap-2 text-[16px] font-bold text-destructive">

```

```

      <AlertTriangle className="size-4" /> {c.name}
    </p>
    <ul className="mt-2 list-disc pl-5 text-[16px]">
      {c.signs.map((s) => (
        <li key={s}>{s}</li>
      ))}
    </ul>
  </CardContent>
</Card>
)}}
</div>

```

```

<SectionTitle>Nearest hospital</SectionTitle>
<Card className="shadow-card">
  <CardContent className="pt-6">
    <p className="text-[16px] font-semibold">City Hospital — Emergency Ward</p>
    <p className="caption-text">2.3 km away · open 24 hours · MG Road</p>
    <div className="mt-3 grid grid-cols-2 gap-2">
      <Button variant="outline" className="h-11" onClick={() => toast("Opening
directions")}>
        <MapPin className="size-4" /> Directions
      </Button>
      <Button variant="outline" className="h-11" onClick={() => toast("Calling
hospital")}>
        <Phone className="size-4" /> Call
      </Button>
    </div>
  </CardContent>
</Card>

```

```
    </Screen>
  </PhoneFrame>
);
}
```

```
function Info({ label, value }: { label: string; value: string }) {
  return (
    <div>
      <p className="caption-text">{label}</p>
      <p className="font-semibold">{value}</p>
    </div>
  );
}
```

family.tsx:

```
import { createFileRoute } from "@tanstack/react-router";

import { FileText, Plus, UserPlus } from "lucide-react";

import { useState } from "react";

import { toast } from "sonner";

import { EmptyState, PageHeader, PhoneFrame, Screen } from "@components/app-shell";
import { Button } from "@components/ui/button";
import { Card, CardContent } from "@components/ui/card";
import {
  Dialog,
  DialogContent,
  DialogFooter,
  DialogHeader,
  DialogTitle,
  DialogTrigger,

```

```

} from "@components/ui/dialog";

import { Input } from "@components/ui/input";

import { Label } from "@components/ui/label";

import { familyMembers as seed } from "@lib/medsimplify-data";

export const Route = createFileRoute("/family")({
  head: () => ({
    meta: [
      { title: "Family members — MedSimplify" },
      {
        name: "description",
        content: "Keep reports and medicines for your whole family in one account and switch between profiles.",
      },
      { property: "og:title", content: "Family members — MedSimplify" },
      { property: "og:description", content: "Manage health records for your whole family." },
    ],
  }),
  component: FamilyScreen,
});

```

```

function FamilyScreen() {
  const [members, setMembers] = useState(seed);
  const [open, setOpen] = useState(false);
  const [name, setName] = useState("");
  const [relation, setRelation] = useState("");
  const [age, setAge] = useState("");

```

```

const add = () => {
  if (!name.trim()) {
    toast.error("Please enter a name");
    return;
  }
  setMembers((m) => [
    ...m,
    { id: `f${m.length + 1}`, name: name.trim(), relation: relation || "Family", age: age || "—",
reports: 0 },
  ]);
  setName("");
  setRelation("");
  setAge("");
  setOpen(false);
  toast.success("Family member added");
};

return (
  <PhoneFrame>
    <PageHeader title="👨👩👧👦 Family" back="/profile" />
    <Screen withNav>
      {members.length === 0 ? (
        <EmptyState
          icon={<UserPlus className="size-6" />}
          title="No family members yet"
          message="Add your family so their reports and medicines stay in one place."
        />
      ) : (

```

```

<div className="flex flex-col gap-3">

  {members.map((m) => (

    <Card key={m.id} className="shadow-card">

      <CardContent className="flex items-center gap-3 pt-6">

        <div className="flex size-12 items-center justify-center rounded-full bg-
primary/10 text-[18px] font-bold text-primary">

          {m.name.charAt(0)}

        </div>

        <div className="min-w-0 flex-1">

          <p className="text-[16px] font-semibold">{m.name}</p>

          <p className="caption-text">

            {m.relation} · {m.age}

          </p>

          <p className="mt-1 flex items-center gap-1 text-[14px] text-muted-foreground">

            <FileText className="size-4" /> {m.reports} reports

          </p>

        </div>

        <Button

          variant="outline"

          className="h-11 text-[14px]"

          onClick={() => toast(`Switched to ${m.name}`)}

        >

          Switch

        </Button>

      </CardContent>

    </Card>

  )})

</div>

```

```
}}
```

```
<Dialog open={open} onOpenChange={setOpen}>
  <DialogTrigger asChild>
    <Button className="mt-6 h-12 w-full text-[16px]">
      <Plus className="size-4" /> Add family member
    </Button>
  </DialogTrigger>
  <DialogContent className="max-w-[360px]">
    <DialogHeader>
      <DialogTitle>Add family member</DialogTitle>
    </DialogHeader>
    <div className="flex flex-col gap-3">
      <div>
        <Label htmlFor="fname">Full name</Label>
        <Input id="fname" value={name} onChange={(e) => setName(e.target.value)}
className="h-12" />
      </div>
      <div>
        <Label htmlFor="frel">Relation</Label>
        <Input
          id="frel"
          value={relation}
          onChange={(e) => setRelation(e.target.value)}
          placeholder="Wife, Son, Mother..."
          className="h-12"
        />
      </div>
    </div>
  </DialogContent>
</Dialog>
```

```

    <div>
      <Label htmlFor="fage">Age & sex</Label>
      <Input
        id="fage"
        value={age}
        onChange={(e) => setAge(e.target.value)}
        placeholder="32F"
        className="h-12"
      />
    </div>
  </div>
  <DialogFooter>
    <Button className="h-12 w-full text-[16px]" onClick={add}>
      Add member
    </Button>
  </DialogFooter>
</DialogContent>
</Dialog>
</Screen>
</PhoneFrame>
);
}
profile.tsx:
import { createFileRoute, Link, useNavigate } from "@tanstack/react-router";

import {
  Bell,
  ChevronRight,
  Globe,
  HeartPulse,

```

```
    Logout,
    ShieldCheck,
    Trash2,
    Users,
  } from "lucide-react";
import { useState } from "react";
import { toast } from "sonner";

import { BottomNav, PhoneFrame, Screen, SectionTitle } from "@components/app-shell";
import { Button } from "@components/ui/button";
import { Card, CardContent } from "@components/ui/card";
import {
  Select,
  SelectContent,
  SelectItem,
  SelectTrigger,
  SelectValue,
} from "@components/ui/select";
import { Switch } from "@components/ui/switch";
import { patient } from "@lib/medsimplify-data";

export const Route = createFileRoute("/profile")({
  head: () => ({
    meta: [
      { title: "Profile & settings — MedSimplify" },
      {
        name: "description",
      }
    ]
  })
});
```

```
        content: "Your details, family members, language, reminders and privacy settings in MedSimplify.",
```

```
    },
```

```
    { property: "og:title", content: "Profile & settings — MedSimplify" },
```

```
    { property: "og:description", content: "Manage your account, language and reminder settings." },
```

```
  ],
```

```
  }},
```

```
  component: ProfileScreen,
```

```
});
```

```
function ProfileScreen() {
```

```
  const navigate = useNavigate();
```

```
  const [reminders, setReminders] = useState(true);
```

```
  const [reportAlerts, setReportAlerts] = useState(true);
```

```
  return (
```

```
    <PhoneFrame>
```

```
      <Screen withNav>
```

```
        <Card className="shadow-card">
```

```
          <CardContent className="flex items-center gap-3 pt-6">
```

```
            <div className="flex size-14 items-center justify-center rounded-full bg-primary/10 text-[20px] font-bold text-primary">
```

```
              {patient.firstName.charAt(0)}
```

```
            </div>
```

```
            <div className="min-w-0 flex-1">
```

```
              <p className="text-[20px] font-bold">{patient.name}</p>
```

```
              <p className="caption-text">
```

```
                {patient.age} · {patient.bloodGroup} · {patient.phone}
```

```
        </p>

    </div>

    <Button variant="outline" className="h-11 text-[14px]" onClick={() => toast("Edit
profile")}>

        Edit

    </Button>

</CardContent>

</Card>
```

```
<SectionTitle>Health</SectionTitle>

<Card className="shadow-card">

    <CardContent className="divide-y divide-border p-0">

        <RowLink to="/family" icon={<Users className="size-5 text-primary" />}
label="Family members" />

        <RowLink to="/symptoms" icon={<HeartPulse className="size-5 text-primary" />}
label="Symptom tracker" />

        <RowLink to="/emergency" icon={<ShieldCheck className="size-5 text-primary" />}
label="Emergency info" />

    </CardContent>

</Card>
```

```
<SectionTitle>Notifications</SectionTitle>

<Card className="shadow-card">

    <CardContent className="flex flex-col gap-4 pt-6">

        <label className="flex items-center justify-between gap-3 text-[16px]">

            <span className="flex items-center gap-2">

                <Bell className="size-5 text-primary" /> Medicine reminders

            </span>

        </label>

    </CardContent>

</Card>
```

```
        <Switch checked={reminders} onCheckedChange={setReminders} aria-
label="Medicine reminders" />

    </label>

    <label className="flex items-center justify-between gap-3 text-[16px]">

        <span className="flex items-center gap-2">

            <Bell className="size-5 text-primary" /> Report ready alerts

        </span>

        <Switch checked={reportAlerts} onCheckedChange={setReportAlerts} aria-
label="Report alerts" />

    </label>

</CardContent>

</Card>
```

```
<SectionTitle>Preferences</SectionTitle>

<Card className="shadow-card">

    <CardContent className="pt-6">

        <label className="mb-2 flex items-center gap-2 text-[16px]" htmlFor="lang">

            <Globe className="size-5 text-primary" /> App language

        </label>

        <Select defaultValue="en" onValueChange={(v) => toast(`Language set to
${v.toUpperCase()})`}>

            <SelectTrigger id="lang" className="h-12 text-[16px]">

                <SelectValue />

            </SelectTrigger>

            <SelectContent>

                <SelectItem value="en">English</SelectItem>

                <SelectItem value="hi">हिन्दी (Hindi)</SelectItem>

                <SelectItem value="ta">தமிழ் (Tamil)</SelectItem>
```

```
      <SelectItem value="bn">বাংলা (Bengali)</SelectItem>
    </SelectContent>
  </Select>
</CardContent>
</Card>
```

```
<SectionTitle>Account</SectionTitle>
<div className="flex flex-col gap-3">
  <Button
    variant="outline"
    className="h-12 w-full justify-start text-[16px]"
    onClick={() => {
      toast("Signed out");
      navigate({ to: "/login" });
    }}
  >
    <LogOut className="size-4" /> Log out
  </Button>
  <Button
    variant="outline"
    className="h-12 w-full justify-start border-destructive text-[16px] text-destructive"
    onClick={() => toast.error("Account deletion needs email confirmation")}
  >
    <Trash2 className="size-4" /> Delete account
  </Button>
  <Link
    to="/doctor"
```

```
        className="tap-target flex items-center justify-center rounded-md text-[14px] text-
muted-foreground underline"
```

```
    >
```

```
        Switch to doctor app
```

```
    </Link>
```

```
</div>
```

```
</Screen>
```

```
<BottomNav />
```

```
</PhoneFrame>
```

```
);
```

```
}
```

```
function RowLink({
```

```
  to,
```

```
  icon,
```

```
  label,
```

```
}: {
```

```
  to: "/family" | "/symptoms" | "/emergency";
```

```
  icon: React.ReactNode;
```

```
  label: string;
```

```
}) {
```

```
  return (
```

```
    <Link to={to} className="tap-target flex items-center gap-3 px-4 py-3 text-[16px]">
```

```
      {icon}
```

```
      <span className="flex-1">{label}</span>
```

```
      <ChevronRight className="size-5 text-muted-foreground" />
```

```
    </Link>
```

```
  );
```

```
}
```

```
login.tsx:
```

```
import { createFileRoute, useNavigate } from "@tanstack/react-router";
```

```
import { Eye, EyeOff, HeartPulse, Loader2, Lock, Mail, Phone, Stethoscope } from "lucide-react";
```

```
import { useState } from "react";
```

```
import { PhoneFrame, Screen } from "@components/app-shell";
```

```
import { Button } from "@components/ui/button";
```

```
import { Card, CardContent } from "@components/ui/card";
```

```
import { Input } from "@components/ui/input";
```

```
import { Label } from "@components/ui/label";
```

```
export const Route = createFileRoute("/login")({
```

```
  head: () => ({
```

```
    meta: [
```

```
      { title: "Sign in — MedSimplify" },
```

```
      { name: "description", content: "Sign in to MedSimplify to view your simplified medical reports, medicines and appointments." },
```

```
      { property: "og:title", content: "Sign in — MedSimplify" },
```

```
      { property: "og:description", content: "Access your simplified health records." },
```

```
    ],
```

```
  }),
```

```
  component: LoginScreen,
```

```
});
```

```
function LoginScreen() {
```

```
  const navigate = useNavigate();
```

```
  const [email, setEmail] = useState("rajesh@email.com");
```

```

const [password, setPassword] = useState("");
const [show, setShow] = useState(false);
const [error, setError] = useState("");
const [loading, setLoading] = useState(false);

function submit(e: React.FormEvent) {
  e.preventDefault();
  if (!email.includes("@")) return setError("Please enter a valid email address.");
  if (password.length < 4) return setError("Password must be at least 4 characters.");
  setError("");
  setLoading(true);
  window.setTimeout(() => navigate({ to: "/home" }), 700);
}

return (
  <PhoneFrame>
    <Screen className="flex flex-col justify-center gap-6">
      <div className="text-center">
        <div className="mx-auto flex size-16 items-center justify-center rounded-2xl bg-
primary text-primary-foreground">
          <HeartPulse className="size-8" />
        </div>
        <h1 className="mt-4">Welcome to MedSimplify</h1>
        <p className="mt-1 text-[14px] text-muted-foreground">Your Health, Simplified</p>
      </div>

      <Card className="shadow-card">
        <CardContent className="pt-6">

```

```

<form className="flex flex-col gap-4" onSubmit={submit} noValidate>

  <div className="flex flex-col gap-2">

    <Label htmlFor="email">Email</Label>

    <div className="relative">

      <Mail className="pointer-events-none absolute left-3 top-1/2 size-4 -translate-y-
1/2 text-muted-foreground" />

      <Input
        id="email"
        type="email"
        value={email}
        onChange={(e) => setEmail(e.target.value)}
        className="h-11 pl-9"
        placeholder="you@email.com"
      />
    </div>
  </div>
</form>

```

```

<div className="flex flex-col gap-2">

  <Label htmlFor="password">Password</Label>

  <div className="relative">

    <Lock className="pointer-events-none absolute left-3 top-1/2 size-4 -translate-y-
1/2 text-muted-foreground" />

    <Input
      id="password"
      type={show ? "text" : "password"}
      value={password}
      onChange={(e) => setPassword(e.target.value)}
      className="h-11 pl-9 pr-11"
      placeholder="••••••••"
    >
  </div>
</div>

```

```

/>

<button
  type="button"
  aria-label={show ? "Hide password" : "Show password"}
  onClick={() => setShow((s) => !s)}
  className="tap-target absolute right-0 top-1/2 flex -translate-y-1/2 items-center
justify-center text-muted-foreground"
  >
  {show ? <EyeOff className="size-4" /> : <Eye className="size-4" />}
</button>
</div>
</div>

```

```

{error ? (
  <p role="alert" className="text-[14px] font-medium text-destructive">
    {error}
  </p>
) : null}

```

```

<Button type="submit" size="lg" className="h-12 w-full text-[16px]"
disabled={loading}>
  {loading ? <Loader2 className="size-4 animate-spin" /> : null}
  {loading ? "Signing in..." : "Login"}
</Button>

```

```

<button type="button" className="text-[14px] font-medium text-primary">
  Forgot Password?
</button>
</form>

```

```
<div className="my-5 flex items-center gap-3">
  <span className="h-px flex-1 bg-border" />
  <span className="caption-text">Or continue with</span>
  <span className="h-px flex-1 bg-border" />
</div>
```

```
<div className="flex flex-col gap-3">
  <Button variant="outline" className="h-12 w-full text-[16px]" onClick={() =>
navigate({ to: "/home" })}>
    Continue with Google
  </Button>
  <Button variant="outline" className="h-12 w-full text-[16px]" onClick={() =>
navigate({ to: "/home" })}>
    <Phone className="size-4" /> Login with phone OTP
  </Button>
</div>
```

```
<p className="mt-5 text-center text-[14px] text-muted-foreground">
  Don't have an account?{" "}
  <button type="button" className="font-semibold text-primary">
    Sign Up
  </button>
</p>
</CardContent>
</Card>
```

```
<Button
  variant="ghost"
```

```
        className="h-12 text-[14px] text-muted-foreground"
        onClick={() => navigate({ to: "/doctor" })}
    >
        <Stethoscope className="size-4" /> I'm a doctor
    </Button>
</Screen>
</PhoneFrame>
);
}
```