

<b>Product number</b>	C series	<b>working environment</b>	High and low temperature environment
<b>electricity demand</b>	220VC,50~60Hz	<b>Control method</b>	Manual
<b>Product Size</b>	Dimensions: 1400 mm * 920 mm * 920 mm	<b>equipment weight</b>	150KG/170KG/250KG

### Application direction

LD/LED/PD test,PCB/ package device test, MATERIAL/device IV/CV characteristic test, internal circuit/electrode /PAD test, hf RF test, etc.r

### Technical characteristics

Pneumatic type mobile platform has the function of fast moving chuck, can meet the needs of efficient manual test by the corresponding gas float switch, provides three kinds of method of fast moving ; Three - stage lifting needle base platform, the needle seat platform can rise and fall rapidly (0,300um,3mm)+ fine adjustment (40mm, moving resolution 2~5μm) ; built-in 3 zoom multi-view, triple-rate concentric focal path system (internal optical zoom: 0.6:1 ; 2.5:1 ; 9:1);shielding cavity structure design, provides the best low noise and low leakage current capacity.At the same time, it keeps the sample under nitrogen or positive pressure environment at low temperature without frosting, and the unique cavity blowing structure prevents cryogenic frosting.

## 7) FA Series Failure Analysis Probe Station



### Product Overview