

# Decision Tree Practical

## Interview Questions

(Practice Project)



## Easy Questions

**1. How would you load the iris dataset and train a Decision Tree classifier using scikit-learn in Python?**

**Ans:**

```
from sklearn.datasets import load_iris
from sklearn.tree import DecisionTreeClassifier
from sklearn.model_selection import train_test_split

iris = load_iris()
X_train, X_test, y_train, y_test =
train_test_split(iris.data, iris.target, test_size=0.3,
random_state=42)
clf = DecisionTreeClassifier()
clf.fit(X_train, y_train)
```

**2. How do you visualize a trained Decision Tree using graphviz in scikit-learn?**

**Ans:**

```
from sklearn.tree import export_graphviz
import graphviz

dot_data = export_graphviz(clf, out_file=None,
feature_names=iris.feature_names,
class_names=iris.target_names, filled=True)
graph = graphviz.Source(dot_data)
graph.render("iris_tree")
```

**3. How do you predict the class of a new sample using a trained Decision Tree classifier?**

**Answer: We can use the predict() method to make predictions:**

```
new_sample = [[5.1, 3.5, 1.4, 0.2]]
prediction = clf.predict(new_sample)
print(prediction)
```

**4. How do you find the accuracy of a Decision Tree model on the test data?**

**Answer: We can calculate the accuracy using the score() method:**

```
accuracy = clf.score(X_test, y_test)
print(f"Accuracy: {accuracy}")
```

### 5. How do you set a maximum depth for a Decision Tree in scikit-learn?

**Answer:** We can set the `max_depth` parameter when initializing the `DecisionTreeClassifier`:

```
clf = DecisionTreeClassifier(max_depth=3)
```

### 6. How do you set the criterion to entropy in a Decision Tree classifier?

**Ans:** `clf = DecisionTreeClassifier(criterion="entropy")`

### 7. How do you split your data into training and testing sets with a 75-25 split?

**Answer:** Use `train_test_split()` and set `test_size` to 0.25:

```
X_train, X_test, y_train, y_test = train_test_split(iris.data, iris.target, test_size=0.25, random_state=42)
```

### 8. How do you ensure that a Decision Tree classifier always splits on a minimum of 5 samples?

**Answer:** Set the `min_samples_split` parameter to 5:

```
clf = DecisionTreeClassifier(min_samples_split=5)
```

### 9. How do you extract the feature importances from a trained Decision Tree model?

**Answer:** Use the `feature_importances_` attribute:

```
importances = clf.feature_importances_
print(importances)
```

### 10. How do you ensure that a leaf node in a Decision Tree contains at least 2 samples?

**Answer:** Set the `min_samples_leaf` parameter to 2:

```
clf = DecisionTreeClassifier(min_samples_leaf=2)
```

## Medium Questions:

### 11. How would you perform 5-fold cross-validation on a Decision Tree model using scikit-learn?

**Answer:** We can perform 5-fold cross-validation using `cross_val_score`:

```
from sklearn.model_selection import cross_val_score

scores = cross_val_score(clf, iris.data, iris.target, cv=5)
print(scores)
```

### 12. How do you tune the hyperparameters of a Decision Tree using GridSearchCV?

**Ans:**

```
from sklearn.model_selection import GridSearchCV

param_grid = {'max_depth': [3, 5, 7], 'min_samples_split':
[2, 5, 10]}
grid_search = GridSearchCV(DecisionTreeClassifier(),
param_grid, cv=5)
grid_search.fit(X_train, y_train)
print(grid_search.best_params_)
```

### 13. How would you plot a confusion matrix for a Decision Tree classifier's predictions?

**Answer:** Use confusion\_matrix and heatmap from seaborn:

```
from sklearn.metrics import confusion_matrix
import seaborn as sns
import matplotlib.pyplot as plt

y_pred = clf.predict(X_test)
cm = confusion_matrix(y_test, y_pred)
sns.heatmap(cm, annot=True, fmt='d')
plt.show()
```

### 14. How do you handle unbalanced data when training a Decision Tree model?

**Answer:** We can use class weights to handle unbalanced data:

```
clf = DecisionTreeClassifier(class_weight='balanced')
```

### 15. How do you handle overfitting in Decision Trees?

**Answer:** You can prune the tree or limit its depth to prevent overfitting:

```
clf = DecisionTreeClassifier(max_depth=5,
min_samples_split=10)
```