

OSCP Notes: Identifying Target OS Type Using Nmap

✓ 1. Initial Nmap Scan (Fast)

bash

CopyEdit

```
nmap -T4 -p- --min-rate=1000 -v <IP>
```

- Scans all 65535 ports quickly
 - Helps find web ports, RDP/SSH, custom ports
-

✓ 2. Detailed Scan on Open Ports

bash

CopyEdit

```
nmap -sCV -p <open-ports> <IP> -oN scan.txt
```

- -sC → default scripts
 - -sV → version detection
 - -oN → saves to file
-

🔍 Identify the Machine Type:

📋 Windows Clues

Port/Service	Clue
135, 139, 445	SMB/NetBIOS = likely Windows
3389	RDP = definitely Windows
WinRM (5985/5986)	Windows remote mgmt
Hostname includes WIN-	Common Windows pattern

bash

CopyEdit

```
nmap -p 445 --script smb-os-discovery <IP>
```

🐧 Linux Clues

Port/Service	Clue
22	SSH with OpenSSH banner
111	RPCbind (NFS) common on Linux
631	CUPS web printing (Linux)
Apache, Samba Often used on Linux	
bash	
CopyEdit	
nmap -p 22 --script ssh-hostkey <IP>	

Web Server (Linux or Windows)

Port	Check
80, 443, 8080 etc	HTTP(S) → check manually
bash	
CopyEdit	
whatweb http://<IP>	
bash	
CopyEdit	
curl -I http://<IP>	
Look for:	
<ul style="list-style-type: none"> • Server: Apache → Linux • Server: Microsoft-IIS → Windows 	

Pro Tip:

Add this to your flow:

bash	
CopyEdit	
nmap -sV -sC -O <IP>	
<ul style="list-style-type: none"> • -O → OS detection (not always accurate, but helpful) 	