Solana project viva guide

Simple answers for explaining our idea, technology, experiments and demo. Start with this page, then practise the questions in each section. The project is a research prototype, not a deployed transaction-warning service.

Our idea in one sentence

We use machine learning to estimate transaction failure risk on Solana when wallet history is unavailable, using earlier outcomes involving other accounts in the transaction.

A short introduction you can say aloud

Our project studies blockchain transaction reliability. A transaction can fail even after reaching a block. Usually a wallet's past activity provides useful clues, but that history may be missing in our data. We test whether the other accounts involved can provide additional clues. We compare two machine-learning models on real historical records. Shared-account history improved failure ranking in reserved tests, although false alarms still need work.

A simple analogy

Imagine a new customer using a payment service. We know little about that customer, but we may know how the service performed earlier. That shared history gives us another clue. In our project, the customer represents the wallet and the service represents accounts the transaction touches. This is an analogy, not a claim that blockchain accounts are literally payment services.

Why does the problem matter

Applications may need to assess reliability even when a signer's earlier outcomes are unavailable. Better ranking could help decide which transactions deserve additional checking. We have not yet shown live fee savings or prevented failures.

What have we actually built

A data-processing and training pipeline, chronological experiments, saved predictions and a local replay dashboard. The dashboard shows real recorded transactions, compares estimates and reveals actual outcomes. No money is moved.

The sentence to remember

Even when wallet history is missing, the accounts involved can provide useful historical clues about failure risk.

Blockchain terms in plain language

What is a blockchain

A shared record maintained by a network of computers. It records transactions and their outcomes. Our project analyses those records; it does not build a new blockchain.

What is Solana

The blockchain whose transaction records we study. We chose a question that uses its declared account roles: which accounts sign, which may change, and which are read only.

What is a wallet and a signer

A wallet helps a user manage keys and authorize transactions. A signer is an account that signs to authorize an operation. Our experiment follows the first declared signer. An address is not proof of a unique person.

What is a transaction

A request to carry out one or more blockchain instructions, such as transferring tokens or interacting with an application. Our label records whether the included transaction succeeded or failed.

What are accounts in this project

On Solana, an account may hold funds, application data or executable program information. A transaction declares the accounts it needs. They are not all human users or wallets.

What do writable and read only mean

Writable means the transaction is allowed to change that account. Read only means it can read the account without changing it. Our added features summarize earlier outcomes involving non-signer writable accounts.

What is shared account history

Past transactions may have used an account that appears again in the current transaction. We summarize those earlier available outcomes. Sharing an account does not prove common ownership or identify the cause of failure.

Does missing history mean a brand new wallet

No. It means our sampled data has no available earlier outcomes for that signer. The address may have activity elsewhere. First appearance also means first appearance in our sampled replay, not on the entire blockchain.

Is a failed transaction always a bad or malicious transaction

No. A protective check may correctly reject an operation. We predict observed execution failure, not fraud, theft, user knowledge or financial loss.

Our contribution and novelty

What is the research question

Does historical participation of writable accounts improve failure ranking for transactions with unavailable signer history, beyond transaction structure, signer history and read-only account information?

What is our novelty claim

Our candidate contribution is a specific empirical benchmark and finding: we evaluate missing signer history explicitly and test the extra signal from writable-account history under delayed feedback and strong controls. We have supporting results on reserved data.

Did we invent a new machine learning algorithm

No. We use established algorithms. The contribution is the question, account-role representation, evaluation and measured finding. Using an existing algorithm can still support an empirical research contribution.

Has related work already been done

Yes. Solana failure characteristics, blockchain prediction and relational learning have all been studied. Our reviewed sources did not evaluate this exact cold-signer account-role benchmark. That does not prove nobody anywhere has studied an equivalent idea.

What is the baseline model

Our comparison model already receives transaction structure, signer history and read-only account and template history. It is not merely a wallet-history model. The candidate adds writable-account history while keeping the learning algorithm and data splits the same.

Why do we also test account identity

A model might just learn that particular account addresses are associated with failures. We learn an additional identity-based score and supply it to both models. Then we check whether explicit writable history still adds useful ranking signal.

How does this differ from contract auditing or DKT

It predicts execution outcomes from blockchain records. It does not inspect smart-contract source code for vulnerabilities and does not trace students' knowledge. Earlier education and auditing work is separate from this study.

Can we call it publishable

We have an implemented research candidate and evidence worth presenting or submitting for review. Acceptance and worldwide originality are not guaranteed. The manuscript still needs venue-specific preparation and stronger generalization evidence.

Technology and algorithms

Technology	What we use it for
Python	Data processing, feature construction and model training
pandas and NumPy	Working with transaction tables and numerical features
PyArrow and Parquet	Reading and storing the public transaction data
scikit-learn	Boosting, logistic regression, calibration and metrics
FastAPI and Uvicorn	Serving the local replay application
HTML CSS and JavaScript	The browser demo and result-reveal interaction
pytest	Tests for history timing, calibration boundaries and replay behaviour

Which main algorithm do we use

Histogram Gradient Boosting for classification, through scikit-learn's HistGradientBoostingClassifier. It combines small decision trees to estimate the chance of the failure class.

How does gradient boosting work

It builds trees in sequence. Later trees help correct errors remaining from earlier trees. The combined model learns patterns between our input features and transaction outcomes.

What does histogram mean here

Numerical feature values are grouped into bins when searching for tree splits. This makes training more efficient. It does not mean our project is a charting application.

What other algorithms do we use

SGD logistic regression learns a comparison score from account identities. Isotonic regression adjusts score-to-probability mapping in a separate calibration follow-up. Calibration does not create new transaction evidence.

Why use trees instead of deep learning

Our inputs are structured numerical history features, so boosted trees are a practical baseline. We have not established that they beat every neural network. The research question is whether additional account history helps, not whether a complex architecture looks impressive.

Important settings if asked

The original boosting model uses 150 iterations, at most 15 leaves, a minimum leaf size of 40 and L2 regularization of 5, with early stopping disabled. Settings remain fixed across the reported windows.

Data training and fair testing

Where does the data come from

SolArchive, a public archive of real Solana transactions, released under CC BY 4.0. We pin the source version and record extraction hashes. We analyse selected row groups, not the whole chain or a verified random sample.

What are our inputs and output

Inputs include account counts, signer and writable roles, and summaries of earlier failure rates and participation counts. The output is a failure-risk estimate. The observed label is success = 0 or failure = 1.

What does the pipeline do

Read selected records; verify statuses and duplicates; put them in time order; build features from available earlier outcomes; train the models; choose thresholds on validation data; evaluate on a later test date; save results for replay.

How do we split the data

Each window has a training day, then a validation day, then a test day. Training learns model parameters. Validation sets thresholds or calibrates scores. Testing measures performance after those choices are fixed. The first six training hours build history.

How do we prevent the model from seeing the answer

We build the current features before adding the current label. Earlier outcomes become available only after an assumed one-hour delay. Current errors, execution logs, actual compute used, balances and paid fees are excluded from prediction inputs.

Does the model use information from the test period

Its histories can use earlier test outcomes after they mature. The fitted boosting model is not retrained on the test day. This is a stated online-feedback replay, not an evaluation with completely frozen histories.

What is a cold-history transaction

Its first signer has no earlier outcome available in the sampled replay. It may have another transaction still waiting for its label. First appearance is stricter: the signer has not previously appeared as first signer in that replay.

How much data did we use

The paper’s original four windows contain 1,588,408 raw sampled rows across twelve dates, before deduplication and exclusions. A later fifth window is reported separately. Do not say all 1.59 million rows were training data or independent wallets.

Results and numbers you should understand

Evaluation	Baseline AP	Our AP	Test group
Paper reserved test	0.1688	0.2004	17,904 first appearances
Later unused-date test	0.2207	0.2393	19,515 first appearances

Both rows compare models that receive an account-identity score. The later result is follow-up evidence, not a number already incorporated into the original paper PDF.

What result should I say in the viva

On the paper's reserved first-appearance test, writable-account history improved average precision from 0.1688 to 0.2004 after the identity control. A later unused-date test also showed a positive gain. This supports better failure ranking, not reliable live prevention.

What is average precision or AP

It summarizes how well failures appear near the top of a model's risk ranking across thresholds. Higher is better on the same test group. AP of 0.2004 does not mean 20.04% classification accuracy.

What is the difference between risk and accuracy

Risk is the model's estimate for one transaction, such as 30.8% failure risk. Accuracy is the fraction of correct class decisions across a set of transactions at a chosen threshold. A higher displayed risk is not a better model score.

What are precision recall and false alarms

Precision asks how many flagged transactions actually failed. Recall asks how many actual failures were flagged. The false-positive rate asks how many successful transactions were wrongly flagged. Threshold changes trade off these quantities.

Why is accuracy alone not enough

Most transactions in our first-appearance groups succeed. Always predicting success could therefore produce high accuracy while catching no failures. We report ranking and warning metrics rather than claiming one accuracy number proves usefulness.

What is our strongest limitation in the paper result

At the inherited threshold, the context model had a 28.65% false-positive rate on the reserved first-appearance group. Better ranking did not make that warning threshold reliable. Calibration results also vary by period.

What do the uncertainty intervals mean

The paper's AP gain is +0.0316 with an hourly bootstrap 95% interval of +0.0168 to +0.0501. The later gain is +0.0186 with interval +0.0095 to +0.0288. These describe uncertainty for sampled fixed predictions; they are not a guarantee for every future day.

How to explain the demo

What should I say before clicking

This is a replay of real historical transactions. Both models produce estimates using earlier available records. I will reveal the actual recorded outcome after comparing them. No live payment is made.

What does no available wallet history mean

Our sample has no matured earlier outcome for this signer. We may still have outcomes involving other accounts the transaction touches. Those accounts provide the extra context we study.

What does 100 percent shared-account history mean

All of the relevant writable accounts have earlier available outcomes in the sample. It measures coverage, not safety, prediction accuracy or confidence that the transaction will succeed.

Why do 41 point 5 percent and 30 point 8 percent differ

The two models estimate the same event: execution failure. They use different input histories. In that example the baseline estimates 41.5% risk and the context model estimates 30.8%. Lower means less estimated risk, not lower accuracy.

Why is one flagged and the other not flagged

Each model has its own warning threshold chosen on validation data. Its risk estimate is compared with that threshold. The threshold is not automatically 50%, and it is not selected using the example's outcome.

Which prediction is correct

Reveal the recorded outcome first. If the transaction fails and our model did not flag it, that is a missed failure. If it succeeds and the baseline flagged it, that is a false alarm. A single outcome cannot validate either exact probability.

What should I demonstrate

Show one correctly flagged failure, one unflagged success, a false alarm and a missed failure. The first four named examples were selected to illustrate these cases. Other examples follow time order. Use the full test results when discussing performance.

Is this live model inference on a new wallet

No. The dashboard displays saved predictions from our historical pipeline. It does not query arbitrary wallet addresses, train a model when I click, or send transactions. The on-screen calibration follow-up differs from the paper's separate identity-controlled comparison.

A simple closing line

The demo shows how extra history changes a prediction and lets us inspect both correct decisions and mistakes. Our experiments, rather than selected examples, provide the research evidence.

Practical value limitations and final viva answers

Is it useful in the real world

The problem is real, and account context is a plausible input for transaction reliability screening. We demonstrated a historical ranking benefit. Real-world usefulness still needs live-arrival data, calibration and comparison with existing simulation tools.

Why not just simulate every transaction

Simulation is an important existing approach. We have not shown our model is better than it. A useful future experiment would test whether history adds information beyond simulation, particularly when conditions change between simulation and execution.

What are the main limitations

One archive provider, sparse samples, limited dates, missing actual submission times and missing attempts that never land in a block. Thresholds drift, calibration is mixed, and account identities do not identify independent people.

What did the calibration follow-up achieve

It adjusted probabilities using early validation rows and chose thresholds on later validation rows. On the later unused-date context-model test, recall rose from 6.61% to 29.87% and false alarms rose from 0.32% to 3.18%. Other periods were less successful, including a period with no alerts. This is a tradeoff, not a universal fix.

What would we improve next

Test denser samples and more periods, independently test stronger identity models, match feedback update schedules, improve warning calibration and collect actual submission and simulation observations. Keep future test data separate from model selection.

Are we using a smart contract or a large language model

The replay demo does not deploy a smart contract or require a language model. It uses ordinary ML on blockchain records. The broader repository contains earlier experiments, but those are not the current research contribution.

What should we never claim

Do not claim the first blockchain failure predictor, a newly invented boosting algorithm, guaranteed transaction success, a fraud detector, proven fee savings, or publication acceptance. Do not report failure-risk percentages as accuracy.

If an examiner asks for a detail I do not know

State what the experiment establishes, then offer to check the exact protocol or report. Do not guess a metric, explain a correlation as a cause, or invent a personal contribution.

Where can I verify the answers

The paper draft and results report are in docs/paper and docs/SOLANA_TRANSACTION_RISK_RESULTS.md. Later findings and the demo walkthrough are in webapp/README.md. Exact parameters and outputs are in research/solana/ml and docs/results/solana_transaction_*.json. Public source: huggingface.co/datasets/solarchive/solarchive.