Status	Finished
Started	Wednesday, 21 October 2026, 10:46 PM
Completed	Wednesday, 21 October 2026, 10:50 PM
Duration	3 mins 49 secs
Grade	**15.00** out of 15.00 (**100**%)

Question **1**

Correct

Mark 1.00 out of 1.00

To open a file a.txt for reading, we use _____

a. infile = open("a.txt", "r") ✓

b. infile = open(file, "a.txt", "r")

c. infile = open(file = "a.txt", "r")

d. infile = open(file = "a.txt", "r")

The correct answer is:
infile = open("a.txt", "r")

Question **2**

Correct

Mark 1.00 out of 1.00

If the file is opened in write mode and already exists, it truncates the existing content and places the filehandle at the beginning of the file.

Select one:

True ✓

False

The correct answer is 'True'.

Question **3**

Correct

Mark 1.00 out of 1.00

Which of the following methods is used to read a single line from a file?

a. readline() ✓

b. readlines()

c. readline(size)

d. read()

The correct answer is: readline()

Question **4**

Correct

Mark 1.00 out of 1.00

Default EOL character of text file in python is ,

a. ,

b. space

c. \t

d. \n ✓

The correct answer is:
\n

Question **5**

Correct

Mark 1.00 out of 1.00

What is the output of the following code?

```
f = open("test.txt", "w")
f.write("Hello, world!")
f.close()
f = open("test.txt", "r")
print(f.read())
f.close()
```

a. world

b. Hello

c. Hello, world! ✓

d. An error is raised

The correct answer is: Hello, world!

Question **6**

Correct

Mark 1.00 out of 1.00

f.seek(5,1) means

- a. move the file pointer five characters ahead from the current position ✓
- b. moves the file pointer to the end of a file
- c. move the file pointer to beginning of the file
- d. move the file pointer five characters behind from the current position

The correct answer is:
move the file pointer five characters ahead from the current position

Question **7**

Correct

Mark 1.00 out of 1.00

The readlines() method returns _____

- a. a list of integers
- b. a list of single characters
- c. str
- d. a list of lines ✓

The correct answer is:
a list of lines

Question **8**

Correct

Mark 1.00 out of 1.00

Select the correct output of the following code

```
fp.seek(5, 1)
```

a. Move file pointer five characters ahead from the beginning

b.
- Move file pointer five characters behind ahead from the end of a file.

c.
- Move file pointer five characters behind from the current position.

d.
- Move file pointer five characters ahead from the current position. ✓

The correct answer is:

- Move file pointer five characters ahead from the current position.

Question **9**

Correct

Mark 1.00 out of 1.00

What does the seek() method do in file handling?

a. Writes data to the file

b. Deletes the file

c. Moves the file cursor to the specified position ✓

d. Reads the file line by line

The correct answer is: Moves the file cursor to the specified position

Question **10**

Correct

Mark 1.00 out of 1.00

What happens if you try to open a file in read mode ('r') that does not exist?

- a. An error is raised ✓
- b. An empty file object is returned
- c. The operation is ignored
- d. A new file is created

The correct answer is: An error is raised

Question **11**

Correct

Mark 1.00 out of 1.00

What will the read() method return if used on an empty file?

- a. An empty string ✓
- b. None
- c. 0
- d. EOFError

The correct answer is: An empty string

Question **12**

Correct

Mark 1.00 out of 1.00

Select the incorrect file access mode

- a. ab+
- b. wb+
- c. rw+ ✓
- d. r

The correct answer is: rw+

Question **13**

Correct

Mark 1.00 out of 1.00

Which method is used to write a list of strings to a file?

a. write()
b. write_all()
c. writelines() ✓
d. write_list()

The correct answer is: writelines()

Question **14**

Correct

Mark 1.00 out of 1.00

file_object.seek(offset [, reference_point])

What is the default, the value of reference_point?

a. null
b. 1
c. garbage
d. 2
e. 0 ✓

The correct answer is:
0

Question **15**

Correct

Mark 1.00 out of 1.00

Which method is used to read a specific number of characters from a file?

a. readline()
b. read(size) ✓
c. readchar()
d. readlines()

The correct answer is: read(size)