Day 42 HTTP Adapter 28/Aug/2026

* Today we are discussing about Reciever Adapter
  ⇒ Till now Covered Address, Authorization, User Role, CSRF Protected } → for HTTP Adapter

* CSRF protected (Talking) —
  So the CSRF protected. Mainly used for Reciever Side and Some time's Sender Side aswell

* Example used: Gmail login Example
  ⇒ Mainly about Session ID → Gmail Session ID
  ⇒ If anyone accessed the Same SessionID Some how, then they hacked your Gmail login etc and directly they can use your Gmail account in another browser
  ∴ The above process is happened due to CSRF protected is not enabled.
  ∴ So the main important thing here is due to over come the above issue we need to use 'CSRF' and for any browser

now a days it is by default Enabled ✓

* Where We Can use the CSRF is When we are trying to Connect any third party Secured System then we can use the "CSRF" token Check Box ☑ in under HTTPS connection Tab ✓

⇒ CSRF → Cross site Request Forgery (CSRF attack)

Steps: To process the CSRF pais we need to follow the below steps

① Get call the API (we need to give the All required Authentication detail's)

② x-csrf-token : fetch → In Response header's we will get token ✓ (Remember)
header Value

③ With this token we need to make the Post call (or) Actual Call ✓

* HttpAdapter Flow → Example demonstration

iflow name → HttpAdapterFlow

⇒ We cannot Complete the request in Single Call ✓

* We need to make the two call's

1st call → Get → URL

x-csrf-token : fetch

2nd call → post → URL

x-csrf-token : This token

Go to headers after fetch and you can see the token over there

⇒ Finally it will work now

* here, if it fail's them we will notice 403 Error ✓

* Client certificate based Authentication

⇒ We need to upload client certificate file in

SAP cpi portal ✓

Explained about External certificate also.

Remember how to add it and where to add it ✓

⇒ So when we selected the, external certificate then the Role Should be USER Role ✓ only

(Remember)

* ESBMessaging.Send → Will be the default Role

* client certificate is better to use in Service itself Rather than uploading in the cpi Flow

* Now, Reciever HTTP Adapter
  * Used "North Wind API" for demonstration
  * Now again be used Standard API of SAP called Message processing logs API from Reciever Side

=> Under Connection Tab:

Address, Query,

$top=1
key value

? Query param's

? top=1

* * Proxy: Internet (or) Onpromise / Method (Rest API calls) CRUD

operations

Send Body ☑, Authentication, Credential name

PrivateKeyAlias, Timeout (in ms), Streaming ✓
Maximum - 60sec
↓
Don't consume more memory ✓
It sends data in chunks ✓

* Retry:

→ Throw exception on failure & Retry the flow ✓

CPI don't have Retry Mechanism but HTTP Adapter to it if failure occurs for 3 time's

→ Attach error details on failure: ☐ To attach the error details, It will attach the details

→ HTTP Error ResponseCode: ☐

→ Retry on Exception: ☐ → Retry on Error Response
→ Retry on Interval
→ Retry Iterations.

Adapters

*

	Sender	Reciever
HTTP	Yes	Yes
SFTP		
SOAP		
OData		
Mail		
IDOC ✓		
RFC (X1)		
JDBC JMS AMQP		

② SFTP Adapter

→ files.com

Step①: Free trail account creation

Step②: In SAP we need to goto monitor tab and go to the connectivity test tile.

Step③: we need to select SSH Tab

Step④: We need to take the host name from Step① and the click send

Copy the host key fingerprint from here

Step⑤: we need to add the (known_hosts) file in (Manage Security Material)

Question: key based Authentication

We will skaare it with SFTP team

Step⑥: Go to key store Manage key store we can create SSH key or key pair

download public open SSH public key

* manage Security material : Basic Auth details
mailID and password ✓
Gmail mailed id and password

* SFTP Adapter: Target Tab.

① Directory: /output
② File Name: File.xml
③ Append Timestamp: ☑
④ Host : Sftp: URI /22 default port (22)
⑤ proxy type: Internet
⑥ Authentication: username or password.
⑦ credential name: Sftp (which we created in Security materials)
⑧ Time out: 10,000
⑨ Maximum Reconnection Attempts: 3.
⑩ Reconnect delay: 1000
⑪ Automatically Disconnect
⑫ Enable Support for Deprecated Algorithms.

* Processing Tab:
——→——
① change Directory step wise: ☐
② create Directories: ☑
③ Pattern File Names: ☐
④ Prevent Directory Traversal: ☐

use fast Exists Check:

~~***~~ ~~Use~~ Handling for Existing Files: Override
Append
Fail
Ignore.
You