Day 45 – Installation & Configuration of Cloud Connector

Class date: 2nd September 2026 | Module: Connectivity (SAP BTP Cloud Connector)

Small correction to your handwritten notes: you described the Rebex Tiny SFTP Server as **"open source software."** It is more accurate to call it **freeware** (free to download and use, including commercially) – the executable itself is free, but it is built on Rebex's own **commercial** File Server library, so it isn't "open source" in the strict sense (its full source code isn't freely licensed for redistribution/modification). This doesn't change how you use it for testing, just the correct terminology if it comes up in conversation.

1. What are we trying to achieve today? (start here first)

Today's goal: actually **install and configure a Cloud Connector** end-to-end, and use it to let CPI place a file into a local/on-premise system's folder via SFTP.

Core scenario: we want to place a file from **SAP CPI (which runs on the cloud)** into **our own system**. CPI cannot simply reach into our local machine directly – some setup steps have to be followed via the Cloud Connector, otherwise the file transfer will not process at all.

Target flow: **SAP CPI** → **Cloud Connector** → **our system**. The task to perform: take data/files from a temporary local SFTP server (Rebex Tiny SFTP Server) and have CPI place a file into it, through the Cloud Connector.

2. Why can't CPI place the file directly?

The target "data" folder is present in **our own local system**. As already established (Day 44), **SAP Cloud Platform Integration (CPI) does not connect directly to our local system** – there is no direct network path, and even if there were, it would be blocked by the firewall protecting our network.

So the flow becomes: **CPI** → **(SFTP/FTP)** → **our system's file system (the "data" folder)**. For CPI to reach *any* folder on our system, that folder first needs to be **exposed** to an SFTP server or FTP server – CPI only ever talks to that SFTP/FTP server, never to the raw file system directly.

3. Exposing the folder – Rebex Tiny SFTP Server

The simplest way to expose a folder as an SFTP endpoint for practice is the **Rebex Tiny SFTP Server**, a small **freeware** tool (see correction above) downloaded as a **.zip folder**.

- It runs **locally** and creates a **temporary** SFTP connection/endpoint on your machine.
- It exposes an SFTP server for one **particular folder only** (single-user, single-folder tool – it is not meant for production use).
- Connection details generated/needed: **Host, Port, Username, and Password**, plus the machine's **IP address**.

SSH stands for **Secure Shell** – the underlying secure protocol that SFTP itself runs over (SFTP = SSH File Transfer Protocol).

Connectivity Test (recap): in CPI's **Monitor** tab, under **Connectivity Test**, selecting **SSH** and providing all the required details (host, port, username, password) tests whether CPI can reach the target SFTP server. **Result at this stage: it does NOT connect directly** – this confirms the need to install the Cloud Connector before CPI can reach a local/on-premise SFTP server.

4. Requirements to set up the Cloud Connector

In a real project, the **Configuration, Installation, and Management** of the Cloud Connector is typically done by the customer's own **Admin/Basis team**, not by the integration developer. As an integration consultant, you are expected to understand the **high-level process** of how Cloud Connector is set up, even if you personally may not be the one installing it in a live client environment.

5. Cloud Connector setup – step by step

1. **Step 0:** Install the Cloud Connector application itself on the on-premise machine/server (following the installer as demonstrated).
2. **Step 1: Add Subaccount** – register the specific SAP BTP subaccount that this Cloud Connector instance should be linked to (recall: Cloud Connector only supports SAP subaccounts, as covered on Day 44).
3. **Step 2: Configuration – add a System Mapping**, with the following fields:

Step 2 – System Mapping fields

Field	What it means
Back-end Type	Type of system being exposed – e.g. SAP System, Non-SAP System, or Other.
Protocol	The communication protocol used, e.g. TCP, RFC (for ABAP function modules/BAPIs), HTTP/HTTPS (for APIs), or messaging protocols like SFTP or JMS (queue/memory-based messaging).
Internal Host & Port	The real host name and port of the actual backend system inside the on-premise network.
Virtual Host & Port	A renamed/aliased host and port that CPI will actually use to refer to this backend – this hides the real internal host name from the outside, and is what you enter as the "Address" (or similar) on the CPI side.

You then enter this **Virtual Host** (not the real internal host) in CPI's adapter configuration – this is the value CPI will use whenever it needs to reach this backend system through the Cloud Connector.

3. **Step 3:** Complete the corresponding configuration on the **CPI side** (in the CPI web application/Integration Suite) – setting the adapter's Proxy Type to On-Premise and pointing it at the Virtual Host configured in Step 2.
4. **Step 4:** Re-run the **Connectivity Test** (Monitor → Connectivity Test → SSH) to confirm CPI can now reach the SFTP server successfully through the Cloud Connector.

(Your notes mention following the trainer's live demo video step by step to complete the actual installation on your own machine – keep that recording handy for hands-on reference while repeating this setup.)

Quick-recall summary

- CPI cannot reach a local/on-premise folder directly – the folder must first be exposed via an **SFTP/FTP server**.

- **Rebex Tiny SFTP Server** = free, temporary, single-folder SFTP server used for local practice/testing (not "open source," strictly speaking – it's freeware built on a commercial library).
- Without Cloud Connector, CPI's Connectivity Test to a local SFTP server will **fail to connect**.
- Setup order: **Add Subaccount** → **System Mapping (Back-end Type, Protocol, Internal Host/Port, Virtual Host/Port)** → **configure CPI side** → **re-test connectivity.**
- CPI always talks to the **Virtual Host**, never the real Internal Host – this keeps the actual backend address hidden from the cloud side.
- In real projects, Cloud Connector install/config/management is usually owned by the customer's **Admin/Basis team**.