Day 20

Converters

name Space : It is notting But a unique identifier Space to that particular field.

Scenario: if you are getting multiple records from the Source

Lets say: Input payload has Book's information CD's information or other information

So in each and every data there is a field called 'id' which is a common field

eg: <root>

<book>

<id> 123 </id>

<name> CPI Book </name>

</book>

<cd>

<id> 456 </id>

<name> movie Songs </name>

</cd>

</root>

* Here When we observe the above payload they

We are getting <id> → field two times

→ Here the point is how you can differentiate

which id & name belongs to which ?

We cannot say directly ?

Eg: if you are reading in Content modifier

//id (xpath) → which id

will read it ? → Content modifier ✓

We Cannot define ✓

So,

for that reason When we are working on multiple payloads to bring a unique identity for the particular field we use name

Space

```
<root>
    <nso:books xmlns:nso="https://books.com">
        <nso:id>123</nso:id>
        <nso:name>CPI Book</nso:name>
    </nso:books>

    <ns1:cd xmlns:ns1="https://cds.com">
        <ns1:id>123</ns1:id>
        <ns1:name>MoviesSongs</ns1:name>
    </ns1:cd>
</root>
```

⇒ nameSpace brings a uniqness for that particular field ✓

Basically, to avoid ambiguity b/w two particular fields

② JSon to xml Converter

① Use name Space mapping: ☐

② Json prefix Separator : Colon(:)

③ Add xml Root Element: ☑

Name: root

* NOW We also works with the Plain file's which is nothing But the csv file (Comma Seperated values) or → text files aswell (Remember)

* NOW the Scenario will be → if Suppose you want to work files and Realtime work will be → csv ⟷ xml

→ Suppose if we are working in SFTP Server then they will ask to send the File (.txt) file not an xml or json file

→ We can get any requirement

* Converting an xml to ~~json~~ csv you need xml to csv Converter

→ XML to CSV Converter : Basic Elements

① Path to Source Element in xml: Which xpath i need to work

② ~~Fie~~ Field Seaperator in csv: Comma(,)

csv header: XML Based ✓

XSD annotation based

Parent Element:

Include Parent Element: ☐

Include Attribute values: ☐

Note If I am Sending Employee details, there can be chance of Sending some other elements like root element which is outside the xml file ∞

ex: <employees>

<status> Active Employees </status>

<employee>

—

—

—

—

</employee>

</employees>

here in the above example if do you want to get status tag value also what you will you do

Include parent Element: ☐

* If you want to get the parent element node field value and also ~~the~~ you want to Convert the xml to csv format Based on the requirement then you will ~~you~~ use xml to csv Converter

* csv to xml

① xml Schema :* _____ Select

② path to Target Element in xsd :* _____

③ Record a mater in csv : _____

④ Field Separator in csv ! Comma(,)

⑤ Enclude First line header : ☑

Step① : Import the xsd Schema

Because when ever the payload do you want to send it to another System in ~~Json~~ xml format

XSD → The fields how many times it will come are etc will tell by XSD Schema

* [With out an XSD you cannot have xml file]

for that i need xml Schema

→ The difference is → xml payload (Standard Format)

↳ our xml to CSV Pallete function will directly identify as it it field and considered it as a new field ✓

But, CSV → xml → I need the xml format

→ Because in which format i need to send the data

→ NOW we need XSD file What we can do it is

Google → xml to XSD Converter (Search) →

→ The point is xml → csv (no need anything)

But ~~xml~~ CSV → xml. (xml Schema is Prerequisite)

Text

Step 6: Import that XSD file

in Realtime → Source people → needs to provide XSD file with you

→ no one will provide the xml data with you → they will provide only XSD File with you

→ If it is a SOAP Service they will share the WSDL file with you

Path to Target Element in XSD → which xpath you want to generate xml

* xml ↔ csv → It only works with simple structures → you have one node → in that node → you have all the fields

<contact> <test> - - - </contact> </test>