Day 28

Data Store

* Write operation: Data Store name: EmpDetails
  Visibility : Global
  EntryID : {property.EmpID}

→ EntryID: What ever the entry ID we are giving Based on that ID the data will be Stored in the Data Store.

Q What is the difference between write and Write variable?.

Write variable: used to store single string value or a single Content, small text Content (Single word)

Write : If you want to store the payload then we will use write Pallet

* if you are writing a data → then there will be a way to fetch that data right? What is that → we have a option called [Get]

[Persistance → Datastore operations → Get]

if you want to fetch any particular entry from a data store then you will use get

Get : processing:

Data store name: EmpDetails

Visibility: Integration Flow, Global

Entry ID: — (Single Record)
↳ particular record

Delete on Completion: ☐

Throw Exception on missing Entry: ☐

↳ If you want to fetch any particular data from data store then we will use Get operation

Payload:

```
<employees>
  <employee>
    <empID> 1 </empID>
  </employee>
</employees>
```

once you pick the data and you want to delete it from that entry or not.

→ If the message is successful → then only that message get deleted from the data

Store

Select: If you want to fetch all the entries (multiple) from Data store then we will use Select

Processing: Data store name: EmpDetails

Visibility: Integration flow

Number of polled messages:

Delete on Completion: ☑

→ for single call how many messages should be picked up

→ we have to provide some number

Requirement: if we placed all the records in Data Store → we need to pick → and → send to Target

* The Condition is → Target will Accept only → 10 records at a time

↓

Then we can use [Select] → Data Store and Set → Number of polled Messages: 10

→ at time ~~use~~ This will fetch 10 records

[Delete:] If you want to delete any EntryID with out using Get (or) Select polled functions then we can use [Delete operation]

Processing:

Data Store Name: EmpDetails

Visibility: Global (or) Integration flow

Entry ID: ---

eg: if the interface is failed (or) Success. the you want to delete the data from Data Store then we can use Delete Operation ~

* In Both Get, Select → if we Select Delete on Completion ☑ then those data will be deleted only when that iFlow processed Successfully and we can see the Completed Status in monitor tab → then only the data Store → data will be deleted

↓

Otherwise → that data won't get deleted

* Now, if you want to delete any data from data Store → without using above option then we can use **Delete operation**

→ Delete → will Delete → 1 entry only at a time

=> If we are not providing the Entry ID they What will happen

→ It won't delete any data

Persist: In cpi if you want to store or save the data then we can use persist

→ If you want to Save the payload ~~then~~ at a particular step then I will use **persist**

Peerist message

processing:

StepID: *

Encrypt stored message: ☐

* if you want to save the data in Backend Database then we will use peerist pallete function

* you cannot see the data i,e is stored by using peerist pallet function in CPI → Because it will be stored in Backend database

→ how to see that persisted payload –

api-service-key → tenant url /api/v1/MPL{ ↓ } /

Message store Entries ← Message ID

* <link href = "MessageStoreEntries

----)/$value"

We Send the get request

So that we will get the payload

It's is Some what difficult process

Manual Call's are more → So we don't use more in realtime.

Because the real time Case's are less to use the persist pallet function.

* So we are going to Discussed about the encoder and Decoder

encoder:

Base64 encoder →

Gzip Compression → .Gzip

MIME Multipart Compression →

Zip Compression → .zip

* Base64 Encoder : if you want to send any data to the target System and they requested you to send the data in Base64 encoded format then we will use Base64 encoder

↓
un readable format

eg: Basic Auth: Client ID, Client Secret → How these details will be going to the target System &

→ Headers → Authorization → Base64 encoding of client ID: Client Secret

↓
Unreadable format

eg: Basic ------

* Base64 Decoder

* MIMEMultipart Decoder

Send → data → form Data format

Requirement: If you want to send the data in form → then we will use MIMEmultipart

Processing:

① Multipart Subtype: mixed ⟶ (Default)
Alternative
Digest
Parallel.
Related

② Add multipart Header's Inline: ✓

③ Fold long Headers: ✓

Why do we MIME Data format

Like ⇒ if we receive multiple messages.
if we want to show that multiple messages
Seaperately in same Form then this
pallet will helpful
multipart → multiple mesages

--- part1 - - - —
part2 - - - —
} → Boundary

multiple payloads → send → 1 message → multipart-

Form data → encode → data → multiple payloads

→ single payload.