Day 35

Mapping Boolean

AND / OR

Input 1	Input 2	AND	OR
True	True	True	True
True	False	False	True
False	True	False	True
False	False	False	False

Here, we need to check for positive case

AND → if the Both Conditions are True then only the output is → true else false

OR → if any Condition is true you will get true (output)

* We are working with Boolean functions, So inputs Should be "Boolean" (true or false)

* Not: here, if the input is true then output is false (True (Input) → False (output); False (Input) → True (output))

* equal's boolean: It will check if the boolean value's is equal or not

* Remember this function doesn't work for the string or numbers

* not equal's: If Both the boolean inputs are not equal → output → true.

* if: if you want to check condition Base

eg: if name = Pavan, then only map product

Quantity > 10, then only map

This 'if' function has 3 inputs

① true value
② Condition
③ false value

Here, it will check first ① & ③ operations if satisfied then it will go for ②

if without Else: here we don't have false

Condition

Condition
true value
☐ keep suppress
↓
Value is not there

UDF → User Defined functions

* What is the difference between if & ifs

→ At a runtime you will not see a any difference (Both are same)

Then What is the use of if & ifs

if → Condition will check "after" evaluating
↓
true and false.

ifs → Condition will check "before" evaluating

true and false

actually it doesn't check

ISNil: it will check the field has {xsi:nil} attribute, if present true else false

eg: <ProductName>phone</ProductName>

↓

<ProductName xsi:nill="true"></ProductName>

output = true (isNill)

Next, Standard function → Constant

① Constant

② Copy value

③ xsi: ~~not~~ nil

Constant: if you want to give any static (or) hardCoded value then you will use Constant

⇒ xsi:nill → If you want to generate that field value as a nil

The main function: Copyvalue

As per the name Suggest, if you want to copy a value, you will use Copyvalue

→ But why do you want to copy that value ?

Demo: NOW for Single xml node its working above all Scenarios But when you Place Second node details in xml input like 2 product details

→ then we are getting error → why

Because → Cannot produce Target element

"Date function" Standard

Current date
dateTrans. (in4out) UTC
Compare date Before (true or false)
date After (true or false)
Compare dates (-1, 0, 1) → output

When you are sending data to the Target then the requirement is you need to send the date for particular field in which format

capital capital capital capital

dd-MM-YYYY HH:mm:ss.SSS

Remember date now by default it will give UTC

Time zone

Co ordinated Universal Time

In mapping → Time zone default will be UTC

no other time zones will come

Example : Scenario, if Quantity is more than

10, then you need to give a discount

if Cost >=100 and Quantity > 10

then i want to give the discount of

100rs

<Cost> 100 </Cost>

<Quantity> 5 </Quantity>

demo

If Cost = 100 and Quantity >=10 then i need
equal

give discount of 100 else no discount

Here usage of mapping functions are

1. Constant - Constant(output)
2. equals - (true or false)(output)
3. greater - (true or false)(output)
4. and - (true or false)(output)
5. multiply - (multiplied -> value)
6. if - (true, condition, false)
7. Subtract - (Subtracted-value)