Day 38 Context Handling

→ Context = Which field → How it should come
is the defining is the context

eg. node → How it should come → will →
defined by Context in message

mapping

Company example:

CEO → only ①

Directors → multiple

Director ① → multiple managers
M1 — E —

Director ② → multiple manages
M2 — —
E

Here, the question is how you can tell for each manage has how many Employees.

eg: CEO

Director ①

Manager 1

Employee 1 EmpID 1

Employee 2 EmpID 2

Manager 2

Employe 3 EmpID 3

Employee 4 EmpID 4

Manager 3

Employee 5 EmpID 5

Employee 6 EmpID 6

Employee 7 EmpID 7

Director ②

Manager ④

Employee 8 EmpID 8

Employee 9 EmpID 9

Manager ⑤

Employee 10 EmpID 10

Director ③

Manager ⑥

Employee 11 EmpID 11

Emp ID to Employee.	Employee to manager
	1 manager with 2 Employees
1 Emp with 1 Emp ID	2nd manager with 2 Employ
	3rd manager with 3 Employees

Employee to Director | CEO with 11 Employees

↓

1 Director with 7 Employees

Now, the Question is how will the System know the how each one is repeated like Employes to manager, Director, CEO

How many people or there

***

→ When you are sending the data, to the target how will you send that for CEO → how many Directors are there, and for Directors How many managers and for manager How many Employees are there How will you tell → So this is the Context

When we are talking about Context, it has two things → ① Context → Employee ② value → EmpID

Empid to Employee

Context : Employee
Value : Empid

Employee to manager

Context : manager
Value : Employee

Employee to Director

Context : Director
Value : Employee

Employee to CEO

Context : CEO
Value : Employee

1 Employee and 1 Empid

Relation Ship

1 manager with 2 Employees
1 manage with 2 Employes
1 manger with 3 Employes

1 Director with 7 Employees

1 CEO with 11 Employes

1 Employee with 1 EmpID

1 manager with 2 EmpIDs
1 manage with 2 EmpIDs
1 manger with 3 EmpIDs

* In message mapping

⇒ gray Spaces are called as

Context

⇒ White Spaces are called as

Values

* How you will identity Context handling

Displayname →