Day 55 APIM Part (4)

* Spike arrest & Cache Refresh after Completing all the policies → the demo will be showed

* Response Cache Requirement :

Populate cache → write the data to cache
lookup Cache → to get the data from cache

* ~~BW~~ NOW → Response cache & populate cache.

→ populate Cache → Stores → only → 1 variable

eg → token.

→ Response cache → Complete payload it stores it's important

Requirement :

Soure → Target
Target ← Soure

Like customer ID (or) order ID

Target System

orderID	orderNamedes
1	order1 1
2	order2 2
3	order3 3

Status
in progress
delivered

Realtime Scenario → In target System if the data is updating in 1st of every month and if the Source is calling the same request to the Target System betor next month 1st date then what will happen Same data will be retrieved untill the next mont 1st date

So the Solution is → every mont 1st the Source System will call the target end point → get the complete required Payload → stores in "Response Cache"

→ So from next call on wards we will get the data from Cache (Response Cache) not from Target System

∴ The above is the use of Response Cache policy in APIM

* Response Cache → Limitation → Target System

→ 1 mont updates, weeks Update
data → not update → frequently

* Data → frequent update then → Response
Cache → doesnot useful (X)

→ populate cache → token storing
→ lookup cache → to read stored token (Variable)
→ Response Cache → Store a payload
(To Reduce the no of Request's to the Target

→ Data → updation → 1 month, 1 week → Batch
Updation only useful

→ Invalidate cache : clear the cache memory
due to some or other reason

⇒ lookup cache → token → yes → X
NO →
(Condition string)

→ lookup cache
→ populate cache
→ Response cache
→ invalidate cache

* we are closing the Traffic management Policies

⇒ Now Security policies :

* Security policies → all the securities → Authentication, Restrictions → we will do.

① Basic Auth : Two operations - encode
- decode

headers → Basic Auth → [decode] → username & password. (from Source)

headers → Basic Auth → [encode] → username → password. (To Target)

If we want to extract the user credentials from Authorization header then we will use

decode → operation to get the username and password

→ Soure System username, password → Basic Auth → decode → Important

Why are we decoding?

→ Target → Authorization header → Basic Auth

→ encode → username, password (Base64)

example: postman

→ Postman → Authorization → Basic → username, password

→ CPI → verify → credentials