Day 57 APIM part 6

* How you will get OAuth-token for APIM ?

* CPI ⇒ credentials → Authenticate → CPI (called)

But

APIM ⇒ first called → Based on the policies

→ it is Authenticated

* In APIM if you want to generate any token then we need policies

⇒ Basically, In APIM the every action is work's under the policies

* Create → generic API proxy → generate Access token

* Now about the credentials → how youll get ?

∴ Developer hub (All the API's are managed)

* Developer hub → myworkspace → create API → design product to ais App → you will have API key & API Secret

Which will act as Client ID & Client Secret

* Validate → OAuth token → verify accesstoken

example: postman → endpoint → post → Bearer token ✓

⇒ ~~Basically~~ → oAuth token → Application

* APIm → Authentication → OAuth2 (Important)

We use mostly use OAuth2 only in Realtime

* token with a custom attributes → set OAuth2 token. → get OAuth2 (for getting)

* JWT → Json web token (Header, payload, Signature) Policy

Javascript object notation

(key, value pair) ✓

~~Encode~~ (Generate JWT)

→ expiresin, issuer, Subject, Audience,

Secret key ✓

→ Decode JWT token → Policy

→ verify JWT token → Policy

→ Secret Key → certificate → Section

→ Read the certificate → Generate token (JWT)

* JWT → token → header, payload, secretkey

* SAML Assertion validation:

Successfactors SAML (OAuth2) → Policy → Template

Scenario:

* APIM → Succes token → { clientID, clientSecret, SAML Content

OAuth2 SAML Bearer Assertion

① st → Call → SAML Content (generation) (~~oauth~~ OAuth/idp)

② nd → call → pass above Content

sapapim-saml content

* SAML Assertion Generation → Configuration

* SAML Assertion validation

* XML threat protection :→ Something like XML

Content validation

When it will work.
Headers → Content type → text/plain

→ Confirming whether the Recieving or (x) → output
Sending XML Content is Correct or not

→ XSD → Structure of XML (validation)

* xml → valid xml or not → XML threat protection

→ without XSD → XML → proper or not

↓

then we will use XML Threat protection

* XSD → fields → XML → fields (verification)

* XML Threat protect → formats everything matched or not ?

* how many fields, how many nodes, every field how much size

if the validation is wrong → through error

eg: 10 child nodes → fail

Scenario → only Source System needs to send only 5 fields if not should be failed.

→ XML Threat protection → field name → Fieldnames → for 10
Value → how much length
Childnods → how many needs to Recieve

eg: EmpID : 5 characters } → limitations options

Communication : how m.

* JSon Threat protection → Same like XML

JSon Content → validation → JSon Threat protection ✓

* demo → on → XML Threat protection

→ XML threat protection

* postman → did the demo ... ✓

Analyze the each and every field in XML threat protection

(Security level validation)