Day - 60

~~Day 60~~ APIM Part 9

* Simple Scenario → APIM → OAuth & API Key Based Authentication We have Seen right

* NOW → Basic Authentication & how we will do it in APIM

* Requirement → postman → APIM → Basic Authentication (username & password) → validate (how we will do)

* Basic Authentication Decode Option → Read the user name & password (In APIM we cannot do it)

So what We will do? → Key value Map operation's We will use.

→ Keyvaluemaps (name) → Store → Username and password

* demo

Basic Authentication → Policies → Basic Auth → (help)

Decode operation (ref = current.username) ✓
ref = current.password) ✓

Soure : request.header.Authorization

Step ② read the existing credential's from

KVM (Key value map)

APIM → keyvalue map → Create →

Credential's → [username → Text/User
password → Text/password → Capital]

Step ③ : policies → KVM → credentials (mapidentifier)
→ get operation (two times) → one for username and one for password ✓

Step ④ : If the Incoming username or password are wrong then we need to through an error
So here we will use Raise fault policy

RaiseFaultError

condition → (current.username != Sapapim.username)
(current.password != Sapapim.password)

* Status Code = 401, error payload →

Search in google

→ Content type = application / Json

→ Run → decode → Raisefaultusername → Raisefaultpassword →

* Now encode: AddAuth Details

→ <username> test </username>, <password> test </password>
Sapapi.username Saapapi.password

→ createNew = "true", request.header (Authorization)

Auth token

→ apiflow → Trace on

→ Basic Encode — Base64decoder (verify)

* OAuth → cache — populate cache, lookup cache } demo of live