Day 19

Log levels

* Manage Integration Content → log Configuration

→ log level's ① None
② Info
③ Error
④ Debug
⑤ Trace

* So we need to Why the above log levels we Can use

* Demo: postman

http's adapter, 2 Content modifiers
message Body data

Now we will discuss about the log Configuration

→ monitor Tab → Select deployed Artifact →

Artifact Details

① Info By default when you deploy the iflow the loglevel will be info

info → what happened to that particular message → Whether it is Successful or failure (It will give that information) → msgid

* for every message a unique Id will be generated

② None: No MPLogs are created even it is Successful or failure or whatever may be the Reason their will be no logs will be created for the message

Scenario: for Suppose you Dont want to Create any MPL log for an iflow then you Can use this option

③ Error: So if iflow triggered and Some how the message processing got failed due to Some error and WE have choosen the level as Error and the error details will be logged

④ **Trace**: This is the main Concept of log level

→ What is the use of trace

When ever you use trace → you can see the message Content at each and every step

Suppose → Source Connected (HTTPS)
message Content,
header, exchange properties, payload

Everything will be captured ~

This option will be enabled for only 10 min

and you can see that traced logs for 1 hr

⑤ **Debug**: If I want to debug the Message flow → which flow the message is moving

multiple directs ⇒ Scenario (Complex Scenarios)
Recievers

→ Debug will enabled till 24 hours
after that debug will get deleted

*(Q) → Till what time the message log's are Persisted → CPI will not persist the message log's forever but it will store till 30 days
After 30 days log's get deleted

Scenario: if you want to see log of Before 1month you can But more than a month you cannot see

* you can push that logs to the external logging System (Splunk, ---etc)

loggly
Datadog
Elastic Search
etc

Dat formats: What are all dataformats are there in: ① xml ② Json ③ csv

What if you are receiving data format as .Json from input and you need to send it to the Target System

What you will do

xml → Json (or) Json → xml

Vise versa

at this time we will use Converters

Pallete functions → Transformation → Converter

① Csv to xml Converter

② EDI to xml Converter.

③ Json to xml Converter

④ xml to csv

⑤ xml to EDI

⑥ xml to Json

Xml → root node is mandatory (only once (1:))

Json → it's not mandatory

Because → Suppose → we send multiple Records → we cannot tell that → we recieved multiple Records in xml → untill unless we have root node

→ [Suppress Json Root Element] (use → Selecting for we dont need root tag for Json data output)

→ Use Namespace mapping

if we want to add the Name Space prefix which is coming from xml input payload. to out Json data then we will check

Use Naive Space mapping: [✓]

Most of the time we will uncheck this

→ Json Prefix Separator: colon(:) ✓

comma(,)

Dot(.)

pipe(|)

Semicolon(;)

Space

We always use Colon ✓

→ Json output encoding: UTF-8 ✓

→ Streaming: for example

If we want to pass [] → [ ]

↳ Array

tag explicitly incase of you getting

Single record as a input at that time

We will go to Streaming

Streaming ✓:

Convert XML elements to JSON Array: All

{

specified ones ✓

/root/EMP