Ethernet and Switching



Ross Bagurdes
NETWORK ENGINEER

@bagurdes



Module Goals



CSMA/CD

Collision Domains

Duplex and Speed

The Ethernet Frame

Switch Operation




OSI Model

7	Application Layer
6	Presentation Layer
5	Session Layer
4	Transport Layer
3	Network Layer
2	Data Link Layer
1	Physical Layer





https://www.pluralsight.com/




Data Link Layer





https://www.pluralsight.com/




Data Link Layer





https://www.pluralsight.com/



Ethernet

















CSMA/CD



























CSMA/CD




Collision Domain

A group of networked devices that will simultaneously detect a voltage spike.




Duplex and Speed





Half duplex
One device communicates at a time


"Walkie talkie"



Full duplex

Two devices communicate at same time "Telephone"









1.3



























Ethernet Speed

Name	Speed
Ethernet	10Mbps
FastEthernet	100Mbps
GigabitEthernet	1Gbps
10GigabitEthernet	10Gbps
40GigabitEthernet	40Gbps



Ethernet Speed

Name	Speed
Ethernet	10Mbps
FastEthernet	100Mbps
GigabitEthernet	1Gbps
10GigabitEthernet	10Gbps
40GigabitEthernet	40Gbps

Requires Full Duplex











Destination MAC Address	Source MAC Address	Туре	Data (Packet)	FCS
48	48	16	MAX	32
bits	bits	bits	1500 Bytes	bits





Destination MAC
Address

Source MAC Address

Type

Data (Packet)

FCS

Frame

A chunk of data, with a data link layer header





Destination MAC
Address
Source MAC
Address
Type
Data
(Packet)
FCS

Ethernet Header


Frame

A chunk of data, with a data link layer header



Ethernet II Frame







Ethernet II Frame



	ion MAC ress	Source MAC Address	Туре	Data (Packet)	FCS
Manufacturer ID	Serial Number	48	16	MAX	32
	: D7:52:7A 1101 0111 0101 0010 0111 1010	bits	bits	1500 Bytes	bits



Manufacturer ID

Serial Number

00:10:D9:D7:52:7A

0000 0000 0001 0000 1101 1001 1101 0111 0101 0010 0111 1010



Ethernet II Frame



	ion MAC ress	Source MAC Address	Туре	Data (Packet)	FCS
Manufacturer ID	Serial Number	48	16	MAX	32
	: D7:52:7A 1101 0111 0101 0010 0111 1010	bits	bits	1500 Bytes	bits



Type Field



Destination MAC Address	Source MAC Address	Туре	Data (Packet)	FCS
48	48	16	MAX	32
bits	bits	bits	1500 Bytes	bits





Frame Check Sequence Cyclical Redundancy Check (CRC)

Destination MAC Address	Source MAC Address	Type	Data (Packet)	FCS
48	48	16	MAX	32
bits	bits	bits	1500 Bytes	bits



Ethernet II Frame



Destination MAC Address	Source MAC Address	Туре	Data (Packet)	FCS
48	48	16	MAX	32
bits	bits	bits	1500 Bytes	bits

Maximum Transmission Unit



Ethernet II Frame



Destination MAC Address	Source MAC Address	Type	Data (Packet)	FCS
48	48	16	MAX	32
bits	bits	bits	1500 Bytes	bits

Protocol Data Unit



Network Topologies









Network Topologies

- Bus
- Ring
- Star



















10Base5 and 10Base2 hardware










IBM Token Ring MAU

















Layer 2 Switch









Ethernet Switch













Port	MAC






Port	MAC
1	
2	
3	
4	
5	
6	






Port	MAC
1	
2	
3	
4	
5	
6	






Port	MAC
1	
2	
3	
4	
5	
6	






Port	MAC
1	
2	
3	
4	
5	
6	






Port	MAC
1	
2	
3	
4	
5	
6	






Port	MAC
1	
2	
3	
4	
5	
6	A7






Port	MAC
1	6E
2	В3
3	3F
4	DF
5	C2
6	A7






Port	MAC
1	6E
2	В3
3	3F
4	DF
5	C2
6	A7






Port	MAC
1	6E
2	В3
3	3F
4	DF
5	C2
6	A7






Port	MAC
1	6E
2	В3
3	3F
4	DF
5	C2
6	A7





Port	MAC
1	6E
2	В3
3	3F
4	DF
5	C2
6	A7





Port	MAC
1	6E
2	В3
3	3F
4	DF
5	C2
6	A7



Broadcasts



Ethernet II Frame



Destination MAC Address	Source MAC Address	Туре	Data (Packet)	FCS
FFFF FFFF	48	16	MAX	32
	bits	bits	1500 Bytes	bits






Broadcast


When the destination MAC address of the frame is all F's, the frame is sent out all active interfaces, except the receiving interface.






Port	MAC
1	6E
2	В3
3	3F
4	DF
5	C2
6	A7






Port	MAC
1	6E
2	В3
3	3F
4	DF
5	C2
6	A7






Port	MAC
1	6E
2	В3
3	3F
4	DF
5	C2
6	A7





Port	MAC
1	6E
2	В3
3	3F
4	DF
5	C2
6	A7





Port	MAC
1	6E
2	В3
3	3F
4	DF
5	C2
6	A7




Broadcast Domain

Group of networked devices which will receive a layer 2 broadcast message.






Demo



Examine the MAC Address Table



Ethernet Switch














Ethernet Switch





Summary



CSMA/CD

Collision Domains

Duplex and Speed

The Ethernet Frame

