

**Instructions: Odd no's (Q1, Q3), Even no's (Q2, Q4)**

**Note: Apply your creativity to design the templates**


**Note: Use External JavaScript file**

**Aim:**

Create a web application using JavaScript to manipulate the CSS Styles and Animation.


Q1) Create a web page to perform various style modification using for the "DIV" box such as background color, text color, font size, width, height and border radius using JavaScript code.

- Change the color of the text for the heading of the page (<h1>) for every 2 seconds. (setInterval)
- For background color and text color, use color chooser html element <input type=color>, trigger the JavaScript function when changing color and apply necessary style changes in "DIV". (onchange event)
- For border radius, use HTML range element using <input type=range>, trigger the JavaScript function when changing the radius and apply necessary style changes in "DIV". (onchange event)
- Select the text size in dropdown and enter the width & height, trigger the JavaScript function when pressing the button and apply necessary style changes in "DIV". (onsubmit event)




Q2) Create a web page to perform various style modification using JavaScript code.


- Change the background color of the webpage for every 2 seconds. (setInterval)
- For background color and text color of <DIV>, use color chooser html element <input type=color>, trigger the JavaScript function when changing color and apply necessary style changes in "DIV". (onchange event)
- Display an image, for changing the opacity, use HTML range element using <input type=range>, trigger the JavaScript function when changing the radius and apply necessary style changes in "DIV". (onchange event)
- Create event handlers that will increase the font size when a mouse moves over a paragraph and decrease the size when the mouse moves off the paragraph.



Q3) Create a web page with JavaScript code to move absolutely-positioned car object (or any image as per your choice) when user clicks the start button and stop the car image when a user clicks the stop button. [Note: Use JavaScript timer functions such as setInterval() or setTimeout()]



Q4) Write JavaScript code to develop an animation game to move a ball image. When the ball moves out of the play area, display an alert message "out of play".



**Source code :**

**Event :**

```
<!DOCTYPE html>
<html lang="en">
<head>
<meta charset="UTF-8">
<meta name="viewport" content="width=device-width, initial-scale=1.0">
<title>Style Modification</title>
<style>
  body {
    font-family: Arial, sans-serif;
    text-align: center;
    background-color: white; /* Set default background color to white */
  }
  #content {
    background-color: lightblue;
    padding: 20px;
    margin-top: 20px;
    border-radius: 8px;
  }
```

```

        display: inline-block; /* Make the blue area inline-block to center it */
    }
    img {
        max-width: 100%;
        height: auto;
        margin-top: 20px;
        transition: opacity 0.5s ease-in-out;
    }

    .box {
        width: 200px;
        height: 200px;
        background-color: lightblue;
        border: 1px solid #ccc;
        padding: 20px;
        margin: 20px auto;
        text-align: center;
        transition: font-size 0.3s ease;
    }
</style>
</head>
<body>

<h2>Style Modification</h2>

<div id="content">
    <p>Change the background color of the webpage:</p>
    <input type="button" id="startButton" value="Start Background Color Change"
onclick="toggleBackgroundColorChange()">
    <input type="button" value="Stop Background Color Change"
onclick="stopBackgroundColorChange()">
    <br><br>
    <label for="backgroundColorPicker">Choose background color:</label>
    <input type="color" id="backgroundColorPicker" onchange="changeBackgroundColor()">
    <br><br>
    <label for="textColorPicker">Choose text color:</label>
    <input type="color" id="textColorPicker" onchange="changeTextColor()">
    <br><br>
    <label for="opacityRange">Adjust image opacity:</label>
    <input type="range" id="opacityRange" min="0" max="1" step="0.1" value="1"
onchange="changeOpacity()">
    <br><br>
    

    <div class="box" onmouseover="increaseFontSize(this)"
onmouseout="decreaseFontSize(this)">
        <p>This is a paragraph inside the box.</p>
    </div>
</div>

```

```
<script>
  var backgroundColorInterval;

  function toggleBackgroundColorChange() {
    if (!backgroundColorInterval) {
      backgroundColorInterval = setInterval(changeBackgroundColor, 2000);
      document.getElementById("startButton").value = "Stop Background Color Change";
    } else {
      clearInterval(backgroundColorInterval);
      backgroundColorInterval = null; // Reset interval variable
      document.getElementById("startButton").value = "Start Background Color Change";
    }
  }

  function stopBackgroundColorChange() {
    clearInterval(backgroundColorInterval);
    backgroundColorInterval = null; // Reset interval variable
    document.getElementById("startButton").value = "Start Background Color Change";
  }

  function changeBackgroundColor() {
    var color = document.getElementById("backgroundColorPicker").value;
    document.getElementById("content").style.backgroundColor = color;
  }

  function changeTextColor() {
    var color = document.getElementById("textColorPicker").value;
    document.getElementById("content").style.color = color;
  }

  function changeOpacity() {
    var opacity = document.getElementById("opacityRange").value;
    document.getElementById("image").style.opacity = opacity;
  }

  var content = document.getElementById("content");
  content.onmouseover = function() {
    this.style.fontSize = "20px";
  };
  content.onmouseout = function() {
    this.style.fontSize = "inherit";
  };

  function increaseFontSize(element) {
    element.style.fontSize = "24px";
  }

  function decreaseFontSize(element) {
    element.style.fontSize = "16px";
  }
</script>
</body>
</html>
```

### Ball:

```
<!DOCTYPE html>
<html lang="en">
<head>
<meta charset="UTF-8">
<meta name="viewport" content="width=device-width, initial-scale=1.0">
<title>Ball Animation Game</title>
<style>
  #playArea {
    width: 500px;
    height: 300px;
    border: 2px solid black;
    position: relative;
    overflow: hidden;
    background-color: rgb(20, 105, 114);
  }
  #ball {
    width: 50px;
    height: 50px;
    background-image: url('ball.png'); /* Replace 'ball_image.png' with the path to your
image */
    background-size: cover; /* Adjusts the size of the background image to cover the entire
element */
    position: absolute;
  }
</style>
</head>
<body>

<div id="playArea">
  <div id="ball"></div>
</div>

<script src="script.js"></script>

</body>
</html>
```

### Script:

```
var ball = document.getElementById("ball");

var posX = 0;
var posY = 0;
ball.style.left = posX + "px";
ball.style.top = posY + "px";

var maxX = 450;
var maxY = 250;
```

```

var speedX = 2;
var speedY = 2;

function moveBall() {
    posX += speedX;
    posY += speedY;

    ball.style.left = posX + "px";
    ball.style.top = posY + "px";

    if (posX < 0 || posY < 0 || posX > maxX || posY > maxY) {
        alert("Out of play");
        clearInterval(animation);
    }
}


var animation = setInterval(moveBall, 20);

```


**Output :**

**Event:**

## Style Modification



**Ball:**



**Result:**

Successfully Created a web application using JavaScript to manipulate the CSS Styles and Animation