Practice program: Create Table 1

Practice program: Create Table 1

Description Code Editor Grading view

File List | Save | Compile & Run | Evaluate | Full screen | Description

sample.sql

```
1  create table customer_master(
2      cust_id varchar(10) primary key,
3      c_first_name varchar(30),
4      c_middle_name varchar(30),
5      c_last_name varchar(30),
6      Gender varchar(10),
7      Street varchar(30),
8      city varchar(30),
9      phoneno varchar(20),
10     email varchar(30)
11 );
```

Practice program: Create Table 2

Description | Code Editor | Grading view

File List | Save | Compile & Run | Evaluate | Full screen | Descript

sample.sql

```sql
create table venue_master (
    venue_id varchar(10),
    event_id varchar(10),
    venue_name varchar(30),
    location varchar(50),
    venue_cost int,
    food varchar(10),
    capacity int,
    wifi varchar(10),
    description varchar(50),
    primary key(venue_id),
    foreign key(event_id) references Event_Master(Event_id)
);
```

Practice program: Alter 1

Description | Code Editor | Grading view

File List | Save | Compile & Run | Evaluate | Full screen | Descrip

sample.sql

```
1  alter table venue_master modify wifi varchar(10) NOT NULL;
```

Practice program: Alter 2

Description | Code Editor | Grading view

File List | Save | Compile & Run | Evaluate | Full screen | Description

sample.sql

```
1  alter table Booking_Master add constraint Fk foreign key(Enquiry_Id) references Enquiry_Master(Enquiry_Id);
```

Practice program: Truncate 1

Description | Code Editor | Grading view

File List | Save | Compile & Run | Evaluate | Full screen

sample.sql

```
1 truncate table Booking_Master;
```

Practice program: Drop 1

Practice program: Drop 1

Description Code Editor Grading view

File List Save Compile & Run Evaluate Full screen Description

sample.sql

```
1 DROP TABLE BOOKING_MASTER;
```

Practice program: Insert 1

Description | **Code Editor** | Grading view

File List | Save | Compile & Run | Evaluate | Full screen | D

sample.sql

```
1 insert into Booking_Master VALUES('B101','EN1001',40000,'Cash');
2 insert into Booking_Master VALUES('B102','EN1012',750000,'Online');
3 insert into Booking_Master VALUES('B103','EN1016',16000,'Cheque');
4 insert into Booking_Master VALUES('B104','EN1007',10000,'Cash');
```

Practice program: Insert 2

Description | Code Editor | Grading view

File List | Save | Compile & Run | Evaluate | Full screen | Description

sample.sql

```
1 insert into Customer_Master (Cust_Id, C_first_name, Gender, City, Phoneno) values('C001','Liam','Male','New York','9235234530');
2 insert into Customer_Master (Cust_Id, C_first_name, Gender, City, Phoneno) values('C002','Olivia','Female','Boston','9235234531');
3 insert into Customer_Master (Cust_Id, C_first_name, Gender, City, Phoneno) values('C003','James','Male','Austin','9235234532');
4 insert into Customer_Master (Cust_Id, C_first_name, Gender, City, Phoneno) values('C004','Henry','Male','San Antonio','9235234533');
5 insert into Customer_Master (Cust_Id, C_first_name, Gender, City, Phoneno) values('C005','Noah','Male','Chicago','9235234534');
```

Practice program: Update 1

Practice program: Update 1

Description Code Editor Grading view

File List Save Compile & Run Evaluate Full screen

sample.sql

```
1  update Customer_Master set
2          Street = 'No.21,Abbey Road', City = 'Denver'
3          where C_first_name = 'emma';
```

Practice program: Update 2

Description | Code Editor | Grading view

File List | Save | Compile & Run | Evaluate | Full screen

sample.sql

```
1  update venue_master set
2      capacity = capacity*1.1
3      where location = 'San Antonio';
```

Practice program: Delete 1

Description | Code Editor | Grading view

File List | Save | Compile & Run | Evaluate | Full screen

sample.sql

```
1  delete From booking_master;
```

Practice program: Delete 2

Description | Code Editor | Grading view

File List | Save | Compile & Run | Evaluate | Full screen | D

sample.sql

```
1  delete from Enquiry_Master
2      where Venue_Id = 'V04' and Status = 'Available';
```

Practice program: Customer Details

Description | Code Editor | Grading view

File List | Save | Compile & Run | Evaluate | Full screen | Description

sample.sql

```
1 select C_first_name,Gender,Phoneno
2 from Customer_Master
3 order by C_first_name;
```

Practice program: Customers Details Based On Name

Description | Code Editor | Grading view | Practice program: Customers Details Based On Name

File List | Save | Compile & Run | Evaluate | Full screen | Description

sample.sql

```
1 select c_first_name,c_last_name,street,city
2 from customer_master
3 where c_first_name like '_m%'
4 order by c_first_name;
```

Practice program: Booking Details

Description | **Code Editor** | Grading view

File List | Save | Compile & Run | Evaluate | Full screen | Description

sample.sql

```
1 select * from Booking_Master;
```

Practice program: Venue Details With Wifi Facility

Description | Code Editor | Grading view

Practice program: Venue Details With Wifi Facility

File List | Save | Compile & Run | Evaluate | Full screen | Description

sample.sql

```
1 select venue_id,venue_name,location,venue_cost,wifi
2 from venue_master
3 where location != 'New York' and location != 'Austin'
4 order by venue_cost;
```

Practice program: Customers Details Based On Last Name And Middle Name

Description | Code Editor | Grading view

File List | Save | Compile & Run | Evaluate | Full screen | Description

sample.sql

```
1  select c_first_name,Phoneno,Gender
2  from customer_master
3  where c_middle_name = null or c_last_name=null
4  order by Phoneno;
```

Practice program: Booking Details Based On Payment Mode

Description | Code Editor | Grading view

File List | Save | Compile & Run | Evaluate | Full screen | Description

sample.sql

```sql
select booking_id,enquiry_id,total_amount
from booking_master
where mode_of_pay ='cash' or mode_of_pay ='credit'
order by enquiry_id;
```

Practice program: Venue Details Based On Capacity

Description | Code Editor | Grading view

Practice program: Venue Details Based On Capacity

File List | Save | Compile & Run | Evaluate | Full screen | Description

sample.sql

```
1 select venue_id,venue_name,venue_cost,Location
2 from venue_master
3 where capacity between 1000 and 20000
4 order by venue_name;
```

Practice program: Customer Contact Info

Description | Code Editor | Grading view

File List | Save | Compile & Run | Evaluate | Full screen | Description

sample.sql

```sql
select cust_id,c_first_name,coalesce(city,Phoneno,email) as 'CONTACT_INFO'
from customer_master
order by 3;

```

Practice program: Venue Details

Description | Code Editor | Grading view

File List | Save | Compile & Run | Evaluate | Full screen | Description

sample.sql

```sql
select venue_name,venue_cost,
case
when venue_cost between 50000 and 200000 then 'Medium Cost'
when venue_cost < 50000 then 'Low Cost'
when venue_cost > 200000 then 'High Cost'
end
as 'Cost_catagory'
from venue_master
order by Capacity desc;
```

Practice program: Customer Info

Description | Code Editor | Grading view

File List | Save | Compile & Run | Evaluate | Full screen | Des

sample.sql

```
1  select concat(c_first_name,' lives in ',City,' and ',
2  case
3  when Gender = 'Female'then 'her'
4  when Gender = 'Male'then 'his'
5  end ,' phone number is ',phoneno) as customer_info
6  from Customer_master
7  order by c_first_name desc;
```

Practice program: Finding Position

Description | Code Editor | Grading view

File List | Save | Compile & Run | Evaluate | Full screen | Description

sample.sql

```
1  select c_first_name,position('m' in c_first_name) as position
2  from customer_Master
3  where City in ('Los Angeles','Boston')
4  order by position desc , c_first_name asc;
```

Practice program: Customer Password

Practice program: Customer Password

Description | Code Editor | Grading view

File List | Save | Compile & Run | Evaluate | Full screen | Description

sample.sql

```
1  select c_first_name as 'user_name',
2  concat(substring(c_first_name,1,3),substring(phoneno,5,6)) as password
3  from customer_master
4  where email != null
5  order by 1;
```

Practice program: Month Name For The Events

Description | Code Editor | Grading view

File List | Save | Compile & Run | Evaluate | Full screen | Description

sample.sql

```
1  select enquiry_id,cust_id, concat(Date_Format(start_date, '%M'),',',Year(start_date))
2  as 'Event_date'
3  from enquiry_master
4  where year(start_date) >2015
5  order by Event_date asc, cust_id asc;
```

Practice program: Number Of Days

Practice program: Number Of Days

Description | Code Editor | Grading view

File List | Save | Compile & Run | Evaluate | Full screen | Description

sample.sql

```sql
select Enquiry_Id,Cust_Id,Venue_Id,
date_format(Start_Date, '%M') as 'month_name',
datediff(End_date+1,Start_Date) as 'no_of_days'
from Enquiry_Master
where month(Start_Date) = 12
order by no_of_days desc;
```

Practice program: Weekend Events

Description | Code Editor | Grading view

File List | Save | Compile & Run | Evaluate | Full screen | Description

sample.sql

```sql
select Enquiry_Id,Cust_Id
from Enquiry_Master
where dayofweek(Start_Date) in (1,7) and dayofweek(End_Date) in (1,7)
order by Cust_Id;
```

Practice program: Maximum Seating Capacity Of Events

Description | Code Editor | Grading view

File List | Save | Compile & Run | Evaluate | Full screen | Description

sample.sql

```sql
select Event_Id, max(capacity) as 'maximum_seating_capacity'
from Venue_Master
where wifi='Yes'
group by Event_Id
order by maximum_seating_capacity desc;
```

Practice program: Min Amount In Cash Or Online Method

Description | Code Editor | Grading view

Practice program: Min Amount In Cash Or Online Method

File List | Save | Compile & Run | Evaluate | Full screen | Description

sample.sql

```sql
select Mode_of_pay, min(Total_amount) as 'MINIMUM_TOTAL_AMOUNT'
from Booking_Master
where Mode_of_pay in ('Cash','Online')
group by Mode_of_pay
order by MINIMUM_TOTAL_AMOUNT;
```

Practice program: Customer Count

Description | **Code Editor** | Grading view

File List | Save | Compile & Run | Evaluate | Full screen | Description

sample.sql

```sql
select count(Enquiry_Id) as 'ENQUIRY_COUNT'
from Enquiry_Master
group by Cust_Id
having ENQUIRY_COUNT > 1
order by ENQUIRY_COUNT desc;
```

Practice program: Average Cost For Location

Description | Code Editor | Gradi

Practice program: Average Cost For Location

File List | Save | Compile & Run | Evaluate | Full screen | Description

sample.sql

```
1 select Location,round(avg(Venue_Cost),2) as Avg_cost
2 from Venue_Master
3 where Capacity > 1000
4 group by Location
5 order by Location;
```

Practice program: Customer Venue Dates

Description | Code Editor | Grading view

File List | Save | Compile & Run | Evaluate | Full screen | Description

sample.sql

```
1  select C_first_name, Venue_Id,Start_date,End_date
2  from Customer_Master c join Enquiry_Master e on c.cust_id = e.cust_id
3  order by 1;
```

Practice program: Customer Details Based On Payments

Description | Code Editor | Grading view

File List | Save | Compile & Run | Evaluate | Full screen | Description

sample.sql

```sql
select distinct c.Cust_Id,c.C_first_name,c.Phoneno,c.Email
from Customer_Master c join Enquiry_Master e join Booking_Master b
on c.Cust_Id = e.Cust_Id and e.Enquiry_Id = b.Enquiry_Id
where b.Mode_of_Pay = 'Online'
order by c.Cust_Id;
```

Practice program: Discount Code For Specific Customer

Description | Code Editor | Grading view

File List | Save | Compile & Run | Evaluate | Full screen | Description

sample.sql

```sql
select distinct c.c_first_name, concat(substring(c.c_first_name,1,3), substring(c.Phoneno,1,3)) as 'Discount_Code'
from Customer_Master c join Enquiry_Master e on c.Cust_Id = e.Cust_Id
join Booking_Master b on e.Enquiry_Id = b.Enquiry_Id
where (c.City = 'Los Angles' or c.City = 'Boston') and b.total_amount > 50000
order by c.c_first_name;
```

Practice program: Number of Days

Description | Code Editor | Grading view

File List | Save | Compile & Run | Evaluate | Full screen | Description

sample.sql

```sql
select e.Cust_Id,b.Booking_Id, DATEDIFF(e.End_Date,e.Start_Date) as 'Days'
from Enquiry_Master e join Booking_Master b on e.Enquiry_Id = b.Enquiry_Id
where DATEDIFF(e.End_Date, e.Start_Date) >3
order by e.Cust_Id desc;
```

Practice program: Number Of Customer For Venues

Description | Code Editor | Grading view

File List | Save | Compile & Run | Evaluate | Full screen | Description

sample.sql

```sql
select v.Venue_name, count(DISTINCT e.Cust_Id) as No_Of_Customers
from Venue_master v left join Enquiry_Master e on v.Venue_Id = e. Venue_Id
group by v.Venue_name
order by v.Venue_name;
```

Practice program: Customer Visited Same Venues

Description | Code Editor | Grading view

File List | Save | Compile & Run | Evaluate | Full screen | Description

sample.sql

```
1 select c.C_first_name, c.City, e.Venue_Id
2 from Customer_Master c join Enquiry_Master e on c.Cust_Id = e.Cust_Id
3 where c.City=e.City and c.Venue_Id = e.Venue_Id
```

Practice program: Customer Without Enquiry And Booking

Description | Code Editor | Grading view

Practice program: Customer Without Enquiry And Booking

File List | Save | Compile & Run | Evaluate | Full screen | Description

sample.sql

```sql
select c.Cust_id, c.C_first_name, c.City, c.Phoneno
from Customer_Master c left join Enquiry_Master e on c.Cust_Id = e.Cust_Id
where e.Cust_Id is null
order by c.C_first_name;
```

Practice program: Customer Total Booking Amount

Description | Code Editor | Grading view

File List | Save | Compile & Run | Evaluate | Full screen | Description

sample.sql

```sql
select c.c_first_name, sum(b.total_amount) as 'total_booking_amount'
from Customer_Master c
join Enquiry_Master e on c.Cust_Id = e.Cust_Id
join Booking_Master b on e.Enquiry_Id = b.Enquiry_Id
where sum(b.total_amount) > (select AVG(total_amount) from Booking_Master)
group by c.Cust_Id,c.c_first_name
order by c.c_first_name;
```

Practice program: Venue Details With Maximum And Minimum Cost

Description | Code Editor | Grading view

File List | Save | Compile & Run | Evaluate | Full screen | Description

sample.sql

```sql
select Venue_Id, Venue_Name, Location
from Venue_Master
where Venue_Cost = (select max(Venue_Cost) from Venue_Master) or Venue_Cost = (select min(Venue_Cost) from Venue_Master)
group by Venue_Id, Venue_Name,Location
order by Venue_Cost;
```

Practice program: Venue Details Based on Bookings

Description | Code Editor | Grading view

Practice program: Venue Details Based on Bookings

File List | Save | Compile & Run | Evaluate | Full screen | Description

sample.sql

```sql
select v.Venue_Id, v.Venue_name, v.Location, v.Category
from Venue_Master v join Enquiry_Master q on v.Venue_Id = q.Venue_Id
join Booking_Master b on q.Enquiry_Id = b.Enquiry_Id
join Event_Master e on v.Event_Id = e.Event_Id
where v.Venue_Id <> ' V10' and (select count(*) from Booking_Master where Venue_Id = 'v10') = (select count(*) from Booking_Master where Venue_Id = v.Venue_Id)
order by v.Venue_name desc;
```

Practice program: Highest Seating Capacity

Description | Code Editor | Grading view

File List | Save | Compile & Run | Evaluate | Full screen | Description

sample.sql

```sql
select v.Category, v.Venue_Name, v.Capacity
from Venue_Master Venue_Master
join Event_Master e on v.Event_Id = e.Event_Id
where v.Capacity = (select max(Capacity) from Venue_Master where Category = v.Category);
```

Practice program: Create view

Description | Code Editor | Grading view

File List | Save | Compile & Run | Evaluate | Full screen

sample.sql

```
1 create view Boston_Customers as select*
2 from Customer_Master
3 where City = 'Boston';
```

Practice program: Customer Info

Practice program: Customer Info

Description | Code Editor | Grading view

File List | Save | Compile & Run | Evaluate | Full screen | Description

sample.sql

```sql
create view Customer_Info as
select Customer_Master.C_first_name,Customer_Master.Phoneno,Customer_Master.City,Booking_Master.total_amount
from Customer_Master join Booking_Master join Enquiry_Master
on Customer_Master.Cust_Id = Enquiry_Master.Cust_Id and Enquiry_Master.Enquiry_Id = Booking_Master.Enquiry_Id
where total_amount < 60000
order by C_first_name;
```

Practice program: Create Index

Practice program: Create Index

Description Code Editor Grading view

File List Save Compile & Run Evaluate Full screen De

sample.sql

```
1 create index stuindex on student(student_name);
```