PSEUDOCODE QUESTIONS FOR HEXAWARE – 2025

Q1. What will be the output of the following pseudocode?

[Note: If (X) gets executed if the value inside if( ), ie, x is not zero].

```
1  integer a, b, c
2  set a=3, b=2
3  if (b-1)
4  for (each c from 1 to 3)
5  a= a-1
6  end for
7  for(each c from 1 to 3)
8  a= a + b
9  end for
10 end if
11 print a+ b
```

- 1
- 8
- 4
- 5

Q2. What will be the output of the following pseudocode?

[Note:&&: Logical AND - The logical AND operator (&&) returns the boolean value True (or 1) if either or both operands is True and returns False(or 0)].

| |: Logical OR - The logical OR operator (| |) returns the boolean value True (or 1) if either or both operands is True and returns False(or 0), otherwise.

```
1  integer a1, a2, p
2  set a1= 16, a2= 234
3  p= (a1 + a2) AND (a1) OR (a2)
4  if ( p not equqls 0)
5  print p + p
6  else
7  print p
8  end if
```

- 500
- 1
- 4
- 3

Q3. What will be the output of the following pseudocode?

```
1  integer a, b, j
2  set a=10, b= 18
3  for (i=6 to a-1) increase i by
4  b= ((b*2)/ 2) + 3
5  end for
6  print b
```

21

24

27

30

Q4. What will be the output of the following pseudocode?

```
1  integer a, b, c
2  set a=13, b= 9, c= 6
3  if (a< b)
4  if (a < c)
5  print a
6  else
7  print c
8  end if
9  else if (b < c)
10 print b
11 else
12 print c
13 end if
```

6 9

9

6

13

Q5. What will be the output of the following pseudocode?

[&& : Logical AND - The logical AND operator (&&) returns the boolean value True (or 1) if either or both operands is True returns False(or 0)
If (X) gets executed if the value inside if( ), ie, x is not zero].

```
1  integer i, a, j
2  set i=6, a=23
3  j= i + a && i / a && a/ i + i
4  if (j)
5  print j
6  else
7  print j + j
8  end if
```

0

20

2

1

Q6. What will be the output of the following pseudocode?

```
1  integer a, b , a, d
2  set a=3, b= 1, c=1
3  for (each d from 1 to 3)
4  a= a-1
5  if(d> 2)
6  a= a- b
7  b=a
8  if (d < 2)
9  jump out of the loop
10 end if
11 a= a + 1
12 end for
13 print a + c
```

3

-5

4

5

Q7. What will be the output of the following pseudocode?

```
1 integer a, b
2 for (each a from 1 to 2)
3 b= 17
4 print b + a - a * a
5 end for
6 print a + 1
```

17 17 16

17 15 4

1 2 3

17 4 15

Q8. What will be the output of the following pseudocode?

```
1  integer k
2  set k=6/7 + 3 - 3
3  if ( k < = 0)
4  if ( k equals 0)
5  print "test1"
6  else
7  print " test2"
8  end if
9  else
10 print "test3"
11 end if
12 print " test completed"
```

test3 test completed

test2 test completed

test completed

test1 test completed

Q9. What will be the output of the following pseudocode?

```
integer j, m
set m=1
integer a[4]= {0, 1,0,2}
a[0] = a[0] - a[2] + a[3]
a[1] = a[0] -a[3]
a[2]= a[1] - a[2]
a[3] = a[2]
m = a[3]
print m
```

6

0

2

1

Q10. What will be the output of the following pseudocode?

```
integer n
set n=15
while( n <=15)
n= n + 6/3
print "biography"
continue with next iteration
end while
```

it will print biography 13 times

it will print biography 15 times

it will print biography 1 time

it will print biography 14 times

Q11. What will be the output of the following pseudocode for p= 8?

```
integer combine(integer p)
if (p < = 17)
combine(combine(p * 2))
end if
return p + 3
end function combine ()
```

13

34

41

12

Q12. What will be the output of the following pseudocode for a= 22?

```
1  integer compact(integer a)
2  if( a <= 45)
3  compact( compact (compact (a * 5 + 1)))
4  end if
5  return a*2
6  end function compact ()
```

22

45

56

888

Q13. What will be the output of the following pseudocode if a = 10?

```
1  integer f5(integer a)
2  if (a mod 2)
3  return a++
4  else
5  return f5(f5 ( a- 1))
6  end if
7  end function f5()
```

9

98

101

87

Q14. What will be the output of the following pseudocode if a = 2 b = 7?

[Note:If (X) gets executed if the value inside

if( ), ie, x is not zero].

```
1  integer funn( integer a, integer b)
2  if (a > -2)
3  if(b + 1)
4  return 2
5  end if
6  return a
7  end if
8  return b
9  end function funn ( )
```

- 0
- 2
- 11
- 1

Q15. What will be the output of the following pseudocode?

[Note: MOD finds the remainder after the division of one number by another. For example, the expression "5 MOD" would evaluate to 1 because 2 leaves a quotient of 2 and a remainder 1].

```
1  character a[20], b[20]
2  set a[20] = "Alpital"
3  integer j, k
4  set j= 0, k=0
5  while (a[j] NOT EQUALS null character)
6  if (j mod 2 EQUALS 0)
7  b[k]= a[j]
8  else
9  b[k]= ' '
10 end if
11 k= k + 1
12 j= j + 1
13 end while
14 set k= 0
15 while (b [k] NOT EQUALS null character)
16 print b [k ]
17 k= k + 1
18 end while
```

- t a l p
- l l a
- A t p l
- A p t l

Q16. All the options mentioned below are real security and privacy risks, except:

- Virus attack
- Spam

Worm attack

Malware attack

Q1. What will be the output of the following pseudocode?

```
1  integer a, b, c
2  set a= -3, b = -2
3  if( b - 2 < b)
4  for (each c from 1 - 1 to 2 - 1)
5  a= a + 1
6  end for
```

```
7  end if
8  print a +b
```

- -4
- 3
- 4
- -3

Q2. Which one of the following gets generated by the given pseudocode for input n=5?

```
1  function(input n)
2  {
3    if (n < 2)
4     return n;
5   else return function (n-1) + function(n-2);
6  }
```

- 5
- 4
- 3
- 1

Q3. What will be the output of the following pseudocode?

```
1  Integer n, c
2  set n= 128, c= 4
3  while( n NOT EQUALS 0)
4     n= n / 10
5     c = c - 1
6  end while
7  print c
```

- 0
- -1
- 2
- 1

Q4. What will be the output of the following pseudocode?

```
1  Integer a, b, c
2  set a= 1, b = 2 , c= 1
```

```
3  a= c
4  c= a
5  b= a
6  print a + b + c
```

- 3
- 13
- 9
- 15

Q5. What will be the output of the following pseudocode?

```
1  Integer a, b, c
2  set a= 7, b= 2, c= 8
3  b = (b&b) + b
4  a= (5 & 11) + a
5  c= c
6  print a + b + c
```

- 30
- 20
- 15
- 22

Q6. What will be the output of the following pseudocode?

```
1  Integer a,b,c
2  Set a=2,b=4,c=6
3  b=(c^b)&b
4  b=(b+1)+c
5  b=(c+11)+b
6  c=(8+11)&a
7  c=(c^12)+a
8  Print a+b+c
```

- 46
- 50
- 42
- 54

Q7. What will be the output of the following pseudocode?

```
1 set p=1, q=1
2 Integer fun ( integer p, integer q)
3 if( q ^ 2 > p ^ 3)
4 p= q ^ 2
5 else
6 q = p & 2
7 end if
8 return p ^ q
9 end function fun ()
```

- 3
- 8
- 2
- 1

Q8. What will be the output of the following pseudocode?

```
1 integer j,m
2 set m=0
3 integer a[4]={10,11,3,2}
4 for (each j from m to m+3)
5 if (j> 0)
6 a[j]= a[j-1] + 2
7 end if
8 end for
9 m= a[0] + a[2] + a[1]
10 print m
```

- 52
- 29
- 41
- 36

Q9. What will be the output of the following pseudocode for **p = 3** and **q = 7**?

```
1 Integer function funn(Integer p, Integer q)
2   Integer r
3   set r=p
4   p=q
5   r=p
6   q=r
7   p=r
8   return p+q
9 End function funn ()
```

- 14
- 16

15

17

Q10. What will be the output of the following pseudocode for a=9,b=2?

```
1  Integer funn(Integer a, Integer b)
2    if (b<a)
3      return a+funn(b+1,a+1)+funn(b+2,a+2)
4    End if
5    return b
```

37

27

41

30

Q11. What will be the output of the following pseudocode for **a=3**, **b=1**, **c=7**?

```
1  Integer funn(Integer a, Integer b, Integer c)
2    c=(3^1)+a
3    b=3&c
4    b=(a+7)^b
5    if ((a^c^3)<(a^b^1)
6      b=a+c
7      c=(1+3)+a
8    End if
9    return a+b+c
```

16

18

15

17

Q12. What will be the output of the following pseudocode?

```
1  Integer p,q,r
2  Set p=5, q=6, r=10
3  q= (r+q)^q
4  if((r^3)<(5+r))
5    q=(11&10)+p
6    p=(q^1)+q
7  End if
8  Print p+q+r
```

58

54

52

65

Q13. What will be the output of the following pseudocode if **p = 3** and **q = 5**?

```
1  Integer fun(Integer p, Integer q)
2    if(q>p)
3     return fun(q-1, p)+q
4    End if
5    return p
```

8

7

9

6

Q14. What will be the output of the following pseudocode?

```
1  Integer a,b,c
2  Set a=3,b=2,c=7
3  for (each c from 5 to 9)
4     b=b+c
5  End for
6  a=(5+10)+a
7  c=(12+10)^c
8  for (each c from 5 to 6)
9     a=(c+b)+b
10    b=(a^9)+b
11 End for
12 Print a+b
```

536

540

547

541

Q15. What will be the output of the following pseudocode?

```
1  Integer p, q, r
2  Set q = 13
3  for (each p from 1 to 4)
4     r = q mod p
5     p = p + 5
```

```
6     q = p + r
7   end for
8   r = q / 5
9   Print q , r
```

- q = 2, r = 1
- q = 6, r = 1
- q = 7, r = 2
- q = 6, r = 4

Q1. What will be the output of the following pseudocode for a= 3 and b= 4?

```
1 integer foo( integer a, integer b)
2 if( a EQUALS 0)
3 return b
4 else if ( a EQUALS 1)
5 return b + 1
6 else
7 return foo(a - 1, a + b +5)
8 end if
9 end function foo()
```

- 20
- 10
- 7
- 5

Q2. What will be the output of the following pseudocode for a= 2?

```
1 integer fun( integer a)
2 integer p=1
3 if( a > 0)
4 return p + fun( a- 1)
5 else
6 p= p + 1
7 return a + p
8 end if
9 end function fun()
```

- 6
- 4

8

2

Q3. What will be the output of the following pseudocode?

```
integer a[10]
set a[10]= { 1,2,3,4,5,6,7,8,9}
for(each i from 1 to 4)
if (a[ i / 2])
print a[ i * 2]
else
print a[ i + 2]
end if
end for
```

2 4 6 8

1 2 3 4 5

2 6 8 0

3 5 7 9

Q4. What will be the output of the following pseudocode?

[Note: The bitwise exclusive OR operator(^) compares each bit of its first operands to the corresponding bit of its second operator. The corresponding result bit is set to 1. Otherwise, the corresponding result bit is set to 0].

```
integer a,b
set a= 0
a= a^ 1
a= a^ 2
a= a^ 3
print a
```

3

0

1

2

Q5. What will be the output of the following pseudocode?

```
integer h
set h= 42
do
print h
h ++
if (h > 45)
jump out of the loop
while()
end do while
```

42 43 44 45

43

42

42 44 45 46

Q6. What will be the following pseudocode?

[Not:&& : Logical AND - The logical AND operator (&&) returns the boolean value True (or 1) if either or both operands is True and returns False(or 0)].

```
1  character p[20], b[20]
2  set p[20]= "Respect Your elders"
3  integer k
4  set k= 0
5  while (p[k] not equals null character AND p[k] not equals space)
6  b[k]= p[k]
7  k= k + 1
8  end while
9  set k =0
10 while( b[k] not equals null character)
11 print b[k]
12 k= k + 1
13 end while
```

Respect elders

R

elders

Respect

Q7. What will be the output of the following pseudocode?

```
1  Set k = 1, m = 9
2
3  If (k + 8 / m) {
4     Print m
5  }
6
7  Set m = m + 1
8
9  If (k * 8 / m) {
10    Print k
11 }
12
13 Set k = k - 1
14
15 For each k from m down to 8 {
16    Print k
17 }
```

9 10 9 9

9 10

9 10 9 8

9 10 9 10

Q8. What will be the output of the following pseudocode?

```
1  integer s
2  set s=78
3  while(s EQUALS 78)
4  if ( s< 89)
5  s= s + 1
6  print "welcome"
7  else
8  jump out of the loop
9  end if
10 end while
```

None of the mentioned options

It will print "welcome" only one time

It will print nothing

It will print "welcome" 78 times

Q9. What will be the output of the following pseudocode for a=3?

```
1 integer fun(integer a)
2 integer arr[]={10,7,2,6,1,2,3}
3 integer p, sum =0
4 for(each p from 0 to a-1)
5 sum = sum + arr [a]
6 end for
7 return sum
8 end function fun()
```

20

19

21

15

Q10. What will be the output of the following pseudocode?

```
1 integer arr[]= {10, 20,30,40,5}
2 integer a, s
3 set s=0
4 set a= arr[ 1] +arr [2]
5 print a
```

50

40

25

5

Q11. What will be the output of the following pseudocode?

In Python ^ is used to find the power of a number.

```
1 integer a, b,c
2 set b=3, a= 5, c=1
3 if( b < a )
4 b= a
5 end if
6 for(each b from 0 to (1^2^3))
7 b= b + 1
8 end for
9 print b
```

6

5

2

1

Q12. What will be the output of the following pseudocode?

```
1 integer a, b
2 set a=15, b= 7
3 a= a mod (a-3)
4 b= b mod (b-3)
5 a= a mod 1
6 b= b mod 1
7 print a + b
```

0

7

15

2

Q13. What will be the output of the following pseudocode for a=2?

```
1 integer fun(integer a)
2 if(a>0)
3 return a+ fun(a-1)
4 else
5 return 0
```

```
6  end if
```

- 6
- 5
- 3
- 4

Q14. What will be the output of the following pseudocode?

```
1  integer a, b,c
2  set b=5, a=2, c=2
3  if(a)
4  a=a-1
5  a=c
6  else
7  c=c+1
8  end if
9  if(a-1)
10 c=c+1
11 else
12 c=c-1
13 end if
14 print a+b+c
```

- 15
- 20
- 10
- 11

Q15. What will be the output of the following pseudocode f(x) x =777.

```
1  Integer fun(Integer x)
2        if (x > 12)
3          fun (x / 9)
4          print x
5        else
6          for (each i from 1 to 3)
7              x = x + i
8              print x
9          end for
10       end if
11 end Function fun( )
```

- 11 13 14 85 777
- 12 15 86 777
- 10 12 15 86 777

10 12 13 85 777

Q1. What will be the output of the following pseudocode?

[Note:- && : Logical AND - The logical AND operator (&&) returns the boolean value True (or 1) if either or both operands is True and returns False(or 0)
If (X) gets executed if the value inside if( ), ie, x is not zero].

```
1  integer a, b, c
2  set a=11, b= 21
3  for(each c from 16 to 17)
4  if ( c-10 > 8)
5  if (1 && 1)
6  a= a + c
```

```
6  a= a + c
7  end if
8  a= a + 1
9  else
10 a= 0
11 end if
12 end for
13 print b + a
```

- 11
- 14
- 21
- 50

Q2. What will be the output of the following pseudocode?

[Note:-&& : Logical AND - The logical AND operator (&&) returns the boolean value True (or 1) if either or both operands is True and returns False(or 0)].

```
1 integer a, b
2 set b= 2
3 set a= b + 3
4 if (a && b - a && 1)
5 a=a +1
6 end if
7 print a
```

- 8
- 5
- 6
- 4

Q3. What will be the output of the following pseudocode?

```
1 integer n, c
2 set n= 128, c= 4
3 while( n NOT EQUALS 0)
4 n= n / 10
5 c = c - 1
6 end while
7 print c
```

- 0
- -1
- 2

1

Q4. What will be the output of the following pseudocode?

```
integer a[5]
set a[5]= { 1,2,3,4}
integer m, j
set m= 1
for ( each j from 0 to 3)
m= m + a[j] + a[ j] + 6
end for
print m
```

43

45

23

46

Q5. How many times the following pseudocodes will print hello?

```
integer k, p, j
set k= 1, p= 4
int j= p + k / 2
if ( j equals p)
print "hello"
end if
j= p + k / 5
if ( j not equals p)
print " hello "
end if
print " hello "
```

Three times

One times

Two times

will not print hello at all

Q6. What will be the output of the following pseudocode?

[Note: If (X) gets executed if the value inside if( ), ie, x is not zero].

```
integer k, p
set k= 56
p = k + 8 - 78 / 8 * 4/7 - 5/ 2
if (p )
print "hello "
else
print " bye"
end if
```

None of these mentioned options

hello

hello bye

bye

7. What will be the output of the following pseudocode?

[Note:-&& : Logical AND - The logical AND operator (&&) returns the boolean value True (or 1) if either or both operands returns False(or 0)].

```
1  integer a, b, c
2  set a= 1, b= 2
3  for (each c from 216 to 217)
4  if( c - 200 > 100)
5  if( 1 && 1)
6  a= a + c
7  end if
8  a= a+ c
9  else
10 a=0
11 end if
12 end for
13 print b + a
```

8

4

2

7

8. What will be the output of the following pseudocode?

```
1  integer a, b, c, d
2  set d= 6
3  for( each a from 1 to 2)
4  for(each b from a to 2)
5  for (each c from b to 2)
6  print d
7  end for
8  end for
9  end for
```

6 6 6 6 6 6

6

6 6 6

6 6 6 6

9. What will be the output of the following pseudocode?

[Note: MOD finds the remainder after the division of one number by another. For example, the expression "5 MOD" would evaluate to 1 because 2 leaves a quotient of 2 and a remainder 1].

```
1  integer a, b, c
2  set a= 108, b= 2, c= 3
3  if (( a MOD 9) EQUALS 0)
4  b= b + (a MOD 2)
5  print b
6  else
7  c= c + ( a MOD 7)
8  print c
9  end if
```

- 2
- 7
- 1
- 3

Q10. What will be the output of the following pseudocode for a=6?

```
1  integer fun (integer a)
2  if (a EQUALS 0)
3  return a+ 9
4  else
5  return fun(a-1)
6  end function fun()
```

- 6
- 0
- 9
- 1

Q11. What will be the output of the following pseudocode?

[Note: MOD finds the remainder after the division of one number by another. For example, the expression "5 MOD" would evaluate to 1 because 2 leaves a quotient of 2 and a remainder 1
| | : Logical OR - The logical OR operator (| |) returns the boolean value True (or 1) if either or both operands is True and returns False(or 0), Otherwise].

```
1  integer i
2  set i=45
3  if( i mod 2 EQUALS 0 OR i mod 2 AND i)
4  print i mod 2
5  else
6  print i
7  end if
```

- 1

0

2

45

Q12. Consider the following algorithm:

p is a pointer to the first node of the linked list, Which of the following operations is performed by the function fun?

```
1  integer fun (Node *(p)
2  integer x= MIN_INT
3  while(p not equals NULL)
4  if (p->data < x)
5  return 0
6  else
7  x= p -> data
8  p -> next
9  end if
10 end loop
11 return x
12 end fun
```

function fun detects a loop in the linked list, it return 1 when a loop is found and 0 when no loop is found

None of the mentioned options

Functions fun finds the largest element of the linked list

Function fun checks whether a linked lists is sorted or not. It returns 0 when the list is not sorted and 1 when it is sorted

Q13. What will be the output of the following pseudocode?

```
1  integer a
2  string str1
3  set str1= " momo"
4  for (each a from 1 to 2)
5  str1= str1 + " mm"
6  end for
7  print (stringLength(str1))
```

7

4

6

11

Q14. What will be the output of the following pseudocode?

```
1  Integer value, n
2  Set value = 1, n = 45
3  while(value less than equal to n)
4    value = value << 1
```

```
5 end loop
6 Print value
```

- 16
- 32
- 64
- 36

Q15. How many times the following pseudocode will print "btech".

```
1 integer a, b
2 for(each a from 0 to 3)
3 for(each b from 0 to a)
4 print "btech"
5 end for
6 end for
```

- 3 times
- 9 times
- 10 times
- 11 times

Q16. Which of the following is used for Computer Games?

- Mouse
- Trackpad
- Joystick
- Touchpad

Q1. What will be the output of the following pseudocode for x = 4 and y = 2?

```
1  Integer fun (int x, int y)
2    if (x > 1)
3       fun (x - 2, y + 2)
4    end if
5    print y
6  End Function fun( )
```

- 4 5 6
- 9 7 5
- 7 6 5
- None of the mentioned options

Q2. What will be the output of the following pseudocode for x = 45?

245

22

2223

1022

Q5. What will be the output of the following pseudocode?

Note: The logical AND operator (&&) returns the Boolean value TRUE or and returns FALSE otherwise.

```
1  Integer x, y, 1, z
2  Set x = 11 , y = 10
3  y = y - 5
4  z = y = 3
5  1 = x AND z
6  Print z, 1
```

4 0

3 3

6 1

2 0

Q6. What will be the output of the following pseudocode for x = 108, y = 3 ?

```
1  Integer fun (Integer x, Integer y)
2     if (x > 1)
3        fun (x/y, y+3)
4        Print y
5     enf if
6  end function fun ()
```

12 9 6

9 6 3

0 6 36 108

6 12

Q7. What will be the output of the following pseudocode?

Note: subString (string, integer-1, integer-2) returns the substring from index equals integer-1 to index equals integer-2, e.g subString ("OkaY", 0,2) would return "Ok" lower(string) converts all the letters of the string to lower case, e.g lower("OkaY) would return "okay" upper(string) converts all the letters of the string to upper case, e.g upper("OkaY") would return "OKAY".

```
1  String str1 = "what" , str2 = "e"
2  Print subString (lower (str1+ upper(str2) + str 2 + str2 + str2) 1, 4)
```

- hta
- ath
- hat
- tah

Q8. What will be the output of the following pseudocode?

Note: >> - Bitwise right shift operator, takes two numbers, right shifts the bits of the first operand, and the second operand decides the number of places to shift.

```
1  Integer v, a, r
2  Set v = 5 , a = 64
3  r = a>>v
4  r = a - r
5  Print r
```

- 64
- 66
- 62
- 68

Q9. What will be the output of the following pseudocode?

```
1  char str[20]
2  Integer s
3  Set str = " ABCDEFGH "
4  s = string_length(str)
5  str[5] = NULL
6  s = strlen(str)
7  print s
```

- None of the mentioned options

6

4

5

Q10. What will be the output of the following pseudocode?

Note: &&-: Logical AND - The logical AND operator (&&) returns the Boolean value true(or 1) if both operands are true and return false (or 0) otherwise.

```
1  Integer p, q, r
2  Set p = 0, q = 3, r = 14
3  if (1< p && (q+p) >(p+q))
4     r = q + r
5  End if
6  print p + q + r
```

17

19

28

14

Q11. What will be the output of the following pseudocode?

Note: reverse(string) reverses the string, e.g. reverse ('okaY') returns 'Yako".

```
1  String str1 = "Start" , str2= "trast"
2  Print reverse(str2 + str1)
```

tratStsart

tratrat

tratstartt

tratStart

Q12. What will be the output of the following pseudocode?

```
1  Integer i
2  Set i = 0
3  Start : i= i + 12
4  Print i
5  if (i < 60)
```

```
    goto Start
else
    Print i + 1
end if
```

- 0 12 0 12 13
- 12 24 36 48 60 61
- 0 12 24 25
- 12 24 36 48 61

Q13. What will be the output of the following pseudocode?

```
Integer p , q
Set q = 280,p=0
for (each p from 1 to 4)
   q = q / 10
   p = p + q + 2
enf for
Print p
```

- 32
- 288
- 12
- 38

Q14. What will be the output of the following pseudocode?

Note: mod finds the remainder after the division of one number by another. For mod to 1 because 5 divided by 2 leaves a quotient of 2 and a reminder of 1.

```
For input a = 5 & b = 5.
 function (input a, input b)
 If (a < b)
 return function (b, a)
 elseif (b != 0)
 return (a * function (a, b - 1))
 else
 return 0
```

15625

3125

625

525

Q15. What will be the output of the following pseudocode for the input pqr?

Note: Here NULL typically means the end of the string.

```
1  fun(char a )
2    if (a[0] EQUALS NULL)
3      Return
4    end if
5    fun(a + 1)
6    fun(a + 1)
7    Print (a[0])
8  end function fun
```

rrqrrqp

ppqqrr

rqppqr

None of the mentioned options.

Q1. What will be the output of the following pseudocode?

```
1  Integer k,a,b,c,p
2  set k=8, a=1, b=2, c=3
3  p=k+b*c/k+b/c
4  if(p)
5     print a*b
6  else
7    print a/b
8  end if
```

- 4
- 3
- 2
- 0

Q2. What will be the output of the following pseudocode?

```
1  Integer a,b,c
2  Set a=4,b=4,c=4
3  for (each c from 2 to 4)
4     b=6+c
5     if((8-a+b)>(b+c))
6        b=(3+7)&b
7        a=(c+5)+b
8     Else
9        Jump out of the loop
10    End if
11    b=7+a
12 End for
13 Print a+b
```

- 31
- 20
- 24
- 27

Q3. What will be the output of the following pseudocode?

```
1  integer a, b, c
2  set a=1, b= 3, c= 2
3  if ((a&b) && (b&c) && (c&a))
4     a = a&b
5  else
6     b= b& a
7  end if
8  print a + b + c
```

8 print a + b + c

- 3
- 6
- 15
- 4

Q4. What will be the output of the following pseudocode?

```
1  Integer j, m
2  Set m=1
3  Integer a[4] = { 0,2,3,3}
4  if (a[0]+a[1]>a[2])
5     for (each j from 0 to 1)
6        if (a[j+1]>1)
7           m=1
8        Else
9           m=a[j+2]
10       End if
11    End for
12 End if
13 Print m
```

- 1
- 10
- -4
- 6

Q5. What will be the output of the following pseudocode?

```
1  Integer a,b,c
2  Set a=4,b=5,c=9
3  b=(c+6)+c
4  if((b^c^a)<(a^b))
5     b=(3+12)+c
6  End if
7  Print a+b+c
```

- 31
- 20
- 24
- 37

Q6. What will be the output of the following pseudocode?

1 Integer

```
Integer a,b,c
Set a=10, b=1, c=3
a=a+1
if (b mod c && c mod a)
   a=a+19
End if
Print a+c-b
```

- 5
- 32
- 2
- None of the mentioned options

Q7. What will be the output of the following pseudocode if a=5, b=2, and c=8?

```
Integer funn(Integer a, Integer b, Integer c)
   for (each c from 5 to 7)
      a=(b+b)^b
      a=9+b
   End for
   for (each c from 4 to 6)
      b=(a+b)^a
   End for
return a+b
```

- 67
- 54
- 57
- 58

Q8. What will be the output of the following pseudocode?

```
Integer a,b,c
Set a=4,b=2,c=15
a=a+b
b=10&b
b=(c&4)+a
Print a+b+c
```

- 31
- 28
- 40

45

Q9. What will be the output of the following pseudocode?

```
1  Integer a,b,c
2  Set a=3,b=4,c=4
3  for (each c from 4 to 8)
4     a=(b^11)+b
5     if((c-a)<(b-c))
6        b=9^b
7     Else
8        Continue
9     End if
10    b=c+b
11 End for
12 Print a+b
```

18

12

74

70

Q10. What will be the output of the following pseudocode?

```
1  Integer p, q, r
2  set p= 1, q= 1, r= 2
3  q = p - 1
4  q = r - 1
5  if (p + 2 > q -6)
6     if (q+2 > p- 6)
7        p = 2
8     end if
9     q= 2
10    if (r> 5)
11       p = q
12    end if
13 end if
14 printf p + q + r
```

3

6

10

17

Q11. What will be the output of the following pseudocode?

```
1  Integer a,b,c
2  Set a=9,b=9,c=8
3  c=c
4  if ((a+b)>(b+a)||4<a)
5     b=(b+11)^c
6     c=1
7  End if
8  Print a+b+c
```

51

19

46

38

Q12. What will be the output of the following pseudocode?

```
1  Integer a, b, c
2  Set a=1, b=4, c=6
3  c=(c+a)+a
4  a=(b+b)+c
5  c=(c^9)+a
6  a=11+a
7  Print a+b+c
```

48

51

54

44

Q13. What will the output of the following pseudocode be?

```
1  integer k, p
2  set k=24
3  p=k mod  5 + k / 10 * 10
4  if(p equals  k or p > 25)
5       if ( p equals 24 and  p <  23)
6            if (p equals 23)
7                 print p
8            end if
9            print p * p
10      enf if
11      print p * p * p
12 end if
```

It will print square of value of p

It will print square of value of p and cube of value of p

It will print cube of value of p

It will print value of p

Q14. What will be the output of the following pseudocode?

```
1  Integer a,b, c
2  Set a = 3, b = 4, c = 5
3  if ((b - c + a)< ( a - b ))
4    a = ( a + 9 ) & a
5    b = ( c & c) + a
```

```
6    if (( a + 6) >(c-a))
7     c = ( c +c) + c
8    End if
9    c = b + a
10   c = 8 + a
11  End if
12  Print a + b+c
```

- 8
- 12
- 22
- 16

Q15. What will be the output of the following pseudocode?

```
1   Integer m=0, n=13, flag=0, i
2   m = n/2
3   for(i = 2 to m)
4    if(n mod i=0)
5     flag = 1
6    go to line number 9
7    end if
8   end for loop
9   if(flag =0) // line 9
10   print n
11  else print 1
```

- 1
- 13
- 0
- 6

Q1. What will be the output of the following pseudocode?

```
1  integer i, j
2  set i=3, j=5
3  while(i>0)    //line
4  i=i-1
5  while(j<6)
6  print "Hello"
7  j=j+1
8  Go to line
9  end while
10 end while
```

- It will print Hello two times
- It will print Hello one time
- It will print Hello four times
- It will print Hello three times

Q2. What will be the output of the following pseudocode?

```
1  Integer p,q,r
2  Set p=4, q=5,r=6
3  q=3+r
4  p=q&p
5  r=q+r
6  p=p+q
7  Print p+q+r
```

- 38
- 33
- 19
- 53

Q3. What will be the output of the following pseudocode?

```
1  Integer b=7, c=1, i, j
2  for (j=2 to 3)
3     for (i = 1 to J)
4        c = c*2
5     end loop
6  end loop
7  b= b+c
8  Print b, c
```

36 43

23 16

71 64

39 32

Q4. What will be the output of the following pseudocode?

```
1  Integer a, b, c
2  set a=5, b= 11, c= 7
3  for ( each c from 2 to 3)
4  b = 9 + a
5  end for
6  print a + b
```

24

20

15

19

Q5. What will be the output of the following pseudocode?

```
1  Integer a, b, c
2  Set a=0, b=6, c=9
3  for(each c from 2 to 5)
4    a = 4 + c
5    if((c+b) <(b-c))
6      b=(b^a)+b
7      a= 10&a
8    End if
9  End for
10 Print a+b
```

24

11

19

15

Q6. What will be the output of the following pseudocode if **a=2**?

```
1  Integer fun(integer a)
2    if(a>0)
3      return a+ fun(a-1)
4    else
5      return 0
6    end if
```

```
7  End Integer fun()
```

- 6
- 5
- 3
- 4

Q7. What will be the output of the following pseudocode for **x=75**?

```
1  Integer fun(integer x)
2    if((x - 35)>(x /4))
3       return (x/2)+5
4    else
5       return fun(fun(x/2))
6    end if
7  End function fun ()
```

- 44
- 42
- 22
- 28

Q8. What will be the output of the following pseudocode?

```
1  integer a, b, c
2  set b= 300, a= 5, c= 1
3  if( b> a)
4  b= a
5  else
6  a= b
7   end if
8  for ( each b from 0 to 5)
9  a= a+ 1
10 end for
11 print a + c
```

- 15
- 13
- 1
- 12

Q9. What will the output of the following pseudocode for b = 18?

```
1  Integer calculate(integer b)
```

```
2  If (b EQUALS 1)
3  Return 0
4  Else
5  Return 5 + calculate(b/2)
6  End function calculate ()
```

- 34
- 20
- 21
- 56

Q10. What will be the output of the following pseudocode?

```
1  integer p, q, r
2  set  p=1, q=4, r=2
3  if (p ^q  > p&q )
4  r= p& q
5  else
6  r=p^ q
7  end if
8  if(q> r  &&  r>p)
9  p = q
10 end if
11 print p- q + r- 2
```

- 3
- -5
- -12
- -4

Q11. What will be the output of the following pseudocode?

```
1  Integer p,q,r
2  Set p=2, q=9, r=12
3  if((r&q)<p)
4    r=q+p
5    r=p+r
6  End if
7  Print p+q+r
```

- 18
- 23

26

33

Q12. What will be the output of the following pseudocode?

```
Integer pp,qq,rr
Set pp=5, qq=7, rr=8
for (each rr from 4 to 7)
  if ((pp-qq+rr)<(rr-pp))
    continue
  End if
  qq=pp^qq
  pp=(3+12)+rr
End for
Print pp+qq
```

54

38

35

41

Q13. What will be the output of the following pseudocode?

```
Integer p,q,r
Set p=3, q=10, r=12
p=(p+4)+q
q=q+r
Print p+q+r
```

58

72

68

51

Q14. What will the output of the following pseudocode?

```
Integer p,q,r
Set p=3, q=8, r=4
q=(r+10)+p
p=(4+6)+q
if((8&q)<(p&8))
  p=(p^1)+r
End if
Print p+q+r
```

- 51
- 49
- 53
- 58

Q15. What will be the output of the following pseudocode?

```
1  Set m=1, T=0, n=3
2  if(m>n)
3    m=m-1
4    Go to step 8
5   else
6    T = T + m
7    m = m*T
8   Go to step 2
9  Print m
```

- 12
- 18
- 7
- None of the mentioned options

Q1. What will be the output of the following pseudocode:

```
1  Integer a,b,c
2  Set a=7,b=7,c=9
3  if ((a^b^c)>(b^a))
4     c=b&b
5  End if
6  Print a+b+c
```

- 23
- 21
- 24
- 27

Q2. What will be the output of the following pseudocode?

```
1  Start
2     Integer p, q, r
3     Set p = 0, q = 8, r = 4
4
5     For each r from 5 to 8
6        Set q = 5 + 12 + p
7        If (r - q - p) < (3 - r) Then
8           Set p = q + p
9        Else
10          Set q = p
11       End If
12    End For
13
14    Print p + q
15 End
```

- 291
- 290

391

390

Q3. What will be the output of the following pseudocode?

```
1  Integer p , q , r , s
2  Set p = 15, q = 0, r = 60, s = 0
3  while ((r MOD p ) EQUALS 0)
4     s = ( s+2) * 2
5     q = q + p
6     while (s < 50 )
7       Print s
8       q = q - 1
9        s = s + q
10    end while
11    p = p -3
12 end while
13 print q
```

4 28 60 23

19 27 54 63 23

4 18 31 43 23

4 18 31 43 26

Q4. What will be the output of the following pseudocode?

```
1  Integer j, m
2  Set m=2
3  Integer a[4] = {2,1,1,2}
4  m=m^a[2]
5  if (a[1]>1)
6     m=m^1
7  Else
8     m=m^2
9  End if
10 Print m
```

8

-1

1

12

Q5. What will be the output of the following pseudocode if p=5, q=10, r=15?

```
1  void fun(Integer p, Integer q, Integer r)
2  p= p>>1
3  q= q>>1
4  r= r>>1
5  p= p>>1
6  q= q>>1
7  r= r>>1
8  Print p+q+r
9  End function fun()
```

7

5

6

10

Q6. What will be the output of the following pseudocode?

```
Integer c, d, e
Set d = 22
for(each c from 2 to 6)
  d= d+c
  e= c+d
end for
e=d/5
Print c,d,e
```

6 41 7

6 42 40

7 42 8

7 41 40

Q7. What will be the output of the following pseudocode?

```
Integer a,b,c
Set a=6,b=6,c=7
for (each c from 3 to 5)
   a=(8+4)+a
End for
c=(6+5)+a
for (each c from 5 to 7)
   b=(3&7)+b
   a=a^b
End for
Print a+b
```

47

45

56

53

Q8. What will be the output of the following pseudocode?

```
Integer p, q, r
set p=1, q=1, r=1
if (0 | | 1 | | 1 )
   p= p & 1
else
   r = r & 1
```

```
7  end if
8  print p + q + r
```

- 18
- -1
- 10
- 3

Q9. What will be the output of the following pseudocode when i=5?

```
1  Integer fun ( Integer i)
2    if((i/2) < (i MOD 2))
3     return i + 1
4    else
5     return fun(fun (i-6))
6   end if
7  End function fun()
```

- -6
- -4
- 12
- 13

Q10. What will be the output of the following pseudocode?

```
1  Integer a,b,c
2  Set a=9,b=6,c=6
3  for (each c from 5 to 9)
4     if((c+a)>(a-c))
5        a=(b+c)+a
6        b=7&c
7     End if
8     a=a^c
9  End for
10 Print a+b
```

- 47
- 75
- 60
- 58

Q11. What will be the output of the following pseudocode?

```
1  Integer a,b,c
```

```
2  Set a=7,b=5,c=5
3  for (each c from 4 to 5)
4    if (c>b)
5      Jump out of the loop
6    End if
7    b=a+b
8    b=(b+a)+c
9  End for
10 Print a+b
```

- 49
- 50
- 61
- 44

Q12. What will be the output of the following pseudocode when a=2 and b=7?

```
1  Integer funn(Integer a, Integer b)
2    if (b>a && b>6)
3      return funn(b,a)+funn(b,1)
4    End if
5    return 1
```

- 16
- 3
- 2
- -2

Q13. What will be the output of the following pseudocode?

```
1  Integer a,b,c
2  Set a=2,b=7,c=4
3  a=(c&b)^a
4  if ((c+5)<(5+c)
5    c=(c+c)+b
6    b=(10+3)^b
7    c=(b^a)^a
8  End if
9  Print a+b+c
```

- 20
- 16
- 17

24

Q14. What will be the output of the following pseudocode for x = 108 and y = 3?

```
1  Integer fun (Integer x, Integer y)
2    if (x > 1)
3       fun (x/y, y+3)
4       Print y
5    enf if
6  end function fun ()
```

12 9 6

9 6 3

0 6 36 108

6 12

Q15. What will be the output of the following pseudocode?

```
1  Integer p,q,r
2  Set p=5, q=8, r=6
3  p=p+q
4  p=(6+5)+p
5  for(each r from 2 to 6)
6   p=r+q
7   if((p+r)>(q-p) OR r<q)
8    q=(r&p)^p
9    Continue
10  End if
11 End for
12 Print p+q
```

40

22

44

33

Q1. What will be the output of the following pseudocode?

```
1  Integer a,b,c
2  Set a=0,b=4,c=8
3  if ((c+a+b)>(b-c))
4     b=(c+c)+a
5     c=(c+c)+a
6  End if
7  if ((c^a^b)<(b^c))
8     a= 3 & a
9  End if
10 Print a+b+c
```

- 32
- 38
- 33
- 29

Q2. What will be the output of the following pseudocode?

```
1  Integer p,q,r
2  Set p=4, q=2, r=12
3  for(each r from 4 to 6)
4     p= (r+7)+p
5     q= (q&11)+p
6  End for
7  for (each r from 2 to 4)
8     q= (4+9)+r
9  End for
10 Print p+q
```

- 56
- 62
- 57
- 60

Q3. What will be the output of the following pseudocode?

```
1  Integer j, m
2  Set m = 2
3  Integer a[4] = { 2,1,1,2 }
4  m = m^a[2]
5  if (a[1]>1)
6     m = m^1
7  Else
8     m = m^2
9  End if
10 Print m
```

8

12

1

-1

. What will be the output of the following pseudocode for x = 23 and y = 222?

```
Integer fun1 (Integer x, Integer y)
  while (y NOT equals 0)
    Integer c = x & y
    x = x ^ y
    y = c << 1
  end while
  return x
End function fun1()
```

245

22

2223

1022

. What will be the output of the following pseudocode?

```
Integer p, q, r
Set p=2, q=6, r=5
q=q+p
r=p+p
p=r+q
p=(r+q)&q
Print p+q+r
```

20

8

30

24

. What will be the output of the following pseudocode?

```
Integer p, q, r
Set p = 0, q = 3, r = 14
if (1<p && (q+p) >(p+q))
   r = q + r
End if
print p + q + r
```

17

19

28

14

Q7. What will be the output of the following pseudocode?

```
1  Integer p,q,r
2  Set p=5, q=8, r=8
3  for (each r from 4 to 5)
4   if((1+9)<(10-p))
5     p=p+q
6   End if
7   p= (p+r)+r
8   q=(12&11)+p
9  End for
10 Print p+q
```

51

54

62

56

Q8. What will be the output of the following pseudocode for **x = 343**?

```
1  Integer fun (Integer x)
2     if ((x MOD 10) EQUALS (x / 10))
3        return (x / 7)
4     else
5        return fun (fun (x/7))
6     end if
7  end function fun()
```

3

1

4

0

Q9. What will be the output of the following pseudocode?

```
1  Integer j,m
2  Set m=1
```

```
Integer a[4]={9,1,3,4}
if(a[0]>a[1])
    m=m+a[3]+a[2]-a[1]-a[0]
End if
Print m
```

- 5
- 9
- -3
- -2

Q10. What will be the output of the following pseudocode?

```
Integer a,b,c,d
Set a=7,b=1,c=2
while ((a*a)>(2*a*b)
    d=a+b+12
    a=a+2
    b=b+2
end while
Print d
```

- 23
- 20
- 25
- 28

Q11. What will be the output of the following pseudocode for a=6, b=4, and c=9?

```
Integer funn(Integer a, Integer b,Integer C)
    if (a>c || (9^5)<a)
        a=2+a
        c=b+a
    End if
return a+b+c
```

25

19

14

30

Q12. What will be the output of the following pseudocode?

```
Integer a[],k,t,m
Set a[]={25,20,30,18,17}
Set t=0
for (each k from 0 to 4)
   t=t+a[k]
   if(t mod 2 EQUALS 1)
      Print true
   otherwise
      Print false
   end if
end for
m=t/5
Print m
```

true true true true false
22

false true true true false
20

true false true true false
15

true false true true false
20

Q13. What will be the output of the following pseudocode for a=8,b=3, and c=5?

```
Integer funn(Integre a, Integer b,Integer c)
   a=(b+c)&c
   a=(a+6)+c
   a=2+a
   a=(3+5)+a
   b=(b+8)+a
   return a+b+c
end function funn()
```

75

44

58

64

```
Integer x, y, l, z
Set x = 11 . v = 10
```

```
3  y = y - 5
4  z = y = 3
5  I = x AND z
6  Print z, I
```

- 4 0
- 3 3
- 6 1
- 2 0

Q15. What will be the output of the following pseudocode?

```
1  Integer p,q,r
2  Set p=2, q=8, r=7
3  p=(q+1)+q
4  if((p^q^r)<(q+r+p))
5    r=(12+12)^p
6    p=(p&p)+r
7  End if
8  Print p+q+r
```

- 53
- 43
- 41
- 49

Q1. What will be the output of the following pseudocode?

```
1  Integer a, b, c
2  Set a=9, b=4, c=15
3  a= (c+9)^b
4  b= (a+9)+a
5  a= 3^b
6  Print a+b+c
```

- 143
- 147
- 156
- 146

Q2. What will be the output of the following pseudocode?

```
1  Integer p,q,r
2  Set p=6, q=7, r=6
3  if(p>q || q<r)
4    r = 12+p
5    q=(q+r)+q
6  End if
7  Print p+q+r
```

- 56
- 19

55

68

Q3. What will be the output of the following pseudocode?

```
1  Integer v, a, r
2  Set v = 5 , a = 64
3  r = a >> v
4  r = a - r
5  Print r
```

64

66

62

68

Q4. What will be the output of the following pseudocode?

```
1  Integer a,b,c
2  Set a=0,b=11,c=10
3  for (each c from 4 to 6)
4     a=(3+4)+b
5     b=a&a
6  End for
7  b=(c+c)+b
8  Print a+b
```

78

69

88

84

Q5. What will be the output of the following pseudocode?

```
1  Integer p,q,r
2  Set p=5, q=4, r=9
3  r=(5+11)+r
4  q=(p+q)^q
5  if(9>q || (1-3)>(r+1))
6     p=p+r
7     r=(p+7)+r
8  End if
9  r= (9+7)+q
10 r=(6&9)^r
11 Print p+q+r
```

50

59

47

43

Q6. Consider the following pseudocode. Predict the output for the given pseudocode if input n=4.

```
1  function (input n){
2     if (n<2)
3        return n;
4     else  return function(n-1)+function(n-2);
5  }
```

8

7

2

3

Q7. What will be the output of the following pseudocode for a=1 and b=5?

```
1  Integer funn(Integer a, Integer b)
2     if (a&b>0)
3        return 1+funn(b-1,a)
4     Else
5        return a+b
6     End if
7  return b^a
```

19

0

14

6

Q8. What will be the output of the following pseudocode?

```
1  Integer p, q, r
2  Set p= 5, q = 5, r = 10
3  For (each r from 4 to 8)
4     q = (5^7) + p
5     if ((3^4) < r)
6       jump out of the loop
7     Else
```

```
8       p= p+r
9     End if
10  End for
11  Print p+q
```

- 50
- 64
- 57
- 56

Q9. What will be the output of the following pseudocode?

```
1  Integer p,q,r
2  Set p=4, q=7, r=8
3  q=(9+4)+r
4  r=p+p
5  r=(9^4)+q
6  p=10&q
7  Print p+q+r
```

- 60
- 55
- 52
- 57

Q10. What will be the output of the following pseudocode for a=3 and b=5?

```
1  Integer funn(Integer a, Integer b)
2    if (a>5 || b>5)
3       a=10
4       b=10
5       a=a+10
6       b=b+10
7       a=a+b
8       b=b+a
9       return a+b
10   Else
11      return funn(b+2,a+2)
12   End if
```

- 89
- 101
- 100
- 110

Q11. What will be the output of the following pseudocode?

```
Integer a,b,c,z
Set a=10, b=20, z=1
if((a>>2) > (b>>1))
   z=z+1
end if
if((a>>1) < (b>>2))
   z=z+1
end if
Print z
```

- 1
- 2
- 3
- None of the mentioned options

Q12. What will be the output of the following pseudocode for a=9 and b=3?

```
Integer funn(Integer a, Integer b)
   if (b<a)
      return funn(a-b,b+b)
   End if
   return b-a
```

- -18
- 15
- 0
- 7

Q13. What will be the output of the following pseudocode?

```
Integer a,b,c
Set a=8,b=5,c=8
if ((b+c)<(c-b))
   a=(c+c)+a
   b=c+a
   a=(c&b)+c
End if
a=(2+11)+b
Print a+b+c
```

- 32
- 31
- 49

24

Q14. What will be the output of the following pseudocode when **fun(10,12)** is called from the main fur

```
1  Integer function fun(int a, int b)
2  while( a not equals to b)
3    if (a>b)
4     return fun (a-b, b)
5    else
6     return fun (a, b-a)
7    end if
8  end while
9  return a
10 End function fun()
```

3

0

2

4

Q15. What will be the output of the following pseudocode?

```
1  Integer j, m, a[]
2  Set a[]={2,3,5,7,1}
3  m=a[0]
4  For (each j from 0 to 4)
5     if (m<a[j])
6        m=a[j]
7     End if
8  End for
9  Print m
```

7

5

2

10

Q16. What will be the output of the following pseudocode?

```
1  Integer q
2  Set q=0
3  for( each q from 0 to 8)
4    q = q+1
5    if(q EQUALS 6)
6      jump out of the loop
7      Print "Successful"
8    end if
9  end for
10 Print q
```

Successful

Successful
6

6

9

Q17. What will be the output of the following pseudocode for x = 4 and y = 2

```
1  Integer fun (int x, int y)
2    if (x > 1)
3       fun (x - 2, y + 2)
4    end if
5    print y
6  End Function fun()
```

4 5 6

9 7 5

7 6 5

None of the mentioned options

Q18. What will be the output of the following pseudocode for a=4 and b=1?

```
1  Integer funn(Integer a, Integer b)
2    if (a > b && (b == (a > 0)))
3       return b + funn(a - b + a + a + a, b - b - b - b + a)
4    End if
5    if (1 > b && a)
6       return a - b
7    End if
8    return a
9
```

5

16

13

Infinite recursive call

Q19. What will be the output of the following pseudocode?

```
1  Integer a,b,c
2  Set a=8,b=4,c=15
3  c=b^a
4  a=7+a
5  a=(a&c)+b
6  Print a+b+c
```

32

28

41

33

Q15. What will be the output of the following pseudocode when a=12 and b=6?

```
1  Integer funn(Integer a, Integer b)
2    if(a+10>b || a>20)
3      return funn(a-10, a+10)
4    End if
5    return a + b + 10
```

34

32

36

None of the mentioned options

Q16. What will be the output of the following pseudocode for a=5 and b=2?

```
1  Integer funn(Integer a, Integer b)
2    if (b<a)
3       a=1
4       b=b+a
5       return funn(a,b+a)
6    End if
7  return a+b+1
```

9

3

6

14

Q17. What will be the output of the following pseudocode?

```
1  Integer p,q,r
2  Set p=4, q=2, r=7
3  q= (7+5)+r
4  r=(p+5)+r
5  if((q+5)<(5-q))
6    p=(r+r)+q
7    r=p+p
8  End if
9  Print p+q+r
```

41

49

36

39

Q18. What will be the output of the following pseudocode?

```
1  Integer a,b,c
2  Set a=2,b=4,c=10
3  b=(7^12)&a
4  b=9&a
5  if ((c+b)<(10-c))
6     b=2^c
7     b=(c^a)+b
8     b=(2+12)^b
9  End if
10 Print a+b+c
```

12

27

13

7

Q19. What will be the output of the following pseudocode for a=2 and b=8?

```
1  Integer funn(Integer a, Integer b)
2     if (a+10>b || a>20)
3        return funn(a+10,a-10)
4     End if
5     return a+b+10
```

24

11

14

None of the mentioned options

Q20. What will be the output of the following pseudocode?

```
1  Integer p, q, r
2  Set p=0, q=4, r=8
3  for(each r from 3 to 7)
4    if((q-r)<(r+q))
5      jump out of the loop
6    End if
7    p=(6+3)+r
8    p=(q+r)+r
9  End for
10 Print p+q
```

2

8

4

10

Q21. What will be the output of the following pseudocode for a=1 and b=4?

```
1  Integer funn(Integer a, Integer b)
2    if (2>a)
3      return funn(a+1,a+2) + funn(a+3,a+4)
4    End if
5  return a+1
```

8

5

13

20

Q22. What will be the output of the following pseudocode?

```
1  Integer p,q,r
2  Set p=1, q=9, r=10
3  p=(12 & 8) + p
4  q= (p^6) & p
5  r = 2 +q
6  Print p+q+r
```

37

29

25

46

Q23. What will be the output of the following pseudocode for a=4?

```
1  function(input a){
2     if (a>=1)
3        return a*function(a-1);
4     else
5        return 1;
6  }
```

18

24

27

6

Q24. What will be the output of the following pseudocode?

```
1  Integer pp, qq, rr
2  Set pp = 2, qq= 5, rr = 6
3  qq = (6&4) + rr
4  qq = (10&6) + pp
5  pp = 9 + rr
6  Print pp + qq + rr
```

3

41

25

30

Q25. What will be the output of the following pseudocode for a=2, b=3, and c=0?

```
1  Integer funn(Integer a, Integer b,Integer c)
2     for (each c from 2 to 3)
3        b=(1+1)^a
4     End for
5     a=(4+6)^a
6     return a+b
7  End function funn()
```

203

109

104

101

Q26. Which of the statements given in the options is correct regarding the following pseudocode?

```
if(x > y):
   if(z > y):
      if(z == x):
         print ("two");
      else:
         print ("one");
   else:
      print ("three");
else:
   print ("four");
```

It will print one if x=15, y =110, z=92

It will print one if x=5, y =10, z=9

It will print three If x=9, y=8, z=10

It will print three If x=9, y=8, z=6

Q27. What will be the output of the following pseudocode?

```
Integer a, b, c, d
Set b=343
for (each a from 1 to 4)
   c=b MOD 10
   d=b/10
   a=a+c+d
end for
Print a
```

45

41

39

None of the mentioned options

Q28. What will be the output of the following pseudocode?

```
Integer p, q, r, s, t
Set q = 81, r = 10
while (q>r)
   p = q + r
   s = p / 10
   t = s * s
   q = q / 3
end while
if (t > s)
   Print s
else
   Print t
end if
```

9

12

3

6

Q29. What will be the output of the following pseudocode?

```
1  Integer a, b, c
2  Set a=8, b=2, c=4
3  if((a^c)<b))
4   if((a+c)<(c-a))
5     a=9+c
6     if((c+8)<(8-c))
7       c=(c+c)+b
8       c=c+a
9     End if
10    End if
11  End if
12  b=(4^3)+c
13  Print a+b+c
```

30

33

23

20

Q30. What will be the output of the following pseudocode for n = 243?

```
1  Integer abc (int n, int b)
2     Integer a, b
3     if (n > 0)
4        a = n mod 10
5        b = b + a
6        return abc(n/10, b)
7     else
8        return b
9  End abc ()
```

2

9

3

342

Q1. **Problem Statement**

You are given an integer array **coins** representing coins of different denominations and an integer amount representing a total amount of money. Return the fewest number of coins that you need to make up that amount. If that amount of money cannot be made up by any combination of the coins, return -1. You may assume that you have an infinite number of each kind of coin.

Example 1

Input:
1 2 5
11
Output:
3
Explanation:
11 = 5 + 5 + 1

Example 2

Input:
2
3
Output:
-1

Input Format

The first line of input consists of denominations of coins separated by spaces.
The second line consists of the amount for which you want to make the change.

Output Format

The output displays the number of coins needed to make up the given amount.

Refer to the sample output for formatting specifications.

Constraints

$1 \le coins.length \le 12$
$0 \le amount \le 10^4$

Sample Input **Sample Output**

```
1 2 5
11
```

```
3
```

Sample Input **Sample Output**

```
1
0
```

```
0
```

Sample Input **Sample Output**

```
2
3
```

```
-1
```

Time Limit: - ms Memory Limit: - kb Code Size: - kb

Q2. **Problem Statement**

Given two strings, **word1, and word2**, return the minimum number of operations required to convert word1 to word2.

You have the following three operations permitted on a word:

1. Insert a character
2. Delete a character
3. Replace a character

Example 1
Input:
horse
ros

Output:
3

Explanation:
horse -> rorse (replace 'h' with 'r')
rorse -> rose (remove 'r')
rose -> ros (remove 'e')

Example 2
Input:
intention
execution

Output:
5

Explanation:
intention -> inention (remove 't')
inention -> enention (replace 'i' with 'e')
enention -> exention (replace 'n' with 'x')
exention -> exection (replace 'n' with 'c')
exection -> execution (insert 'u')

Input Format

The input consists of two strings, word1, and word2, which represent the two words for which the minimum edit distance needs to be calculated.

Output Format

The output displays the minimum edit distance between the two words.

Refer to the sample output for the formatting specifications.

Constraints

In the given scenario, the test cases will fall under the following constraints:
0 ≤ word1.length, word2.length ≤ 100
word1 and word2 consist of lowercase English letters.

Sample Input **Sample Output**

```
horse
ros
```

```
3
```

Sample Input **Sample Output**

```
intention
execution
```

```
5
```

Time Limit: - ms Memory Limit: - kb Code Size: - kb

70

Q2. What will be the output of the following pseudocode?

```
1  Integer j, m
2  Set m=1
3  Integer a[4] = { 0,2,3,3}
4  if (a[1]<1)
5     if ( a[2]<2)
6        m=a[3]
7     Else
8        m=a[1]
9     End if
10    m=m^a[1]
11 End if
12 Print m
```

5

0

1

12

Q3. What will be the output of the following pseudocode?

```
1  Integer i
2  Set i = 3
3  do
4     print i + 3
5     i = i - 1
6  while(i not equals 0)
7  end do while
```

6 6 6

6 5 6

5 5 5

6 5 4

Q4. What will be the output of the following pseudocode for a=4, b=3, and c=8?

```
1  Integer funn(Integer a, Integer b,Integer c)
2     for (each c from 5 to 9)
3        a=(c^5)^a
4        if(b^c^a)<(c&a&b)
5           b=(1&11)&c
6        Else
7           Continue
8        End if
9        b=(c+2)+a
10    End for
11 return a+b
```

16

0

7

19

Q5. What will be the output of the following pseudocode?

```
1  Integer a,b,c
2  Set a=3,b=4,c=5
3  if ((b-c+a)<(a-b)
4     a=(a+9)&a
5     b=(c&c)+a
6     if ((a+6)>(c-a))
7        c=(c+c)+c
8     End if
9     c=b+a
10    c=8+a
11 End if
12 Print a+b+c
```

16

8

22

12

Q6. What will be the output of the following pseudocode f(x) x =777

```
1  Integer fun(Integer x)
2     if (x > 12)
3        fun (x / 9)
4        print x
5     else
6        for (each i from 1 to 3)
7           x = x + i
8           print x
9        end for
10    end if
11 end Function fun()
```

11 13 14 85 777

12 14 15 86 777

10 12 15 86 777

10 12 13 85 777

Q7. What will be the output of the following pseudocode?

```
1  Integer a,b,c
2  Set a=3,b=2,c=10
3  for (each c from 3 to 7)
4     b=3+b
```

```
5     a=(11+1)^c
6   End for
7   c=6+a
8   a=b+c
9   for (each c from 3 to 4)
10    a=(b+12)+b
11  End for
12  Print a+b
```

- 60
- 68
- 72
- 63

Q8. What will be the output of the following pseudocode?

```
1   Integer a,b,c,d,i
2   Set a=1, b=0,c=6,d=7
3   for (each i from 0 to 3)
4     if (a||b||(c && d))
5       print a++
6     end if
7     if (a equals 2)
8       print a++
9     end if
10    if (a equals 1)
11      jump out of the loop
12    end if
13  end for
14  print "journey"
```

- 1 2 journey
- 1 2 3 4 5
- 1 2
- 1 2 3 4 5 journey

Q9. What will be the output of the following pseudocode?

```
1   Integer a,b,c
2   Set a=9,b=2,c=13
3   a=(a+2)+a
4   c=10&b
5   a=(c&c)+c
6   Print a+b+c
```

- 5
- 8
- 12

13

Q10. What will be the output of the following pseudocode?

```
Integer j, m
Set m=0
Integer a[4] = { 3,0,2,1}
for (each j from 0 to 3)
   if (a[j])
      m=a[j]
   End if
   if (j)
      m=a[j]+1
   End if
End for
Print m
```

2

5

1

8

Q11. What will be the output of the following pseudocode?

```
Integer pp, qq,rr
Set pp=6, qq=8, rr=8
for(each rr from 2 to 3)
  if((pp-rr)<(rr+pp))
    qq=qq+pp
  End if
  qq=qq+pp
  pp=10&pp
End for
Print pp+qq
```

22

37

30

26

Q12. What will be the output of the following pseudocode?

```
Integer a, b, c
Set a=0, b=9, c=5
a=(c+12)^b
if((b+c)>(c-b) || 3>b)
  b= (11+5)&b
End if
b=1&c
Print a+b+c
```

40

30

31

25

Q13. What will be the output of the following pseudocode?

```
1  Integer p,q,r
2  Set p=9, q=6, r=5
3  p=(r&5)^r
4  p=(q+q) + q
5  q = 10 ^p
6  Print p+q+r
```

47

46

57

56

Q14. What will be the output of the following pseudocode?

```
1  Integer arr[] = {10,7,2,6,1,2,3}
2  Integer sum , x
3  Set sum =0
4  for(each x from 0 to 6)
5   if(arr[-1] mod 3 >1)
6     sum = sum +arr[x]
7   End if
8  End for
9  Print arr[4]
```

4

9

1

5

Q15. What will be the output of the following pseudocode?

```
1  Integer p,q,r
2  Set p=9, q=10, r=6
3  q=8+q
4  if((p>r || ((q+r) > (r-q)))
5     p=(p&12)+p
6  End if
7  p=(r+4)^r
8  Print p+q+r
```

37

36

44

32

Q16. What will be the output of the following pseudocode if the value of n=5 and v=1, 2, 3, 4, 5?

```
Integer n, s, c, v
Set n=5, s=0
for(each c from 1 to n)
    Read the value of v
    s=s+v
    s=s+n
end for
Print s
```

22

25

45

40

Q17. What will be the output of the following pseudocode?

```
Integer a , b, c
Set a=1, b=4, c=8
if(b>c OR (a+b)<(b-a))
   a= (7+10) + a
   b= (8+5) + a
End if
Print a + b + c
```

13

26

17

8

Q18. What will be the output of the following pseudocode?

```
Integer p,q,r
Set p=3, q=8, r=10
for(each r from 3 to 7)
   q= (11+9)+q
   p= 12+p
End for
```

```
7   for(each r from 2 to 4)
8     q=(7+4)^q
9   End for
10  Print p+q
```

- 183
- 172
- 160
- 166

Q19. What will be the output of the following pseudocode?

```
1  integer a1, p1
2  set a1= 15
3  a1= a1- 1
4  a1= a1 * 2 + 8
5  a1= a1 / 2 + 9 * 5
6  p1 = a1 / 5 + 6
7  print p1
```

- 18
- 23
- 19
- 3

Q1. What will be the output of the following pseudocode?

```
1  Integer p,q,r
2  Set p=7,q=2,r=6
3  p=r+q
4  q=p^p
5  for (each r from 3 to 5)
6     p=(q+8)+p
7     if ((p-r)>(r+p)||q>r)
8        p=(8+3)+p
9        q=(r+r)+q
10       continue
11    End if
12 End for
13 Print p+q
```

- 32
- 50
- 27
- 41

Q2. What will be the output of the following pseudocode?

```
1  Integer p,q,r
2  Set p=3, q=7, r=8
3  p=9+r
4  if((p+r)<(r-q))
5    q=(q+r)+p
6  End if
7  Print p+q+r
```

- 26

32

37

46

Q3. What will be the output of the following pseudocode for a=9, b = 7?

```
1  integer funn(integer a, integer b)
2  integer c
3  set c=2
4  b= b MOD c
5  a= a MOD c
6  return a+b
7  end function funn( )
```

17

5

-5

2

Q4. What will be the output of the following pseudocode?

```
1  Integer a,b,c
2  Set a=9,b=11,c=9
3  if (b>c && (c+a)>(a-c))
4     c=(c^10)+c
5  End if
6  Print a+b+c
```

37

30

32

41

Q5. What will be the output of the following pseudocode?

```
1  Integer array1[6], p,j,q
2  Set p=3
3  Set array1[6]={ 3,6,10,12,23,33}
4  for (each j from 0 to 5)
5     if((array1[j] MOD p) EQUALS 0)
6        p=array1[j]-p*3
7     end if
8  q=p+array1[j]-3
9  end for
10 Print q
```

54

64

44

34

Q6. What will be the output of the following pseudocode?

```
1  Integer p , q
2  Set q = 280,p=0
3  for (each i from 1 to 4)
4     q = q / 10
5     p = p + q + 2
6  end for
7  Print p
```

32

288

12

38

Q7. What will be the output of the following pseudocode?

```
1   Integer p,q,r
2   Set p=1, q=5, r=10
3   if((r-q+p) > (p+r))
4      p=q+p
5   End if
6   if((r-7)< (7+r))
7      p=(r+r)+p
8      r=p+q
9   End if
10  Print p+q+r
```

51

56

63

52

Q8. What will be the output of the following pseudocode when funn(2,6,11) called?

```
1  Integer funn( Integer a, Integer b, Integer c)
2    for(each c from 2 to 3)
3      a = 3 + a
4      if(b > a)
5       b= 5 + 3 ) + a
6     End if
```

```
7  End for
8  return a + bQ
```

- 32
- 29
- 19
- 24

Q9. What will be the output of the following pseudocode?

```
1  integer a, b,c
2  set b=3, a= 5, c=1
3  if( b < a )
4  b= a
5  end if
6  for(each b from 0 to (1^2^3))
7  b= b + 1
8  end for
9  print b
```

- 6
- 5
- 2
- 1

Q10. What will be the output of the following pseudocode if **a=0** and **b=0**?

```
1   Integer funn(Integer a, Integer b)
2     for (each c from 1 to 6)
3       a=(b+5)+c
4       if((b+c)<(a&b))
5         b=(9&b)
6       Else
7         continue
8       End if
9       c=(b+3)+a
10    End for
11  return c+a
```

- 15
- 17
- 19
- 18

Q11. What will be the output of the following code?

```
1  Function m()
```

```
Function m()
print hi
End Function

Function main()
m();
End main
```

- hi
- Compile Time Error
- Nothing
- Varies

Q12. What will be the outputs of the following pseudocode if a=25 and a=16 are executed separately?

```
integer a
if((a mod 10) IS EQUAL TO 0)
   a=a*2
else if((a mod 5 ) IS EQUAL TO 0)
   a=a/5
else
   a=a-1
end if
print a
```

- a=5 and a=15
- a=15 and a=20
- a=25 and a=15
- a=35 and a=25

Q13. What is the output of this code?

```
Declare integer x=0
if (x EQUALS TO 0)
Print true,
Elseif (x EQUALS TO 10)
Print false,
Print x
```

- false,0
- true,0
- true,10

Compile time error

Q14. What will be the output of the following algorithm?

```
1  Start
2  Declare a, I and b
3  for I =0 to 4
4  Increment a by 1
5  if I = 3 then
6  print hello
7  get out of the loop
8  End if
9  End for
10 print a
```

4

1

hello4

hello

Q15. What will be the output of the following pseudocode?

```
1  Integer a,b,count,count1
2  Set a=1, b=1
3  while(a<=5)
4  b=1
5  while(b<=5)
6  b=b+1
7  count1 = count1 + 1
8  end while
9  a= a + 1
10 count = count +1
11 End while
12 Print count, count1
```

count=5 count1=25

count=45 count1=25

count=50 count1=5

count=50 count1=25

Q16. What will be the output of the following pseudocode?

```
1  Input f = 6,g = 9 and set sum = 0
2  Integer n
3  if (g > f)
4  for(n=f; n<g; n=n+1)
5  sum=sum+n
6  End of loop
7  else
8  print Error messages
9  print sum
```

21

15

9

2

Q16. What will be the output of the following pseudocode if n=40 and LIMIT=100 ?

```
1  Integer fun2(Integer n);
2  if(n < +0)
3  return 1;
4  if(n > LIMIT)
5  return 2;
6  Print n
7  fun2(2*n);
8  Print n
9  End function fun2()
```

10 20 20 10

20 40 40 20

40 80 80 40

80 120 120 80

Q17. What will be the output of the following code?

```
1  Class Automobile
2     Private Method drive()
3        Return "Driving vehicle"
4
5  Class Car inherits Automobile
6     Protected Method drive()
7        Return "Driving car"
8
9  Class ElectricCar inherits Car
10    Override Final Method drive()
11       Return "Driving an electric car"
12
13    Method main(wheels)
14       Create final instance of Car as ElectricCar
15       Print car.drive()
```

Driving vehicle

Driving an electric car

Driving car

The code does not compile

Q18. What will be the value of t if a = 56 and b = 876?

```
1  Read a,b
2  Function mul(a, b)
3  t = 0
4  while (b != 0)
5  t = t + a
6  b=b-1
7  End While
8  return t;
9  End Function
```

490563

49056

490561

None of the mentioned options

Q19. What will be the output of the following code?

```
1  Function fact(int n)
2  Integer result;
3  if n is equal to 1
4   then return 1;
5  End if
6  result = fact(n-1) * n;
7  return result;
8  End recursion
9
10 class output
11 Function main
12 create a recursion object obj;
13 print obj.fact(1);
14 End main
15 End output
```

0

1

undefined

None of the mentioned options

Q20. What will be the output of the following code?

```
1  Class One
2     Constructor One()
3        Print "One"
```

```
3       Print "One,"
4
5   Class Two inherits One
6     Constructor Two()
7       Print "Two,"
8
9   Class Three inherits Two
10    Constructor Three()
11      Print "Three"
12
13  Class Test
14    Method main(args)
15      Create instance of Three
```

- Three
- One
- One,Two,Three
- Run-time error

Q21. What is the output for the following pseudocode?

```
1   Class Dog:
2     Attribute name (String)
3
4     Method bark:
5       Print "Woof!"
6
7   Class Test:
8     Method main:
9       Declare variable myDog of type Dog
10      Assign a new Dog object to myDog
11      Set myDog's name attribute to "Buddy"
12      Call the bark method on myDog
```

- Woof!
- Woof!
Buddy
- Buddy
Woof!
- Buddy

Q22. What is the output for the following code?

```
1   Class Math
2     Public Final Variable secret = 2
3
4   Class ComplexMath inherits Math
5     Public Final Variable secret = 4
6
7   Class InfiniteMath inherits ComplexMath
8     Public Final Variable secret = 8
9
10    Method main(numbers)
11      Create instance of Math as InfiniteMath
12      Print math.secret
```

2.0

4.0

8.0

Compile Time Error

Q23. What will be the output of the following pseudocode for x=3 and y=4?

```
1  integer fun(int x, int y)
2  if(x>0)
3  fun(x-1,y+1);
4  End if
5  Print y
6  End function fun()
```

8 5 4 2

7 6 5 4

2 0 1 4

5 0 3 4

Q24. What is the output for the following pseudocode?

```
1  Class Animal:
2    Attribute name (String)
3
4    Method speak:
5      Print name + " makes a sound."
6
7  Class Main:
8    Method main:
9      Declare variable dog of type Animal
10     Assign a new Animal object to dog
11     Set dog's name attribute to "Dog"
12     Call the speak method on dog
```

Dog makes a sound.

makes a sound.

Dog

Compile Time Error

Q25. What is the output of the following code?

```
1  Declare integer k = 0;
2  for (k)
3  Print Hello
```

Compile Time Error

Hello

No output

Runtime Error

Q26. What is the output of this code?

```
1 Declare integer a=10,c
2 Declare double b=5.6
3 c=a+b
4 Print c
```

15

15.6

16

10

Q27. What is the output of the following function for a start point to the first node of the following linked list? 1->2->3->4->5->6

```
1 fun(struct node* start)
2 if start = Null
3 return;
4 print start->data
5 if start->next != NULL
6 call fun(start->next->next)
7 print start->data
```

1 4 6 6 4 1

1 3 5 1 3 5

1 2 3 5

1 3 5 5 3 1

Q28. What will be the output of the following pseudocode?

```
1 Integer a,b,c
```

```
set a= 0, b= 5, c=12
if (3<c)
a= 10 & c
end if
if ((c - a + b) > (b - c))
a= ( a + 6 ) + c
c = ( a = a ) & b
end if
print a + b + c
```

- 32
- 40
- 35
- 50

Q29. What will be the output of the following pseudocode?

```
Integer a,b,c
Set a=0
for (each b from 0 to 10)
   a=a+b
   if (a MOD 4 EQUALS 0)
      Print "True"
      Jump out of the loop
   end if
end for
Print b
```

- 0
- 0
  1
- True
  0
- None of the mentioned options

Q30. What will be the output of the following pseudocode?

```
Integer p,q,r
Set p=1, q=3, r=8
p=3^1
if((r^3)<8 && (4^6)<r)
  q=r^q
Else
  p=(p+q)+r
End if
Print p+q+r
```

- 30
- 25
- 27

24