TCS-NQT-2(14.09.2024)-Technical

192124033.sse@saveetha.com Switch account

Draft saved

Your email will be recorded when you submit this form

* Indicates required question

MCQ

Which is the super class of all exception classes *

- ○ Exception
- ○ Object
- ○ Error
- ◉ Throwable

```
#include <stdio.h>
int main() {
 int i;
 for(i = 0; i < 5; i++) {
  int a = i;
 }
 printf("%d",a);
 return 0;
}
```

- 4
- 5
- (●) Compile time Error
- Run time Error

```
#include<stdio.h>
int main(){
   char *names[] = { "Suresh", "Siva", "Sona", "Baiju", "Ritu"};
   int i;
   char *t;
   t = names[3];
   names[3] = names[4];
   names[4] = t;
   for(i=0; i<=4; i++)
      printf("%s,", names[i]);
   return 0;}
```

*

- A.Suresh, Siva, Sona, Baiju, Ritu
- B.Suresh, Siva, Sona, Ritu, Baiju
- C.Suresh, Siva, Baiju, Sona, Ritu
- D.Suresh, Siva, Ritu, Sona, Baiju

Integer a, b, c *
Set b = 40, a = 20, c = 20
a = a + c
c = c + a
a = a + c
c = c + a
Print a + b + c

- ○ 200
- ○ 300
- ○ 250
- ◉ 320

.**What is the output of the Java code snippet?** *

```
int a=10, b=20;

int c = a++*2;

int d = --b*2;

System.out.println(c +"," + d);
```

- ○ A) 20,40
- ○ B) 22,40
- ◉ C) 20,38
- ○ D) 22,38

```
#include<stdio.h>
int main(){
   char p[] = "%d\n";
   p[1] = 'c';
   printf(p, 65);
   return 0;}
```

*

- (●) A.A
- ( ) B.a
- ( ) C.c
- ( ) D.65

16. A pointer is a memory address. Suppose the pointer variable has p address 1000, and that p is declared to have type int*, and an int is 4 bytes long. What address is represented by expression p + 2? *

- ( ) a.002
- ( ) b.1004
- ( ) c.1006
- (●) d.1008

Study the following program: *

i = 2, 10

j = 3, 5

add = i + j

print(add)

What will be the output of this program?

- a)(5, 10)
- b)20
- c)(2, 10, 3, 5)
- (selected) SyntaxError: invalid syntax

int main() *

```
{
   if( (-100 && 100)||(20 && -20) )
      printf("%s","Condition is true.");
   else
      printf("%s","Condition is false.");
   return 0;
}
```

- Condition is false
- (selected) Condition is true
- Compiler error.
- None of the above.

```
switch(c)
 case '1':
  display "One"
 case '7':
  display "Seven"
 case '2':
  display "Two"
 default:
  display "Hello"
 break
end-switch
```

*

- ○ SEVEN TWO
- ○ SEVEN TWO HELLO
- ○ ONE SEVEN TWO HELLO
- ◉ None of the above

Predict the output *

```
#include<stdio.h>

int main()

{

        void  num=10;

        printf("%v", num);

        return 0;

}
```

- ○ Run time Error
- ○ 10
- ◉ Compilation Error
- ○ None of the above

Integer a, b *
Set a = 15, b = 7
a = a mod (a - 3)
b = b mod (b – 3)
a = a mod 1
b = b mod 1
Print a + b

- ○ 1
- ◉ 0
- ○ 2
- ○ -1

A single try block must be followed by which of these? *

- ○ A. finally
- ○ B. catch
- ◉ C. catch or finally
- ○ D. None of the mentioned

Predict the Output *

```
#include <stdio.h>
int main()
{
 int size = sizeof(int) + sizeof(double);
 printf("%d", ++size);
 return 0;
}
```

- 12
- 13
- 8
- 9

```
int main()
{
   int a=5, b=8;
   if( a==5 && (b=9) )
   {
      printf("Gorilla Glass=");
   }
   printf("%d %d", a, b);

   return 0;
}
```

*

- ○ A) 5 8
- ○ B) 5 9
- ○ C) Gorilla Glass=5 8
- ◉ D) Gorilla Glass=5 9

What is byte code in Java? *

- ◉ a)Code generated by a Java compiler
- ○ b)Code generated by a Java Virtual Machine
- ○ c)Name of Java source code file
- ○ d)Block of code written inside a class

The advantage of using the PreparedStatement in Java is: *

- ○ a. More memory usage
- ◉ b. Prevents SQL injection
- ○ c. Encourages SQL injection
- ○ d. Slow performance

What will be the output of given Python code? *

```
str1="hello"
c=0
for x in str1:
  if(x!="l"):
    c=c+1
  else:
    pass
print(c)
```

- ○ A. 2
- ○ B. 0
- ○ C. 4
- ◉ D. 3

```
#include <stdio.h>
int main()
{
   if( 10 > 9 )
      printf("Singapore\n");
   else if(4%2 == 0)
      printf("England\n");
      printf("Poland");
   return 0;
}
```

*

- A) Singapore
- B) Singapore Poland
- C) Singapore England Poland
- D) England Poland

What will be the output of the C program? *

```
#include<stdio.h>
int main()
{
        printf("%d\t",sizeof(2.5));
        printf("%d\t",sizeof(2));
        printf("%d",sizeof('A'));
        return 0;
}
```

- ○ 8 4 1
- ○ 8 4 2
- ○ 4 4 4
- ◉ 8 4 4

Predict the Output *

```
#include <stdio.h>

int main() {

 int i;

 for(i = 0; i < 5; i++) {

  int a = i;
  printf("%d",a);

 }
 return 0;

}
```

- ○ Error
- ◉ 01234
- ○ 1234
- ○ None of the above

Between Postfix and Prefix arithmetic operators in Java, which operators have more priority? *

- ◉ A) Postfix operators have more priority than Prefix operators
- ○ B) Prefix operators have more priority than Postfix operators
- ○ C) Both Prefix and Postfix operators have equal priority
- ○ D) None of the above

```
void main()
{
   char val=1;
   if(val-- ==0)
      printf("TRUE");
   else
      printf("FALSE");
}
```

*

- (●) FALSE
- ( ) TRUE
- ( ) Run time error
- ( ) None of the above

Predict the Output *

```
#include<stdio.h>

int main()

{

        char num = 127;

        num = num + 1;

        printf("%d", num);

        return 0;

}
```

- ○ 128
- ○ Error
- ◉ -128
- ○ None of the above

Predict the output *

```
n=7
c=0
while(n):
    if(n>5):
        c=c+n-1
        n=n-1
    else:
        break
print(n)
print(c)
```

- (●) A. 5 11
- ( ) B. 5 9
- ( ) C. 7 11
- ( ) D. 5 2

Predict the Output *

```
#include<stdio.h>
int main()
{
        static int num = 6;
        printf("%d ",num--);
        if(num)
        main();
        return 0;
}
```

- ○ Compilation Error
- ○ Runtime Error
- ○ 6
- ◉ 6 5 4 3 2 1

```
int main()
{
   int x=1;
   float y = 1.0;
   if(x == y)
   {
      printf("Polo\n");
   }
   if( 1 == 1.0)
   {
      printf("Golf\n");
   }

   if( 1.0 == 1.0f )
   {
       printf("Boxing\n");
   }
   return 0;
}
```

*

- ○ A) No Output
- ○ B) Boxing
- ○ C) Golf Boxing
- ◉ D) Polo Golf Boxing

What is the output of the Java code snippet? *

```
int a=6, b=5;
if(++b == a--)
{
  System.out.println("RABBIT");
}
else
{
  System.out.println("BUNNY");
}
```

- (●) A) RABBIT
- ( ) B) BUNNY
- ( ) C) Compiler error
- ( ) D) None of the above

What will be the output of the C program? *

```
#include<stdio.h>
int main()
{
        char num = '\010';
        printf("%d", num);
        return 0;
}
```

- ○ 010
- ○ 10
- ◉ 8
- ○ Error

```
#include<stdio.h>
int main(){
   int i;
   char a[] = "\0";
   if(printf("%s", a))
      printf("The string is empty\n");
   else
      printf("The string is not empty\n");
   return 0;}
```

*

- (●) A.The string is empty
- ( ) B.The string is not empty
- ( ) C.No output
- ( ) D.Error

```
#include<stdio.h>#include<string.h>
int main(){
   char str1[20] = "Hello", str2[20] = " World";
   printf("%s\n", strcpy(str2, strcat(str1, str2)));
   return 0;}
```

*

- ( ) A.Hello
- ( ) B.World
- (●) C.Hello World
- ( ) D.WorldHello

```
#include<stdio.h>
int main ()
{
 char c,a,b;
 c='f';
 a='s';
 b='x';
 int sum= c+a+b;
 printf ("%d", sum);
}
```

*

- ○ 335
- ◉ 337
- ○ Error
- ○ No output

What will be the output of the C program? *

```
#include<stdio.h>
int main()
{
        float x = 3.14;
        double y = 3.14;
        printf("%f %ff",x, y);
        return 0;
}
```

- ○ 3.140000 3.140000
- ◉ 3.140000 3.140000f
- ○ 3.140000f 3.140000f
- ○ Error

When an expression consists of int, double, long, float, then the entire expression will get promoted into a data type that is: *

- ○ a. float
- ◉ b. double
- ○ c. int
- ○ d. long

```
#include<stdio.h>
int main(){
   static char mess[6][30] = {"Don't walk in front of me...",
                              "I may not follow;",
                              "Don't walk behind me...",
                              "Just walk beside me...",
                              "And be my friend." };

   printf("%c, %c\n", *(mess[2]+9), *(*(mess+2)+9));
   return 0;}
```

*

- ○ A.t, t
- ◉ B.k, k
- ○ C.n, k
- ○ D.m, f

Which of the following Python code will give different output from the others? *

- ○ A. for i in range(0,5): print(i)
- ○ B. for j in [0,1,2,3,4]: print(j)
- ◉ C. for k in [0,1,2,3,4,5]:print(k)
- ○ D. for l in range(0,5,1):print(l)

Predict the Output *

```
#include<stdio.h>

int main()

{

        int size = sizeof(volatile) + sizeof(const);

        printf("%d",++size);

        return 0;

}
```

- ○ 8
- ○ 12
- ◉ Compilation Error
- ○ Run time Error

Study the following program: *

```
print(int(6 == 6.0) * 3 + 4 % 5)
```

What will be the output of this program?

- ○ a)22
- ○ b)18
- ○ c)20
- ◉ d)7

Which of the following would give an error? *

- ○ A. list1=[]
- ○ B. list1=[]*3
- ○ C. list1=[2,8,7]
- ◉ D. None of the above

Study the following program: *

```
_ = '1 2 3 4 5 6'

print(_)
```

What will be the output of this program?

- ○ a)SyntaxError: EOL while scanning string literal
- ○ b)SyntaxError: invalid syntax
- ○ c)NameError: name '_' is not defined
- ◉ 1 2 3 4 5 6

```
#include<stdio.h>

int main()

{

        float a = 5.0;

        printf ("Result is = %d ", (24 / 5) * a);

        return 0;

}
```

*

- (●) Error
- ( ) 20.0
- ( ) 20
- ( ) 24.0

```
int main()
{
   int a=10;
   if(a==10)
   {
      printf("Hello...");
      break;
      printf("Ok");
   }
   else
   {
      printf("Hii");
   }
   return 0;
}
```

*

- ○ Hello
- ○ Hi
- ◉ Compiler error.
- ○ None of the above.

```
#include<stdio.h>
int main(){
   void fun();
   fun();
   printf("\n");
   return 0;}void fun(){
   char c;
   if((c = getchar())!= '\n')
      fun();
   printf("%c", c);}
```

*

- ○ A.abc abc
- ○ B.bca
- ○ C.Infinite loop
- ◉ D.Cba

Integer a, b
Set a = 1, b = 1
a = (a ^ 1) & (1) + (b ^ 1) & (1)
Print a + b

*

- ○ 1
- ◉ 2
- ○ 0
- ○ -1

```
#include<stdio.h>
int main(){
    int num = - -2;
    printf("num = %d", num);
    return 0;
}
```

*

- (●) 2
- ( ) -2
- ( ) Compilation Error
- ( ) None of the above

Back Submit Clear form

Never submit passwords through Google Forms.

This form was created inside of Saveetha Institute of Medical and Technical Sciences. Report Abuse

Google Forms