Technical Assessment - MCQ

192124033.sse@saveetha.com Switch account

Saving...

Your email will be recorded when you submit this form

* Indicates required question

If both numerator and denominator of a division operation in C language are integers, then we get.? *

- ○ A) Expected algebraic real value
- ◉ B) Unexpected integer value
- ○ C) Compiler error.
- ○ D) None of the above

What is the output? *

```
#include <stdio.h>
void main(){
const char var='A';
++var;
printf("%c",var);
}
```

- ○ B
- ○ A
- ◉ ERROR
- ○ 66

What is the output? *

```
#include <stdio.h>
void main(){
char var=10;
printf("var is = %d",++var++);
}
```

- ○ ERROR : Can not modify var.
- ◉ ERROR : L-Value required.
- ○ ERROR : Expression syntax.
- ○ 12

*

What will be the output of the program?

```
#include<stdio.h>

int main()
{
   char c=48;
   int i, mask=01;
   for(i=1; i<=5; i++)
   {
      printf("%c", c|mask);
      mask = mask<<1;
   }
   return 0;
}
```

- ○ 12400
- ◉ 12500
- ○ 12480
- ○ 12556

What will be the output of the program? *

```
#include<stdio.h>

int main()
{
   printf("%d >> %d %d >> %d\n", 4 >> 1, 8 >> 1);
   return 0;
}
```

- ○ 4 >> 1 8 >> 1
- ○ 4 1 8 1
- ○ 2 >> 4 Garbage value >> Garbage value
- ◉ 2 4

What is the output? *

```
#include <stdio.h>
int main(){
int x,y;
x=(100,200);
y=100,200;
printf("x=%d,y=%d",x,y);
return 0;
}
```

- ○ x=100,y=200
- ○ x=200,y=200
- ○ ERROR
- ◉ x=200,y=100

Can you use C Modulo Division operator % with float and int? *

- ○ A) Only int variables = Okay
- ○ B) Only float variables = Okay
- ○ C) int or float combination = Okay
- ◉ D) Numerator int variable, Denominator any variable = Okay

What is x? *

```
#include <stdio.h>
int main()
{
int x = 4, y = 2;
x /= x / y;
printf("%d\n", x);
return 0;
}
```

- ◉ 2
- ○ 3
- ○ 4
- ○ 1

```
#include <stdio.h>
void main()
{
int y = 4;
int x = 9 % 2 * 4 / 2;
printf("Value of x is %d", x);
}
```

Find x? *

- ○ 1
- ◉ 2
- ○ 3
- ○ 4

What is the Output ? *

```
#include <stdio.h>

void main(){

   printf("value is = %d",(10++));

}
```

- ○ 10
- ○ 11
- ○ 0
- ◉ ERROR

What is the output?

```
int main() {
int sum = 2 + 4 / 2 + 6 * 2;
printf("%d", sum);
return 0;
}
```

- ○ 2
- ○ 15
- ◉ 16
- ○ 18

Clear selection

What is the output? *

```
#include <stdio.h>
int main() {
 int first = 10, second = 20;
 int third = first + second;
 {
 int third = second - first;
 printf("%d ", third);
 }
 printf("%d", third);
return 0;
}
```

- ◉ 10 30
- ○ 30 10
- ○ 10 20
- ○ 20 10

What is the output? *

```
#include <stdio.h>
void main(){
int a=10,b=2,x=0;
x=a+b*a+10/2*a;
printf("value is =%d",x);
}
```

- (●) valie is =1250
- ( ) value is =80
- ( ) value is =125
- ( ) ERROR

*

If an unsigned int is 2 bytes wide then, What will be the output of the program ?

```
#include<stdio.h>
int main()
{
 unsigned int m = 32;
 printf("%x\n", ~m);
 return 0;
}
```

- ( ) 0000
- ( ) ffff
- (●) ffdf
- ( ) ddfd

What is the output? *

```
#include <stdio.h>
int main() {
int a = 3, b = 5;
int t = a;    a = b;    b = t;
printf("%d %d", a, b);
return 0;
}
```

- ○ 3 5
- ○ 3 3
- ○ 5 5
- ◉ 5 3

What will be the output of the program? *

```
#include<stdio.h>
int main()
{
   unsigned char i = 0x80;
   printf("%d\n", i<<1);
   return 0;
}
```

- ○ 0
- ◉ 256
- ○ 100
- ○ 80

What is the priority of operators *, / and % in C language.? *

- A) * > / > %
- B) % > * > /
- C) Both % = / , * are same
- D) All three operators *, / and % are same.

What is the output?

```
#include <stdio.h>
int main() {
int x = printf("Hello");
printf(" %d", x);
}
```

- 10
- 5
- 1
- 0

Clear selection

What will be the output of the program ? *

```
#include<stdio.h>

int main()
{
   int i=32, j=0x20, k, l, m;
   k=ilj;
   l=i&j;
   m=k^l;
   printf("%d, %d, %d, %d, %d\n", i, j, k, l, m);
   return 0;
}
```

- ○ 0, 0, 0, 0, 0
- ○ 0, 32, 32, 32, 32
- ◉ 32, 32, 32, 32, 0
- ○ 32, 32, 32, 32, 32

What is the output? *

```
#include <stdio.h>
void main(){
int x=10;
x+=(x++)+(++x)+x;
printf("%d",x);
}
```

- ○ 44
- ○ 45
- ◉ 46
- ○ 47

int a = 3.5 + 4.5; *

- ○ 8
- ○ 8.0
- ◉ 7
- ○ Error

Which bitwise operator is suitable for turning on a particular bit in a number? *

- ○ && operator
- ○ & operator
- ○ || operator
- ◉ | operator

The expression 5 -2 – 3 * 5 – 2 will evaluate to 18, if *

- ◉ A. – is left associative and * has precedence over –
- ○ B. – is rightt associative and * has precedence over –
- ○ C. – is right associative and – has precedence over *
- ○ D. – is left associative and – has precedence over *

What is the output ?

```
#include <stdio.h>

static int i;

int main(){

int i;

printf(“i is %d”,i);


return 0;

}
```

- ○ 0
- ○ 1
- ◉ Garbage value
- ○ Runtime Error

Clear selection

What is the output? *

```
#include <stdio.h>
int main(){
int x;
x=100,30,50;
printf("x=%d\n",x);
x=(100,30,50);
printf("x=%d\n",x);
return 0;
}
```

- ○ x=100 x=100
- ◉ x=100 x=50
- ○ x=50 x=50
- ○ x=50 x=100

What is the Output? *

```
Integer x, y, z
Set x = 4, y = 3, z = 1
if (x >> (z – 1) && y << (z + 1))
      x = x + c
else
      y = x << z
End if
Print x – y + z
```

- ◉ 5
- ○ 3
- ○ 8
- ○ None of the above

What will be the output of the program? *

```
#include<stdio.h>

int main()
{
   printf("%d %d\n", 32<<1, 32<<0);
   printf("%d %d\n", 32<<-1, 32<<-0);
   printf("%d %d\n", 32>>1, 32>>0);
   printf("%d %d\n", 32>>-1, 32>>-0);
   return 0;
}
```

- ○ Garbage values
- ◉ Option 2

64 32
0 32
16 32
0 32

- ○ compile error
- ○ All zeros

int a = 10 + 4.867; a=? *

- ○ 14
- ○ 15
- ◉ 10
- ○ Error

*

Assuming, integer is 2 byte, What will be the output of the program?

```
#include<stdio.h>
int main()
{
printf("%x\n", -1>>1);
return 0;
}
```

- ○ 0fff
- ◉ ffff
- ○ 0000
- ○ fff0

```
#include <stdio.h> *
int main()
{
int x = 5, y = 2;
x *= x - y;
printf("%d", x);
return 0;
}
```

find x?

- (●) 15
- ( ) 23
- ( ) No output
- ( ) Error

What is the output? *

```
#include <stdio.h>
int main(){
int var;
var=- -10;
printf("value of var= %d\n",var);
var=+ +10;
printf("value of var= %d\n",var);
return 0;
}
```

- ( ) ERROR
- (●) var= -10 var= 10
- ( ) var= 10 var= 10
- ( ) var= 10 var= 11

What is the output? *

```
#include <stdio.h>
void main(){
int a=3,b=2;
a=a==b==0;
printf("%d,%d",a,b);
}
```

- (●) 1,2
- ( ) 3,2
- ( ) 0,0
- ( ) 2,3

Choose the correct statements *

- ( ) A. address operator cannot be applied to register variables
- ( ) B. misuse of register declaration will increase the execution time
- (●) C. Both (a) & (b)
- ( ) D. none of above

What will be the output of the following pseudocode? *

Integer p, q

Set p = 1, q = 1

p = (p ^ 1) & (1) + (q ^ 1) & (1)

Print p + q

- ○ 1
- ◉ 2
- ○ 3
- ○ None of these

What is the output ?

```
#include <stdio.h>

int main(){

static int I;

int j;

for(j=0;j<10;j++){

        i+=2;

        i-=j;

}

printf(“%d”,i);

return 0;

}
```

- ○ -27
- ◉ -25
- ○ Cannot be Determined
- ○ -21

Clear selection

What is the output ?

```
#include <stdio.h>

int main(){

static int i;

printf(“i is %d”, i);


return 0;

}
```

- (●) 0
- ( ) 1
- ( ) Garbage value
- ( ) Run time Error

Clear selection

What is the output? *

```
#include <stdio.h>
void main(){
int x=(20 || 40 ) && (10);
printf("x= %d",x);
}
```

- ( ) x= 60
- ( ) x= 70
- ( ) x= 0
- (●) x= 1

What is the output ?

```
#include <stdio.h>

int main(){

float f=0.1;

if(f==0.1)

        printf(“Yes”);

else

        printf(“No”);


return 0;
}
```

- (●) No
- ( ) Yes
- ( ) Error
- ( ) No Output

Clear selection

What is the output ? *

```
#include <stdio.h>

int main(){

int x,y;

for(x=5;x>=1;x- -){

        for(y=1;y<=x;y++){

printf("%d\n",y);

}

}


return 0;
}
```

- (●) 15
- ( ) 10
- ( ) 11
- ( ) 13

The expression 4 + 6 / 3 * 2 – 2 + 7 % 3 evaluates to *

- ( ) A. 3
- ( ) B. 4
- ( ) C. 6
- (●) D. 7

What will be the output of the program? *

```
#define P printf("%d\n", -1^~0);
#define M(P) int main()\
        {\
          P\
          return 0;\
        }
M(P)
```

- ○ 1
- ◉ 0
- ○ -1
- ○ 2

In which numbering system can the binary number 1011011111000101 be easily converted to? *

- ○ Decimal system
- ◉ Hexadecimal system
- ○ Octal system
- ○ No need to convert

What will be the output of the following pseudocode? *

```
Integer a, b, c
Set a = 1, b = 1, c = 7
a = a + b
if(a + b)
if(b + (c ^ a))
a = 2
b = a
End if
End if
Print a + b + c
```

- ○ 13
- ◉ 11
- ○ 12
- ○ 16

Associativity of C Operators *, /, %, +, - and = is.? *

- ◉ A) Operators *, / and % have Left to Right Associativity. Operators + and - have Left to Right Associativity. Operator = has Right to Left Associativitiy.
- ○ B) Operators *, / and % have Right to Left Associativity. Operators + and - have Left to Right Associativity. Operator = has Right to Left Associativitiy.
- ○ C) Operators *, / and % have Right to Left Associativity. Operators + and - have Right to Left Associativity. Operator = has Right to Left Associativitiy.
- ○ D) Operators *, / and % have Right to Left Associativity. Operators + and - have Right to Left Associativity. Operator = has Left to Right Associativitiy.

Which bitwise operator is suitable for turning off a particular bit in a number? *

- (●) & operator
- ( ) && operator
- ( ) || operator
- ( ) ! operator

What is the output? *

```
#include <stdio.h>
void main(){
unsigned short var='B';
var+=2;
var++;
printf("var : %c , %d ", var,var);
}
```

- (●) var : E, 69
- ( ) var : E, 68
- ( ) var : D, 68
- ( ) var : D, 69

What is the output of the C program with Modulo Division operator with - or Negative numbers.? int main() *

```
{
int a = -25%-10;
int b = -25%10;
int c = 25%-10;
printf("%d %d %d", a, b, c);
return 0;
}
```

- ○ 5 -5 -5
- ○ B) 5 -5 5
- ◉ C) -5 -5 5
- ○ D) 5 5 5

What is the output? *

```
#include <stdio.h>
int main() {
int a[] = {1, 2, 3, 4};
int sum = 0;
for(int i = 0; i < 4; i++) {
 sum += a[i];
}
printf("%d", sum);
return 0;
}
```

- ○ 1
- ○ 4
- ○ 20
- ◉ 10

If an unsigned int is 2 bytes wide then, What will be the output of the program ? *

```
#include<stdio.h>

int main()
{
   unsigned int a=0xffff;
   ~a;
   printf("%x\n", a);
   return 0;
}
```

- ○ 0000
- ◉ ffff
- ○ ddfd
- ○ 00ff

Assuming a integer 2-bytes, What will be the output of the program? *

```
#include<stdio.h>

int main()
{
   printf("%x\n", -1<<3);
   return 0;
}
```

- ◉ fff8
- ○ ffff
- ○ 0
- ○ -1

Back Submit Clear form

Never submit passwords through Google Forms.

This form was created inside of Saveetha Institute of Medical and Technical Sciences. Report Abuse

Google Forms