SIMATS - SAVEETHA SCHOOL OF ENGINEERING

Technical MCQ

Providing a comprehensive overview of your Technical Expertise.

Remaining Time : 09:19

1. What will be the output of the following program : void main() { int i; for (i=-10; !i; i++); printf("%d",-i); }

- (●) 0
- ( ) Compile-Time Error
- ( ) 10
- ( ) No Output

2. What will be the output of the following program : void main() { printf("d%",8); }

- ( ) 8
- (●) Compile-Time Error
- ( ) d%
- ( ) None of these

3. If the length of a Broadcast LAN is 2 Km and it has 107 bps bandwidth and uses CSMA/CD and the signal travels along the wire at 2108m/s, then what is the minimum size of the packet?

- (●) 100 bytes
- ( ) 200 bytes
- ( ) 50 bytes
- ( ) None of these

4. The output of the following C program is_____ void f1(int a, int b) { int c; c=a; a=b; b=c; } void f2(int *a, int *b) { int c; c=*a; *a=*b; *b=c; } int main(){ int a=4, b=5, c=6; f1(a,b); f2(&b, &c); printf("%d",c-a-b); }

- ( ) -5

SIMATS - SAVEETHA SCHOOL OF ENGINEERING

- (●) 0

5. What will be the output of the following program : void main() { static int i; while (i <= 10) (i > 2) ? i++ : i--; printf("%d",i); }

- ( ) Compile-Time Error
- (●) 11
- ( ) 32767
- ( ) None of these

6. What does the following fragment of C-program print? char c[] = "GATE2011"; char *p =c; printf("%s", p + p[3] - p[1]);

- ( ) GATE2011
- (●) E2011
- ( ) 2011
- ( ) 0 11

7. Consider the following C function. void convert(int n){ if(n<0) printf("%d",n); else { convert(n/2); printf("%d",n%2); } } Which one of the following will happen when the function convert is called with any positive integer n as an argument?

- ( ) It will print the binary representation of n and terminate
- (●) It will print the binary representation of n in the reverse order and terminate
- ( ) It will print the binary representation of n but will not terminate
- ( ) It will not print anything and will not terminate

8. Consider the following C function definition: int Trial (int a, int b, int c) { if ((a > = b) && (c < b)) return b; else if (a > = b) return Trial (a,c,b); else return Trial (b,a,c); } The function Trial:

- ( ) Finds the maximum of a, b, and c
- ( ) Finds the minimum of a, b and c

SIMATS - SAVEETHA SCHOOL OF ENGINEERING

9. Which of the following is the most popular 16-ibit operating system?

- ○ TRS-DOS
- ○ CP/M
- ◉ MS-DOS
- ○ UNIX

10. What will be the output of the following program : void main() { int a=555,*ptr=&a,b=*ptr=777; printf("%d %d",--*&b,*(int *)&b); }

- ◉ Compile-Time Error
- ○ 776 777
- ○ 554 555
- ○ None of these

11. What will be the output of the following program : void main() { int val=97; "Printing..."+printf("%c",val); }

- ○ Printing...97
- ○ 97
- ◉ Compile-Time Error
- ○ a

12. Consider the following C function: int f(int n) { static int r = 0; if (n <= 0) return 1; if (n > 3) { r = n; return f(n-2)+2; } return f(n-1)+r; } What is the value of f(5) ?

- ○ 5
- ○ 7
- ○ 9
- ◉ 18

SIMATS - SAVEETHA SCHOOL OF ENGINEERING

- ○ 2 2
- ◉ 2 1
- ○ 0 1
- ○ 0 2

14. What will be the output of the following program : void main() { char a,b,c; scanf("%c%c%c",&a,&b,&c); printf("a=%c b=%c c=%c",a,b,c); } [NOTE : THE USER INPUT IS :A B C]

- ◉ a=A b=B c=C
- ○ a=A b= c=B
- ○ a=A b= c=C
- ○ None of these

15. The following function reverse() is supposed to reverse a singly linked list. There is one line missing at the end of the function. /* Link list node */ struct node { int data; struct node* next; }; /* head_ref is a double pointer whi

- ○ *head_ref = prev;
- ◉ *head_ref = current;
- ○ *head_ref = next;
- ○ *head_ref = NULL;

Reset Submit