SIMATS - SAVEETHA SCHOOL OF ENGINEERING

Technical MCQ

Providing a comprehensive overview of your Technical Expertise.

Remaining Time : 20:32

1. Consider that a computer on a 10Mbps network is regulated by a token bucket. The token bucket is filled at a rate of 2Mbps. It is initially filled to capacity with 16 Megabits. What is the maximum duration for which the computer can transmit at the full 1

- (●) 8 seconds
- ( ) 5 seconds
- ( ) 2 seconds
- ( ) 1.6 seconds

2. What will be the output of the following program : void main() { int val=50; const int *ptr1=&val; int const *ptr2=ptr1; printf("%d %d %d",++val,*ptr1,*ptr2); *(int *)ptr1=98; printf("\n%d %d %d",++val,*ptr1,*ptr2);

- ( ) Compile-Time Error
- (●) 51 50 50 99 98 98
- ( ) Run-Time Error
- ( ) None of these

3. The pairs of OSI protocol layer/sub-layer and its functionality are given below, the INCORRECT pair from among these are:

- ( ) Data Link Layer and Bit synchronization
- ( ) Network Layer and Routing
- (●) Medium Access Control sub-layer and Channel sharing
- ( ) Transport Layer and End-to-end process communication

SIMATS - SAVEETHA SCHOOL OF ENGINEERING

- ○ Compile-Time Error
- ○ 5 9.76723
- ○ 5 9.76
- ◉ 5 9.77

5. What will be the output of the following pseudocode? Integer a, b, c Set a = 4, b = 4, c = 4 if (a & (b ^ b) & c) a = a >> 1 End if Print a + b + c

- ○ 16
- ○ 24
- ○ 8
- ◉ 12

6. What will be the output of the following program : void main() { int val=1234; int *ptr=&val; printf("%d %d",val,(*ptr)++); }

- ○ 1234 1234
- ○ 1235 1235
- ◉ 1234 1235
- ○ 1235 1234

7. What will be the output of the following program : void main() { printf("%d"+1,123); }

- ○ 123
- ◉ Compile-Time Error
- ○ d
- ○ No Output

8. What will be the output of the following pseudocode for a = 10, b = 11? Integer funn(Integer a, Integer b) if(0) return a - b - funn(-7, -1) End if a = a + a + a + a return a End function funn()

- ◉ 40

SIMATS - SAVEETHA SCHOOL OF ENGINEERING

- ○ 0

9. What is the output? int main() { printf("%d",sizeof("a")); }

- ◉ 2
- ○ 1
- ○ error
- ○ None of these

10. Take the example of 1 Mbps error-free line, with the maximum frame size of 1000 bits and new packets generated about 1 second apart . Timeout interval is 10 m/sec if the special acknowledgement timer were eliminated, unnecessary timeout would occur . In t

- ○ Twice
- ○ Only once
- ○ Thrice
- ◉ None of the above

11. What will be the output of the following program : struct names { char str[25]; struct names *next; }; typedef struct names slist; void main() { slist *list,*temp; list=(slist *)malloc(sizeof(slist)); // Dynamic Memory Allocation

- ○ Compile-Time Error
- ◉ HaiFriends
- ○ FriendsHai
- ○ None of these

12. What will be the output of the following program : void main() { int i; for (i=-10; !i; i++); printf("%d",-i); }

- ◉ 0
- ○ Compile-Time Error
- ○ 10

SIMATS - SAVEETHA SCHOOL OF ENGINEERING

13. Output ? int main() { const int x=5; int *ptr; ptr=&x; *ptr=10; printf("%d",x); }

- ○ error
- ◉ compiler dependent
- ○ 10
- ○ 0

14. If two computers C1 and C2 are configured as follows and C1 has IP address 203.197.2.53 and netmask 255.255.128.0, while C2 has IP address 203.197.75.201 and netmask 255.255.192.0, then which of the following statements is true?

- ○ C2 assumes C1 is on the same network, but C1 assumes C2 is on a different network
- ◉ C1 assumes C2 is on the same network, but C2 assumes C1 is on a different network
- ○ C1 and C2 both assume they are on different networks
- ○ C1 and C2 both assume they are on the same networks

15. The concatenation of two lists is to be performed in O(1) time. Which of the following implementations of a list should be used?

- ◉ singly linked list
- ○ doubly linked list
- ○ circular doubly linked list
- ○ array implementation of lists

Reset Submit