
DOVETARL JOINT


AZM: To produce a dovetail joint from the given work piece. APPLICATION: bross Bars in a cot, ahelies. SUPPLZED MATERIAL SPECIFICATION: Venterk wood of the 150 x 45 x 30 TOOLS REQUIRED. 1) Jack plane. 2) Hand Sant. 3) Steel rule. 4) Pencil. of Marking gauge. 6) Try square. 7) Firmer chisel. 8) Cleaning brush. 9) Woodent. 2) Preparing. 2) Marking. 3) Cutting. 4) Filirishing. SEQUENCE OF OPERATIONS WORKENG STEPS: a) prepare the work piece as described in previous with a length of 150 mm, Asmer, 30 mm. a) Adjust the marking gauge to 15 new and det out 2) MARKENER the distance from the pace wide (A) at one end b) with Try square & scriber check a perpendicular line In the face elde (A), from the marked line at a distance of 45 min pointe ende this will produce a rectangular of 45 × 15 at the and of the

c) Now on (A) side ark a line on all jour colde & pace of the edge (B). on (B) side mark fast grow 53 min second

one after 45 nemo

DIAGRAM:





d) Mark a live on 6 miches from the also rule measurement. e) Now on (A) dide mark 45 nm gfter 5m ev up and down state . p) men on (B) side apren 53mm & 45 mm in between mark 5mm on top & bottom. 3) WITENES / SAWENG: a) First, hand dawing the back part of the (1) side tills. He marking. b) they saw the source and some marking or the (B) state and use finner chisel and whoden wallet to thip of the wood. d) the Rosp to smooth up the sawed area & the you up hor preces once you cut the prece by and e John the two pieces in form of e- 9. saw pan do middle. a) Take a series of semall cuts delicately on both the side pieces to senione the excess wood. b) Ostalie a fine finish of the seaker and Broulder assembly joins & crear of are made by wire brush the Dove Tail joint was produced from the girou work piece and assembled joint was submitted or maluation.