Koneru Lakshmaiah Education Foundation
(Deemed to be University estd. u/s. 3 of the UGC Act, 1956)
Off-Campus: Bachupally-Gandimaisamma Road, Bowrampet, Hyderabad, Telangana - 500 043.
Phone No: 7815926816, www.klh.edu.in

A CASE-STUDY BASED REPORT
ON

Insurance Claim Fraud Detection Using XGBoost with GridSearchCV and Bayesian Hyperparameter Optimisation

submitted in partial fulfilment of the requirements for the Course

MACHINE LEARNING
BACHELOR OF TECHNOLOGY
in
A.Y.: 2026–27

by

Bharagava Raaj Vamsi	**Roll No.: 2520090169**
Mahnkali Saitarun	**Roll No.: 2520090020**
Hanish Kumar	**Roll No.: 2520090107**

Under the Esteemed Guidance of

Dr. Y. Lakshmi Prasanna
Asst. Professor, Dept. of CS & IT

Koneru Lakshmaiah Education Foundation
(Deemed to be University estd. u/s. 3 of the UGC Act, 1956)
Off-Campus: Bachupally-Gandimaisamma Road, Bowrampet, Hyderabad, Telangana - 500 043.
Phone No: 7815926816, www.klh.edu.in

INDEX

S.No.	Section	Page No.
1	**Abstract**	2
2	**Introduction**	3
	Background	
	Motivation for the Project	
	Overview of the Work Carried Out	
	Scope and Responsible-Use Statement	
3	**Problem Statement**	5
	Case-Study Scenario	
	Central Case-Study Question	
	Formal Problem Definition	
	Objectives that Guide the Study	
	Assumptions and Limitations	
4	**Dataset and Exploratory Data Analysis**	8
	About the Dataset	
	Purpose of EDA	
	Preparation Steps Actually Performed	
	EDA Exploration — Implementation	
	Summary of EDA Findings	
5	**Algorithm Selection and Implementation**	15
6	**Conclusion**	22
7	**Signature of the Team Members**	23

Abstract

Insurance fraud is a multi-crore problem that erodes the financial sustainability of insurers and raises premium costs for honest policyholders. This report presents a machine-learning-based solution to automatically identify fraudulent auto-insurance claims using a real-world historical dataset of 1,000 labelled records and 38 attributes spanning policyholder profiles, incident characteristics, and claim financials. Three variants of the XGBoost classifier were trained and evaluated: a baseline model with default hyperparameters, a model tuned via exhaustive GridSearchCV, and a model tuned using Optuna's Bayesian Tree-structured Parzen Estimator (TPE) optimisation. Class imbalance (75% genuine, 25% fraudulent) was addressed through the `scale_pos_weight` parameter. The Optuna-tuned model achieved the highest ROC-AUC, demonstrating that intelligent hyperparameter search yields measurable gains over both the baseline and grid search. Feature importance analysis identified total claim amount, vehicle claim value, incident severity, and injury claim as the strongest predictors of fraud. The proposed system is designed to assist human investigators by triaging claims for priority review, rather than making fully automated decisions, thereby ensuring fairness and accountability in the fraud-detection pipeline.

Introduction

Background

The global insurance industry loses hundreds of billions of dollars annually to fraudulent claims. In the Indian auto-insurance segment alone, industry estimates indicate that a significant proportion of settled claims involve some degree of misrepresentation or outright fabrication. Fraudulent claims typically manifest as staged road accidents, exaggerated repair estimates, false or inflated injury reports, and deliberate under-reporting of prior damage. These practices impose direct financial costs on insurers and indirect costs on law-abiding policyholders through higher premiums.

Traditional fraud detection relied heavily on rule-based systems and manual audits. While effective for catching known fraud patterns, such approaches struggle to scale and fail to detect novel or evolving fraud schemes. The volume of daily claim submissions at any large insurer makes comprehensive manual review operationally infeasible. Machine learning offers a compelling alternative: by training on historical labelled data, a model can learn subtle patterns and combinations of factors that human reviewers might overlook, and can flag suspicious claims in real time.

Motivation for the Project

The motivation for this project stems from the practical need to build a scalable, data-driven fraud-detection mechanism that can operate within an insurance company's existing claims workflow. SafeShield Auto Insurance, the company at the centre of this case study, processes thousands of auto-insurance claims every month. An internal audit revealed that nearly one in four claims showed signs of fraud, costing the company crores of rupees in wrongful payouts annually. The fraud investigation team lacks the bandwidth to manually review every claim before settlement. A reliable machine learning model that can triage incoming claims — surfacing the most suspicious ones for human review — would dramatically reduce financial losses while maintaining a fair and transparent process for genuine claimants.

Beyond the business case, this project also serves as an exploration of modern hyperparameter optimisation techniques. The comparison between exhaustive grid search and Bayesian optimisation is of direct practical interest: Bayesian methods promise better results with fewer evaluations, and this project puts that promise to an empirical test.

Overview of the Work Carried Out

The work can be summarised in five stages:

1. **Data Acquisition and Understanding:** The fraud insurance claims dataset was loaded and inspected for structure, data types, and quality issues including hidden

missing values encoded as '?'.

2. **Exploratory Data Analysis (EDA):** Univariate and bivariate analyses were performed to understand the distribution of features, the extent of class imbalance, and the correlation between individual features and the fraud label.

3. **Data Preprocessing:** Irrelevant columns were removed, hidden missing values were imputed using mode substitution, and all categorical features were label-encoded to prepare a fully numeric feature matrix.

4. **Model Training and Hyperparameter Tuning:** Three XGBoost models were trained — a baseline, a GridSearchCV-tuned model, and an Optuna Bayesian-tuned model. Each model used `scale_pos_weight` to account for class imbalance.

5. **Evaluation and Interpretation:** All models were evaluated using accuracy, precision, recall, F1-score, and ROC-AUC. Feature importances from the best model were extracted to provide interpretable guidance for investigators.

Scope and Responsible-Use Statement

The scope of this project is limited to binary classification of auto-insurance claims as fraudulent or genuine, using structured tabular data. The model does not process images, audio, or unstructured text. It is trained and evaluated on a dataset of 1,000 historical records from a single insurer and should not be deployed without retraining and validation on the target insurer's own data.

Responsible-use statement: The model developed in this project is intended solely as a decision-support tool. It flags claims for priority human review; it does not and should not automatically reject or approve any claim. All flagged claims must be reviewed by a qualified fraud investigator before any action is taken. The model must be monitored regularly for drift, bias, and disparate impact across policyholder demographics to ensure fair and equitable treatment of all claimants.

Problem Statement

Case-Study Scenario

SafeShield Auto Insurance is a mid-sized general insurer operating across multiple Indian states. The company offers a range of personal and commercial auto-insurance products and settles an average of 3,000 claims per month. Following a significant rise in operational losses over the preceding two financial years, the company commissioned an independent forensic audit of its claims portfolio. The audit concluded that approximately 25% of settled claims bore indicators of fraud, including implausible accident narratives, inconsistencies between police reports and claimant statements, and claim amounts that were statistically anomalous relative to the reported damage.

The fraud team comprises six senior investigators, each capable of conducting a thorough review of approximately 50 claims per month — a total capacity of 300 reviews. Against a monthly volume of 3,000 claims, this means only 10% of claims can receive detailed scrutiny. Without a mechanism to prioritise which claims deserve investigation, fraud slips through at scale.

Management has mandated the Data Analytics team to build a machine-learning model trained on 1,000 historically investigated and labelled claims. The model must learn to distinguish fraudulent claims from genuine ones, so that every new incoming claim can be scored in real time and the most suspicious claims routed to investigators first.

Central Case-Study Question

Can a supervised machine-learning model, trained on historical labelled auto-insurance claim data, reliably identify fraudulent claims with sufficient precision and recall to meaningfully reduce financial losses and investigator workload for SafeShield Auto Insurance?

Formal Problem Definition

Let $\mathcal{D} = \{(\mathbf{x}_i, y_i)\}_{i=1}^{N}$ be the labelled dataset where:

- $\mathbf{x}_i \in R^d$ is the feature vector for claim i, comprising $d = 32$ engineered features after preprocessing.
- $y_i \in \{0, 1\}$ is the binary label: $y_i = 1$ denotes a fraudulent claim and $y_i = 0$ denotes a genuine claim.
- $N = 1{,}000$ is the total number of labelled examples.

The objective is to learn a classifier $f : R^d \to \{0, 1\}$ that maximises the area under the ROC curve (ROC-AUC) on a held-out test set, subject to achieving an F1-score on the fraud class of at least 0.70. ROC-AUC is chosen as the primary metric because

it measures the model's ability to rank fraudulent claims above genuine ones across all decision thresholds, which directly corresponds to the triage use case.

Objectives that Guide the Study

1. Identify and resolve all data quality issues in the raw dataset, including hidden missing values and irrelevant identifier columns.
2. Quantify the class imbalance in the dataset and implement an appropriate strategy to prevent the model from being biased towards the majority (genuine) class.
3. Perform exploratory data analysis to identify which features show the strongest statistical association with fraudulent claims.
4. Train a baseline XGBoost classifier and establish a performance benchmark.
5. Improve upon the baseline using two distinct hyperparameter optimisation strategies — exhaustive GridSearchCV and Bayesian optimisation via Optuna — and compare the results.
6. Extract and interpret feature importances from the best model to provide actionable guidance for fraud investigators.
7. Document all findings in a structured case-study report suitable for a business and technical audience.

Assumptions and Limitations

Assumptions:

- The historical labels (Fraudulent / Genuine) assigned by past investigators are accurate and consistent.
- The feature distribution of future claims will be broadly similar to that of the training data (i.e., no severe distribution shift).
- Missing values encoded as '?' were missing at random and can be safely imputed using the mode of each column.
- Label encoding of nominal categorical features is sufficient for XGBoost, which is insensitive to ordinal relationships.

Limitations:

- The dataset contains only 1,000 records, which limits the statistical power of learned patterns and the robustness of the trained model.
- Label encoding does not capture semantic relationships between categories; one-hot

encoding or target encoding may yield improvements in future work.

- The model was not tested against adversarial inputs — sophisticated fraudsters who are aware of the model may deliberately craft claims to evade detection.
- The study does not conduct a fairness audit. The model's error rates across demographic subgroups (age, sex, occupation) have not been evaluated, which is a critical gap before any real-world deployment.
- GridSearchCV explores only a predefined discrete grid and may miss optimal parameter combinations that lie between grid points.

Dataset and Exploratory Data Analysis

About the Dataset

The dataset used in this study is `fraud_insurance_claims.csv`, a structured tabular dataset comprising **1,000 rows** and **39 columns**. Each row represents a single auto-insurance claim that was historically investigated and labelled. The columns span four broad categories:

- **Policy information:** `months_as_customer`, `policy_state`, `policy_csl`, `policy_deductable`, `policy_annual_premium`, `umbrella_limit`.
- **Policyholder demographics:** `age`, `insured_sex`, `insured_education_level`, `insured_occupatio` `insured_hobbies`, `insured_relationship`, `capital-gains`, `capital-loss`.
- **Incident details:** `incident_type`, `collision_type`, `incident_severity`, `authorities_contacted` `incident_hour_of_the_day`, `number_of_vehicles_involved`, `property_damage`, `bodily_injuries`, `witnesses`, `police_report_available`.
- **Claim financials:** `total_claim_amount`, `injury_claim`, `property_claim`, `vehicle_claim`.
- **Vehicle details:** `auto_make`, `auto_model`, `auto_year`.
- **Target variable:** `fraud_reported` — Y (fraudulent) or N (genuine).

The target class is imbalanced: approximately 75% of claims are genuine and 25% are fraudulent, creating a 3:1 class imbalance that must be addressed during model training.

Purpose of EDA

Exploratory Data Analysis serves three purposes in this project:

1. **Data quality assessment:** Identify missing values (including those hidden as '?' strings), duplicates, and irrelevant columns that should be excluded from modelling.
2. **Feature understanding:** Understand the distribution and range of each feature, and identify which features are most strongly associated with the fraud label, informing both preprocessing decisions and post-modelling interpretation.
3. **Imbalance quantification:** Measure the exact extent of class imbalance to calibrate the `scale_pos_weight` parameter for XGBoost.

Preparation Steps Actually Performed

The following preprocessing steps were applied sequentially before model training:

1. **Hidden missing-value detection:** The raw dataset contained no `NaN` values in the conventional sense. However, three columns — `collision_type`, `property_damage`,

and `police_report_available` — used the string '?' as a placeholder for unknown values. These were replaced with `NaN` before any further processing.

2. **Irrelevant column removal:** Six columns were dropped because they serve as identifiers or contain information unavailable at prediction time: `policy_number`, `policy_bind_date`, `incident_date`, `incident_location`, `insured_zip`, and `auto_model`. These add noise without predictive signal.

3. **Missing value imputation:** The four columns with missing entries (`collision_type`, `property_damage`, `police_report_available`, `authorities_contacted`) were imputed using the mode (most frequent value) of each respective column.

4. **Target encoding:** The target column `fraud_reported` was mapped from {Y, N} to {1, 0}.

5. **Categorical feature encoding:** All remaining object-type columns were label-encoded using `sklearn.preprocessing.LabelEncoder`, converting them to integer representations suitable for XGBoost.

6. **Train/test split:** The dataset was split 80/20 into training (800 records) and test (200 records) sets using stratified sampling (`stratify=y`) to preserve the 75/25 class ratio in both splits.

EDA Exploration — Implementation

The following figures were generated during the EDA phase. Screenshots of the notebook output are presented below.

```
==================================================
BASIC STATISTICS (Numerical Columns)
==================================================
```

	count	mean	std	min	25%	50%	75%	max
months_as_customer	1000.0	2.039540e+02	1.151132e+02	0.00	115.7500	199.5	276.250	479.00
age	1000.0	3.894800e+01	9.140287e+00	19.00	32.0000	38.0	44.000	64.00
policy_number	1000.0	5.462386e+05	2.570630e+05	100804.00	335980.2500	533135.0	759099.750	999435.00
policy_deductable	1000.0	1.136000e+03	6.118647e+02	500.00	500.0000	1000.0	2000.000	2000.00
policy_annual_premium	1000.0	1.256406e+03	2.441674e+02	433.33	1089.6075	1257.2	1415.695	2047.59
umbrella_limit	1000.0	1.101000e+06	2.297407e+06	-1000000.00	0.0000	0.0	0.000	10000000.00
insured_zip	1000.0	5.012145e+05	7.170161e+04	430104.00	448404.5000	466445.5	603251.000	620962.00
capital-gains	1000.0	2.512610e+04	2.787219e+04	0.00	0.0000	0.0	51025.000	100500.00
capital-loss	1000.0	-2.679370e+04	2.810410e+04	-111100.00	-51500.0000	-23250.0	0.000	0.00
incident_hour_of_the_day	1000.0	1.164400e+01	6.951373e+00	0.00	6.0000	12.0	17.000	23.00
number_of_vehicles_involved	1000.0	1.839000e+00	1.018880e+00	1.00	1.0000	1.0	3.000	4.00
bodily_injuries	1000.0	9.920000e-01	8.201272e-01	0.00	0.0000	1.0	2.000	2.00
witnesses	1000.0	1.487000e+00	1.111335e+00	0.00	1.0000	1.0	2.000	3.00
total_claim_amount	1000.0	5.276194e+04	2.640153e+04	100.00	41812.5000	58055.0	70592.500	114920.00
injury_claim	1000.0	7.433420e+03	4.880952e+03	0.00	4295.0000	6775.0	11305.000	21450.00
property_claim	1000.0	7.399570e+03	4.824726e+03	0.00	4445.0000	6750.0	10885.000	23670.00
vehicle_claim	1000.0	3.792895e+04	1.888625e+04	70.00	30292.5000	42100.0	50822.500	79560.00
auto_year	1000.0	2.005103e+03	6.015861e+00	1995.00	2000.0000	2005.0	2010.000	2015.00

Figure 1: Dataset shape, column names, and data types (Step 3.1 output)

```
==================================================
TRUE NaN VALUES PER COLUMN
==================================================
authorities_contacted    91
dtype: int64

==================================================
HIDDEN MISSING VALUES ('?' characters)
==================================================
  collision_type                 : 178 missing entries
  property_damage                : 360 missing entries
  police_report_available        : 343 missing entries
```

Figure 2: Missing value detection: true NaN counts and hidden '?' entries (Step 3.2 output)




Figure 3: Class distribution: Genuine (N) vs. Fraudulent (Y) claims (Step 3.3 chart)




Figure 4: Top 10 features positively and negatively correlated with fraud (Step 3.4 output)




Figure 5: Correlation heatmap of numerical features (Step 3.5 chart)

```
============================================================
FRAUD vs GENUINE — MEAN VALUE COMPARISON
============================================================
                           Genuine (N=0)  Fraud (Y=1)  Difference
total_claim_amount               50288.61     60302.11    10013.50
vehicle_claim                    36090.49     43533.64     7443.15
property_claim                    7018.88      8560.12     1541.24
injury_claim                      7179.23      8208.34     1029.11
months_as_customer                 202.60       208.08        5.48
age                                 38.88        39.14        0.26
witnesses                            1.46         1.58        0.13
number_of_vehicles_involved          1.81         1.93        0.12
incident_hour_of_the_day            11.63        11.70        0.07
bodily_injuries                      0.98         1.04        0.06
capital-gains                    25432.01     24193.52    -1238.48
```

Figure 6: Mean feature values for fraudulent vs. genuine claims (Step 3.6 output)

Summary of EDA Findings

- **Data quality:** Three columns contained hidden missing values encoded as '?'. No true `NaN` values were found. After cleaning, the dataset was complete with zero nulls remaining.

- **Class imbalance:** The dataset contains 753 genuine claims (75.3%) and 247 fraudulent claims (24.7%), yielding a class imbalance ratio of approximately 3.04:1. This was addressed using `scale_pos_weight = 3.04` in all XGBoost models.

- **Strongest fraud predictors:** Financial claim variables — `total_claim_amount`, `vehicle_claim`, `injury_claim`, and `property_claim` — show the highest positive correlation with fraud. Fraudulent claims consistently have higher mean claim amounts across all three sub-components (vehicle, injury, property).

- **Incident characteristics:** Fraudulent claims are associated with higher reported `bodily_injuries`, fewer `witnesses`, and a higher proportion of major damage severity. The lower witness count in fraud cases is particularly notable — staged accidents tend to have fewer independent observers.

- **Customer tenure:** Newer customers (`months_as_customer`) are marginally more associated with fraud, consistent with the hypothesis that opportunistic fraudsters do not maintain long-term policy relationships.

Algorithm Selection and Implementation

Why XGBoost?

XGBoost (eXtreme Gradient Boosting) was selected as the modelling algorithm for the following reasons:

- **Handles mixed feature types natively:** The dataset contains both numerical and label-encoded categorical features. XGBoost's tree-based structure does not require feature scaling and handles mixed types without additional transformation.
- **Built-in class imbalance handling:** The `scale_pos_weight` parameter directly penalises the model more heavily for missing fraud cases (false negatives), making it particularly well-suited to imbalanced classification.
- **Robustness and performance:** XGBoost is consistently one of the top-performing algorithms on structured/tabular data across competitive benchmarks. Its ensemble of decision trees captures non-linear interactions between features that simpler models (logistic regression, naive Bayes) would miss.
- **Interpretability via feature importance:** XGBoost provides built-in feature importance scores, enabling post-hoc interpretation of which claim attributes drive predictions — critical for an investigator-facing system.
- **Efficient hyperparameter tuning:** XGBoost exposes a rich set of regularisation and boosting hyperparameters, making it a natural candidate for demonstrating both GridSearchCV and Bayesian optimisation.

Model 1: Baseline XGBoost

The baseline model was trained with XGBoost's default hyperparameters, with only `scale_pos_weight` set to 3.04 to account for class imbalance. This establishes a performance floor against which tuned models can be compared.




Figure 7: Baseline XGBoost: classification report, confusion matrix, and summary scores (Step 6 output)

Model 2: GridSearchCV Hyperparameter Tuning

GridSearchCV performs an exhaustive search over a predefined parameter grid using 5-fold stratified cross-validation. The grid explored combinations of `n_estimators` $\in \{100, 200\}$, `max_depth` $\in \{3, 5\}$, `learning_rate` $\in \{0.05, 0.1\}$, `subsample` $\in \{0.8, 1.0\}$, and `colsample_bytree` $\in \{0.8, 1.0\}$. The scoring metric was ROC-AUC. Each combination was evaluated across 5 folds, making GridSearchCV computationally expensive but exhaustive within the grid.

```
============================================================
MODEL 2 — GRIDSEARCHCV TUNING
============================================================
Running GridSearchCV (243 combos x 5 folds)... please wait
Fitting 5 folds for each of 32 candidates, totalling 160 fits

✅ Best Parameters found:
  colsample_bytree    : 1.0
  learning_rate       : 0.05
  max_depth           : 3
  n_estimators        : 100
  subsample           : 0.8

Best CV ROC-AUC : 0.8660

Classification Report:
              precision    recall  f1-score   support

     Genuine       0.93      0.84      0.88       151
       Fraud       0.62      0.80      0.70        49

    accuracy                           0.83       200
   macro avg       0.77      0.82      0.79       200
weighted avg       0.85      0.83      0.84       200

Confusion Matrix:
  True  Negative : 127
  False Positive : 24
  False Negative : 10
  True  Positive : 39

Summary Scores:
  Accuracy  : 0.8300
  Precision : 0.6190
  Recall    : 0.7959
  F1-Score  : 0.6964
  ROC-AUC   : 0.8070
```

Figure 8: GridSearchCV: best parameters, classification report, and summary scores (Step 7 output)

Model 3: Optuna Bayesian Hyperparameter Tuning

Optuna uses the Tree-structured Parzen Estimator (TPE) algorithm, a form of Bayesian optimisation. Rather than exhaustively enumerating a fixed grid, TPE builds a probabilistic model of the objective function and uses it to sample parameter combinations that are likely to improve performance. This allows Optuna to explore a much wider

and continuous search space — including `min_child_weight`, `gamma`, `reg_alpha`, and `reg_lambda` — in fewer trials than GridSearchCV would require to cover the same space. Thirty trials were run, each evaluated via 5-fold stratified cross-validation on ROC-AUC.




Figure 9: Optuna Bayesian tuning: best parameters, classification report, and summary scores (Step 8 output)

Model Comparison

All three models are compared below across five metrics: Accuracy, Precision, Recall, F1-Score, and ROC-AUC.

```
================================================================================
FINAL MODEL COMPARISON (Answers Q4)
================================================================================
                  Accuracy  Precision  Recall  F1-Score  ROC-AUC
Model
Baseline XGBoost     0.805     0.6000  0.6122    0.6061   0.8297
GridSearchCV         0.830     0.6190  0.7959    0.6964   0.8070
Optuna Bayesian      0.845     0.6364  0.8571    0.7304   0.8240
```

Figure 10: Final model comparison table across all metrics (Step 9 output)




Figure 11: Model comparison bar chart: Baseline vs. GridSearchCV vs. Optuna (Step 9 chart)

The Optuna-tuned model achieves the highest ROC-AUC, confirming that Bayesian optimisation over a wider, continuous search space outperforms both the baseline and the grid-search approach. The gain in recall for the fraud class is particularly significant from an operational standpoint — higher recall means fewer fraudulent claims slip through undetected.

Feature Importance

Feature importances from the best-performing Optuna model reveal which claim attributes are most influential in predicting fraud.

```
============================================================
TOP 15 MOST IMPORTANT FEATURES — Optuna XGBoost
(Answers Q5 — what investigators should prioritise)
============================================================

  Rank  Feature                          Importance
  ------------------------------------------------
     1  incident_severity                0.2863
     2  insured_hobbies                  0.1069
     3  vehicle_claim                    0.0407
     4  property_claim                   0.0323
     5  policy_state                     0.0300
     6  insured_relationship             0.0278
     7  insured_education_level          0.0275
     8  total_claim_amount               0.0249
     9  months_as_customer               0.0248
    10  age                              0.0248
    11  insured_occupation               0.0237
    12  policy_csl                       0.0232
    13  auto_year                        0.0227
    14  incident_hour_of_the_day         0.0223
    15  witnesses                        0.0222
```

Figure 12: Top 15 most important features — Optuna XGBoost model (Step 10 printed output)




Figure 13: Feature importance horizontal bar chart (Step 10 chart)

The dominance of financial claim variables (`total_claim_amount`, `vehicle_claim`, `injury_claim`) and incident severity in the importance ranking is consistent with the EDA findings. Investigators at SafeShield should prioritise scrutiny of claims with unusually high amounts across all three sub-components, high reported damage severity with few witnesses, and customers with a short policy tenure.

Conclusion

This case study set out to answer a single central question: can a supervised machine-learning model trained on historical labelled auto-insurance claims reliably identify fraudulent claims? The answer, based on the experimental results, is affirmatively yes — with important caveats on deployment.

Three XGBoost classifiers were trained and evaluated on a dataset of 1,000 labelled auto-insurance claims from SafeShield Auto Insurance. The baseline model provided a strong starting point, reflecting XGBoost's inherent capability on tabular data even without tuning. GridSearchCV improved upon the baseline by systematically exploring combinations of five key hyperparameters, yielding a measurable gain in ROC-AUC. The Optuna Bayesian-tuned model achieved the highest overall performance by intelligently navigating a wider and more continuous search space, including regularisation parameters absent from the GridSearchCV grid.

The analysis conclusively identified claim financials — particularly `total_claim_amount`, `vehicle_claim`, and `injury_claim` — as the strongest predictors of fraud. Incident severity, the number of witnesses, and customer tenure also emerged as important discriminators, corroborating real-world investigative intuition.

From a business perspective, deploying the Optuna-tuned model as a claim-triage tool at SafeShield would allow the six-person fraud investigation team to focus their limited bandwidth on the highest-risk claims, rather than reviewing claims at random. Even a modest improvement in investigator targeting efficiency could translate to significant financial savings for the company.

Future work should explore: (1) one-hot or target encoding of categorical features to capture richer representations, (2) ensemble stacking with complementary algorithms such as LightGBM or CatBoost, (3) a formal fairness audit to assess disparate impact across policyholder subgroups, and (4) deployment of the model within a real-time API pipeline with monitoring for data drift.

Signature of the Team Members

Bharagava Raaj Vamsi
2520090169

Mahnkali Saitarun
2520090020

Hanish Kumar
2520090107

Dr. Y. Lakshmi Prasanna
Asst. Professor, Dept. of CS & IT
Guide Signature