JSP Life Cycle -----

_jspinit

_jspservice is called many times depending on the request

_jspdestroy

JSP notations

| <% %> | scriplet | We write java code | It is copied directly in thejspservice method of the servlet |
|-----------|-------------------|--|--|
| <%= %> | Output expression | We write a variable name or a method call that returns a value | It is copied in the out.write() in the _jspservice method of the servlet |
| <%! %> | , | | This is copied directly in the servlet class |

Inbuilt - IMPLICIT objects that are available in JSP

| request | HttpServletRequest |
|-------------|---------------------------------------|
| response | HttpServletResponse |
| session | HttpSession |
| application | ServletContext |
| out | response.getWriter() |
| exception | exception occurred when the page runs |
| pageContext | to store page level data |

Exercise --- write a JSP that shows total hit count and user wise hit count from 3 browsers

JSP Directives --- <%@ %>

| 12 | 1 | Page directive | Different settings that can be added to internal servlet |
|----|---|------------------------------|---|
| | | attributes of page directive | import , session , isErrorPage , contentType, |
| | 2 | Include directive | To include another page in the current page , REUSE of the page |
| | 3 | Taglib directive | To create custom(user defined) tags |

Exercise - Write a JSP that shows todays date .

Exercise ---- Write a JSP that accepts ---- id , name and cost and inserts the record in the database

| Error Handling We do not want to show the technical errors on the browser, because end user is a non technical person. | | | | | | |
|---|---|--------------------|--|--|--|--|
| If a | So the page pa | | e of the application ten in a separate jsp ne pages. | | | |
| Adva | antage - Reuse o | of page part , sin | ngle point changes!!!! we do using include directive | | | |
| Exer | cise LOG | O .jsp | | | | |
| | | | | | | |
| JSP a | ections | | | | | |
| | <jsp:forward></jsp:forward> | Forward action | | | | |
| | <jsp:include></jsp:include> | Include action | | | | |
| | <jsp:param></jsp:param> | Param action | | | | |
| | \${} | guage !!! Short I | nand notation to access data in JSP | | | |
| 3001 | - L3 | - Of the variables | , | | | |
| | page Request Session Application | | | | | |
| Pleas | se install STS ID | E = https://sprir | ng.io/tools | | | |

New Section 1 Page 2

