

# Data Import

*David Gerard*

*2019-02-08*

## Learning Objectives

- Import data from CSV's,
- Working Directories
- Chapter 11 of [RDS](#)

## Working Directories

- The working directory is where R will look for and save things by default.
- When you specify to save a figure, save a file, or load some data, it will be with respect to the working directory.
- You can see where the current working directory is by `getwd()`, or by looking at the top of the console in RStudio.
- You can change the working directory by Session > Set Working Directory > Choose Directory. Or by CONTROL + SHIFT + H. Or you can use the `setwd()` command.
- A shortcut is to set the working directory to your source file location with Session > Set Working Directory > To Source File Location.
- When you read and write files/figures, you can then specify the path from the position of the working directory.
- Suppose we want to save the following figure:

```
suppressPackageStartupMessages(library(tidyverse))
data("mpg")
p1 <- ggplot(mpg, aes(x = hwy, y = cty)) +
  geom_point()
```

- To save `p1` in the current folder, we would use:

```
ggsave(filename = "./my_saved_plot.pdf", plot = p1)
```

- The “.” means “the current folder”.
- To save `p1` in the folder one level up we would use:

```
ggsave(filename = "../my_saved_plot.pdf", plot = p1)
```

- The “..” means “go one level up”.
- If we are in the analysis folder, and we want to save `p1` in the output folder, we would use:

```
ggsave(filename = "../output/my_saved_plot.pdf", plot = p1)
```

- If we have a subfolder called “fig” within our current folder. We could save `p1` in “fig” with

```
ggsave(filename = "../fig/my_saved_plot.pdf", plot = p1)
```

- **NEVER USE ABSOLUTE PATHS.** For example, you should never start the path from “C” if you use Windows. This makes your code non-transferable to other users.

## readr

- A lot of datasets come in comma-separated or tab-separated formats. For example, These are the first few rows of `hate_crimes2.csv` (available at [https://dcgerard.github.io/stat\\_412\\_612/data.html](https://dcgerard.github.io/stat_412_612/data.html)):

```
state,median_house_inc,share_unemp_seas,share_pop_metro,share_pop_hs,share_non_citizen,share_white
Alabama,42278,0.06,0.64,0.821,0.02,0.12,0.472,0.35,0.63,0.125838926,1.806410489
Alaska,67629,0.064,0.63,0.914,0.04,0.06,0.422,0.42,0.53,0.143740118,1.656700109
Arizona,49254,0.063,0.9,0.842,0.1,0.09,0.455,0.49,0.5,0.225319954,3.413927994
Arkansas,44922,0.052,0.69,0.824,0.04,0.12,0.458,0.26,0.6,0.069060773,0.869208872
California,60487,0.059,0.97,0.806,0.13,0.09,0.471,0.61,0.33,0.255805361,2.397985899
Colorado,60940,0.04,0.8,0.893,0.06,0.07,0.457,0.31,0.44,0.390523301,2.804688765
Connecticut,70161,0.052,0.94,0.886,0.06,0.06,0.486,0.3,0.41,0.335392269,3.772701469
Delaware,57522,0.049,0.9,0.874,0.05,0.08,0.44,0.37,0.42,0.322754169,1.469979563
District of Columbia,68277,0.067,1,0.871,0.11,0.04,0.532,0.63,0.04,1.52230172,10.95347971
```

- In the file, each column is separated by a comma. Each row is separated by a new line.
- We will use the `readr` package to load these datasets into R.
- The `readr` package is a part of the `tidyverse`, and so it is automatically loaded when you load the `tidyverse`.
- To read a CSV (comma-separated values) file into R, use the `read_csv()` function from the `readr` package.

```
library(tidyverse)
hate_crimes <- read_csv(file = "../data/hate_crimes1.csv")
```

```
## Parsed with column specification:
## cols(
##   `state` median_house_inc    share_unemp_seas    share_pop_metro share_pop_hs    share_non_citizen
## )
```

- If the CSV is online and you know the URL, you can use that URL for the `file` argument.

```
library(tidyverse)
hate_crimes <- read_csv(file = "https://dcgerard.github.io/stat_412_612/data/hate_crimes2.csv")
```

```
## Parsed with column specification:
## cols(
##   state = col_character(),
```

```
## median_house_inc = col_double(),
## share_unemp_seas = col_double(),
## share_pop_metro = col_double(),
## share_pop_hs = col_double(),
## share_non_citizen = col_double(),
## share_white_poverty = col_double(),
## gini_index = col_double(),
## share_non_white = col_double(),
## share_vote_trump = col_double(),
## hate_crimes_per_100k_splc = col_double(),
## avg_hatecrimes_per_100k_fbi = col_double()
## )
```

- Use `read_tsv()` if columns are separated by tabs.
- Use `read_csv2()` if columns are separated by semicolons.
- Other file formats are listed in [RDS](#).
- You want to import data directly from Excel? Don't.
  - First export the Excel spreadsheet as a CSV. Then read the CSV file into R.
- You are using colors to represent meaningful information in Excel? Don't.
  - Edit the data so that the information is encoded by a new variable.

## Special Considerations

- **Always check your data immediately after importing it.**
  - Check that the types are correct for each of the variables.
  - Check that the missing data were coded correctly.
  - Later on, when you notice something weird, consider that this might have resulted because of a problem during data import.

```
hate_crimes %>%
  summarize_all(class)
```

```
## # A tibble: 1 x 12
##   state median_house_inc share_unemp_seas share_pop_metro share_pop_hs
##   <chr> <chr>           <chr>           <chr>           <chr>
## 1 char~ numeric      numeric      numeric      numeric
## # ... with 7 more variables: share_non_citizen <chr>,
## #   share_white_poverty <chr>, gini_index <chr>, share_non_white <chr>,
## #   share_vote_trump <chr>, hate_crimes_per_100k_splc <chr>,
## #   avg_hatecrimes_per_100k_fbi <chr>
```

```
hate_crimes %>%
  summarize_all(funs(sum(is.na(.))))
```

```
## # A tibble: 1 x 12
##   state median_house_inc share_unemp_seas share_pop_metro share_pop_hs
##   <int>          <int>          <int>          <int>          <int>
## 1      0              0              0              0              0
## # ... with 7 more variables: share_non_citizen <int>,
## #   share_white_poverty <int>, gini_index <int>, share_non_white <int>,
## #   share_vote_trump <int>, hate_crimes_per_100k_splc <int>,
## #   avg_hatecrimes_per_100k_fbi <int>
```

```
head(hate_crimes)
```

```
## # A tibble: 6 x 12
##   state median_house_inc share_unemp_seas share_pop_metro share_pop_hs
##   <chr>          <dbl>          <dbl>          <dbl>          <dbl>
## 1 Alab~          42278            0.06            0.64            0.821
## 2 Alas~          67629            0.064           0.63            0.914
## 3 Ariz~          49254            0.063           0.9             0.842
## 4 Arka~          44922            0.052           0.69            0.824
## 5 Cali~          60487            0.059           0.97            0.806
## 6 Colo~          60940            0.04            0.8             0.893
## # ... with 7 more variables: share_non_citizen <dbl>,
## #   share_white_poverty <dbl>, gini_index <dbl>, share_non_white <dbl>,
## #   share_vote_trump <dbl>, hate_crimes_per_100k_splc <dbl>,
## #   avg_hatecrimes_per_100k_fbi <dbl>
```

- Sometimes the files code missing data other than NA. For example, it's common to use periods ., or in some genomic settings they use -9 as missing.
- R won't know how to handle this without you telling it, so you'll have to know what the missing data encoding is and specify it with the `na` argument in `read_csv()`.
- readr will try to guess the type for each column (double, integer, character, logic, etc). Sometimes it guesses wrong. If it seems to be guessing wrong, use the `col_types` to explicitly specify the column types.
- Sometimes there are comments at the start of a data file. You can skip the first few lines before starting to read data with the `skip` argument.
- If the comments begin with a special character, you can use the `comment` argument.
- **Exercise:** Successfully load all of the `hate_crimes` CSV files at [https://dcgerard.github.io/stat\\_412\\_612/data.html](https://dcgerard.github.io/stat_412_612/data.html).

## Data Export

- You can write comma-separated and tab-separated files using `write_csv()`, `write_csv2()`, and `write_tsv()`.
- The defaults are usually fine.